



# Local Installation

Generated on: 2021-10-11 05:00:35 GMT+0000

SAP Commerce Cloud in the Public Cloud | 2005

**PUBLIC**

Original content: <https://help.sap.com/viewer/8be4e0379b294fbabf36d26e7ca4169d/v2005/en-US>

## Warning

This document has been generated from the SAP Help Portal and is an incomplete version of the official SAP product documentation. The information included in custom documentation may not reflect the arrangement of topics in the SAP Help Portal, and may be missing important aspects and/or correlations to other topics. For this reason, it is not for productive use.

For more information, please visit the <https://help.sap.com/viewer/disclaimer>.

# Set Up Your Build

After you have successfully downloaded and unpacked the required files, you must then create your SAP Commerce Cloud project directories before proceeding.

To set up SAP Commerce Cloud, carry out the following steps.

1. Set up Apache Ant
2. Start a clean build to create your project directories

## Setting up Apache Ant

SAP Commerce Cloud comes pre-bundled with Apache Ant, a tool for automating the software build processes. Configure Apache Ant before you build SAP Commerce Cloud.

### Context

SAP Commerce Cloud provides three script files that you can use to set your Ant environment for the current command console session:

- **setantenv.bat**: a batch file for Microsoft Windows systems
- **setantenv.ps1**: a shell script file for Windows Powershell
- **setantenv.sh**: a shell script file for Unix-based systems such as Linux or Mac OS X

### Procedure

1. Open a command prompt in Microsoft Windows, or a shell in the Unix family
2. Navigate to `hybris/bin/platform` in your installation.

For example:

```
C:\hybris\bin\platform
```

3. Run the provided script for your platform.
  - For Windows systems, enter `setantenv.bat`
  - For Windows Powershell, enter `.\setantenv.ps1`
  - For Unix systems, including Mac OSX, enter `./setantenv.sh`

Do not close the command window, as you need it for the next steps of the installation procedure. Doing so may require you to set the Ant environment once again.

### Results

You should see something similar to the following:

```
platform — -bash — 98x8
[C02P20K9G3QP:platform $ ./setantenv.sh
Apache Ant(TM) version 1.10.5 compiled on July 10 2018
ant home: /opt/com/hybris-commerce-suite-1905.0/hybris/bin/platform/apache-ant
ant opts: -Xmx2g -Dfile.encoding=UTF-8 -Djdk.util.jar.enableMultiRelease=force
C02P20K9G3QP:platform $
```

## Creating the Project Directories

Once you have set up your Ant environment, use Ant to create your SAP Commerce Cloud project framework.

### Context

Running `ant clean all` on a new instance of SAP Commerce Cloud creates any configuration files and other essential directories. This is a necessary step in the installation process, and must be done once before you proceed with the configuration.

If a build already exists, it deletes and recreates it. Repeat this command any time you wish to create a new build in place of an old one.

#### → Tip

If you are installing on MacOS and encounter any warnings about unverified third party libraries, follow the steps in [Allowing Apps on MacOS](#).

### Procedure

1. At the command prompt, navigate to `/hybris/bin/platform` and enter the following command.

```
ant clean all
```

The system prompts you to choose a configuration template for your environment. You can choose from either development, or production.

```
Buildfile: C:\hybris\bin\platform\build.xml
[echo]
[mkdir] Created dir: C:\hybris\log
[mkdir] Created dir: C:\hybris\data
[mkdir] Created dir: C:\hybris\temp\hybris
[input]
[input] **** NO CONFIG FOLDER FOUND **** use the jar utility to
        unzip the zip file on unix based systems, as this will change the timesta
        the contained files and break the build process.Buildfile: C:\hybris\bin\
[echo]
[mkdir] Created dir: C:\hybris\log
[mkdir] Created dir: C:\hybris\data
[mkdir] Created dir: C:\hybris\temp\hybris
[input]
[input]
[input] No config folder was found at C:\hybris-4.5\hybris\config.
```

```

[input] A "fresh" folder containing basic configuration files and the hybris
[input] demo licence will be created for your convenience.
[input] Please adjust and review the configuration files (and license) and
[input] call 'ant' again. This directory will never be overridden or
[input] touched again. Always use this configuration folder for configuration
[input] of platform, do not change anything within the platform folder.
[input]
[input] Please choose the configuration template.
[input] Press [Enter]
[input] to use the default value ([develop], production)

```

2. Select the appropriate configuration template.

- To choose the default develop template, press .
- To choose the production template, type production, then press .

Always choose the **develop** template for test, development, and demonstration purposes.

When the build process is complete, you should see output similar to the following:

```

server:
[echo]
[echo] Configuring server at C:\hybris\bin\platform\tomcat-6
[echo] Using config set at C:\hybris\config\tomcat
[echo]
[mkdir] Created dir: C:\hybris\log\tomcat
[mkdir] Created dir: C:\hybris\data\media
[copy] Copying 8 files to C:\hybris\bin\platform\tomcat-6
[copy] Copying 6 files to C:\hybris\bin\platform\tomcat-6
[copy] Copying 1 file to C:\hybris\bin\platform\tomcat-6\lib
[echo]
[echo] Embedded server does not seem to be running (no PID found). No restart necessary.
[echo]

all:
[echo] Build finished on 26-March-2013 11:23:33.
[echo]

BUILD SUCCESSFUL
Total time: 3 minutes 15 seconds
C:\hybris\bin\platform>

```

## Results

Your hybris directory now contains the following:

