

```
ROUTER#
ROUTER#configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
ROUTER(config)#
ROUTER(config)#Interface ethernet 0/0
ROUTER(config-if)#
ROUTER(config-if)#ip address 50.0.0.1 255.0.0.0
ROUTER(config-if)#no shutdown
ROUTER(config-if)#exit
ROUTER(config)#show ip interface brief
      ^
% Invalid input detected at '^' marker.

ROUTER(config)#exit
ROUTER#
*Aug 17 05:35:48.964: %SYS-5-CONFIG_I: Configured from console by console
ROUTER#
ROUTER#
ROUTER#show ip interface brief
Interface      IP-Address      OK? Method Status      Protocol
Ethernet0/0    50.0.0.1        YES manual  up          up
Ethernet0/1    unassigned      YES TFTP   down        down
Ethernet0/2    unassigned      YES TFTP   down        down
Ethernet0/3    unassigned      YES TFTP   down        down
ROUTER#
ROUTER#
```



```

ROUTER#
Ethernet0/1          unassigned    YES TFTP    down
Ethernet0/2          unassigned    YES TFTP    down
Ethernet0/3          unassigned    YES TFTP    down
ROUTER#
ROUTER#disable
ROUTER>
ROUTER>enable
ROUTER#
ROUTER#
ROUTER#configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
ROUTER(config)#
ROUTER(config)#
ROUTER(config)#exit
ROUTER#
ROUTER#
*Aug 17 05:38:33.496: %SYS-5-CONFIG_I: Configured from console by console
ROUTER#show ip interface brief
Interface            IP-Address      OK? Method Status      Protocol
Ethernet0/0          50.0.0.1        YES manual up          up
Ethernet0/1          unassigned      YES TFTP    down        down
Ethernet0/2          unassigned      YES TFTP    down        down
Ethernet0/3          unassigned      YES TFTP    down        down
ROUTER#

```

QEMU (Win)

```

Administrator: Command Prompt
Media State . . . . . : Media disconnected
Connection-specific DNS Suffix . . :
Tunnel adapter 6T04 Adapter:
Connection-specific DNS Suffix . . :
IPv6 Address. . . . . : 2002:3200:a::3200:a
Default Gateway . . . . . :
C:\Users\user>
C:\Users\user>
C:\Users\user>ping 50.0.0.1
Pinging 50.0.0.1 with 32 bytes of data:
Reply from 50.0.0.1: bytes=32 time=2ms TTL=255
Reply from 50.0.0.1: bytes=32 time=1ms TTL=255
Reply from 50.0.0.1: bytes=32 time=1ms TTL=255
Reply from 50.0.0.1: bytes=32 time=1ms TTL=255
Ping statistics for 50.0.0.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 1ms, Maximum = 2ms, Average = 1ms
C:\Users\user>

```

User Access Verification

Username: console

Password:

ROUTER>

ROUTER>

ROUTER>

ROUTER>

ROUTER>

ROUTER>

Administrator: Command Prompt

Tunnel adapter 6T04 Adapte

Connection-specific DNS

IPv6 Address.

Default Gateway

Re C:\Users\user>

C:\Users\user>

C:\Users\user>ping 50.0.0.1

Pinging 50.0.0.1 with 32 byte

Reply from 50.0.0.1: bytes=32

Reply from 50.0.0.1: bytes=32

Reply from 50.0.0.1: bytes=32

Reply from 50.0.0.1: bytes=32

Con Ping statistics for 50.0.0.1:

Packets: Sent = 4, Received

Approximate round trip times in

Minimum = 1ms, Maximum = 2ms

C:\Users\user>

C:\Users\user>

C:\Users\user>

