

OSI Layers

Total 7 Layers

Reverse to varnam numbers

ARP
Packet Flow
Test

- 7 - Application
- 6 - Presentation
- 5 - Session
- 4 - Transport
- 3 - Network
- 2 - Data link
- 1 - Physical Layers

→ Encapsulation
↓
Decapsulation

7 - Application → Echo data → 32 bytes → ICMP

Internet control msg protocol

6 - presentation → Echo data + Format Encap

5 - Session → Echo data + Format + Time Encap → Sending and receive Time

4 - Transport → Echo + Format + Time +

3 - Network → [Echo + Format + T + $\left[\begin{matrix} SIP: 50.0.0.10 \\ DIP: 50.0.0.20 \end{matrix} \right] IP$]

After Network Encap is called Packet

2 - Data link → E + F + T + IP + $\left[\begin{matrix} S.mac: 00A \\ D.mac: 00B \end{matrix} \right]$ → Ethernet Protocol

1st time

Ethernet protocol helps to find the Dest mac address

ping = 10pk ARP: Address resolution protocol is use to destination mac with the help of destination IP

2nd time 8pk

RF

ARP Table

50.0.0.20 - 00B → 5mins Hold

ARPReq → ARP receive

It is called Frame Encap

1. Physical Layer → NIC function

ARP = Address Resolution Protocol

It is a protocol is use to find destination

Mac with the help of destination IP

ARP TABLE