

Search Function

Ethan's
Learn from experts

```
import re

line = "this is the string contain sentence"
matchObj = re.search("This is the string Match", line, re.I)

if matchObj:
    print "\n matchObj.group() : \n", matchObj.group()
    print "\n matchObj.group(1) : \n", matchObj.group(1)
else:
    print "No match!!"
```

Slide 205 www.ethans.co.in

Findall Function

Ethan's
Learn from experts

- It scan the complete string and get all occurrences of a given pattern within a string
- The re.findall function returns a list of all matches.
- Help on match function:

```
>>> import re
>>> help(re.findall)
```

Parameter	Description
pattern	The regex/pattern which need to match
string	This is the string, where re need to be matches
flags	Modifiers or Flags to support more functionality to re

Slide 206 www.ethans.co.in

Findall Function ex:

Ethans
Learn from experts

```
import re

line = "this is the string contain sentence"
allMatches = re.findall("This", line, re.I)

if len(allMatches):
    print "\n allMatches : \n", allMatches
else:
    print "No match!!"
```

Slide 207 www.ethans.co.in

The First Wildcard

Ethans
Learn from experts

Wildcards (are also called as quantifiers) are the operator symbols which have specific meaning inside regular expression.

For example: . (Dot or period) matches any character, digit, alphanumeric character except newline character (\n).

```
def refind(pat, str):
    match = re.search(par, str)
    if match:
        print match.group()
    else:
        print 'Pattern not found'
```

```
>>> refind('a.b', 'this is acb string')
acb
>>> refind('a.b', 'this is jatbin string')
atb
>>> refind('a.b', 'this is a b string')
a b
>>> refind('a.b', 'this is a\btb string')
a            b
```

Slide 208 www.ethans.co.in

Match Operator Itself



In many cases, user may wants to match the operator symbol itself in the regular expression. We can suppress the wild cards and special characters itself by backslash (\)

Ex:

```
>>> refind('10.', 'this is a number 101 and ip address 10.')
101
>>> refind('10\.', 'this is a number 101 and ip address 10.')
10.
```

Slide 209

www.ethans.co.in

Other Wildcards



These wildcard characters do not matches themselves. Until and unless they suppressed by backslash.

Following are the other wildcards:

Wildcard	Meaning
*	matches Zero or more occurrence of previous character/s
+	matches One or more occurrence of previous character/s
?	matches Zero or One occurrence of previous character/s

Slide 210

www.ethans.co.in

Other Wildcards

Ethans
Learn from experts

REGEX	Matches
AbC*	It matches A followed by b followed by either Zero or more occurrence of C. i.e. Ab, AbC, AbCCCC. AbCCCCCCCCCCCC
AbC+	It matches A followed by b followed by minimum one or more occurrence of C i.e. Abc, AbCCCCCCC, AbCCC
AbC?	It matches A followed by b followed by one or Zero occurrence of C. i.e. Ab, AbC
Ab(cd)*	It matches A followed by b followed by either Zero or more occurrence of cd i.e. Ab, Abcd, Abcdcd
Ab(cd)+	It matches A followed by b followed by minimum one or more occurrence of cd i.e. Abcd, Abcdcd
Ab(cd)?	It matches A followed by b followed by either one or zero occurrence of cd i.e. Abcd, Ab

Slide 211 www.ethans.co.in

Combine Wildcards

Ethans
Learn from experts

REGEX	Matches
Ab+C*	It matches A followed by minimum one or more occurrence of b followed by either Zero or more occurrence of C. i.e. Ab, Abc, Abbccc, Abbccccccccccc
A.C+	It matches A followed by any character followed by minimum one or more occurrence of C i.e. Azc, Azcc. AEcccccccccc
..C?	It matches any two characters followed by b followed by one or Zero occurrence of C. i.e. Ab, Abc
<.*>	It matches anything inside tags <> i.e. <HTML>, <TAGS>
\(.+\)	It matches minimum one character inside brackets cd i.e. (Abcd), (a)
ab+c?	It matches a followed by one or more b followed by zero or one c. i.e. "abbbbc" or "abc", but not "ac"

Slide 212 www.ethans.co.in

Character Class



REGEX	Matches
[abc]	It matches any string which has either 'a' or 'b' or 'c'
[abcdefghijklmnopqrstuvwxyz]	It matches any string which has either 'a' or 'b' or 'c' or so on till 'z'
[a-z]	It matches any string which has either 'a' or 'b' or 'c' or so on till 'z'
[0-9]	It matches any string which has 0 or 1 or 2 or 3 till 9
[a-zA-Z0-9]	It matches any string which has characters from a-z and A-Z and 0-9
[a-zA-Z_]	It matches any string which has characters from a-z or _ (underscore)

Slide 213

www.ethans.co.in

Character Class



REGEX	Matches
[^abc]	It matches any string which has neither 'a' nor 'b' nor 'c'
[^abcdefghijklmnopqrstuvwxyz]	It matches any string which has neither 'a' or 'b' or 'c' or so on till 'z'
[^a-z]	It matches the string which has neither 'a' or 'b' or 'c' or so on till 'z'
[^aeiou]	It matches the string which has no vowels.
[lL][^abc]	It matches the string has 'l' or 'L' should not followed by 'a' nor 'b' nor 'c'
[^a-zA-Z_]	It matches the string doesn't have a-z or _ (underscore)

Slide 214

www.ethans.co.in

Character Class

Ethans
Learn from experts

REGEX	Matches
[aA][0-9]+	It matches any string which has 'a' or 'A' followed by any number and occurrence can any number of times.
A+.[.]?	It matches any string which has 'A' any number of times followed by any character followed by either '.' or '?'
a[bc]	It matches any string which has 'a' followed by either 'b' or 'c'
A[abc]?	It matches the string which has 'A' followed by zero or one occurrence of either 'a' or 'b' or 'c'
[a-zA-Z]\@	It matches the string has 'a' to 'z' or '_' or '!' followed by '@'

Slide 215 www.ethans.co.in

Shortcuts

Ethans
Learn from experts

Shortcut	Say	Meaning
\s	Any space, tab or new line characters	[\t\n]
\S	Other than space, tab or newline character	[^ \t\n]
\d	Any digit	[0-9]
\D	Other than digit	[^0-9]
\w	Digits, characters or _ (underscore)	[a-zA-Z0-9_]
\W	Other than digit, character or _	[^a-zA-Z0-9_]

Slide 216 www.ethans.co.in

Objective – Module 9



Database Interface

- Creating a Database with SQLite 3
- CRUD Operations,
- Creating a Database Object.
- Python MySQL Database Access
- DML and DDL Operations with Databases
- Performing Transactions
- Handling Database Errors
- Disconnecting Database

Slide 217

DB Interface with Python



Python Database modules supports a wide range of database servers:

- IBM DB2
- Firebird
- Informix
- Ingres
- MySQL
- Oracle
- PostgreSQL
- SAP DB
- Microsoft SQL Server
- Microsoft Access
- Sybase
- Teradata
- IBM Netezza

Slide 218

www.ethans.co.in

DB Interface with Python -2

Ethans
Learn from experts

Standard for RDBMS Databases

Python DB API/drivers/modules provides conventional approach while working with databases using Python standard structures and syntax.

This includes the following:

- Importing the Python-DB module.
- Acquire a connection with the database.
- Create a DB cursor
- Issuing SQL statements and stored procedures.
- Closing the connection

Slide 219 www.ethans.co.in

SQLite Database

Ethans
Learn from experts



• SQLite is a relational database management system contained in a C programming library.

• SQLite is a popular choice as embedded database software for local/client storage in application software such as web browsers.

• It is fast, reliable and the entire DB is stored in single disk file.

• Python module sqlite3 intended to work with SQLite3.

Source: <https://en.wikipedia.org/wiki/SQLite>

Slide 220 www.ethans.co.in

Acquire DB connection



- Python sqlite3 module will be used to connect SQLite3 Database
- It is default available along with the Python installable.
- connect, close are the functions in below example

```
>>> # Importing sqlite3 DB
>>> import sqlite3
>>> # Creating a DB in RAM
>>> dbr = sqlite3.connect(':memory:')
>>> # Creating/Using a DB in/from a file
>>> db = sqlite3.connect('ethans')
>>> # Closing a DB connection
>>> db.close()
```

Slide 221

www.ethans.co.in

Create table



```
import sqlite3 # Importing module
db = sqlite3.connect('ethans')
dbCursor = db.cursor() # DB cursor
dbCursor.execute(""" CREATE TABLE
    employee(id int, name text,dept text,
    salary int) """)
db.close()
```

```
>>> help(dbCursor.execute)
execute(...)
    Executes a SQL statement.

>>> dir(dbCursor)
['arraysize', 'close', 'connection', 'description', 'execute', 'executemany',
'executescript', 'fetchall', 'fetchmany', 'fetchone', 'lastrowid', 'next',
'row_factory', 'rowcount', 'setinputsizes', 'setoutputsizes']
```

Slide 222

www.ethans.co.in

Insert Data - 1

Ethan's
Learn from experts

```
''' Insert a record '''

import sqlite3 # Importing module

db = sqlite3.connect('ethanstech')
dbCursor = db.cursor() # DB cursor

dbCursor.execute(""" INSERT INTO employee
    values (1, 'ethans','training', '50000')
""")

db.commit()
db.close()
```

Slide 223

www.ethans.co.in

Insert Data - 2

Ethan's
Learn from experts

```
''' Insert a record '''

import sqlite3 # Importing module

db = sqlite3.connect('ethanstech')
dbCursor = db.cursor() # DB cursor

dbCursor.execute(""" INSERT INTO employee
    values (?, ?, ?, ?)""",
    (1, 'ethans','training', 50000))

db.commit()
db.close()
```

Slide 224

www.ethans.co.in

Insert Data - 3



```
''' Insert a record '''

import sqlite3 # Importing module

db = sqlite3.connect('ethanstech')
dbCursor = db.cursor() # DB cursor

eid, name, dept, salary = 1, 'ethans', 'training', 50000

dbCursor.execute(""" INSERT INTO employee
    values (?, ?, ?, ?)""",
    (eid, name, dept, salary))

db.commit()
db.close()
```

Slide 225

www.ethans.co.in

Insert Data - 4



```
import sqlite3, sys
db = sqlite3.connect('Employee')
cursor = db.cursor()

id, name, dept, salary = 6, 'Chetan', 'IT', 10000
sql = '''INSERT INTO emp values (%d, '%s', '%s', %d)''' \
    %(id, name, dept, salary)

cursor.execute(sql)
db.commit()

cursor.execute('''Select * from emp''')
for record in cursor.fetchall():
    print record

db.close()
```

Slide 226

www.ethans.co.in

Insert Data - 5



```
''' Insert a record '''

import sqlite3 # Importing module

db = sqlite3.connect('ethanstech')
dbCursor = db.cursor() # DB cursor

eid, name, dept, salary = 1, 'ethans', 'training', 50000
dbCursor.execute(""" INSERT INTO employee
    values (:id, :name, :dept, :salary) """,
    {'name':name, 'id':eid, 'dept':dept, 'salary':salary})
db.commit()
db.close()
```

Slide 227

www.ethans.co.in

Insert Data - 6



```
''' Insert a record '''

import sqlite3 # Importing module

db = sqlite3.connect('ethanstech')
dbCursor = db.cursor() # DB cursor

eid, name, dept, salary = 1, 'ethans', 'training', 50000
dbCursor.executemany(""" INSERT INTO employee
    values (?,?,?,?,?) """,
    [(eid, name, dept, salary), (2, 'Steve', 'training', 60000)])
db.commit()
db.close()
```

Slide 228

www.ethans.co.in

Insert and Select Data



```
import sqlite3, sys
db = sqlite3.connect('Employee')
cursor = db.cursor()

id, name, dept, salary = 7, 'Santosh', 'IT', 10000
cursor.execute(''INSERT INTO emp values (:id, :name, :dept, :sal)'''
               {'sal':salary, 'name':name, 'dept':dept, 'id':id})
db.commit()

cursor.execute(''Select * from emp where dept = ?'', ('IT',))
for record in cursor.fetchall():
    print list(record)

db.close()
```

Slide 229

www.ethans.co.in

Insert using executemany and select



```
import sqlite3, sys
db = sqlite3.connect('Employee')
cursor = db.cursor()

id1, name1, dept1, salary1 = 8, 'Nitin', 'IT', 10000
id2, name2, dept2, salary2 = 9, 'Bob', 'IT', 20000

dataset = [(id1, name1, dept1, salary1), (id2, name2, dept2, salary2)]
cursor.executemany(''INSERT INTO emp values (?, ?, ?, ?)'', dataset)
db.commit()

cursor.execute(''Select * from emp where dept = ?'', ('IT',))
for record in cursor.fetchall():
    print list(record)

db.close()
```

Slide 230

www.ethans.co.in

Drop table



Slide 231 www.ethans.co.in

```
''' Drop a table '''

import sqlite3 # Importing module

db = sqlite3.connect('ethanstech')
dbCursor = db.cursor() # DB cursor

dbCursor.execute("""" DROP table employee""") 

db.close()
```

Objective – Module 10



Introduction to python modules

- Introduction to Python repository
- What are modules and how to locate?
- Install modules
- What is pip, easy_install and source forge?
- Install modules using pip and easy install
- Python compiler for windows
- XLS modules
- Web scraping using Python
- Important modules

Slide 232

Py Repository

Ethan's
Learn from experts

- Python Package Index or PyPI is the official third-party software repository for the Python programming language. Python developers intend it to be a comprehensive catalog of all open source Python packages
- While the PyPI website is maintained by the Python Software Foundation, its contents are uploaded by individual package maintainers. Python package managers such as [pip](#) default to downloading packages from PyPI.
- Location: <https://pypi.python.org/pypi/>
- Access: <http://pypi-ranking.info/alltime> to know the ranking of all packages

Source: Wiki

Slide 233 www.ethans.co.in

What are tools to install modules

Ethan's
Learn from experts

There are many ways to install and manage Python packages from PyPI.

- **easy_install** - https://pythonhosted.org/setuptools/easy_install.html
- **Pip** - <http://docs.python-guide.org/en/latest/starting/install/win/>
- **Setup** - <https://docs.python.org/2/install/>
- **Windows Installation (Unofficial)**
<http://www.lfd.uci.edu/~gohlke/pythonlibs>
- **Source Forge** - <https://sourceforge.net/projects/numpy/>
- **MySQL Example** – <https://pypi.python.org/pypi/MySQL-python/1.2.5#downloads>

Slide 234 www.ethans.co.in

Easy Install

Ethans
Learn from experts

- `easy_install` is a python module that lets you download, build, install, and manage Python packages automatically.
- `easy_install` default available in python >= 2.7.9 version
- To install `easy_install`, download the `ez_setup.py` file from <https://pypi.python.org/pypi/setuptools>
- To install a package using `easy_install`, only supply the filename or URL of a source distribution or .egg
- On Windows, an `easy_install.exe` launcher will also be installed, so that you can just type `easy_install` as long as it's on your PATH. If typing `easy_install` at the command prompt doesn't work, check to make sure your PATH includes the appropriate `C:\Python2X\Scripts` directory.

Slide 235 www.ethans.co.in

easy_install commands

Ethans
Learn from experts

- To get the help page
`easy_install --help`
- Install any package by name – Search PyPI for the latest version and download it. Build and install the package manually.
`easy_install xlrd`
- Install a package via URL
`easy_install -f https://pypi.python.org/pypi/xlwt`
`easy_install http://example.com/path/to/MyPackage-1.2.3.tgz`
- To upgrade a package
`easy_install "SomePackage==2.0"`
`easy_install "SomePackage>2.0"`
`easy_install --upgrade beautifulsoup`
- To uninstall the package:
`easy_install -m&N PackageName`

Slide 236 www.ethans.co.in

pip

Ethan's
Learn from experts

- pip is a package management system used to install and manage software packages written in Python. Many packages can be found in the [Python Package Index \(PyPI\)](#).
- Python 2.7.9 and later (on the python2 series), and Python 3.4 and later include pip (pip3 for Python 3) by default.
- pip is a recursive acronym that can stand for either "Pip Installs Packages" or "Pip Installs Python".
- pip is quite similar to easy_install. It is a python module that lets you download, build, install, and manage Python packages automatically.
- To install pip, download the get-pip.py file from <https://pip.pypa.io/en/latest/installing.html>
- To install the package using pip, supply the filename only.

Slide 237

www.ethans.co.in

pip commands

Ethan's
Learn from experts

The most common scenario to install a package using pip is:

• pip -h	# to display the help page
• pip list	# to display the installed packages
• pip list --outdated	# to display all outdated package
• pip search xlrd	# to search the package in repo
• pip install Package	# latest version
• pip install Package==1.0.4	# specific version
• pip install 'Package>=1.0.4'	# minimum version requirement
• pip uninstall package	# to uninstall the package
• pip install --upgrade	# to upgrade the package

Slide 238

www.ethans.co.in

Interact with spreadsheets

Ethans
Learn from experts

There are so many python packages available to work with Excel files that will run on any Python platform and that do not require either Windows or Excel to be used. They are fast, reliable and open source:

openpyxl - for reading and writing Excel 2010 files (ie: .xlsx)

xlsxwriter - An alternative package for writing data, formatting information and, in particular, charts in the Excel 2010 format (ie: .xlsx)

xlrd - This package is for reading data and formatting information from older Excel files (ie: .xls)

xlwt - This package is for writing data and formatting information to older Excel files (ie: .xls)

xlutils - This package collects utilities that require both xlrd and xlwt, including the ability to copy and modify or filter existing excel files.

Slide 239 www.ethans.co.in

Read data from xlrd

Ethans
Learn from experts

```
import xlrd
myWorkBook = xlrd.open_workbook('sampleFile.xlsx')
for sheet in myWorkBook.sheets():
    print 'Sheet:',sheet.name
    for row in range(sheet.nrows):
        for col in range(sheet.ncols):
            print "cell: row - %d col - %d and value
- %r "%(row, col,
sheet.cell(row,col).value)
```

Slide 240 www.ethans.co.in