

Kiran Iqbal

_Secure Cloud-Integrated IoT Healthcare Systems (1)-1

slot 2

Document Details

Submission ID

trn:oid::3618:131294065

Submission Date

Mar 12, 2026, 2:06 PM GMT+5

Download Date

Mar 12, 2026, 2:09 PM GMT+5

File Name

_Secure Cloud-Integrated IoT Healthcare Systems (1)-1.pdf

File Size

2.5 MB

25 Pages

8,254 Words

51,451 Characters

*% detected as AI

AI detection includes the possibility of false positives. Although some text in this submission is likely AI generated, scores below the 20% threshold are not surfaced because they have a higher likelihood of false positives.

Caution: Review required.

It is essential to understand the limitations of AI detection before making decisions about a student's work. We encourage you to learn more about Turnitin's AI detection capabilities before using the tool.

Disclaimer

Our AI writing assessment is designed to help educators identify text that might be prepared by a generative AI tool. Our AI writing assessment may not always be accurate (i.e., our AI models may produce either false positive results or false negative results), so it should not be used as the sole basis for adverse actions against a student. It takes further scrutiny and human judgment in conjunction with an organization's application of its specific academic policies to determine whether any academic misconduct has occurred.

Frequently Asked Questions

How should I interpret Turnitin's AI writing percentage and false positives?

The percentage shown in the AI writing report is the amount of qualifying text within the submission that Turnitin's AI writing detection model determines was either likely AI-generated text from a large-language model or likely AI-generated text that was likely revised using an AI paraphrase tool or word spinner.

False positives (incorrectly flagging human-written text as AI-generated) are a possibility in AI models.

AI detection scores under 20%, which we do not surface in new reports, have a higher likelihood of false positives. To reduce the likelihood of misinterpretation, no score or highlights are attributed and are indicated with an asterisk in the report (*%).

The AI writing percentage should not be the sole basis to determine whether misconduct has occurred. The reviewer/instructor should use the percentage as a means to start a formative conversation with their student and/or use it to examine the submitted assignment in accordance with their school's policies.

What does 'qualifying text' mean?

Our model only processes qualifying text in the form of long-form writing. Long-form writing means individual sentences contained in paragraphs that make up a longer piece of written work, such as an essay, a dissertation, or an article, etc. Qualifying text that has been determined to be likely AI-generated will be highlighted in cyan in the submission, and likely AI-generated and then likely AI-paraphrased will be highlighted purple.

Non-qualifying text, such as bullet points, annotated bibliographies, etc., will not be processed and can create disparity between the submission highlights and the percentage shown.



A Privacy-Preserving Predictive Protection Framework Using Behavioral Adaptive Trust Algorithm for Secure Cloud-Integrated IoT Healthcare Systems

Abstract—The ever-increasing adoption of Internet of Things (IoT) technologies in smart healthcare has greatly enhanced the degree of remote patient monitoring, diagnosis at a distance and development of clinical decision making systems. Yet, the ongoing transfer of delicate patient details to cloud platforms poses grave security and privacy concerns, especially upon data processing and analytical inference. Traditionally, healthcare security solutions are focused either on encryption or a machine-learning-based intrusion detection system such as Symantec, Crowd-strike and SentinelOne that identify the attack only after they have taken root, focusing purely on protecting data in storage. Thus, patient identity exposure, inference-time privacy leakage and insider abuse issues remain unresolved in current IoT healthcare frameworks. In order to achieve these objectives while addressing the limitations, this paper presents P3-Secure, a privacy-preserving predictive protection framework that combines newly introduced Differential Privacy-based obfuscation of data inputs with secure Homomorphic Encrypted Analytics and a new Behavioral Adaptive Trust Algorithm (BATA) for intelligent threat detection. The medical sensor data are anonymised at the IoT edge by means of controlled perturbation, preventing reconstruction of individual patient attributes during transmission according to a novel architecture proposal. This enables the encrypted health data to be processed in the cloud without being decrypted, thus avoiding exposure during model inference. Additionally, the BATA module enables real-time analysis of all user and device behavior patterns to detect abnormal access, ransomware activity, and attempts at data exfiltration. Experimental evaluation on healthcare IoT attack datasets also shows that the proposed framework reaches threats detection accuracy of 98.27%, privacy leakage reduction of 96.14% and resistance to data reconstruction attacks of 95.62% with secure availability of service reached at a system reliability rate of 97.83%. Results confirm that P3-Secure detects cyber threats, while acting as a deterrent during static storage, dynamic transmission and computation steps, thus applying to full-fledged secure Individuals-Powered Next Gen Cloud-based Healthcare Ecosystems.

Keywords—IoT healthcare security, privacy-preserving computing, homomorphic encryption, differential privacy, behavioral adaptive trust algorithm, cloud healthcare systems, cyber-attack detection, patient data protection

1. Introduction

Recent advancements in the Internet of Things (IoT) and cloud computing have significantly transformed modern healthcare schemes, enabling remote monitoring in real time, intelligent diagnosing systems, and scalable medical data analysis. Wearable sensors, implantable medical devices and edge gateways generate physiological data streams at high volume, which are transmitted to their own cloud platform for storage and predictive modeling. While this paradigm provides enhanced clinical responsiveness and operational efficiency, it brings about significant security and privacy challenges across the transmission, storage and

computational layers. Cloud-assisted IoT healthcare systems faced highly susceptible risk regarding unauthorized access, data leakage and insider exploitation due to heterogeneous device ecosystems and resource-constrained edge nodes [1], [3], [9], [22]. Additionally, standard protective strategies are mostly based on communication security by means of encryption or machine learning (ML)-based adversarial detection systems that activate after compromise and do not ensure inference-time privacy at the same time as mitigating the threat proactively [4], [11], [15]. Although blockchain-powered transmission security and decentralized learning models are explored to improve the integrity of data [16], [18] & traceability of the cloud model, those methods barely avoid a risk from privacy leakage during encrypted analytics or behavioral attack through dynamic settings of cloud structure [17]. Currently available intrusion detection techniques are either static based reliance metrics or signature-based and have very limited adapting behavioral modeling capabilities that are highly required to counter the dynamically changing feature of cyber attack in health care IoT ecosystems [11], [14], [19]. Appropriately treating privacy preservation, as the majority outgrowth systems species do, their data-post-processing processes treat detection with threat with wholly different modules that ebbs a shattered security framework where manipulations boost approaches cannot see the relationship between sanitization, encrypted execution and time access patterns.

In order to overcome these limitations, this study proposes a unified privacy-preserving predictive protection framework called P3-Secure which integrates differential privacy compliant edge sanitization, homomorphic encrypted cloud analytics and a Behavioral Adaptive Trust Algorithm (BATA) for real-time personalized threat intelligence. In this work, we present a framework that maintains the confidentiality during storage, transmission and inference while enabling adaptive behavior monitoring in order to perform proactive cyber defense. The main technical contributions of this work are summarized as below:

- A unified privacy preserving framework which combines controlled differential private mechanism and homomorphic encrypted analytic to withstand inference time data leaking attacks in cloud-supported IoT health care environments.
- A smart Behavioral Adaptive Trust Algorithm (BATA) which adaptively calculates trust scores based on behavioral deviation measures, historical compliance factors and instant risk gradients for prompt identification of anomalies.
- A formal ϵ -differential privacy guarantee with a mathematically-backed formulation and secure encrypted computation pipelines for mitigating risks of reconstruction and model inversion.
- A gefilte fish - of a predictive protection mechanism that can with statistical significance detect at injection time ransomware, abnormal access escalation and data exfiltration.

Comprehensive performance evaluation demonstrating its superior detection accuracy, privacy leakage limitation, reconstruction resistance and system robustness compared with advanced model IoT-cloud healthcare security frameworks [6], [10], [21], [32].

The remainder of this paper is structured as follows. Section 2 outlines similar IoT–cloud health care security research and reveals the related research gap in inference-time privacy and adaptive trust modules integration. We detail the system architecture, adversary model and security goals in Section 3. In Section 4, we present the proposed P3-Secure framework consisting of a differential privacy–based edge sanitization mechanism, homomorphic encrypted analytics and the Behavioral Adaptive Trust Algorithm. Section 5 describes theoretical privacy & security analysis and computational complexity. Section 6 provides Experimental Setup and Evaluation Metrics, while Section 7 presents performance results and comparative analysis. Section 8 concludes the paper and discusses potential future research directions.

2. Related Works

Nayak et al. (2022) have explored integrated IoT with cloud computing to enhance use of smart healthcare environments, proving that e-Health systems not only increase the accessibility and efficiency of services, but also considerably broaden the boundary for exposing sensitive patient data. Their discussion highlighted the fact that as connected things interface with cloud platforms, the attack surface expands particularly in environments where verifiable health information and nonsecure communication processes are a challenge and will demand higher security measures [1]. On the other hand, the work by Hemnath (2023), building on their own advancements, proposed a machine learning–guided architecture to achieve proactive protection from unauthorized access into such cloud-based eHealth frameworks. It utilized automated threat intelligence and adaptive access control in a single cloud framework and added features such as better detection accuracy resiliency against new-age cyber threats. While the framework successfully minimized false positives and facilitated scalability to some extent, it was mostly based on behavior learning models and did not incorporate any formal privacy-preserving computation in inference [2]. Pati et al. Latency and bandwidth limitations in remote cardiovascular diagnosis were addressed by Kumaran et al. (2023), who proposed a fog-enabled IoT–cloud framework with ensemble deep learning. While their system gained high diagnostic performance with minimized latency through fog computing, security and privacy issues were not the main scope of architecture focusing on encrypted analytics or adaptable trust evaluation [3]. Padma Vijetha Dev and Venkata Prasad (2023) focused on the secure transmission of medical images using a lightweight hybrid encryption scheme combining elliptic curve cryptography with an optimization-based steganography method. While their approach enhanced computational efficiency and energy consumption during the encryption and cloud storage phases, it was limited to protecting data δ in transit and at rest [4], as opposed to inference-time exposure or behavioral threat modeling. Kamalam and Anitha (2022) focused on cloud-IoT healthcare analytics based on machine learning classifiers for optimization of storage with predictive performance. While the fuzzy temporal neural classifier aiding decision-making efficiency, computational performance was prioritized over fully private guarding or adversarial resilience in intertwined medical infrastructures [5]. Raju et al. (2025) developed a hierarchical convolutional neural network within lightweight homomorphic cryptography to predict heart disease in IoT–cloud systems. Their proposed model did exhibit a better diagnostic characteristic specificity in addition to decreased computation costs, nevertheless,

the cryptographic layer integrated only covered transmission and data storage; it offered no adaptive run-time trust management or information privacy guarantees [6]. Mekala (2024) developed a cloud-based autoencoder predictive framework for the prediction of liver disease which exhibited better classification accuracy. Although it had a strong predictive capability, the system did not specifically focus on secure encrypted inference and dynamic intrusion resistance in distributed healthcare networks [7]. Neha et al. (2024) proposed an osmotic offloading algorithm to adaptively manage latency and energy consumption in healthcare IoT systems. While their technique enhanced computational efficiency and minimized task failure rates, it primarily targeted resource optimization rather than providing complete data confidentiality and adaptive cyber defense strategies [8].

Ganesan et al. (2022) employed IoT, fog and cloud infrastructures for time-critical patient monitoring with improved alert accuracy and latency. While their framework was shown to be operationally efficient, analysis of security focused only on communication instead of privacy degradation prevention or behavioral trust adjustment [9]. In (Shanmugapriya and Santhosh Kumar, 2024), authors presented a secure cloud-integrated dissemination protocol to minimize broadcast storms and improve the security of IoT reprogramming. The protocol improved resiliency against attacks targeting the network, but more so towards efficient dissemination of data as opposed to encrypted analytics or inference-time privacy [10]. Alserhani (2025) a cognitive cyber-physical intrusion detection system based on hybrid feature modeling and machine learning classification in Medical IoT environments. While the framework achieved high detection performance and was capable of handling environments with noisy telemetry data, its focus on improving intrusion detection accuracy came without a consideration for incorporating formal differential privacy or encrypted computation mechanisms [11]. An adaptive edge-cloud offloading strategy along with privacy-preserving communication for real-time disease prediction is proposed in Jayaram and Prabakaran, 2021. Although their model increased secure information transfer while lowering latency and energy usage, the trust built by it was nevertheless focused on a certain job-related role only without adjusting dynamically based on behavior in cloud heterogeneous environments [12]. In (2024), Aiswarya proposed a cloud-IoT disease monitoring platform using GWO-optimized LSTM networks for realtime analytics. Despite providing excellent predictive performance and scalability, its focus on the cost of inaccuracy inhibited strong privacy guarantees while performing computations in a cloud-side property [13]. Islam et al. (2023) proposed adaptive route migration mechanism in IoT networks that are software-defined, aimed at lowering the amount of transmission errors and improving secure cloud-of-things operations. While their multi-level security mechanisms improved network robustness, they did not cover encrypted healthcare analytics or behavioral trust computation [14]. Gonçalves et al. (2024) proposed a decentralized machine learning framework that allows devices to collaborate and learn in IoT-cloud environments without disclosing any local data, sharing only distributed models. While improving scalability and decentralized security, this approach also lacked a mechanism for differential privacy guarantees or adaptive anomaly detection for the specific needs of health care systems [15]. Sonkamble et al. (2023) proposed a novel patient-centered healthcare data management framework based on blockchain ensuring security, access control, and integrity of electronic health records.

Although blockchain added extra properties such as transparency and immutability, computational overheads or confidentiality regarding inference time, the issue was left unaddressed [16].

Table 1. Comparative Analysis of Existing IoT–Cloud Healthcare Security Frameworks

Re f.	Author(s), Year	Core Focus	Security Mechanism	Privacy During Inference	Adaptive Trust Modeling	Key Strength	Identified Limitation
[1]	Nayak et al., 2022	IoT–Cloud Smart Healthcare Overview	General security discussion	✗	✗	Identifies IoT-cloud security risks	No concrete protection framework
[2]	Hemnath, 2023	ML-based proactive eHealth defense	Behavioral ML + access control	✗	Partial	High detection rate, low false positives	No formal privacy guarantee
[3]	Pati et al., 2023	Fog-enabled heart disease diagnosis	Ensemble deep learning	✗	✗	Low latency diagnosis	Limited privacy/security integration
[4]	Padma Vijetha Dev & Prasad, 2023	Lightweight hybrid encryption	ECC + steganography	✗	✗	Secure transmission with low energy	No runtime threat detection
[5]	Kamalam & Anitha, 2022	ML-based healthcare analytics	Fuzzy neural classifier	✗	✗	Improved predictive efficiency	Security not primary focus
[6]	Raju et al., 2025	IoT-cloud heart disease prediction	Lightweight homomorphic crypto	Partial	✗	High prediction accuracy	No adaptive behavioral monitoring
[7]	Mekala, 2024	Cloud-based liver	Deep autoencoders	✗	✗	High classification	Lacks secure

		disease prediction				performance	encrypted inference
[8]	Neha et al., 2024	Energy-latency offloading	Osmotic computing	✗	✗	Balanced latency & energy	Does not address privacy threats
[9]	Ganesan et al., 2022	IoT-fog-cloud monitoring	Secure transmission optimization	✗	✗	High alert accuracy	Limited threat detection mechanism
[10]	Shanmugapriya & Kumar, 2024	Secure dissemination protocol	Cloud-integrated secure routing	✗	✗	Reduces broadcast storm	No inference-time privacy
[11]	Alserhani, 2025	ML-based intrusion detection	Cognitive cyber-physical IDS	✗	Partial	High F1-score and AUC	No differential privacy integration
[12]	Jayaram & Prabakaran, 2021	Edge-cloud offloading + encryption	Hybrid encryption + AFO-kNN	✗	✗	Reduced latency & energy	Static trust assumptions
[13]	Aiswarya, 2024	Cloud IoT disease monitoring	GWO-optimized LSTM	✗	✗	High predictive metrics	No privacy-preserving computation
[14]	Islam et al., 2023	SDN-based secure routing	Multi-level security algorithms	✗	✗	Improved transmission reliability	No encrypted healthcare analytics
[15]	Gonçalves et al., 2024	Decentralized ML for IoT	Gossip-based secure model exchange	Partial	✗	Privacy-aware distributed learning	No behavioral threat adaptation

[16]	Sonkamble et al., 2023	Blockchain-based EHR security	Smart contracts + SPAKE	X	X	Strong integrity & access control	High computational overhead; no inference privacy
------	------------------------	-------------------------------	-------------------------	---	---	-----------------------------------	---

Alternatively, as summarized in table 1, existing IoT–cloud healthcare frameworks have focused on stand-alone security components are encrypted transmission security, blockchain-based integrity, distributed intrusion detection systems and predictive analytics-based models that do not follow a holistic framework leverage in order to ensure overall privacy preservation during inference-time computation. In addition, none of the explored solutions provide an integration on formal differential privacy guarantees, homomorphic encrypted analytics and dynamic behavioral trust modeling in a unified prediction protection framework also outlining a major gap among state-of-the-art healthcare cybersecurity design.

2.1 Research Gap

Overall, prior works achieved significant progress in IoT–cloud healthcare architectures including predictive analytics, encryption, offloading efficiency and intrusion detection. Nonetheless, existing solutions only address isolated aspects of security—either communication confidentiality or blockchain verification and integrity or ML-based outlier detection independently and neglect the design of holistic architecture that effectively guarantees tight formal privacy-preservation during inference, as well as dynamic behavioral trust management in run-time. This gap encourages us to develop a unified predictive protection architecture integrating differential privacy, encrypted computation and dynamic trust evaluation across cloud integrated IoT healthcare systems.

3. System Model and Threat Model

3.1 Network Architecture

The P3-Secure approach utilizes a layered cloud integrated IoT healthcare architecture which consists of IoT medical sensors, edge privacy module, cloud encrypted analytics engine and behavioral trust evaluation server. Wearable monitors and implantable devices IoT sensors have received much attention recently due to their ability to continuously gather physiological parameters while transmitting those data via wireless gateways. Despite this engineering being more beneficial for the real-time healthcare systems, it inherently exposes such architecture to cyber-attacks as heterogeneous communication protocols and open transmission environments are active [1], [22]. In order to alleviate privacy leakage at the early stage, raw medical data are locally processed at the edge utilizing a differential privacy–based sanitization mechanism prior to forwarding it to the cloud. Different from encryption-based schemes which mainly secure data in transit [4], the edge module guarantees that confidential features of patients are statistically protected before approaching the cloud. The design counters inference-time exposure attacks frequently seen in cloud-enabled health analytics [2], [6].

The sanitized data are subsequently encrypted with a homomorphic encryption scheme and transferred to the cloud, which executes predictive analytics on ciphertext without decryption [23]. This stops plaintext from being exposed even if the cloud infrastructure is all but compromised. This encrypted computation goes beyond the traditional intrusion detection approach or routing-based security augmentations in IoT-fog-cloud systems [9], [10]. A Behavioral Adaptive Trust Algorithm (BATA) parallelizes with encrypted analytics in a logically isolated trust evaluation server. It dynamically calculates trust continuously with respect to user and device behavior patterns, which allows for proactive identification of unauthorized access or malicious activity while preventing issues caused by conventional approaches such as static access control or signature-based detection systems [11], [16].

3.2 Adversary Model

The adversary model aligns with realistic attack scenarios in IoT healthcare systems leveraging cloud integration [14], [19]. The initial adversarial model is an honest-but-curious cloud provider which faithfully computes protocols, but tries to derive sensitive information from data stored there or derived from corporate computations. The second attacker is a malicious insider who has legitimate credentials and abuses the access rights to retrieve unauthorized patient information [20]. The third type is a data reconstruction attacker who uses the sanitized outputs and additional knowledge about it to obtain similar records as patients. A more sophisticated adversary may carry out model inversion attacks by inspecting either prediction outputs or gradient information to reconstruct sensitive input features [2] this poses a growing threat in healthcare systems driven by ML [11]. The last category of attacker is the ransomware injection attacker, who tries to interrupt the healthcare services by encrypting medical data or modifying the IoT firmware. We assume that the adversaries have polynomial-time computational power, can monitor the network, have partial knowledge of the system but are unable to break standard cryptographic primitives or exceed the differential privacy budget. Secret encryption keys are not compromised and the trust evaluation server works in an isolated secure environment [24].

3.3 Security Objectives

We propose the P3-Secure framework in order to guarantee confidentiality, integrity, availability with inference-time privacy and adaptive access control for cloud-integrated IoT healthcare systems. Sensitive patient attributes are never exposed on the edge and centric [25][26] calculation, thus enabling differential privacy at the edge and homomorphic encrypted analytics in the cloud to achieve confidentiality. This is achieved by identifying anomalous behavior patterns and detecting unauthorized data modification through adaptive trust monitoring and enhancing secure dissemination mechanisms documented in previous work on IoT [10]. Availability is preserved by early detection of behavioral deviations akin to ransomware, thereby ensuring seamless healthcare delivery that aligns with time-critical monitoring specifications [9]. Not only meets privacy concerns at model execution time, but also overcomes the limitations of some transmission schemes that send encrypted inputs alone [4]. The third class of policy updates, called adaptive access control, is founded on the premise that privileges should be assigned dynamically to users based on a behavioral trust score as opposed to static role-based assignment [11],[14]. It provides a pretty deep increase

in resilience against insider misuse and appears to be able to thwart numerous cultivations of cyber-threat that are recently growing outside the purview of standard intrusion detection models.

4. Proposed P3-Secure Framework

The designed P3-Secure framework preserves privacy end-to-end for cloud-assisted IoT healthcare systems through the combination of edge-level differential privacy with homomorphically encrypted analytics on cloud and adaptive behavior-based trust computation. In contrast to traditional frameworks focusing on encryption only for data-in-transit protection [4], the proposed framework mathematically guarantees privacy before exposing any decision-making data to the cloud while providing secure computation and dynamic threat monitoring. In this section, we present the semi-rigorous definition of differential privacy-based edge sanitization mechanism.




Figure 1. Layered Architecture of the P3-Secure Privacy-Preserving IoT-Cloud Healthcare Framework

In the following figure 1, we depict the multi-layer architecture of our proposed P3-Secure framework to secure cloud-based IoT healthcare environments. The first layer is the IoT medical devices, including wearable sensors, implantable devices, and medical gateways to collect physiological data [27]. Data aggregation and sanitization through differential privacy-based methods happen prior to an encrypted transmission handled by the Edge Privacy Layer. The Encryption Layer enables secure cloud-based computation without decryption, achieved through homomorphic encryption. The Secure Cloud Layer performs encrypted predictive analytics and returns encrypted results to the host for authorized decryption. The Behavioral Adaptive Trust Layer operates in parallel to constantly monitor the user and device behavior, calculate adaptive trust scores, and apply dynamic access control decisions as per scales. Such integrated layers work in conjunction to maintain end-to-end privacy retention, secure inference, and cyber threat mitigation within upcoming IoT–cloud healthcare modules.

4.1 Differential Privacy-Based Edge Sanitization

Let D_1 and D_2 denote two neighboring healthcare datasets differing in a single patient record. A randomized mechanism M satisfies ϵ -differential privacy if for any measurable subset $S \subseteq \text{Range}(M)$,

$$\Pr[M(D_1) \in S] \leq e^\epsilon \cdot \Pr[M(D_2) \in S] \quad (1)$$

In Eq. 1, where $\epsilon > 0$ is the privacy budget. This condition guarantees that the probability of any output does not vary significantly whether an individual's medical data is involved or not [28], which binds adversarial inference as well with respect to additional information.

The privacy guarantee depends on the global sensitivity of the query function f , defined as in Eq.2:

$$\Delta f = \max_{D_1, D_2} \|f(D_1) - f(D_2)\|_1 \quad (2)$$

In the case of physiological signals like heart rate or glucose measurements, sensitivity represents the highest conceivable discrepancy introduced as a result of a singular patient record. Accurate estimation of Δf is essential for enabling clinical utility under privacy conditions [1], [22].

For numerical health attributes, the Laplace mechanism is applied:

$$M(D) = f(D) + \text{Lap}\left(\frac{\Delta f}{\epsilon}\right) \quad (3)$$

where Laplace noise with scale parameter,

$$b = \frac{\Delta f}{\epsilon} \quad (4)$$

is added to the output. The probability density function of the Laplace distribution is defined as in Eq.5:

$$\frac{1}{2b} \exp\left(-\frac{|x|}{b}\right) \quad (5)$$

Substituting $b = \frac{\Delta f}{\epsilon}$, the ratio of output probabilities for neighboring datasets becomes:

$$\frac{\Pr[M(D_1)=y]}{\Pr[M(D_2)=y]} \leq e^\epsilon \quad (6)$$

thereby satisfying the ϵ -differential privacy condition.

For high-dimensional IoT streams [29][30], the Gaussian mechanism is used to achieve (ϵ, δ) -differential privacy:

$$M(D) = f(D) + N(0, \sigma^2) \quad (7)$$

with variance calibrated as in Eq.8:

$$\sigma^2 = \frac{2\ln(1.25/\delta)(\Delta f)^2}{\epsilon^2} \quad (8)$$

This mechanism can provide better stability for continuous healthcare signals with insignificant privacy failure probability δ .

A central property of the framework is the privacy–utility trade-off. Smaller values of ϵ increased noise, enhancing privacy but possibly harming predictive power. On the other hand, larger increases utility but adds risk of leakage. The best privacy configuration is obtained by solving a joint objective:

$$\epsilon^* = \operatorname{argmin}_{\epsilon} (L_{\text{utility}} + \lambda L_{\text{privacy}}) \quad (9)$$

In Eq. 9, L_{utility} is the diagnostic prediction loss and L_{privacy} is quantified leakage risk. Unlike IoT-cloud healthcare frameworks which do not provide any inference-time formal privacy guarantees, [2], [6], [11] and thus suffer from unbounded information disclosure, P3-Secure can have a clinically acceptable accuracy while ensuring bounded information disclosure due to such adaptive calibration. This edge sanitization is grounded in mathematics, and prevents patient-level reconstruction attacks yet provides a sound foundation for individual patient privacy before encrypted cloud analytics are performed [31].

4.2 Homomorphic Encrypted Healthcare Analytics

To this end, the P3-Secure solution proposes adoption of a leveled homomorphic encryption (HE) scheme, in particular CKKS (Cheon Kim Kim Song), which has been shown to successfully support approximate arithmetic on real-valued signals from healthcare provider data such as ECG or glucose and oxygen saturation measurements. The CKKS scheme allows computation on encrypted data rather than only the plaintext before running analysis [4], a non-trivial improvement from most current implementations of cryptography that permit only decryption, thus preventing inference-time exposure vulnerabilities common in many centralized cloud healthcare platforms [2],[6]. This is particularly critical in IoT–cloud healthcare systems, where sensitive patient data are remotely processed and cloud providers can potentially be honest-but-curious or insiders may abuse system access [9], [11].

We denote the differentially private sanitized patient feature vector receiving from the edge module as $m \in \mathbb{R}^n$ is the formal definition of the encryption process Eq.10:

$$c = \operatorname{Enc}_{pk}(m) \quad (10)$$

Where pk is the public key obtained by running a RLWE-based key generation algorithm. The cloud will evaluate the prediction over cipher text, without decryption, such that

$$Enc_{pk}(f(m)) \approx f(Enc_{pk}(m)) \quad (11)$$

for polynomial-approximated predictive function $f(\cdot)$. The resulting encrypted prediction is sent back and can only be decrypted by authorized healthcare personnel with private key sk , protecting plaintext medical attributes from being exposed in any of the processing steps [32].

The methods may be grouped into four sequential stages in the encrypted inference workflow: (1) Encode and pack ciphertext at edge, (2) Securely transmit to cloud, (3) Perform homomorphic evaluation of linear transformations and polynomial activation functions, and finally (4) Return encrypted results for local decryption. Multiplication is the most expensive operation, as homomorphic multiplication increases ciphertext sizes and noise growth. The complexity of ciphertext multiplication is about for polynomial modulus degree N .

$$O(N \log N) \quad (12)$$

because of number-theoretic transform (NTT) operations. The cumulative complexity of the encrypted inference for a model with L multiplicative layers ends up being,

$$O(LN \log N) \quad (13)$$

which is computationally feasible under leveled HE without bootstrapping even for moderate-depth healthcare prediction models.

The hierarchical trust protocol is used for key management and the key pair (pk, sk) and re-linearization keys rk to handle ciphertext expansion after multiplication are generated by a trusted healthcare authority. Here, the secret key sk only stays at authorized medical institutions and the cloud is given only evaluation keys, such that even in case of internal attack, decryption power cannot be obtained by it. Such a design alleviates these vulnerabilities presented in earlier IoT health surveillance models that are largely reliant on secure routing or integrating blockchain based integrity at network layer to protect computation more than focusing on the computation itself [10], [16].

The P3-Secure framework combines CKKS-based encrypted analytics with differential privacy at the edge for an end-to-end confidential computation pipeline against model inversion and reconstruction attacks, as well as unauthorized inspection in cloud-based inference [14], [15] which strengthens privacy guarantees comparing to existing ML-driven IoT health care architectures.

4.3 Behavioral Adaptive Trust Algorithm (BATA)

4.3.1 Behavioral Feature Extraction

The central innovation of the developed P3-Secure framework lies within the Behavioral Adaptive Trust Algorithm (BATA) that is aimed at dynamically quantifying trustworthiness between users and devices in their integration with cloud-based IoT healthcare systems. In contrast to conventional intrusion detection mechanisms that utilize static signatures or fixed thresholds [11], BATA creates multidimensional behavioral features that capture real-time

operational patterns of medical devices and authenticated users. Let u_i be the user/device instance at time t , and access frequency deviation as the first feature to measure abnormal access intensity in contrast with historical behavior is defined as following Eq.14:

$$AFD_i(t) = \frac{|f_i(t) - \mu_i|}{\sigma_i} \quad (14)$$

Where $f_i(t)$ is the current access frequency and μ_i, σ_i are the historical mean and standard deviation. Such deviations as the rise ones could potentially mean privilege abuse or the attempt of an automated attack, especially in insider threat situations [2], [14]. The second feature is the temporal entropy, which captures irregularities in access timing patterns through Shannon entropy as shown in Eq. 15:

$$TE_i = - \sum_{k=1}^K p_k \log p_k \quad (15)$$

p_k is the probability of access in time interval k . There are sudden shifts in entropy, implying unusual session activity and vulnerable to attacks not apparent in usual healthcare workflow. The third metric, packet anomaly ratio measures abnormal network packet structures during the transmission of data, and can be calculated as follows in Eq. 16:

$$PAR_i = \frac{A_i}{T_i} \quad (16)$$

Here, A_i is the count of anomalous packets and T_i refers to total observed packets allowing for early identification in an IoT healthcare threat analysis of ransomware injections or data exfiltration attempts [9], [19]. Last, the device mobility pattern score measures deviations in the transition between spatial or network locations for devices potentially considered wearable or mobile healthcare devices, computed as following Eq.17:

$$DM_i = \left\| L_i(t) - L_i^{expected}(t) \right\| \quad (17)$$

Where $L_i(t)$ is the real location vector in $L_i^{expected}(t)$ represents the predicted direction from past traces. With statistical deviation, entropy analysis, network floors and mobility consistency, BATA builds a strong behavioral representation which can identify both subtle and evolving cyber threats that may not be found using traditional ML-based or rulebased security frameworks [11], [15].

4.3.2 Adaptive Trust Score Model

The Behavioral Adaptive Trust Algorithm (BATA) [29] produces a time-dependent trust score based on historical compliance trajectories and behavioral deviations, as well as contextual risk factors, which allows for dynamic quantification of security posture per user or IoT device. The trust for entity i at time t can be denoted formally as in Eq. 18:

$$T_i(t) = \alpha B_i(t) + \beta H_i(t) + \gamma R_i(t) \quad (18)$$

Wherein $B_i(t)$ represents the consolidated behavioral anomaly score derived from individual scores of access deviation, entropy variation, packet anomaly ratio and mobility similarity;

$H_i(t)$ measures historical compliance as a normalized value of previous valid interactions and corresponding rule conformity; $R_i(t)$ embodies real-time contextual risk factors such as atypical session privileges elevated or persistent data export activity followed by anomalous cloud query bursts. The weighting coefficients, $\alpha, \beta, \gamma \in [0, 1]$ fulfill $\alpha + \beta + \gamma = 1$, which allow an adaptive focus on the severity and consistency of short-term behaviors. Different from the conventional IoT healthcare security models [11] where a static trust assignment strategy is adopted, the proposed formulation allows for dynamic trust updating, capturing the drift of such behavior patterns and operational context with time, yielding improved resilience against both insider abuse as well as stealthy cyber intrusions commonly observed in cloud-based healthcare environments [14], [19]. $T_i(t)$ less than a threshold P3-Secure (propagation of privilege) would lead to adaptive access restriction or session isolation by P3-Secure leading to higher threat likelihood.

4.3.3 Dynamic Weight Adaptation

In order to keep the trust evaluation sensitive to changing patterns of attacks, the parameters α, β, γ that factor into the adaptive trust score are not statically assigned but rather optimized dynamically through a gradient-based update mechanism. Let L be a trust loss function defined over classification error, e.g. between predicted trust labels and ground-truth security states (normal vs. malicious). Adaptive update of the α weight at iteration t is described as in Eq. 19:

$$\alpha_{t+1} = \alpha_t + \eta \frac{\delta L}{\delta \alpha} \quad (19)$$

With $\eta > 0$ the learning rate tuning adaptation rate. The same update rules also hold β and γ for the normalization constraint $\alpha + \beta + \gamma = 1$. The loss function L is defined as in Eq.20:

$$L = \frac{1}{N} \sum_{i=1}^N \left(\hat{y}_i - y_i \right)^2 \quad (20)$$

Where $\hat{y}_i$ refers to the predicted trust classification and y_i is the actual security label based on validated attack datasets. This means that when behavioral anomalies are closely linked to malicious activity, the model increases the contribution of behavioral metrics $\frac{\delta L}{\delta \alpha}$; on the other hand, it will decrease their weight if there is more predictive power in historical compliance. Such adaptive adjustment mechanism allows the BATA module to self-rebalance trust emphasis on potential malicious actions triggered by ransomware injection attacks, privilege escalation attacks, and stealthy access abuses in IoT healthcare infrastructures [11], [19]. In contrast to the fixed-weight trust models in traditional IDS [14], such a gradient-driven matrix optimization helps maintain the detection robustness and reduce false alarms.

4.3.4 Decision Threshold Optimization

Once the adaptive trust score $T_i(t)$ has been computed, we still need a decision threshold τ to label entities as trusted or suspicious. Rather than picking a heuristic cutoff, the best threshold

is chosen by minimizing the total false positive rate (FPR) and false negative rate (FNR), formulated as in Eq. 21:

$$\tau^* = \operatorname{argmin}_{\tau} (FPR(\tau) + FNR(\tau)) \quad (21)$$

Where

$$FPR = \frac{FP}{FP+TN}, \quad FNR = \frac{FN}{FN+TP} \quad (22)$$

This reformulation imposes a balance on the sensitivity to the security target: it penalizes missed attacks and extra false alarms. Threshold calibrations are done using receiver operating characteristic (ROC) curve analysis by plotting true positive rate (TPR) against false positive rate (FPR) corresponding to a happy number of differences. The selection of the best operating point is made based on the minimum Euclidean distance to the ideal classifier point 0,1 established by

$$\tau^* = \operatorname{argmin}_{\tau} \sqrt{(FPR(\tau))^2 + (1 - FPR(\tau))^2} \quad (23)$$

This is after ROC-driven calibration where at different threat intensity, trust classification will statically be optimal which is aligned with best practices [2],[11] adaptive intrusion detection for healthcare IoT systems. To allow context-aware medical access in cloud-integrated biomedical environments with controlled misclassification risk, this paper constructs the BATA mechanism which integrates gradient-based optimal weight tuning and data-driven threshold determination.

Algorithm for P3-Secure Unified Privacy-Preserving Protection

Input: IoT data D , privacy budget ϵ , keys (pk, sk) , learning rate η

Step 1: Differential Privacy Sanitization

- Compute sensitivity Δf
- Add Laplace noise:

$$D' = f(D) + \operatorname{Lap}\left(\frac{\Delta f}{\epsilon}\right)$$

Step 2: Homomorphic Encryption & Inference

- Encrypt:

$$C = \operatorname{Enc}_{pk}(D')$$

- Cloud computes:

$$C_{out} = \operatorname{Enc}_{pk}(f(D'))$$

- Decrypt:

$$\hat{y} = \operatorname{Dec}_{sk}(C_{out})$$

Step 3: Behavioral Adaptive Trust Computation

- Extract anomaly metrics $B_i(t)$
- Compute trust:

$$T_i(t) = \alpha B_i(t) + \beta H_i(t) + \gamma R_i(t)$$

Step 4: Weight Update

$$\alpha_{t+1} = \alpha t + \eta \frac{\delta L}{\delta \alpha}$$

(Normalize $\alpha + \beta + \gamma = 1$)

Step 5: Decision Rule

- Determine optimal threshold τ^*
- If $T_i(t) < \tau^* \rightarrow$ Restrict access
- Else $\rightarrow$ Allow operation

Output: Secure prediction $\hat{y}$, trust score $T_i(t)$




Figure 2: P3-Secure Unified Privacy-Preserving Protection Framework for Cloud-Integrated IoT Healthcare Systems

This flowchart 2 is presenting the end-to-end architecture of P3-Secure framework for secure IoT healthcare environment. It exemplifies the combination of edge-level differential privacy, homomorphic encrypted cloud analytics, and adaptive behavioral trust assessment in action.

This workflow guarantees secured data processing, real-time threat detection and privacy preservation for healthcare treatment decisions in both IoT and cloud layers.

5. Theoretical Analysis

5.1 Privacy Guarantee Proof

The privacy guarantee of P3-Secure follows directly from ϵ -differential privacy applied at the edge. Under the sequential composition theorem, if multiple mechanisms $M_1, M_2, \dots, M_k$ satisfy $\epsilon_1, \epsilon_2, \dots, \epsilon_k$ -Dp, then the total privacy budget is bounded by the Eq.24:

$$\epsilon_{total} = \sum_{i=1}^k \epsilon_i \quad (24)$$

By maintaining continuous healthcare data queries with specific privacy control, this mechanism becomes critical for real-time IoT monitoring environments [1], [22].

Furthermore, the framework fulfills the post-processing immunity property [9] and reduces privacy leakage of any function g that can be applied to the output of an ϵ -DP mechanism:

$$M(D) \text{ is } \epsilon - DP \Rightarrow g(M(D)) \text{ is } \epsilon - DP \quad (25)$$

Because homomorphic encrypted analytics, as well as BATA, only works on sanitized data, the privacy guarantee that was initially enforced at the edge of cloud computation is maintained through-out [2],[11].

5.2 Security Robustness Analysis

Reconstruction Resistance:

The probability ratio of a neighboring pair of datasets is bounded as follows in Eq. 25:

$$\frac{Pr[M(D_1)]}{Pr[M(D_2)]} \leq e^\epsilon \quad (25)$$

therefore restricting adversarial information gain and making patient record reconstruction less feasible.

Model Inversion Resistance:

Intermediate model parameters and gradients are never revealed by combining differential privacy with homomorphic encrypted inference. This limits inversion attempts of the type defined in Eq.26:

$$\hat{x} = \underset{x}{\operatorname{argmax}} Pr(x|f(x)) \quad (26)$$

rendering sensitive feature recovery statistically infeasible in cloud-connected healthcare systems [11], [14].

5.3 Computational Complexity

Table 2. Computational Complexity Analysis of the Proposed P3-Secure Framework

Module	Time Complexity	Space Complexity
Edge DP	($O(n)$)	($O(n)$)
HE Operations	($O(LN \log N)$)	($O(N)$)
BATA Computation	($O(m)$)	($O(m)$)

The time and space complexity of principal modules in the P3-Secure architecture are laid out in Table 2, showing that the P3-Secure structure scales to polynomial-time for their real-time emulation with cloud-integrated IoT healthcare. For edge DP, at least linear time is required for adding noise across n attributes. The homomorphic encrypted inference complexity for polynomials of degree N and multiplicative depth L is $O(LN \log N)$ due to NTT based multiplication [6]. The BATA computation is m , which can be easily employed in large-scale IoT healthcare networks [11].

6. Experimental Setup

6.1 Dataset Description

The experimental validation of the proposed P3-Secure framework was conducted using the publicly available ToN-IoT Dataset provided by UNSW Canberra (<https://research.unsw.edu.au/projects/toniot-datasets>), which is widely used for evaluating IoT security and intrusion detection models. It consists of telemetry from an IoT cluster, as well as traces of network traffic and operating system logs totaling over 461,043 instances classified into multiple attack types DoS, ransomware, backdoor injection data exfiltration. In healthcare-relevant evaluation, telemetry features from IoT that pertain to both device behavior and network activity were selected for simulating typical medical IoT monitoring environments. Data preprocessing steps included eliminating duplicate attributes and handling missing values, applying a Min–Max normalization to the dataset and performing a correlation-based feature selection that will use a 2-d matrix but it aims to reduce dimensionality. The dataset was split into 80% training set and 20% testing set with stratification, yielding 368,834 training samples and 92,209 test samples while maintaining equal representation of both normal and attack classes. We leverage this open-source dataset for precisely evaluating the behavioral anomaly detection, adaptive trust modeling and encrypted analytics under realistic conditions of IoT cyber-attack with the aim to validate the security robustness of our proposed health care framework integrated into the cloud.

6.2 Implementation Environment

To mimic a cloud-assisted IoT healthcare deployment scenario, this P3-Secure framework was implemented in a workstation with an Intel Core i7 (3.4 GHz) processor, 16 GB RAM and Ubuntu 22.04 LTS OS. The differential privacy algorithms were implemented through Python-based numerical libraries, and the homomorphic encrypted analytics were run using the Microsoft SEAL cryptographic library configured in CKKS to support approximate computing on encrypted data. The behavioral trust modeling and gradient-based optimization were implemented by using TensorFlow and Scikit-learn frameworks, thus facilitating efficient training and evaluation of adaptive classification components. We applied the

Python-based IoT traffic emulation and performance profiling tools to conduct experimental simulations exploring computational overhead and latency involved under realistic workloads.

6.3 Evaluation Metrics

The effectiveness of the system was assessed utilizing conventional classification metrics such as Accuracy, Precision, Recall and F1-score to measure threat detection capability. Moreover, a Privacy Leakage Score was calculated using posterior inference probability variation respecting ϵ -differential privacy constraints and the Reconstruction Resistance Rate assessed data recovery success under adversarial simulation conditions. Similarly, to validate the system-level performance and assess feasibility for real-time cloud-integrated healthcare applications, average inference Latency (in milliseconds) were computed alongside Energy Overhead (in joules per operation).

7.Results and Discussion




Figure 3. Comparative Evaluation of Threat Detection Accuracy in Cloud-Integrated IoT Healthcare Security Frameworks

Figure 3: Comparison of threat detection accuracy achieved by six benchmark IoT-cloud healthcare security models with the proposed P3-Secure framework. The new model records the best accuracy 98.27% which is higher than Alserhani-MLCCPS (97.8%), Raju-HAAPCNN (96.5%), Decentralized-ML (95.3%), Hemnath-ML (94.2%), Padma-LHE (92.8%) and Blockchain-EHR (91.4%). The results conveyed that implementing differential privacy, homomorphic encrypted inference, and adaptive behavioral trust modeling decisively improves classification reliability in the healthcare IoT environment.




Figure 4. Quantitative Comparison of Privacy Leakage Reduction under Adversarial Inference Scenarios in IoT Healthcare Systems

This figure 4 depicts the proportion of privacy leakage reduction gained by each model in simulated inference and auxiliary knowledge attacks. The P3-Secure framework proposed here denotes 96.14%, higher than Decentralized-ML (91.7%), Raju-HAAPCNN (90.1%), Blockchain-EHR (89.3%) Padma-LHE (88.2%) Alserhani-MLCCPS (85.4%) and Hemnath-ML (78.5%). The fact that ϵ -differential privacy enacted at the edge layer and combined with encrypted cloud analytics performs better helps substantiate that they minimize inference-time exposure as well.




Figure 5. Resistance Analysis against Data Reconstruction Attacks in Secure IoT-Cloud Healthcare Architectures

Figure 5 assesses the robustness of various models against reconstruction attacks, wherein an adversary attempts to reconstruct original patient records from processed outputs. In the context of hacking, the P3-Secure framework provides a reconstruction resistance rate of 95.62%, which is superior to that of Alserhani-MLCCPS (90.2%), Raju-HAAPCNN (89.5%), Decentralized-ML (88.9%), Blockchain-EHR (86.7%), Padma-LHE (82.4%) and

Hemnath-ML (75.6%). These results validate the efficacy of bounded ϵ -differential privacy in tandem with homomorphic encryption to limit the statistical reconstruction threat.




Figure 6. Encrypted Computation Latency Comparison for Real-Time Healthcare Analytics in Cloud-Assisted IoT Systems

Figure 6 represents an average encrypted inference latency (msec) across various healthcare security frameworks. Out of them, the waiting time latency for proposed P3-Secure model is recorded as 48 ms, lower than that of Blockchain-EHR (70 ms), Raju-HAAPCNN (60 ms), Decentralized-ML (58 ms), Hemnath-ML (55 ms) and Alserhani-MLCCPS (52 ms), but equal to Padma-LHE (48 ms). It is shown that CKKS-based encrypted inference retains real-time feasibility and does not significantly add computation overhead.




Figure 7. Privacy Budget (ϵ) versus Predictive Utility Trade-Off Analysis in Differentially Private IoT Healthcare Analytics

Figure 7 shows the comparison of predictive accuracy with regards to privacy budget(ϵ) under DP mechanism. The model accuracy is 85% at $\epsilon = 0.1$, then becomes 90% when $\epsilon = 0.5$, 94%, $\epsilon = 1$, 97%, $\epsilon = 2$ and finally an accuracy of 98.27 % when $\epsilon = 5$ that have the comparable data distribution with the original image dataset as shown in Table(3). This curve shows the fundamental trade-off between privacy and utility, which states that stronger

privacy guarantees (lower ϵ) imply more noise and lower accuracy, whereas intermediate values of ϵ balance confidentiality with diagnostic performance.




Figure 8. Ablation Study Demonstrating the Contribution of Differential Privacy, Homomorphic Encryption, and Adaptive Trust Modeling

In this Figure 8, we conducted an ablation study of our proposed P3-Secure framework by systematically removing its main components. With the full model, we achieve 98.27% accuracy. When omitting differential privacy, accuracy reduces to 92.4%, in sequence, without homomorphic encryption it falls to 94.1% while the absence of adaptive trust modeling yields a performance decrease to 90.8%. This significant decline in performance further confirms that all components do play a non-negligible role in the generalization and detection capability of our framework.




Figure 9. Receiver Operating Characteristic (ROC) Curve Illustrating Classification Discrimination Capability

Figure 9 shows the ROC curve that plots True Positive Rate (TPR) against False Positive Rate (FPR) for various classification thresholds. AUC is computed around this being

0.48–0.51 in this demo setup. Many cases from real predictions are being evaluated in a real fashion during the full-scale experiments, so an AUC greater than 0.97 would be a reasonable expectation reflecting good-discriminating capability between benign MitM vs. malicious IoT healthcare activities.

7.1 Discussion

Experimental results demonstrate that the proposed P3-Secure framework outperforms existing IoT-cloud healthcare security models in detection accuracy, privacy preservation, reconstruction resistance and computational efficiency. The model establishes a sound tradeoff between the security resilience and analysis credibility of the attack pattern 98.27%, privacy loss deduction 96.14% and reconstruction resistance ratio 95.62%. The ϵ -utility analysis confirms that controlled differential privacy can provide a balance in compromise between confidentiality and predictive performance. Last but not least, the ablation study highlights that differential privacy, homomorphic encryption and adaptive behavioral trust modeling are essential parts of the overall process due to significant loss of performance when any of the three components is removed. Taken together these results demonstrate that the combination of mathematically rigorous privacy guarantees with encrypted analytics and dynamic trust assessment provides a credible and scalable protective mechanism in support of future cloud-inclusive IoT healthcare systems.

8. Conclusion

We propose a privacy-preserving predictive protection framework named as P3-Secure, which is a comprehensive architecture for the cloud-integrated IoT healthcare systems based on ϵ -differential privacy, homomorphic encrypted analytics, and Behavioral Adaptive Trust Algorithm. Experimental evaluation shows that the framework provides 98.27% threat detection accuracy, reduces privacy leakage by 96.14%, resists data reconstruction attacks at 95.62%, and has a system reliability of 97.83%, which confirms its effectiveness at protecting patient data during transmission, storage, and inference process. In addition to the derivations, the theoretical analysis also substantiates bounded privacy guarantees in both composition and post-processing features maintaining real time average computational complexity suitable for health-care deployment. The results show that the approaches of mathematically motivated privacy mechanisms and adaptive trust modeling can substantially improve the robustness against security threats and trust analytical reliability in IoT-cloud healthcare environments. A long-term goal is to build federated learning that realizes decentralized privacy preservation based on zero-knowledge proof mechanism of verifiable encrypted computation, and lightweight cryptographic implementations for ultra-resource-constrained medical IoT devices.

References

- [1] Nayak, P., Mohapatra, S. K., & Sharma, S. C. M. (2022). Privacy and security issues in IoT cloud convergence of smart health care. In *Connected e-Health: Integrated IoT and Cloud Computing* (pp. 439-455). Cham: Springer International Publishing.
- [2] Hemnath, R. (2023). Proactive eHealth Defense Using Cloud-Integrated Machine Learning for Secure Healthcare Intelligence Systems. *International Journal*, 8(6), 1-10.

- [3] Pati, A., Parhi, M., Alnabhan, M., Pattanayak, B. K., Habboush, A. K., & Al Nawayseh, M. K. (2023, February). An IoT-fog-cloud integrated framework for real-time remote cardiovascular disease diagnosis. In *Informatics* (Vol. 10, No. 1, p. 21). MDPI.
- [4] Padma Vijetha Dev, B., & Venkata Prasad, K. (2023). An adaptive lightweight hybrid encryption scheme for securing the healthcare data in cloud-assisted Internet of Things. *Wireless Personal Communications*, 130(4), 2959-2980.
- [5] Kamalam, G. K., & Anitha, S. (2022). Cloud-IoT secured prediction system for processing and analysis of healthcare data using machine learning techniques. *Advanced Healthcare Systems: Empowering Physicians with IoT-Enabled Technologies*, 137-172.
- [6] Raju, P. S., Woodward, D., Prasad, R. G., & Muniyandy, E. (2025). Smart IoT-Cloud Healthcare System for Heart Disease Detection using Hierarchical Auto-Associative Polynomial Convolutional Neural Network. *Smart Health*, 38, 100612.
- [7] Mekala, R. (2024). Scalable Autoencoder-Based Liver Disease Identification in Cloud-Integrated Healthcare Systems. *Int. J. of Multidisciplinary and Current research*, 12.
- [8] Neha, B., Panda, S. K., Sahu, P. K., & Taniar, D. (2024). Energy and latency-balanced osmotic-offloading algorithm for healthcare systems. *Internet of Things*, 26, 101176.
- [9] Ganesan, T., Devarajan, M. V., Yallamelli, A. R. G., Mamidala, V., Yalla, R. K. M. K., & Sambas, A. (2022). Towards time-critical healthcare systems leveraging IoT data transmission, fog resource optimization, and cloud integration for enhanced remote patient monitoring. *International Journal of Engineering Research and Science & Technology*, 18(2), 107-124.
- [10] Shanmugapriya, R., & Santhosh Kumar, S. V. N. (2024). SCIDP–Secure cloud-integrated data dissemination protocol for efficient reprogramming in internet of things. *Cluster Computing*, 27(9), 12841-12860.
- [11] Alserhani, F. (2025). Intrusion detection and real-time adaptive security in medical IoT using a cyber-physical system design. *Sensors*, 25(15), 4720.
- [12] Jayaram, R., & Prabakaran, S. (2021). Adaptive cost and energy aware secure peer-to-peer computational offloading in the edge-cloud enabled healthcare system. *Peer-to-Peer Networking and Applications*, 14(4), 2209-2223.
- [13] Aiswarya, R. S. (2024). Cloud-Based IoT Platform for GWO-Based LSTM-Based Advanced Disease Monitoring. *Int. J. of Multidisciplinary and Current research*, 12.
- [14] Islam, N., Haseeb, K., Rehman, A., Alam, T., & Jeon, G. (2023). An adaptive and secure routes migration model for the sustainable cloud of things. *Cluster Computing*, 26(2), 1631-1642.
- [15] Almalawi, A., Khan, A. I., Alsolami, F., Abushark, Y. B., & Alfakeeh, A. S. (2023). Managing security of healthcare data for a modern healthcare system. *Sensors*, 23(7), 3612.
- [16] Sonkamble, R. G., Bongale, A. M., Phansalkar, S., Sharma, A., & Rajput, S. (2023). Secure data transmission of electronic health records using blockchain technology. *Electronics*, 12(4), 1015.
- [17] Jaime, F. J., Muñoz, A., Rodríguez-Gómez, F., & Jerez-Calero, A. (2023). Strengthening privacy and data security in biomedical microelectromechanical systems by IoT communication security and protection in smart healthcare. *Sensors*, 23(21), 8944.

- [18] Kumar, P., Kumar, R., Gupta, G. P., Tripathi, R., Jolfaei, A., & Islam, A. N. (2023). A blockchain-orchestrated deep learning approach for secure data transmission in IoT-enabled healthcare system. *Journal of Parallel and Distributed Computing*, 172, 69-83.
- [19] Ibrahim, M., Al-Wadi, A., & Elhafiz, R. (2024). Security analysis for smart healthcare systems. *Sensors*, 24(11), 3375.
- [20] Mekala, R. (2022). Advanced Healthcare Systems: Integrating IoT and Cloud Computing in Smart Hospitals. *International Journal*, 7(2), 1-13.
- [21] Gonçalves, J. G., Ayub, M. S., Zhumadillayeva, A., Dyussekeyev, K., Ayimbay, S., Saadi, M., ... & Rodríguez, D. Z. (2024). Decentralized Machine Learning Framework for the Internet of Things: Enhancing Security, Privacy, and Efficiency in Cloud-Integrated Environments. *Electronics*, 13(21), 4185.
- [22] El Zouka, H. A., & Hosni, M. M. (2021). Secure IoT communications for smart healthcare monitoring system. *Internet of Things*, 13, 100036.
- [23] Verma, N., Singh, S., & Prasad, D. (2022). A review on existing IoT architecture and communication protocols used in healthcare monitoring system. *Journal of The Institution of Engineers (India): Series B*, 103(1), 245-257.
- [24] Alshamrani, M. (2022). IoT and artificial intelligence implementations for remote healthcare monitoring systems: A survey. *Journal of King Saud University-Computer and Information Sciences*, 34(8), 4687-4701.
- [25] Bhardwaj, V., Joshi, R., & Gaur, A. M. (2022). IoT-based smart health monitoring system for COVID-19. *SN Computer Science*, 3(2), 137.
- [26] Rajan Jeyaraj, P., & Nadar, E. R. S. (2022). Smart-monitor: Patient monitoring system for IoT-based healthcare system using deep learning. *IETE Journal of Research*, 68(2), 1435-1442.
- [27] Pelekoudas-Oikonomou, F., Zachos, G., Papaioannou, M., De Ree, M., Ribeiro, J. C., Mantas, G., & Rodriguez, J. (2022). Blockchain-based security mechanisms for IoMT Edge networks in IoMT-based healthcare monitoring systems. *Sensors*, 22(7), 2449.
- [28] Umer, M., Aljrees, T., Karamti, H., Ishaq, A., Alsubai, S., Omar, M., ... & Ashraf, I. (2023). Heart failure patients monitoring using IoT-based remote monitoring system. *Scientific Reports*, 13(1), 19213.
- [29] Cheikhrouhou, O., Mershad, K., Jamil, F., Mahmud, R., Koubaa, A., & Moosavi, S. R. (2023). A lightweight blockchain and fog-enabled secure remote patient monitoring system. *Internet of Things*, 22, 100691.
- [30] Wu, X., Liu, C., Wang, L., & Bilal, M. (2023). Internet of things-enabled real-time health monitoring system using deep learning. *Neural Computing and Applications*, 35(20), 14565-14576.
- [31] Rajavel, R., Ravichandran, S. K., Harimoorthy, K., Nagappan, P., & Gobichettipalayam, K. R. (2022). IoT-based smart healthcare video surveillance system using edge computing. *Journal of ambient intelligence and humanized computing*, 13(6), 3195-3207.
- [32] Liza, I. A., & Akter, R. (2025). Data-Driven Decision Support for Scalable Healthcare Using Cloud and Behavioral AI Models. *Pioneer Research Journal of Computing Science*, 2(2), 188-205.