Rajalakshmi Engineering College

Name: Gowthaman A

Email: 241801073@rajalakshmi.edu.in

Roll no: 241801073 Phone: 9344421607

Branch: REC

Department: I AI & DS FB

Batch: 2028

Degree: B.E - AI & DS



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 2_COD_Question 5

Attempt : 1 Total Mark : 10 Marks Obtained : 10

Section 1: Coding

1. Problem Statement

Ashwin is tasked with developing a simple application to manage a list of items in a shop inventory using a doubly linked list. Each item in the inventory has a unique identification number. The application should allow users to perform the following operations:

Create a List of Items: Initialize the inventory with a given number of items. Each item will be assigned a unique number provided by the user and insert the elements at end of the list.

Delete an Item: Remove an item from the inventory at a specific position.

Display the Inventory: Show the list of items before and after deletion.

If the position provided for deletion is invalid (e.g., out of range), it should

display an error message.

Input Format

The first line contains an integer n, representing the number of items to be initially entered into the inventory.

The second line contains n integers, each representing the unique identification number of an item separated by spaces.

The third line contains an integer p, representing the position of the item to be deleted from the inventory.

Output Format

The first line of output prints "Data entered in the list:" followed by the data values of each node in the doubly linked list before deletion.

If p is an invalid position, the output prints "Invalid position. Try again."

If p is a valid position, the output prints "After deletion the new list:" followed by the data values of each node in the doubly linked list after deletion.

Refer to the sample output for the formatting specifications.

Sample Test Case

```
Input: 4
1 2 3 4
5
Output: Data entered in the list: node 1 : 1
node 2 : 2
node 3 : 3
node 4 : 4
Invalid position. Try again.
```

Answer

```
// You are using GCC
#include<stdio.h>
#include<stdlib.h>
```

```
24,180,1013
                                                24,80,1013
 struct Node {
int data;
   struct Node* next;
   struct Node* prev;
void insertAtEnd(struct Node** head, int data){
   struct Node* newNode =(struct Node*)malloc(sizeof(struct Node));
   newNode->data=data;
   newNode->next=NULL;
   if(*head==NULL){
     newNode->prev=NULL;
     *head=newNode;
     return;
                                                                         241801013
  struct Node* last=*head;
   while(last->next!=NULL){
     last=last->next;
   last->next=newNode;
   newNode->prev=last;
void deleteAtPosition(struct Node** head, int position){
   if(*head==NULL){
     return;
   }
   struct Node* temp=*head;
   if (position == 1){
     *head = temp->next;
     if(*head != NULL){
       (*head)->prev=NULL;
     free(temp);
     return;
   }
   for (int i=1;temp !=NULL && i<position;i++){
     temp=temp->next;
   }
   if (temp==NULL){
                                                                         241801013
                                                241801013
     printf("Invalid position. Try again.\n");
     return;
```

```
if (temp->prev != NULL){
         temp->prev->next=temp->next;
      if(temp->next != NULL){
        temp->next->prev=temp->prev;
      free(temp);
    void displayList(struct Node* node){
      int count =1;
      while (node != NULL){
         printf(" node %d : %d\n",count, node->data);
         node = node->next;
         count++;
    void freeList(struct Node* head){
      struct Node* temp;
      while (head != NULL){
         temp=head;
         head=head->next;
         free(temp);
      }
    }
    int main() {
      struct Node* head=NULL;
scanf("%d",&n);
for (int i=Ω··
      for (int i=0;i< n;i++){
         scanf("%d",&item);
         insertAtEnd(&head, item);
      }
      scanf("%d",&p);
      printf("Data entered in the list:\n");
      displayList(head);
      if(p<1||p>n){
         printf("Invalid position. Try again.\n");
      }else{
         deleteAtPosition(&head,p);
                                                      241801013
         printf("\nAfter deletion the new list:\n");
         displayList(head);
```

241801013

241801013

241801013

freeList(head);
return 0;

Status: Correct

24,180,1013

24/80/073

Marks : 10/10

24,180,1013