

Rajalakshmi Engineering College

Name: Gowthaman A

Email: 241801073@rajalakshmi.edu.in

Roll no: 241801073

Phone: 9344421607

Branch: REC

Department: I AI & DS FB

Batch: 2028

Degree: B.E - AI & DS

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 7_COD_Question 3

Attempt : 1

Total Mark : 10

Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

In a messaging application, users maintain a contact list with names and corresponding phone numbers. Develop a program to manage this contact list using a dictionary implemented with hashing.

The program allows users to add contacts, delete contacts, and check if a specific contact exists. Additionally, it provides an option to print the contact list in the order of insertion.

Input Format

The first line consists of an integer n , representing the number of contact pairs to be inserted.

Each of the next n lines consists of two strings separated by a space: the name of the contact (key) and the corresponding phone number (value).

The last line contains a string *k*, representing the contact to be checked or removed.

Output Format

If the given contact exists in the dictionary:

1. The first line prints "The given key is removed!" after removing it.
2. The next *n* - 1 lines print the updated contact list in the format: "Key: *X*; Value: *Y*" where *X* represents the contact's name and *Y* represents the phone number.

If the given contact does not exist in the dictionary:

1. The first line prints "The given key is not found!".
2. The next *n* lines print the original contact list in the format: "Key: *X*; Value: *Y*" where *X* represents the contact's name and *Y* represents the phone number.

Refer to the sample outputs for the formatting specifications.

Sample Test Case

Input: 3

Alice 1234567890

Bob 9876543210

Charlie 4567890123

Bob

Output: The given key is removed!

Key: Alice; Value: 1234567890

Key: Charlie; Value: 4567890123

Answer

```
// You are using GCC
```

```
#include <stdio.h>
```

```
#include <string.h>
```

```
#define MAX 50
```

```

struct Contact {
    char name[11];
    char phone[11];
};

int main() {
    int n;
    scanf("%d", &n);

    struct Contact contacts[MAX];
    int size = 0;

    for (int i = 0; i < n; i++) {
        scanf("%s %s", contacts[i].name, contacts[i].phone);
        size++;
    }

    char key[11];
    scanf("%s", key);

    int found = 0;
    for (int i = 0; i < size; i++) {
        if (strcmp(contacts[i].name, key) == 0) {
            found = 1;
            for (int j = i; j < size - 1; j++) {
                contacts[j] = contacts[j + 1];
            }
            size--;
            break;
        }
    }

    if (found) {
        printf("The given key is removed!");
    } else {
        printf("The given key is not found!");
    }

    for (int i = 0; i < size; i++) {
        printf(" Key: %s; Value: %s", contacts[i].name, contacts[i].phone);
    }
}

```

```
} return 0;
```

Status : Correct

Marks : 10/10