

# Rajalakshmi Engineering College

Name: GOWTHAM KUMAR P.S  
Email: 240701826@rajalakshmi.edu.in  
Roll no: 240701826  
Phone: 9345582664  
Branch: REC  
Department: CSE - Section 8  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 5\_CY

Attempt : 1  
Total Mark : 40  
Marks Obtained : 40

#### Section 1 : Coding

##### 1. Problem Statement

Meera is working as a developer for CityGas Supply Board, which wants to build a household gas billing system.

Each household's gas account has:

A Customer ID (integer) A Customer Name (string) Units Consumed in cubic meters (double)

The gas bill is calculated based on these rules:

For the first 50 units    4 per unit For the next 100 units (51–150)    6 per unit  
For units above 150    8 per unit If the total bill exceeds 2000, a 15% discount is applied on the final bill.

Meera has been asked to implement this system using:

A class with attributes for customer details. A constructor to initialize customer details. Setter methods to update details if needed. Getter methods to retrieve details. Objects of the class to represent customers.

Finally, display each customer's details and final bill amount.

### ***Input Format***

The first line of input contains an integer N, representing the number of customers.

For each customer:

- The next line contains the Customer ID (integer).
- The following line contains the Customer Name (string).
- The next line contains the Units Consumed (double).

### ***Output Format***

For each customer, print the details in the following format:

Customer ID: <customer\_id>

Customer Name: <customer\_name>

Final Bill: <final\_bill> (The final bill must be rounded to one decimal place.)

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 1

1001

Ravi Kumar

30

Output: Customer ID: 1001

Customer Name: Ravi Kumar

Final Bill: 120.0

### ***Answer***

```
import java.util.Scanner;
```

```

// Customer class
class Customer {
    private int customerId;
    private String customerName;
    private double unitsConsumed;
    private double finalBill;

    // Constructor
    public Customer(int customerId, String customerName, double
unitsConsumed) {
        this.customerId = customerId;
        this.customerName = customerName;
        this.unitsConsumed = unitsConsumed;
        calculateFinalBill();
    }

    // Getter methods
    public int getCustomerId() { return customerId; }
    public String getCustomerName() { return customerName; }
    public double getUnitsConsumed() { return unitsConsumed; }
    public double getFinalBill() { return finalBill; }

    // Setter methods
    public void setCustomerId(int customerId) { this.customerId = customerId; }
    public void setCustomerName(String customerName) { this.customerName =
customerName; }
    public void setUnitsConsumed(double unitsConsumed) {
        this.unitsConsumed = unitsConsumed;
        calculateFinalBill();
    }

    // Method to calculate final gas bill
    private void calculateFinalBill() {
        double total = 0;

        if (unitsConsumed <= 50) {
            total = unitsConsumed * 4;
        } else if (unitsConsumed <= 150) {
            total = 50 * 4 + (unitsConsumed - 50) * 6;
        } else {
            total = 50 * 4 + 100 * 6 + (unitsConsumed - 150) * 8;
        }
    }
}

```

```

    }

    // Apply 15% discount if total exceeds 2000
    if (total > 2000) {
        total *= 0.85;
    }

    finalBill = total;
}

// Display customer details
public void display() {
    System.out.println("Customer ID: " + customerId);
    System.out.println("Customer Name: " + customerName);
    System.out.printf("Final Bill: %.1f%n", finalBill);
}
}

// Main class
public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);

        int N = Integer.parseInt(sc.nextLine().trim());
        Customer[] customers = new Customer[N];

        for (int i = 0; i < N; i++) {
            int id = Integer.parseInt(sc.nextLine().trim());
            String name = sc.nextLine().trim();
            double units = Double.parseDouble(sc.nextLine().trim());

            customers[i] = new Customer(id, name, units);
        }

        for (Customer c : customers) {
            c.display();
        }

        sc.close();
    }
}

// You are using Java

```

Status : Correct

Marks : 10/10

## 2. Problem Statement

Anjali is now working as a developer for the City Marathon Association, which wants to build a system to track and find the fastest runner among marathon participants.

Each runner's record has:

Runner ID (integer) Runner Name (string) An array of times (in minutes) taken in 5 marathon events (integers)

The system must calculate:

The average time of each runner (sum of all times / 5). Identify the fastest runner (the one with the lowest average time). If two or more runners have the same average time, the one with the lower Runner ID is considered the fastest runner.

Anjali has been asked to implement this system using:

A class with attributes for runner details. A constructor to initialize runner details. Getter and Setter methods to retrieve and update runner details if required. A method to calculate the average time. Objects of the class to represent runners.

Finally, display each runner's details and announce the Fastest Runner.

### **Input Format**

The first line of input contains an integer N (number of runners).

For each runner:

- The next line contains the Runner ID (integer).
- The following line contains the Runner Name (string).
- The next line contains 5 integers separated by spaces (times in minutes for 5 marathon events).

### **Output Format**

For each runner the output prints the following details:

- Runner ID: <runner\_id>
- Runner Name: <runner\_name>
- Average Time: <average\_time>

Finally, print "Fastest Runner: <runner\_name> with <average\_time> minutes"

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 1

1001

Ravi Kumar

240 250 245 255 260

Output: Runner ID: 1001

Runner Name: Ravi Kumar

Average Time: 250

Fastest Runner: Ravi Kumar with 250 minutes

### **Answer**

```
import java.util.Scanner;
```

```
// Runner class
```

```
class Runner {
```

```
    private int runnerId;
```

```
    private String runnerName;
```

```
    private int[] times; // 5 marathon times
```

```
    private int averageTime;
```

```
// Constructor
```

```
public Runner(int runnerId, String runnerName, int[] times) {
```

```
    this.runnerId = runnerId;
```

```
    this.runnerName = runnerName;
```

```
    this.times = times;
```

```
    calculateAverageTime();
```

```

    }

    // Getter methods
    public int getRunnerId() { return runnerId; }
    public String getRunnerName() { return runnerName; }
    public int getAverageTime() { return averageTime; }

    // Setter methods
    public void setRunnerId(int runnerId) { this.runnerId = runnerId; }
    public void setRunnerName(String runnerName) { this.runnerName =
runnerName; }
    public void setTimes(int[] times) {
        this.times = times;
        calculateAverageTime();
    }

    // Calculate average time
    private void calculateAverageTime() {
        int sum = 0;
        for (int t : times) {
            sum += t;
        }
        this.averageTime = sum / times.length;
    }

    // Display runner details
    public void display() {
        System.out.println("Runner ID: " + runnerId);
        System.out.println("Runner Name: " + runnerName);
        System.out.println("Average Time: " + averageTime);
    }
}

// Main class
public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);

        int N = Integer.parseInt(sc.nextLine().trim());
        Runner[] runners = new Runner[N];

        for (int i = 0; i < N; i++) {

```

```

int id = Integer.parseInt(sc.nextLine().trim());
String name = sc.nextLine().trim();
int[] times = new int[5];
String[] timeInputs = sc.nextLine().trim().split(" ");
for (int j = 0; j < 5; j++) {
    times[j] = Integer.parseInt(timeInputs[j]);
}
runners[i] = new Runner(id, name, times);
}

// Display details and find fastest runner
Runner fastest = runners[0];
for (Runner r : runners) {
    r.display();
    if (r.getAverageTime() < fastest.getAverageTime() ||
        (r.getAverageTime() == fastest.getAverageTime() && r.getRunnerId() <
fastest.getRunnerId())) {
        fastest = r;
    }
}

System.out.println("Fastest Runner: " + fastest.getRunnerName() + " with " +
fastest.getAverageTime() + " minutes");
sc.close();
}
}
// You are using Java

```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

Arjun is working as a developer for CityWater Supply Board, which wants to build a household water billing system.

Each household's water account has:

A Customer ID (integer) A Customer Name (string) Liters Consumed (double)

The water bill is calculated based on these rules:

For the first 500 liters 2 per literFor the next 500 liters (501–1000) 3 per literFor liters above 1000 5 per literIf the total bill exceeds 3000, a 10% discount is applied on the final bill.

Arjun has been asked to implement this system using:

A class with attributes for customer details.A constructor to initialize customer details.Setter methods to update details if needed.Getter methods to retrieve details.Objects of the class to represent customers.

Finally, display each customer's details and final bill amount.

### ***Input Format***

The first line of input contains an integer N, representing the number of customers.

For each customer:

- The next line contains the Customer ID (integer).
- The following line contains the Customer Name (string).
- The next line contains the Liters Consumed (double).

### ***Output Format***

For each customer, print the details in the following format:

Customer ID: <customer\_id>

Customer Name: <customer\_name>

Final Bill: <final\_bill> (rounded to one decimal place)

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 1

1001

Ravi Kumar

300

Output: Customer ID: 1001  
Customer Name: Ravi Kumar  
Final Bill: 600.0

**Answer**

```
import java.util.Scanner;
```

```
// Customer class
```

```
class Customer {  
    private int customerId;  
    private String customerName;  
    private double litersConsumed;  
    private double finalBill;
```

```
// Constructor
```

```
    public Customer(int customerId, String customerName, double  
    litersConsumed) {  
        this.customerId = customerId;  
        this.customerName = customerName;  
        this.litersConsumed = litersConsumed;  
        calculateBill();  
    }
```

```
// Getter methods
```

```
    public int getCustomerId() { return customerId; }  
    public String getCustomerName() { return customerName; }  
    public double getFinalBill() { return finalBill; }
```

```
// Setter methods
```

```
    public void setCustomerId(int customerId) { this.customerId = customerId; }  
    public void setCustomerName(String customerName) { this.customerName =  
customerName; }  
    public void setLitersConsumed(double litersConsumed) {  
        this.litersConsumed = litersConsumed;  
        calculateBill();  
    }
```

```
// Method to calculate the bill
```

```
    private void calculateBill() {  
        double bill = 0.0;  
        if (litersConsumed <= 500) {  
            bill = litersConsumed * 2;
```

```

    } else if (litersConsumed <= 1000) {
        bill = 500 * 2 + (litersConsumed - 500) * 3;
    } else {
        bill = 500 * 2 + 500 * 3 + (litersConsumed - 1000) * 5;
    }
    // Apply discount if bill > 3000
    if (bill > 3000) {
        bill = bill - bill * 0.10;
    }
    finalBill = bill;
}

// Display customer details
public void display() {
    System.out.println("Customer ID: " + customerId);
    System.out.println("Customer Name: " + customerName);
    System.out.println("Final Bill: " + String.format("%.1f", finalBill));
}
}

```

```

// Main class
public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int N = Integer.parseInt(sc.nextLine().trim());
        Customer[] customers = new Customer[N];

        for (int i = 0; i < N; i++) {
            int id = Integer.parseInt(sc.nextLine().trim());
            String name = sc.nextLine().trim();
            double liters = Double.parseDouble(sc.nextLine().trim());
            customers[i] = new Customer(id, name, liters);
        }

        for (Customer c : customers) {
            c.display();
        }

        sc.close();
    }
}
// You are using Java

```

Status : Correct

Marks : 10/10

#### 4. Problem Statement

You are working as a developer for CityMobile, which wants to build a basic mobile data usage management system.

Each customer has:

A Customer ID (integer)  
A Customer Name (string)  
An Initial Data Balance (in GB, double)

The company allows two types of operations:

Recharge – increases the data balance.  
Usage – decreases the data balance only if enough data is available.

If the usage amount is greater than the available data balance, the usage should not happen, and the balance should remain the same.

You are required to implement this system using:

A class with attributes for customer details.  
A constructor to initialize customer details.  
Setter methods to update details if needed.  
Getter methods to retrieve details.  
Objects of the class to represent customers.

Finally, display each customer's details after all operations.

#### **Input Format**

The first line of input contains an integer N, representing the number of customers.

For each customer:

- The next line contains the Customer ID (integer).
- The following line contains the Customer Name (string).
- The next line contains the Initial Data Balance (double).
- The next line contains the Recharge Amount in GB (double).
- The next line contains the Usage Amount in GB (double).

#### **Output Format**

For each customer, print the details in the following format:

Customer ID: <customer\_id>

Customer Name: <customer\_name>

Final Data Balance: <final\_data\_balance> GB (The final balance must be rounded to one decimal place.)

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 1

1234

Ravi Kumar

5.0

2.0

3.0

Output: Customer ID: 1234

Customer Name: Ravi Kumar

Final Data Balance: 4.0 GB

### **Answer**

```
import java.util.Scanner;
```

```
// Customer class
```

```
class Customer {
```

```
    private int customerId;
```

```
    private String customerName;
```

```
    private double dataBalance;
```

```
// Constructor
```

```
public Customer(int customerId, String customerName, double dataBalance) {
```

```
    this.customerId = customerId;
```

```
    this.customerName = customerName;
```

```
    this.dataBalance = dataBalance;
```

```
}
```

```
// Getter methods
```

```

public int getCustomerId() { return customerId; }
public String getCustomerName() { return customerName; }
public double getDataBalance() { return dataBalance; }

// Setter methods
public void setCustomerId(int customerId) { this.customerId = customerId; }
public void setCustomerName(String customerName) { this.customerName =
customerName; }
public void setDataBalance(double dataBalance) { this.dataBalance =
dataBalance; }

// Method to perform recharge
public void recharge(double amount) {
    if (amount >= 0) {
        dataBalance += amount;
    }
}

// Method to perform usage
public void useData(double amount) {
    if (amount <= dataBalance) {
        dataBalance -= amount;
    }
}

// Display customer details
public void display() {
    System.out.println("Customer ID: " + customerId);
    System.out.println("Customer Name: " + customerName);
    System.out.println("Final Data Balance: " + String.format("%.1f",
dataBalance) + " GB");
}

// Main class
public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int N = Integer.parseInt(sc.nextLine().trim());
        Customer[] customers = new Customer[N];

        for (int i = 0; i < N; i++) {

```

```
int id = Integer.parseInt(sc.nextLine().trim());
String name = sc.nextLine().trim();
double initialBalance = Double.parseDouble(sc.nextLine().trim());
double rechargeAmount = Double.parseDouble(sc.nextLine().trim());
double usageAmount = Double.parseDouble(sc.nextLine().trim());

customers[i] = new Customer(id, name, initialBalance);
customers[i].recharge(rechargeAmount);
customers[i].useData(usageAmount);
}

for (Customer c : customers) {
    c.display();
}

sc.close();
}
}
// You are using Java
```

**Status :** Correct

**Marks :** 10/10