

redis-exercises-questions

Redis - Hands-On Exercises

- Q1.** Set a key `user:1:name` with the value `"Alice"`. Then retrieve it.
- Q2.** Set a key `user:1:loginCount` with value `0`. Increment it by 1 using a Redis command (without manually reading and writing). Run the increment 3 more times. Then retrieve the final value.
- Q3.** Set a session key `session:abc123` with value `"user_data_here"` that automatically **expires in 30 minutes**.
- Q4.** Check how many seconds remain on `session:abc123`. Then remove the expiry so it becomes permanent. Verify the key no longer has an expiry.
- Q5.** Check whether the key `user:1:email` exists. Then delete `user:1:name` and verify it no longer exists.
- Q6.** What does a TTL of `-1` mean? What does `-2` mean? Demonstrate both cases with actual keys.
- Q7.** You are building a notification queue. Push the following messages to a list called `notifications:user1` - push `"You have a new message"` to the left, then `"Your order has shipped"` and `"Password changed successfully"` to the right.
- Q8.** Retrieve all elements of `notifications:user1` without removing them.
- Q9.** Add 5 messages to a list called `taskQueue`. Then retrieve only the first 3 tasks without removing them.
- Q10.** Store a user profile for user ID 201 under the key `user:201` with these fields:
- `name` : "Bob"
 - `email` : "bob@example.com"
 - `age` : "34"
 - `role` : "developer"
- Q11.** Retrieve only the `email` field of `user:201`.
- Q12.** Retrieve all fields and values of `user:201`.
- Q13.** Check whether the field `phone` exists in `user:201`. Then add it with value `"9876543210"` and verify it was added.
- Q14.** Add the following users to a set `online:users` : `"alice"`, `"bob"`, `"carol"`, `"alice"`. Retrieve all members. How many are stored?
- Q15.** Remove `"bob"` from the set. Confirm the count dropped by 1.
- Q16.** You have two sets: `page:home:viewers` with `{"alice", "bob", "carol"}` and `page:about:viewers` with `{"carol", "david", "eve"}`. Find the users who viewed **both pages** (intersection).
- Q17.** Build a game leaderboard called `leaderboard:game1`. Add these players with their scores:
- `"alice"` : 1500
 - `"bob"` : 2300
 - `"carol"` : 800
 - `"david"` : 3100
 - `"eve"` : 1900
- Q18.** Display the full leaderboard from **highest to lowest** score, showing scores alongside names.
- Q19.** Explore commands `SCAN` & `OBJECT IDLETIME`