CSS

Cascading Style Sheets
It is about controlling the visual presentation of HTML content

Roles of CSS:

1. controlling fonts, colors, spacing
2. defining page layouts (flex and grid properties)
3. animations and interations
4. separation of content from design

Ways to Apply CSS:

1. Inline CSS
```
<h1 style="color: red;">Hello World</h1>
```
- it will only style the elements having the style attribute / property

2. Internal CSS
Writing the styles within the same html document
for this we use style tags

```
<style>
    h1 {
        color: red;
    }
</style>
```

3. External CSS
Best practice as it separates content and design
css is written into its own file with extension '.css'

```
<link rel="stylesheet" href="index.css">
```

4. Cascading Concept
Cascading means styles can come from multiple sources and
are prioritized on the basis of:

- Location = Inline > Internal > External
- Specificity = ID > Class > Element
- Order of Appearance = Later overrides earlier

© 2026 GUVI GEEK NETWORK PVT LTD. All rights reserved. No part of this document may be reproduced or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior permission from GUVI.

Selectors in CSS
Selectors target HTML elements so that it can apply styles to it.

1. Element Selector
Targeting the elements based on tag name

2. Class Selectors
Selectors are defined using a dot '.'
and for elements class attribute defines the selector name
these can be reused, meaning multiple elements can have same class name.

3. ID Selectors
Selectors are defined using hash '#'
and for elements id attribute defines the selector name
these are meant to be unique - used only once per page.

!important voids any cascading happening and applies the property value.

Specificity

a - inline styles	1,0,0,0
b - ID	0,1,0,0
c - Classes / pseudo-classes	0,0,1,0
d - elements / pseudo elements	0,0,0,1

Higher the number from left to right, more specific is the rule going to be

div	0,0,0,1
.box	0,0,1,0
section .box	0,0,1,1

© 2026 GUVI GEEK NETWORK PVT LTD. All rights reserved. No part of this document may be reproduced or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior permission from GUVI.

Display Property

It determines how an element behaves in layout flow of the page.

- block = full width and starts on a different line
- inline = shares the line with other content,
  can not access height and width property
- inline-block = inline behavior, but height width can be used
- none = removes element from layout

Pseudo Classes

Pseudo classes are used to style elements in a specific state or situation

a:link - unvisited links
a:visited - after being clicked
a:hover - when mouse hovers over
a:active - when link is being clicked

Link -> Visited -> Hover -> Active

Pseudo Elements

to add content before or after an elements actual content e can use pseudo elements

::before
::after

© 2026 GUVI GEEK NETWORK PVT LTD. All rights reserved. No part of this document may be reproduced or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior permission from GUVI.