Supertex inc.

32-Channel Serial To Parallel Converter
With Open Drain Outputs

Ordering Information

Device	Recommended Operating V_{PP} max	Package Options			
		44 J-Lead Quad Ceramic Chip Carrier	44 J-Lead Quad Plastic Chip Carrier	44 Lead Quad Plastic Gullwing	Die
HV5522	220V	HV5522DJ	HV5522PJ	HV5522PG	HV5522X
HV5530	300V	HV5530DJ	HV5530PJ	HV5530PG	HV5530X
HV5622	220V	HV5622DJ	HV5622PJ	HV5622PG	HV5622X
HV5630	300V	HV5630DJ	HV5630PJ	HV5630PG	HV5630X

Features

❏ Processed with HVCMOS® technology

❏ Sink current minimum 100mA

❏ Shift register speed 8MHz

❏ Polarity and Blanking inputs

❏ CMOS compatible inputs

❏ Forward and reverse shifting options

❏ Diode to V_{PP} allows efficient power recovery

❏ 44-lead ceramic surface mount package

❏ Hi-Rel processing available

General Description

The HV55 and HV56 are low-voltage serial to high-voltage parallel converters with open drain outputs. These devices have been designed for use as drivers for AC-electroluminescent displays. They can also be used in any application requiring multiple output high voltage current sinking capabilities such as driving inkjet and electrostatic print heads, plasma panels, vacuum fluorescent, or large matrix LCD displays.

These devices consist of a 32-bit shift register, 32 latches, and control logic to perform the polarity select and blanking of the outputs. Data is shifted through the shift register on the high to low transition of the clock. The HV55 shifts in the counterclockwise direction when viewed from the top of the package, and the HV56 shifts in the clockwise direction. A data output buffer is provided for cascading devices. This output reflects the current status of the last bit of the shift register. Operation of the shift register is not affected by the $\overline{LE}$ (latch enable), $\overline{BL}$ (blanking), or the $\overline{POL}$ (polarity) inputs. Transfer of data from the shift register to the latch occurs when the $\overline{LE}$ (latch enable) input is high. The data in the latch is stored when $\overline{LE}$ is low.

Absolute Maximum Ratings

Supply voltage, V_{DD}[1]		-0.5V to +15V
Output voltage, V_{PP}[1]	HV5530/HV6630	-0.5V to +315V
	HV5522/HV5622	-0.5V to +230V
Logic input levels[1]		-0.5V to V_{DD} + 0.5V
Ground current[2]		1.5A
Continuous total power dissipation[3]	Ceramic	1500mW
	Plastic	1200mW
Operating temperature range	Ceramic	-55°C to +125°C
	Plastic	-40°C to +85°C
Storage temperature range		-65°C to +150°C
Lead temperature 1.6mm (1/16 inch) from case for 10 seconds		260°C

Notes:
1. All voltages are referenced to V_{SS}.
2. Duty cycle is limited by the total power dissipated in the package.
3. For operation above 25°C ambient derate linearly to maximum operating temperature at 20°C for plastic and at 15mW/°C for ceramic.

Electrical Characteristics (over recommended operating conditions unless noted)

DC Characteristics

Symbol	Parameter		Min	Max	Units	Conditions
I_{DD}	V_{DD} supply current			15	mA	f_{CLK} = 8MHz F_{DATA} = 4MHz
I_{DDQ}	Quiescent V_{DD} supply current			100	µA	V_{IN} = 0V
$I_{O(OFF)}$	Off state output current			10	µA	All outputs high All SWS parallel
I_{IH}	High-level logic input current			1	µA	V_{IH} = V_{DD}
I_{IL}	Low-level logic input current			-1	µA	V_{IL} = 0V
V_{OH}	High-level output data out		V_{DD} - 1.0V		V	I_{Dout} = -100µA
V_{OL}	Low-level output voltage	HV_{OUT}		15.0	V	I_{HVout} = +100mA
		Data out		1.0	V	I_{Dout} = +100µA
V_{OC}	HV_{OUT} clamp voltage			-1.5	V	I_{OL} = -100mA

AC Characteristics (V_{DD} = 12V, T_C = 25°C)

Symbol	Parameter	Min	Max	Units	Conditions
f_{CLK}	Clock frequency		8	MHz	
t_W	Clock width high or low	62		ns	
t_{SU}	Data set-up time before clock falls	25		ns	
t_H	Data hold time after clock falls	10		ns	
t_{ON}	Turn on time, HV_{OUT} from enable		500	ns	R_L = 2KΩ to V_{PP} MAX
t_{DHL}	Delay time clock to data high to low		100	ns	C_L = 15pF
t_{DLH}	Delay time clock to data low to high		100	ns	C_L = 15pF
t_{DLE}	Delay time clock to $\overline{LE}$ low to high	50		ns	
t_{WLE}	Width of $\overline{LE}$ pulse	50		ns	
t_{SLE}	$\overline{LE}$ set-up time before clock falls	50		ns	

Recommended Operating Conditions

| Symbol	Parameter		Min	Max	Units
V_{DD}	Logic supply voltage		10.8	13.2	V
HV_{OUT}	High voltage output	HV5530 and HV5630	-0.3	+300	V
		HV5522 and HV5622	-0.3	+220	V
V_{IH}	High-level input voltage		V_{DD} - 2V	V_{DD}	V
V_{IL}	Low-level input voltage		0	2.0	V
f_{CLK}	Clock frequency			8	MHz
T_A	Operating free-air temperature	Plastic	-40	+85	°C
		Ceramic	-55	+125	°C

Note:
Power-up sequence should be the following:
1. Connect ground.
2. Apply V_{DD}.
3. Set all inputs to a known state.

Power-down sequence should be the reverse of the above.

Input and Output Equivalent Circuits

Logic Inputs	Logic Data Output	High Voltage Outputs

Switching Waveforms

Functional Block Diagram

Polarity

Blanking

Latch Enable

Data Input

Clock

32-Bit Shift Register

Data Out

Latch

Latch

Latch

Latch

HV_OUT1

HV_OUT2

(Outputs 3 to 30 not shown)

HV_OUT31

HV_OUT32

Function Table

Function	Inputs					Outputs				
	Data	CLK	$\overline{LE}$	$\overline{BL}$	$\overline{POL}$	Shift Reg		HV Outputs		Data Out
						1	2…32	1	2…32	*
All on	X	X	X	L	L	*	*…*	On	On…On	*
All off	X	X	X	L	H	*	*…*	Off	Off…Off	*
Invert mode	X	X	L	H	L	*	*…*	$\overline{*}$	$\overline{*…*}$	*
Load S/R	H or L	↓	L	H	H	H or L	*…*	*	*…*	*
Load Latches	X	H or L	↑	H	H	*	*…*	*	*…*	*
	X	H or L	↑	H	L	*	*…*	$\overline{*}$	$\overline{*…*}$	*
Transparent Latch mode	L	↓	H	H	H	L	*…*	Off	*…*	*
	H	↓	H	H	H	H	*…*	On	*…*	*

Notes:

H = high level, L = low level, X = irrelevant, ↓ = high-to-low transition, ↑ = low-to-high transistion.

* = dependent on previous stage's state before the last CLK ↓ or last $\overline{LE}$ high.

4

Pin Configurations

HV55
44 Pin J-Lead Package

Pin	Function	Pin	Function
1	HV$_{OUT}$ 16	23	Clock
2	HV$_{OUT}$ 17	24	V$_{SS}$
3	HV$_{OUT}$ 18	25	V$_{DD}$
4	HV$_{OUT}$ 19	26	$\overline{\text{Latch Enable}}$
5	HV$_{OUT}$ 20	27	$\overline{\text{Data In}}$
6	HV$_{OUT}$ 21	28	$\overline{\text{Blanking}}$
7	HV$_{OUT}$ 22	29	N/C
8	HV$_{OUT}$ 23	30	HV$_{OUT}$ 1
9	HV$_{OUT}$ 24	31	HV$_{OUT}$ 2
10	HV$_{OUT}$ 25	32	HV$_{OUT}$ 3
11	HV$_{OUT}$ 26	33	HV$_{OUT}$ 4
12	HV$_{OUT}$ 27	34	HV$_{OUT}$ 5
13	HV$_{OUT}$ 28	35	HV$_{OUT}$ 6
14	HV$_{OUT}$ 29	36	HV$_{OUT}$ 7
15	HV$_{OUT}$ 30	37	HV$_{OUT}$ 8
16	HV$_{OUT}$ 31	38	HV$_{OUT}$ 9
17	HV$_{OUT}$ 32	39	HV$_{OUT}$ 10
18	Data Out	40	HV$_{OUT}$ 11
19	N/C	41	HV$_{OUT}$ 12
20	N/C	42	HV$_{OUT}$ 13
21	N/C	43	HV$_{OUT}$ 14
22	$\overline{\text{Polarity}}$	44	HV$_{OUT}$ 15

HV56
44 Pin J-Lead Package

Pin	Function	Pin	Function
1	HV$_{OUT}$ 17	23	Clock
2	HV$_{OUT}$ 16	24	V$_{SS}$
3	HV$_{OUT}$ 15	25	V$_{DD}$
4	HV$_{OUT}$ 14	26	$\overline{\text{Latch Enable}}$
5	HV$_{OUT}$ 13	27	Data In
6	HV$_{OUT}$ 12	28	$\overline{\text{Blanking}}$
7	HV$_{OUT}$ 11	29	N/C
8	HV$_{OUT}$ 10	30	HV$_{OUT}$ 32
9	HV$_{OUT}$ 9	31	HV$_{OUT}$ 31
10	HV$_{OUT}$ 8	32	HV$_{OUT}$ 30
11	HV$_{OUT}$ 7	33	HV$_{OUT}$ 29
12	HV$_{OUT}$ 6	34	HV$_{OUT}$ 28
13	HV$_{OUT}$ 5	35	HV$_{OUT}$ 27
14	HV$_{OUT}$ 4	36	HV$_{OUT}$ 26
15	HV$_{OUT}$ 3	37	HV$_{OUT}$ 25
16	HV$_{OUT}$ 2	38	HV$_{OUT}$ 24
17	HV$_{OUT}$ 1	39	HV$_{OUT}$ 23
18	Data Out	40	HV$_{OUT}$ 22
19	N/C	41	HV$_{OUT}$ 21
20	N/C	42	HV$_{OUT}$ 20
21	N/C	43	HV$_{OUT}$ 19
22	$\overline{\text{Polarity}}$	44	HV$_{OUT}$ 18

Package Outline

top view
44-pin J-Lead Package

Pin Configurations

Package Outline

HV55

44-Pin Quad Plastic Gullwing Package

Pin	Function	Pin	Function
1	HV_{OUT} 11	23	Data Out
2	HV_{OUT} 12	24	N/C
3	HV_{OUT} 13	25	N/C
4	HV_{OUT} 14	26	N/C
5	HV_{OUT} 15	27	Polarity
6	HV_{OUT} 16	28	Clock
7	HV_{OUT} 17	29	V_{SS}
8	HV_{OUT} 18	30	V_{DD}
9	HV_{OUT} 19	31	Latch Enable
10	HV_{OUT} 20	32	Data In
11	HV_{OUT} 21	33	Blanking
12	HV_{OUT} 22	34	N/C
13	HV_{OUT} 23	35	HV_{OUT} 1
14	HV_{OUT} 24	36	HV_{OUT} 2
15	HV_{OUT} 25	37	HV_{OUT} 3
16	HV_{OUT} 26	38	HV_{OUT} 4
17	HV_{OUT} 27	39	HV_{OUT} 5
18	HV_{OUT} 28	40	HV_{OUT} 6
19	HV_{OUT} 29	41	HV_{OUT} 7
20	HV_{OUT} 30	42	HV_{OUT} 8
21	HV_{OUT} 31	43	HV_{OUT} 9
22	HV_{OUT} 32	44	HV_{OUT} 10

top view
44-pin Quad Plastic Gullwing Package

HV56

44-Pin Quad Plastic Gullwing Package

Pin	Function	Pin	Function
1	HV_{OUT} 22	23	Data Out
2	HV_{OUT} 21	24	N/C
3	HV_{OUT} 20	25	N/C
4	HV_{OUT} 19	26	N/C
5	HV_{OUT} 18	27	Polarity
6	HV_{OUT} 17	28	Clock
7	HV_{OUT} 16	29	V_{SS}
8	HV_{OUT} 15	30	V_{DD}
9	HV_{OUT} 14	31	Latch Enable
10	HV_{OUT} 13	32	Data In
11	HV_{OUT} 12	33	Blanking
12	HV_{OUT} 11	34	N/C
13	HV_{OUT} 10	35	HV_{OUT} 32
14	HV_{OUT} 9	36	HV_{OUT} 31
15	HV_{OUT} 8	37	HV_{OUT} 30
16	HV_{OUT} 7	38	HV_{OUT} 29
17	HV_{OUT} 6	39	HV_{OUT} 28
18	HV_{OUT} 5	40	HV_{OUT} 27
19	HV_{OUT} 4	41	HV_{OUT} 26
20	HV_{OUT} 3	42	HV_{OUT} 25
21	HV_{OUT} 2	43	HV_{OUT} 24
22	HV_{OUT} 1	44	HV_{OUT} 23

12/13/01

Supertex inc.

1235 Bordeaux Drive, Sunnyvale, CA 94089
TEL: (408) 744-0100 • FAX: (408) 222-4895
www.supertex.com

## 44-Lead PLCC Package Outline (PJ)
### .653x.653in body, .180in height (max.), .050in pitch

Top View

Side View

Side View

View B

Note:
1. A Pin 1 identifier must be located in the index area indicated. The Pin 1 identifier may be either a mold, or an embedded metal or marked feature.
2. Exact shape of this feature is optional.

Symbol		A	A1	A2	b	b1	D	D1	E	E1	e
Dimension (inches)	MIN	.165	.090	.062	.013	.026	.685	.650	.685	.650	.050 BSC
	NOM	.172	.105	-	-	-	.690	.653	.690	.653	
	MAX	.180	.120	.083	.021	.036	.695	.656	.695	.656	

JEDEC Registration MS-018, Variation AC, Issue A, June, 1993.
Drawings are not to scale.

Supertex inc.
1235 Bordeaux Drive, Sunnyvale, CA 94089
TEL: (408) 222-8888 / FAX: (408) 222-4895

44-Lead PQFP Package Outline (PG)

Top View

View B

Side View

Note 1:
A Pin 1 identifier must be located in the index area indicated. The Pin 1 identifier may be either a mold, or an embedded metal or marked feature.

Symbol		A	A1	A2	b	D	D1	E	E1	e	L	L1	L2	θ	θ1
Dimension (mm)	MIN	-	0.25	1.95	0.30	13.65	9.80	13.65	9.80	0.80 BSC	0.73	1.95 REF	0.25 BSC	3.5°	5°
	NOM	-	-	2.00	-	13.90	10.00	13.90	10.00		0.88			-	-
	MAX	2.45	-	2.10	0.45	14.15	10.20	14.15	10.20		1.03			7°	16°

JEDEC Registration M0-112, Variation AA-2, Issue B, Sep.1995.

Doc. #: DSPD-44PQFPPG
A031607

Supertex inc.
1235 Bordeaux Drive, Sunnyvale, CA 94089
TEL: (408) 222-8888 / FAX: (408) 222-4895
www.supertex.com