

Particle System Model

Flux

February 7, 2026

1 State and Dynamics

Let n particles evolve in $\mathbb{R}^2$ with positions

$$X(t) = (x_1(t), \dots, x_n(t)), \quad x_i(t) \in \mathbb{R}^2.$$

The motion with friction is

$$\ddot{x}_i + \alpha \dot{x}_i = -f_E(x_i) - f_I(X, x_i), \quad i = 1, \dots, n,$$

where $\alpha \geq 0$ is the friction coefficient.

2 External Force (Context-Free)

The external term depends only on the local position:

$$f_E(x) : \mathbb{R}^2 \rightarrow \mathbb{R}^2.$$

In this application, f_E is built from user-controlled radial centers and does not depend on the current full particle configuration X .

3 Internal Force (In-Context)

Internal interactions depend on the whole configuration X :

$$f_I(X, x_i) = \frac{1}{n} \sum_{k=1}^K \sum_{j=1}^n v_k g_{s_k}(x_i - x_j) (x_i - x_j).$$

The Gaussian head kernel is

$$g_s(r) = \exp\left(-\frac{\|r\|^2}{2s^2}\right).$$

The self-interaction terms ($j = i$) are set to zero in implementation.

Unity On/Off Vector Term

Define

$$w_{ij} = \begin{cases} \frac{x_i - x_j}{\|x_i - x_j\|}, & \text{Unity On,} \\ x_i - x_j, & \text{Unity Off.} \end{cases}$$

4 Two-Head Case ($K = 2$)

With two heads:

$$v_1 > 0 \quad (\text{repulsive}), \quad v_2 < 0 \quad (\text{attractive}).$$

Using UI amplitudes

$$a_R = |v_1|, \quad a_A = |v_2|,$$

we write

$$v_1 = +a_R, \quad v_2 = -a_A.$$

With radii s_R (repulsion) and s_A (attraction), the scalar radial profile is

$$\phi(r) = a_R \exp\left(-\frac{r^2}{2s_R^2}\right) - a_A \exp\left(-\frac{r^2}{2s_A^2}\right),$$

and

$$f_I(X, x_i) = \frac{1}{n} \sum_{j=1}^n \phi(\|x_i - x_j\|) (x_i - x_j),$$

with the $j = i$ contribution removed.

Attention On/Off

With the w_{ij} notation above, two internal-force modes are used.

Attention Off

$$f_i = \frac{1}{n} \sum_{k=1}^K \sum_{j=1}^n v_k g_{s_k}(x_i - x_j) w_{ij}.$$

Attention On

$$f_i = \sum_{k=1}^K \sum_{j=1}^n v_k \frac{g_{s_k}(x_i - x_j)}{\sum_{\ell=1}^n g_{s_k}(x_i - x_\ell)} w_{ij}.$$