

Code and Data
**for “Computing the gradients with respect to all parameters of a quantum
neural network using a single circuit”**

Guang Ping He
School of Physics, Sun Yat-sen University, Guangzhou 510275, China
hegp@mail.sysu.edu.cn

Overview:

All the software code of the Python programs for generating these data are located in the “code” directory.

All the output data of the experiments in the paper are in the “data” directory.

About the programs:

- File list:
 - 1_grad_conventional_real_8d.py*
 - 2_grad_conventional_sim_8d.py*
 - 3_grad_conventional_sim_784d.py*
 - 4_grad_improved_real_8d.py*
 - 5_grad_improved_sim_8d.py*
 - 6_grad_improved_sim_784d.py*
 - 7_individual_shot_loader.py*
 - 8_input_data_generator.py*
- File name explanation:
 - “8d”: taking the 8-dimensional input data set *input_data_8d.pickle* generated by program 8.
 - “784d”: taking the 784-dimensional input data, i.e., the MNIST data set*.
 - “real”: using a real quantum hardware.
 - “sim”: using a quantum simulator.
 - “conventional”, “conv”: using the conventional approach.
 - “improved”, “impr”: using the improved approach.
- * The MNIST data set is available at:
<https://github.com/mnielsen/neural-networks-and-deep-learning/archive/master.zip>
- Programs 1-3 read *parameters.csv* and output the following files:
gradient_conv.csv: the gradients with respect to the adjustable parameters of the

VQC.

job_result_conv.pickle: raw data generated by the quantum simulator or real quantum hardware.

mapped_data_conv.pickle: the processed result of the data generated by the quantum simulator or real quantum hardware.

other_results_conv.csv: runtimes and other related informations.

cost_conv.csv (for program 3 only): the values of all the unshifted and shifted cost functions.

- Programs 4-6 read *parameters.csv* and output the following files:
gradient_impr.csv: the gradients with respect to the adjustable parameters of the VQC.
job_result_impr.pickle: raw data generated by the quantum simulator or real quantum hardware.
mapped_data_impr.pickle: the processed result of the data generated by the quantum simulator or real quantum hardware.
other_results_impr.csv: runtimes and other related informations.
individual_shot_impr.pickle: the individual shot numbers for all the unshifted and shifted cost functions.
cost_impr.csv (for program 6 only): the values of all the unshifted and shifted cost functions.
- Program 7 *individual_shot_loader.py*:
Load the file *individual_shot_impr.pickle* and convert it into *individual_shot_impr.csv*.
- Program 8 *input_data_generator.py*:
Generate the data set *input_data_8d.pickle*.

About the data files:

- *parameters.csv*:
The initial values of all adjustable parameters of all the variational quantum circuits (VQCs) used in the paper.
The VQC with 8-dimensional classical input uses the first 6 data in the file only.
The VQC with 784-dimensional classical input uses all the 30 data in the file.
The values are generated randomly, uniformly distributed over the interval $[0, \pi)$.
- *input_data_8d.pickle*:
The input data set for the VQC with 8-dimensional classical input.
Generated randomly by the program *8-input_data_generator.py*, uniformly distributed over the interval $[0, 1)$.

- *fig4_data.csv*:
Data for Fig.4.
Each row contains the individual shot numbers corresponding to each input data point. The individual shot numbers in the 1st column are for the unshifted cost functions, while the individual shot numbers in the 2nd to 13rd columns are for the shifted cost functions.
Computed by *5_grad_improved_sim_8d.py*, then converted from the output file *individual_shot Impr.pickle* using *7_individual_shot_loader.py*.

- *fig5_data.csv*:
Data for Fig.5.
The content is self-explained.
The data for Fig.5a is computed using programs 2 and 5.
The data for Fig.5b is computed using programs 1 and 4.
The data for Fig.5c is computed using programs 3 and 6.
(The value of “num_data” in these programs needs to be adjusted manually for different data point in the figures.)

- The data for Table 1 of the paper (not shown here) is computed using programs 2 and 5, where the value of “shots” in program 2 needs to be adjusted manually.