



# UMD DATA605: Big Data Systems

## Lesson 1.3: Data Models

**Instructor:** Dr. GP Saggese - [gsaggese@umd.edu](mailto:gsaggese@umd.edu)


# Data Models

---

- **Data modeling**
  - Represents and captures structure and properties of real-world entities
  - Abstraction: real-world → **representation**
- **Data model**
  - Describes how data is *represented* (e.g., relational, key-value) and *accessed* (e.g., insert operations, query)
  - Schema in a DB describes a specific data collection using a data model
- **Why need data model?**
  - Know data structure to write general-purpose code
  - Share data across programs, organizations, systems
  - Integrate information from multiple sources
  - Preprocess data for efficient access (e.g., building an index)

# Multiple Layers of Data Modeling

- **Physical layer**
  - How is the data physically stored
  - How to represent complex data structures (e.g., B-trees for indexing)
- **Logical layer**
  - Entities
  - Attributes
  - Type of information stored
  - Relationships among the above
- **Views**
  - Restrict information flow
  - Security and/or ease-of-use



# Data Models: Logical Layer

- **Modeling constructs**


- Concepts to represent data structure
- E.g.,
  - Entity types
  - Entity attributes
  - Relationships between entities
  - Relationships between attributes

- **Integrity constraints**

- Ensure data integrity
  - Avoid errors and inconsistencies
  - E.g., field can't be empty, must be an integer

- **Manipulation constructs**

- E.g., insert, update, delete data



# Examples of Data Models

---

- We will cover:
  - Relational model (SQL)
  - Entity-relationship (ER) model
  - XML
  - Object-oriented (OO)
  - Object-relational
  - RDF
  - Property graph
- Serialization formats as data models
  - CSV
  - Parquet
  - JSON
  - Protocol Buffer
  - Avro/Thrift
  - Python Pickle

# Good Data Models

---

- Data model should be:
  - Expressive
    - Capture real-world data
  - Easy to use
  - Perform well
- Tension between characteristics
  - Powerful models
    - Represent more datasets
    - Harder to use/query
    - Less efficient (e.g., more memory, time)
- Evolution of data modeling tools captures data structure
  - Structured data → Relational DBs
  - Semi-structured web data → XML, JSON
  - Unstructured data → NoSQL DBs

# Data Independence

---

- **Logical data independence**
  - Change data representation without altering programs
  - E.g., API abstracting backend
- **Physical data independence**
  - Change data layout on disk without altering programs
    - Index data
    - Partition/distribute/replicate data
    - Compress data
    - Sort data

# Databases: A Brief History

---

- **1960s: Early beginning**
  - Computers become attractive technology
  - Enterprises adopt computers
  - Applications use own data stores
    - Each application has its own format
    - Data unavailable to other programs
  - **Database:** term for “shared data banks” by multiple applications
    - Define data format
    - Store as “data dictionary” (schema)
    - Implement “database management” software to access data
  - Issues:
    - How to write data dictionaries?
    - How to access data?
    - Who controls the data?
    - E.g., integrity, security, privacy concerns



# Databases: A Brief History

---

- **1960s, Hierarchical and Network Model**
  - Connect records of different types
  - Example: connect accounts with customers
  - Network model aimed for generality and flexibility
- IBM's IMS Hierarchical Database (1966)
  - Designed for Apollo space program
  - Predates hard disks
  - Used by over 95% of top Fortune 1000 companies
  - Processes 50 billion transactions daily, manages 15 million gigabytes of data
- Cons:
  - Exposed too much internal data (structures/pointers)
  - Leaky abstraction

# Relational, Hierarchical, Network Model

- **Relational model**


- Data as tuples in relations
- SQL

- **Hierarchical model**


- Tree-like structure
  - One parent, many children
  - Connected through links
- XML DBs resurgence in 1990s

- **Network model**

- Graph organization
  - Multiple parents and children
- Graph DBs resurgence in 2010s



Customer ID	Tax ID	Name	Address	[More fields...]
1234567890	555-5512222	Ramesh	323 Southern Avenue	...
2223344556	555-5523232	Adam	1200 Main Street	...
3334445563	555-5533323	Shweta	871 Rani Jhansi Road	...
4232342432	555-5325523	Sarfaraz	123 Maulana Azad Sarani	...





# Databases: A Brief History

---

- **1970s: Relational model**
  - Set theory, first-order predicate logic
    - Ted Codd developed the Relational Model
  - Elegant, formal model
    - Provided data independence
    - Users didn't worry about data storage, processing
  - High-level query language
    - SQL based on relational algebra
  - Notion of normal forms
    - Reason about data and relations
    - Remove redundancies
- Influential projects:
  - INGRES (UC Berkeley), System R (IBM)
  - Ignored IMS compatibility
- Debates: Relational Model vs Network Model proponents

# Entity-Relationship Model

- 1976: Peter Chen proposed “Entity-Relationship Model”
- Describes knowledge as entities and relationships
- **Entities**: Physical or logical objects, “Nouns”
- **Relationships**: Connections between entities, “Verbs”
- Map ER model to relational DB:  
Entities, relationships → tables



# Databases: A Brief History

---

- **1980s: Relational model acceptance**
  - SQL standard due to IBM's backing
  - Enhanced relational model
    - Set-valued attributes, aggregation
- Late 80's
  - Object-oriented DBs
    - Store objects, not tables
    - Overcome *impedance mismatch* between languages and databases
  - Object-relational DBs
    - User-defined types
    - Combine object-oriented benefits with relational model
  - No expressive difference from pure relational model

# Object-Oriented

---

- OOP is a data model
  - Object behavior described through data (fields) and code (methods)
- **Composition**
  - Aka has-a relationships
  - E.g., Employee class has an Address class
- **Inheritance**
  - Aka is-a relationships
  - E.g., Employee class derives from Person class
- **Polymorphism**
  - Code executed depends on the class of the object
  - One interface, many implementations
  - E.g., draw() method on a Circle vs Square object, both descending from Shape class
- **Encapsulation**
  - E.g., private vs public fields/members
  - Prevents external code from accessing inner workings of an object

# Databases: A Brief History

- **Late 90's-today**
- Web/Internet emerges
- XML: eXtensible Markup Language
  - For *semi-structured* data
  - Tree-like structure
  - Flexible schema

```
<?xml version="1.0" encoding="UTF-8"?>
```

```
<CATALOG>
```

```
<CD>
```

```
<TITLE>Empire Burlesque</TITLE>
```

```
<ARTIST>Bob Dylan</ARTIST>
```

```
<COUNTRY>USA</COUNTRY>
```

```
<COMPANY>Columbia</COMPANY>
```

```
<PRICE>10.90</PRICE>
```

```
<YEAR>1985</YEAR>
```

```
</CD>
```

```
<CD>
```


```
<TITLE>Hide your heart</TITLE>
```

```
<ARTIST>Bonnie Tyler</ARTIST>
```

```
<COUNTRY>UK</COUNTRY>
```

# Resource Description Framework

- Aka RDF
- Key construct:  
“subject-predicate-object” triple
  - Subject=sky
  - Predicate=has-the-color
  - Object=blue
- Maps to a labeled, directed multi-graph
  - More general than a tree
- Stored in:
  - Relational DBs
  - Dedicated “triple-stores” DBs



```
01 <[\textcolor{blue}{\under  
02 <[\textcolor{blue}{\under  
03 <[\textcolor{blue}{\under  
04 <[\textcolor{blue}{\under  
05 <[\textcolor{blue}{\under  
06 <[\textcolor{blue}{\under  
07 <[\textcolor{blue}{\under
```



# Property Graph Model

- Graph:
  - Vertices and edges
  - Properties for each edge and vertex
- Stored in:
  - Relational DBs
  - Graph DBs

