

Distributed Gaussian Processes for Large-Scale Probabilistic Regression

Marc Deisenroth

Department of Computing
Imperial College London

<http://wp.doc.ic.ac.uk/sml/marc-deisenroth>

Joint work with Jun Wei Ng

Workshop on Gaussian Process Approximations
Copenhagen, 21 May 2015

Scaling Gaussian Processes to Large Data Sets

Two orthogonal approaches

- Sparse Gaussian processes
 - ▶▶ Use (smart) subset of data.
- Distributed Gaussian processes
 - ▶▶ Use full data set, distribute computations

Sparse Gaussian Processes

- Sparse approximations typically approximate a GP with N data points by a model with $M \ll N$ data points

Sparse Gaussian Processes

- Sparse approximations typically approximate a GP with N data points by a model with $M \ll N$ data points
- **Selection of these M data points can be tricky** and may involve non-trivial computations (e.g., optimizing inducing inputs)

Sparse Gaussian Processes

- ▶ Sparse approximations typically approximate a GP with N data points by a model with $M \ll N$ data points
- ▶ **Selection of these M data points can be tricky** and may involve non-trivial computations (e.g., optimizing inducing inputs)
- ▶ Simple (random) subset selection is fast and generally robust (Chalupka et al., 2013)


Sparse Gaussian Processes

- ▶ Sparse approximations typically approximate a GP with N data points by a model with $M \ll N$ data points
- ▶ **Selection of these M data points can be tricky** and may involve non-trivial computations (e.g., optimizing inducing inputs)
- ▶ Simple (random) subset selection is fast and generally robust (Chalupka et al., 2013)
- ▶ Computational complexity: $\mathcal{O}(M^3)$ or $\mathcal{O}(NM^2)$ for training


Sparse Gaussian Processes

- ▶ Sparse approximations typically approximate a GP with N data points by a model with $M \ll N$ data points
- ▶ **Selection of these M data points can be tricky** and may involve non-trivial computations (e.g., optimizing inducing inputs)
- ▶ Simple (random) subset selection is fast and generally robust (Chalupka et al., 2013)
- ▶ Computational complexity: $\mathcal{O}(M^3)$ or $\mathcal{O}(NM^2)$ for training
- ▶ Practical limit of the data set size is $N \in \mathcal{O}(10^6)$

Distributed Gaussian Processes




Distributed Gaussian Processes




- Randomly split the full data set into M chunks of size P

Distributed Gaussian Processes




- ▶ Randomly split the full data set into M chunks of size P
- ▶ Place M **independent GP experts** on these small chunks

Distributed Gaussian Processes



- ▶ Randomly split the full data set into M chunks of size P
- ▶ Place M **independent GP experts** on these small chunks
- ▶ Block-diagonal approximation of kernel matrix \mathbf{K} (sim. to PIC)

Distributed Gaussian Processes



- ▶ Randomly split the full data set into M chunks of size P
- ▶ Place M **independent GP experts** on these small chunks
- ▶ Block-diagonal approximation of kernel matrix \mathbf{K} (sim. to PIC)
- ▶ Combine independent computations to an overall result

Training the Distributed GP

- ▶ Randomly split data set of size N into M chunks of size P
- ▶ Independence of experts ►► Factorization of marginal likelihood:

$$\log p(\mathbf{y}|\mathbf{X}, \boldsymbol{\theta}) \approx \sum_{k=1}^M \log p_k(\mathbf{y}^{(k)}|\mathbf{X}^{(k)}, \boldsymbol{\theta})$$

Training the Distributed GP

- ▶ Randomly split data set of size N into M chunks of size P
- ▶ Independence of experts ►► Factorization of marginal likelihood:

$$\log p(\mathbf{y}|\mathbf{X}, \boldsymbol{\theta}) \approx \sum_{k=1}^M \log p_k(\mathbf{y}^{(k)}|\mathbf{X}^{(k)}, \boldsymbol{\theta})$$

- ▶ Distributed optimization and training straightforward
- ▶ No inducing/variational parameters ►► Easy optimization


Training the Distributed GP

- ▶ Randomly split data set of size N into M chunks of size P
- ▶ Independence of experts ►► Factorization of marginal likelihood:

$$\log p(\mathbf{y}|\mathbf{X}, \boldsymbol{\theta}) \approx \sum_{k=1}^M \log p_k(\mathbf{y}^{(k)}|\mathbf{X}^{(k)}, \boldsymbol{\theta})$$

- ▶ Distributed optimization and training straightforward
- ▶ No inducing/variational parameters ►► Easy optimization
- ▶ Computational complexity: $\mathcal{O}(MP^3)$ [instead of $\mathcal{O}(N^3)$]
- ▶ Memory footprint: $\mathcal{O}(MP^2 + ND)$ [instead of $\mathcal{O}(N^2 + ND)$], potentially distributed across M computing nodes


Scaling



- ▶ NLML is proportional to training time
- ▶ Full GP (16K training points) \approx sparse GP (32K training points) \approx distributed GP (16M training points)


► Push practical limit by order(s) of magnitude

Predictions with the Distributed GP



- ▶ Prediction of each GP expert is Gaussian $\mathcal{N}(\mu_i, \sigma_i^2)$
- ▶ How to combine them to an overall prediction $\mathcal{N}(\mu, \sigma^2)$?

Predictions with the Distributed GP



- ▶ Prediction of each GP expert is Gaussian $\mathcal{N}(\mu_i, \sigma_i^2)$
- ▶ How to combine them to an overall prediction $\mathcal{N}(\mu, \sigma^2)$?

▶▶ Product-of-GP-experts

- ▶ PoE (product of experts) ▶▶ (Ng & Deisenroth, 2014)
- ▶ gPoE (generalized product of experts) ▶▶ (Cao & Fleet, 2014)
- ▶ BCM (Bayesian Committee Machine) ▶▶ (Tresp, 2000)
- ▶ rBCM (robust BCM) ▶▶ (Deisenroth & Ng, 2015)

Objectives

- **Scale** to large data sets ✓

Objectives

- **Scale** to large data sets ✓
- **Good approximation** of full GP (“ground truth”)

Objectives




Figure: Two computational graphs

- ▶ **Scale** to large data sets ✓
- ▶ **Good approximation** of full GP (“ground truth”)
- ▶ Predictions **independent of computational graph**
 - ▶ Heterogeneous computing infrastructures (laptop, cluster, ...)

Objectives





Figure: Two computational graphs

- ▶ **Scale** to large data sets ✓
- ▶ **Good approximation** of full GP (“ground truth”)
- ▶ Predictions **independent of computational graph**
 - ▶ Heterogeneous computing infrastructures (laptop, cluster, ...)
- ▶ **Reasonable predictive variances**

Running Example



- ▶ Investigate various product-of-experts models
Same training procedure, but different mechanisms for predictions

Product of GP Experts

- Prediction model (independent predictors):

$$p(f_* | \mathbf{x}_*, \mathcal{D}) = \prod_{k=1}^M p_k(f_* | \mathbf{x}_*, \mathcal{D}^{(k)}),$$
$$p_k(f_* | \mathbf{x}_*, \mathcal{D}^{(k)}) = \mathcal{N}(f_* | \mu_k(\mathbf{x}_*), \sigma_k^2(\mathbf{x}_*))$$

Product of GP Experts


- ▶ Prediction model (independent predictors):

$$p(f_* | \mathbf{x}_*, \mathcal{D}) = \prod_{k=1}^M p_k(f_* | \mathbf{x}_*, \mathcal{D}^{(k)}),$$
$$p_k(f_* | \mathbf{x}_*, \mathcal{D}^{(k)}) = \mathcal{N}(f_* | \mu_k(\mathbf{x}_*), \sigma_k^2(\mathbf{x}_*))$$

- ▶ Predictive precision and mean:

$$(\sigma_*^{\text{poe}})^{-2} = \sum_k \sigma_k^{-2}(\mathbf{x}_*)$$
$$\mu_*^{\text{poe}} = (\sigma_*^{\text{poe}})^2 \sum_k \sigma_k^{-2}(\mathbf{x}_*) \mu_k(\mathbf{x}_*)$$


Computational Graph



Prediction:

$$p(f_* | \mathbf{x}_*, \mathcal{D}) = \prod_{k=1}^M p_k(f_* | \mathbf{x}_*, \mathcal{D}^{(k)})$$

Computational Graph




Prediction:

$$p(f_*|\mathbf{x}_*, \mathcal{D}) = \prod_{k=1}^M p_k(f_*|\mathbf{x}_*, \mathcal{D}^{(k)})$$

Multiplication is associative: $a * b * c * d = (a * b) * (c * d)$

Computational Graph




Prediction:

$$p(f_*|\mathbf{x}_*, \mathcal{D}) = \prod_{k=1}^M p_k(f_*|\mathbf{x}_*, \mathcal{D}^{(k)})$$

Multiplication is associative: $a * b * c * d = (a * b) * (c * d)$

$$\prod_{k=1}^M p_k(f_*|\mathcal{D}^{(k)}) = \prod_{k=1}^L \prod_{i=1}^{L_k} p_{k_i}(f_*|\mathcal{D}^{(k_i)}), \quad \sum_k L_k = M$$

Computational Graph



Prediction:


$$p(f_*|\mathbf{x}_*, \mathcal{D}) = \prod_{k=1}^M p_k(f_*|\mathbf{x}_*, \mathcal{D}^{(k)})$$

Multiplication is associative: $a * b * c * d = (a * b) * (c * d)$

$$\prod_{k=1}^M p_k(f_*|\mathcal{D}^{(k)}) = \prod_{k=1}^L \prod_{i=1}^{L_k} p_{k_i}(f_*|\mathcal{D}^{(k_i)}), \quad \sum_k L_k = M$$

►► Independent of computational graph ✓

Product of GP Experts



- Unreasonable variances for $M > 1$:

$$(\sigma_*^{\text{poe}})^{-2} = \sum_k \sigma_k^{-2}(\mathbf{x}_*)$$

- The more experts the more certain the prediction, even if every expert itself is very uncertain **✗** ►► Cannot fall back to the prior

Generalized Product of GP Experts (Cao & Fleet, 2014)

- Weight the responsibility of each expert in PoE with β_k

Generalized Product of GP Experts (Cao & Fleet, 2014)

- ▶ Weight the responsibility of each expert in PoE with β_k
- ▶ Prediction model (independent predictors):

$$p(f_* | \mathbf{x}_*, \mathcal{D}) = \prod_{k=1}^M p_k^{\beta_k}(f_* | \mathbf{x}_*, \mathcal{D}^{(k)})$$

$$p_k(f_* | \mathbf{x}_*, \mathcal{D}^{(k)}) = \mathcal{N}(f_* | \mu_k(\mathbf{x}_*), \sigma_k^2(\mathbf{x}_*))$$

Generalized Product of GP Experts (Cao & Fleet, 2014)

- ▶ Weight the responsibility of each expert in PoE with β_k
- ▶ Prediction model (independent predictors):

$$p(f_* | \mathbf{x}_*, \mathcal{D}) = \prod_{k=1}^M p_k^{\beta_k}(f_* | \mathbf{x}_*, \mathcal{D}^{(k)})$$

$$p_k(f_* | \mathbf{x}_*, \mathcal{D}^{(k)}) = \mathcal{N}(f_* | \mu_k(\mathbf{x}_*), \sigma_k^2(\mathbf{x}_*))$$

- ▶ Predictive precision and mean:

$$(\sigma_*^{\text{gpoe}})^{-2} = \sum_k \beta_k \sigma_k^{-2}(\mathbf{x}_*)$$

$$\mu_*^{\text{gpoe}} = (\sigma_*^{\text{gpoe}})^2 \sum_k \beta_k \sigma_k^{-2}(\mathbf{x}_*) \mu_k(\mathbf{x}_*)$$

Generalized Product of GP Experts (Cao & Fleet, 2014)

- ▶ Weight the responsibility of each expert in PoE with β_k
- ▶ Prediction model (independent predictors):

$$p(f_* | \mathbf{x}_*, \mathcal{D}) = \prod_{k=1}^M p_k^{\beta_k}(f_* | \mathbf{x}_*, \mathcal{D}^{(k)})$$

$$p_k(f_* | \mathbf{x}_*, \mathcal{D}^{(k)}) = \mathcal{N}(f_* | \mu_k(\mathbf{x}_*), \sigma_k^2(\mathbf{x}_*))$$


- ▶ Predictive precision and mean:

$$(\sigma_*^{\text{gpoe}})^{-2} = \sum_k \beta_k \sigma_k^{-2}(\mathbf{x}_*)$$

$$\mu_*^{\text{gpoe}} = (\sigma_*^{\text{gpoe}})^2 \sum_k \beta_k \sigma_k^{-2}(\mathbf{x}_*) \mu_k(\mathbf{x}_*)$$

- ▶ With $\sum_k \beta_k = 1$, the model can fall back to the prior ✓
 - ▶▶ Log-opinion pool model (e.g., Heskes, 1998)


Computational Graph



Prediction:

$$p(f_* | \mathbf{x}_*, \mathcal{D}) = \prod_{k=1}^M p_k^{\beta_k}(f_* | \mathbf{x}_*, \mathcal{D}^{(k)}) = \prod_{k=1}^L \prod_{i=1}^{L_k} p_{k_i}^{\beta_{k_i}}(f_* | \mathcal{D}^{(k_i)}), \quad \sum_{k,i} \beta_{k_i} = 1$$

Computational Graph




Prediction:

$$p(f_* | \mathbf{x}_*, \mathcal{D}) = \prod_{k=1}^M p_k^{\beta_k}(f_* | \mathbf{x}_*, \mathcal{D}^{(k)}) = \prod_{k=1}^L \prod_{i=1}^{L_k} p_{k_i}^{\beta_{k_i}}(f_* | \mathcal{D}^{(k_i)}), \quad \sum_{k,i} \beta_{k_i} = 1$$

- Independent of computational graph if $\sum_{k,i} \beta_{k_i} = 1$ ✓

Computational Graph




Prediction:

$$p(f_* | \mathbf{x}_*, \mathcal{D}) = \prod_{k=1}^M p_k^{\beta_k}(f_* | \mathbf{x}_*, \mathcal{D}^{(k)}) = \prod_{k=1}^L \prod_{i=1}^{L_k} p_{k_i}^{\beta_{k_i}}(f_* | \mathcal{D}^{(k_i)}), \quad \sum_{k,i} \beta_{k_i} = 1$$

- Independent of computational graph if $\sum_{k,i} \beta_{k_i} = 1$ ✓
- A priori setting of β_{k_i} required ✗
 - ▶ $\beta_{k_i} = 1/M$ a priori (✓)

Generalized Product of GP Experts



- ▶ Same mean as PoE
- ▶ Model no longer overconfident and falls back to prior ✓
- ▶ **Very conservative** variances ✗

Bayesian Committee Machine (Tresp, 2000)

- ▶ Apply Bayes' theorem when combining predictions (and not only for computing predictions)

Bayesian Committee Machine (Tresp, 2000)

- ▶ Apply Bayes' theorem when combining predictions (and not only for computing predictions)
- ▶ Prediction model (conditional independence: $\mathcal{D}^{(j)} \perp\!\!\!\perp \mathcal{D}^{(k)} | f_*$):

$$p(f_* | \mathbf{x}_*, \mathcal{D}) = \frac{\prod_{k=1}^M p_k(f_* | \mathbf{x}_*, \mathcal{D}^{(k)})}{p^{M-1}(f_*)}$$

Bayesian Committee Machine (Tresp, 2000)

- ▶ Apply Bayes' theorem when combining predictions (and not only for computing predictions)
- ▶ Prediction model (conditional independence: $\mathcal{D}^{(j)} \perp\!\!\!\perp \mathcal{D}^{(k)} | f_*$):

$$p(f_* | \mathbf{x}_*, \mathcal{D}) = \frac{\prod_{k=1}^M p_k(f_* | \mathbf{x}_*, \mathcal{D}^{(k)})}{p^{M-1}(f_*)}$$

- ▶ Predictive precision and mean:

$$\begin{aligned} (\sigma_*^{\text{bcm}})^{-2} &= \sum_{k=1}^M \sigma_k^{-2}(\mathbf{x}_*) - (M-1) \sigma_{**}^{-2} \\ \mu_*^{\text{bcm}} &= (\sigma_*^{\text{bcm}})^2 \sum_{k=1}^M \sigma_k^{-2}(\mathbf{x}_*) \mu_k(\mathbf{x}_*) \end{aligned}$$

Bayesian Committee Machine (Tresp, 2000)

- ▶ Apply Bayes' theorem when combining predictions (and not only for computing predictions)
- ▶ Prediction model (conditional independence: $\mathcal{D}^{(j)} \perp\!\!\!\perp \mathcal{D}^{(k)} | f_*$):

$$p(f_* | \mathbf{x}_*, \mathcal{D}) = \frac{\prod_{k=1}^M p_k(f_* | \mathbf{x}_*, \mathcal{D}^{(k)})}{p^{M-1}(f_*)}$$

- ▶ Predictive precision and mean:

$$\begin{aligned}(\sigma_*^{\text{bcm}})^{-2} &= \sum_{k=1}^M \sigma_k^{-2}(\mathbf{x}_*) - (M-1)\sigma_{**}^{-2} \\ \mu_*^{\text{bcm}} &= (\sigma_*^{\text{bcm}})^2 \sum_{k=1}^M \sigma_k^{-2}(\mathbf{x}_*) \mu_k(\mathbf{x}_*)\end{aligned}$$

- ▶ Product of GP experts, divided by $M-1$ times the prior

Bayesian Committee Machine (Tresp, 2000)

- ▶ Apply Bayes' theorem when combining predictions (and not only for computing predictions)
- ▶ Prediction model (conditional independence: $\mathcal{D}^{(j)} \perp\!\!\!\perp \mathcal{D}^{(k)} | f_*$):


$$p(f_* | \mathbf{x}_*, \mathcal{D}) = \frac{\prod_{k=1}^M p_k(f_* | \mathbf{x}_*, \mathcal{D}^{(k)})}{p^{M-1}(f_*)}$$

- ▶ Predictive precision and mean:

$$\begin{aligned}(\sigma_*^{\text{bcm}})^{-2} &= \sum_{k=1}^M \sigma_k^{-2}(\mathbf{x}_*) - (M-1)\sigma_{**}^{-2} \\ \mu_*^{\text{bcm}} &= (\sigma_*^{\text{bcm}})^2 \sum_{k=1}^M \sigma_k^{-2}(\mathbf{x}_*) \mu_k(\mathbf{x}_*)\end{aligned}$$

- ▶ Product of GP experts, divided by $M-1$ times the prior
- ▶ Guaranteed to fall back to the prior outside data regime ✓


Computational Graph



Prediction:

$$p(f_* | \mathbf{x}_*, \mathcal{D}) = \frac{\prod_{k=1}^M p_k(f_* | \mathbf{x}_*, \mathcal{D}^{(k)})}{p^{M-1}(f_*)}$$

Computational Graph




Prediction:

$$p(f_* | \mathbf{x}_*, \mathcal{D}) = \frac{\prod_{k=1}^M p_k(f_* | \mathbf{x}_*, \mathcal{D}^{(k)})}{p^{M-1}(f_*)}$$

$$\frac{\prod_{k=1}^M p_k(f_* | \mathcal{D}^{(k)})}{p^{M-1}(f_*)} = \frac{\prod_{k=1}^L \prod_{i=1}^{L_k} p_{k_i}(f_* | \mathcal{D}^{(k_i)})}{p^{M-1}(f_*)}$$

Computational Graph




Prediction:

$$p(f_* | \mathbf{x}_*, \mathcal{D}) = \frac{\prod_{k=1}^M p_k(f_* | \mathbf{x}_*, \mathcal{D}^{(k)})}{p^{M-1}(f_*)}$$

$$\frac{\prod_{k=1}^M p_k(f_* | \mathcal{D}^{(k)})}{p^{M-1}(f_*)} = \frac{\prod_{k=1}^L \prod_{i=1}^{L_k} p_{k_i}(f_* | \mathcal{D}^{(k_i)})}{p^{M-1}(f_*)}$$

►► Independent of computational graph ✓

Bayesian Committee Machine



- ▶ Independent of computational graph ✓
- ▶ Variance estimates are about right ✓
- ▶ When leaving the data regime, the BCM can produce junk ✗

►► **Robustify**

Robust Bayesian Committee Machine

- Combine gPoE (weighting of experts) with the BCM (Bayes' theorem when combining predictions)

Robust Bayesian Committee Machine

- ▶ Combine gPoE (weighting of experts) with the BCM (Bayes' theorem when combining predictions)
- ▶ Prediction model (conditional independence $\mathcal{D}^{(j)} \perp\!\!\!\perp \mathcal{D}^{(k)} | f_*$):

$$p(f_* | \mathbf{x}_*, \mathcal{D}) = \frac{\prod_{k=1}^M p_k^{\beta_k}(f_* | \mathbf{x}_*, \mathcal{D}^{(k)})}{p^{\sum_k \beta_k - 1}(f_*)}$$

Robust Bayesian Committee Machine


- ▶ Combine gPoE (weighting of experts) with the BCM (Bayes' theorem when combining predictions)
- ▶ Prediction model (conditional independence $\mathcal{D}^{(j)} \perp\!\!\!\perp \mathcal{D}^{(k)} | f_*$):

$$p(f_* | \mathbf{x}_*, \mathcal{D}) = \frac{\prod_{k=1}^M p_k^{\beta_k}(f_* | \mathbf{x}_*, \mathcal{D}^{(k)})}{p^{\sum_k \beta_k - 1}(f_*)}$$

- ▶ Predictive precision and mean:

$$\begin{aligned} (\sigma_*^{\text{rbcm}})^{-2} &= \sum_{k=1}^M \beta_k \sigma_k^{-2}(\mathbf{x}_*) + (1 - \sum_{k=1}^M \beta_k) \sigma_{**}^{-2}, \\ \mu_*^{\text{rbcm}} &= (\sigma_*^{\text{rbcm}})^2 \sum_k \beta_k \sigma_k^{-2}(\mathbf{x}_*) \mu_k(\mathbf{x}_*) \end{aligned}$$


Computational Graph



Prediction:

$$p(f_* | \mathbf{x}_*, \mathcal{D}) = \frac{\prod_{k=1}^M p_k^{\beta_k}(f_* | \mathbf{x}_*, \mathcal{D}^{(k)})}{p^{\sum_k \beta_k - 1}(f_*)} = \frac{\prod_{k=1}^L \prod_{i=1}^{L_k} p_{k_i}^{\beta_{k_i}}(f_* | \mathcal{D}^{(k_i)})}{p^{\sum_k \beta_k - 1}(f_*)}$$

Computational Graph




Prediction:

$$p(f_* | \mathbf{x}_*, \mathcal{D}) = \frac{\prod_{k=1}^M p_k^{\beta_k}(f_* | \mathbf{x}_*, \mathcal{D}^{(k)})}{p^{\sum_k \beta_k - 1}(f_*)} = \frac{\prod_{k=1}^L \prod_{i=1}^{L_k} p_{k_i}^{\beta_{k_i}}(f_* | \mathcal{D}^{(k_i)})}{p^{\sum_k \beta_k - 1}(f_*)}$$


►► Independent of computational graph, even with arbitrary β_k ✓

Robust Bayesian Committee Machine




- Does not break down in case of weak experts ► Robustified ✓
- Robust version of BCM ► Reasonable predictions ✓
- Independent of computational graph (for all choices of β_k) ✓

Empirical Approximation Error



- ▶ Simulated robot arm data (10K training, 30K test)
- ▶ All models use hyper-parameters of ground-truth full GP
- ▶ RMSE as a function of the training time
- ▶ Sparse GP (SOR) performs worse than any distributed GP
- ▶ rBCM performs best with “weak” GP experts

Empirical Approximation Error (2)




- ▶ NLPD as a function of the training time ►► Mean and variance
- ▶ BCM and PoE are not robust to weak experts
- ▶ gPoE suffers from too conservative variances
- ▶ rBCM consistently outperforms other methods

Large Data

- ▶ Predict US Airline Delays (01/2008–04/2008) of commercial flights
- ▶ Inputs: age of aircraft, flight distance, departure/arrival time, airtime, day of week, day of month, month,
- ▶ Training data: 700K, 2M, 5M. Test data: 100K


Training Data: 700K — RMSE



- ▶ (r)BCM and (g)PoE with 4096 GP experts
- ▶ Gradient time: 13 seconds (12 cores)
- ▶ Inducing inputs: Dist-VGP (Gal et al., 2014), SVI-GP (Hensman et al., 2013)

- ▶ rBCM performs best
- ▶ (g)PoE and BCM performs not worse sparse GPs


Training Data: 700K — NLPD



- ▶ (r)BCM and (g)PoE with 4096 GP experts
- ▶ Gradient time: 13 seconds (12 cores)
- ▶ No results reported for inducing input methods (Gal et al., 2014; Hensman et al., 2013)

- ▶ gPoE performs best, just ahead of rBCM


Training Data: 2M — RMSE



- ▶ (r)BCM and (g)PoE with 8192 GP experts
- ▶ Gradient time: 39 seconds (12 cores)
- ▶ Inducing inputs: Dist-VGP (Gal et al., 2014)

- ▶ rBCM performs best
- ▶ (g)PoE as good as best results reported for sparse methods
- ▶ BCM suffers from weak experts


Training Data: 2M — NLPD



- ▶ (r)BCM and (g)PoE with 8192 GP experts
- ▶ Gradient time: 39 sec (12 cores)
- ▶ Inducing inputs: no results reported

- ▶ rBCM and gPoE perform best
- ▶ BCM suffers from weak experts
- ▶ PoE suffers from under-estimation of variances


Training Data: 5M — RMSE



- ▶ (r)BCM and (g)PoE with 32768 GP experts
- ▶ Gradient time: 90 sec (12 cores)

- ▶ rBCM performs best
- ▶ (g)PoE produce good results
- ▶ BCM off the chart ► suffers from weak experts

Training Data: 5M — NLPD



- ▶ (r)BCM and (g)PoE with 32768 GP experts
- ▶ Gradient time: 90 sec (12 cores)

- ▶ rBCM and gPoE perform best
- ▶ PoE and BCM significantly worse

Overview Airline Delays

- ▶ RMSE: rBCM consistently performs best
- ▶ NLPD: rBCM and gPoE approximately the same
 - ▶▶ gPoE recovers because of conservative variance estimates
- ▶ BCM suffers from “wrong means”, PoE suffers from overconfident estimates
- ▶ All models: Training time is acceptable
- ▶ All experiments (DGP) run on a laptop

Summary

- Distributed product-of-experts approaches to scaling Gaussian processes to large data sets
- Robust Bayesian Committee Machine
- Model **conceptually straightforward** and **easy to train**
 - ▶ Only kernel hyper-parameters need to be optimized
- **Independent of computational graph**
- **Scales** to arbitrarily large data sets (in principle)

`m.deisenroth@imperial.ac.uk`

Thank you for your attention

References

- [1] Y. Cao and D. J. Fleet. Generalized Product of Experts for Automatic and Principled Fusion of Gaussian Process Predictions. <http://arxiv.org/abs/1410.7827>, October 2014.
- [2] K. Chalupka, C. K. I. Williams, and I. Murray. A Framework for Evaluating Approximate Methods for Gaussian Process Regression. *Journal of Machine Learning Research*, 14:333–350, February 2013.
- [3] M. P. Deisenroth and J. Ng. Distributed Gaussian Processes. In *Proceedings of the International Conference on Machine Learning*, 2015.
- [4] Y. Gal, M. van der Wilk, and C. E. Rasmussen. Distributed Variational Inference in Sparse Gaussian Process Regression and Latent Variable Models. In *Advances in Neural Information Processing Systems*. 2014.
- [5] J. Hensman, N. Fusi, and N. D. Lawrence. Gaussian Processes for Big Data. In A. Nicholson and P. Smyth, editors, *Proceedings of the Conference on Uncertainty in Artificial Intelligence*. AUAI Press, 2013.
- [6] T. Heskes. Selecting Weighting Factors in Logarithmic Opinion Pools. In *Advances in Neural Information Processing Systems*, pages 266–272. Morgan Kaufman, 1998.
- [7] J. Ng and M. P. Deisenroth. Hierarchical Mixture-of-Experts Model for Large-Scale Gaussian Process Regression. <http://arxiv.org/abs/1412.3078>, December 2014.
- [8] J. Quiñero-Candela and C. E. Rasmussen. A Unifying View of Sparse Approximate Gaussian Process Regression. *Journal of Machine Learning Research*, 6(2):1939–1960, 2005.
- [9] E. Snelson and Z. Ghahramani. Sparse Gaussian Processes using Pseudo-inputs. In Y. Weiss, B. Schölkopf, and J. C. Platt, editors, *Advances in Neural Information Processing Systems 18*, pages 1257–1264. The MIT Press, Cambridge, MA, USA, 2006.
- [10] M. K. Titsias. Variational Learning of Inducing Variables in Sparse Gaussian Processes. In *Proceedings of the International Conference on Artificial Intelligence and Statistics*, 2009.
- [11] V. Tresp. A Bayesian Committee Machine. *Neural Computation*, 12(11):2719–2741, 2000.