

Anomaly Detection



In this lecture we want to talk about anomaly detection using neural networks.



We want to do this in a unsupervised manner



Image Credits openclipart.org:

by cactus_cowboy
by buggi
by trubinal_guru
by dtjohnnymonkey
by magicvince



Romeo Kienzler

So remember, in supervised learning we have our data..




Image Credits openclipart.org:

by cactus_cowboy
by buggi
by trubinal_guru
by dtjohnnymonkey
by magicvince

IBM Watson IoT™ © Copyright IBM Corp. 2017 Romeo Kienzler

..but each item in our data set needs to be assigned with a label, either a class or a continuous values.



Image Credits openclipart.org:

by cactus_cowboy
by buggi
by trubinal_guru
by dtjohnnymonkey
by magicvince



Romeo Kienzler

We call this target value which we want to predict.



Image Credits openclipart.org:

by cactus_cowboy
by buggi
by trubinal_guru
by dtjohnnymonkey
by magicvince

IBM Watson IoT™ © Copyright IBM Corp. 2017 Romeo Kienzler

In the case of anomaly detection this can be a binary target indicating an anomaly or not





Image Credits openclipart.org:

by cactus_cowboy
by buggi
by trubinal_guru
by dtjohnnymonkey
by magicvince

IBM Watson IoT™ © Copyright IBM Corp. 2017 Romeo Kienzler


Or a continuous value - so an anomaly score or R-U-L - value for example. R-U-L stands for remaining useful lifetime



IBM Watson IoT™ © Copyright IBM Corp. 2017

Romeo Kienzler

Given that labeled data a model is trained



- in this case - a supervised mode since we tell the model to replicate the hidden functions underlying the labeled dataset.



Image Credits openclipart.org:
by cactus_cowboy
by buggi
by trubinal_guru
by dtjohnnymonkey
by magicvince

IBM Watson IoT™ © Copyright IBM Corp. 2017

Romeo Kienzler

since there is far more unlabelled data available




Image Credits openclipart.org:

by cactus_cowboy
by buggi
by trubinal_guru
by dtjohnnymonkey
by magicvince

IBM Watson IoT™ © Copyright IBM Corp. 2017

Romeo Kienzler

than labeled.....





Image Credits openclipart.org:

by cactus_cowboy
by buggi
by trubinal_guru
by dtjohnnymonkey
by magicvince

IBM Watson IoT™ © Copyright IBM Corp. 2017

Romeo Kienzler


therefore we want to get rid of the boss



Data Credit:
<http://csegroups.case.edu/bearingdatacenter/pages/welcome-case-western-reserve-university-bearing-data-center-website>




So it turns out that this is not a trivial task. So look at this time series from two accelerometer based vibration sensors attached to a bearing. One vibration axis is shown in red, the other one in blue. So how can we predict if the bearing is in a healthy or faulty condition? In this case I'm telling you that the bearing is totally fine. So let's have a look at data from a faulty bearing.




Data Credit:
<http://csegrou...>




Hard to tell, isn't it? :) ... so let's zoom in a bit and check again....



So on the top we see healthy data...




...and on the bottom faulty one...ok...at least we can tell that they are different. We are using our biological neural network in order to see this. So what if we use an artificial neural network for doing the same?




IBM Watson IoT™ © Copyright IBM Corp. 2017 Romeo Kienzler

So if your brain...




IBM Watson IoT™ © Copyright IBM Corp. 2017 Romeo Kienzler

looks




IBM Watson IoT™ © Copyright IBM Corp. 2017 Romeo Kienzler

at two different time series plots it might be able to spot the difference. So in theory we would implement a neural network which does exactly the same. A convolution neural network for example can look at the two different figures and tell us whether it finds an anomaly or not. To be honest, I haven't tried that, so I leave this up to you as an exercise :)




IBM Watson IoT™ © Copyright IBM Corp. 2017 Romeo Kienzler

But what we can do is using a LSTM - a Long Short Term Memory network for analysis. Remember, a LSTM is touring complete and ideally fit's time series and sequence data.




IBM Watson IoT™ © Copyright IBM Corp. 2017 Romeo Kienzler

But isn't there a problem? Since this is unsupervised machine learning we have no way in training this neural network because we need a label




So the task of the neural network is to take X...




IBM Watson IoT™ © Copyright IBM Corp. 2017 Romeo Kienzler

and adjust the weights..so that it



reconstructs y .



By Chervinskii (Own work) [CC BY-SA 4.0 (<https://creativecommons.org/licenses/by-sa/4.0>)], via Wikimedia Commons



But hopefully you remember what an auto encoder does. So an auto encoder is trained by using X as input and as output as well. So an auto encoder will try to reconstruct it's input at the output side. And if we now train an LSTM auto encoder with healthy time series data it will learn to reconstruct healthy data but will have a hard time to reconstruct faulty data.




Image Credits openclipart.org:
by doodleguy

IBM Watson IoT™ © Copyright IBM Corp. 2017 Romeo Kienzler

But how do we know if we are training the model with healthy or faulty data? So this is quite simple.



Image Credits openclipart.org:
by cactus_cowboy
by buggi
by trubinal_guru
by dtjohnnymonkey
by magicvince

IBM Watson IoT™ © Copyright IBM Corp. 2017

Romeo Kienzler

Because in a real world scenario




Image Credits openclipart.org:

by cactus_cowboy
by buggi
by trubinal_guru
by dtjohnnymonkey
by magicvince

IBM Watson IoT™ © Copyright IBM Corp. 2017

Romeo Kienzler

there is much more healthy...




Image Credits openclipart.org:

by cactus_cowboy
by buggi
by trubinal_guru
by dtjohnnymonkey
by magicvince

IBM Watson IoT™

© Copyright IBM Corp. 2017

Romeo Kienzler

than broken data available for training. So if we randomly pick a sample chances are very low that we pick faulty data. There are much more strategies behind this which are often domain specific, therefore we won't go into more details here.

Implement an anomaly detector



In the next module we will implement an LSTM auto encoder based anomaly detector in Keras, so stay tuned :)