

+ C

Name Last Modified

- DB0201EN-Week3-1-1-Conn... 10 days ago
- DB0201EN-Week3-1-2-Quer... 10 days ago
- DB0201EN-Week3-1-4-Anal... 3 days ago
- DB0201EN-Week4-1-1-Real... 5 hours ago
- DB0201EN-Week4-2-Peer... seconds ago

Launcher X DB0201EN-Week4-2-Peer X Markdown Python ○



Assignment: Notebook for Peer Assignment

Introduction

Using this Python notebook you will:

- Understand 3 Chicago datasets
- Load the 3 datasets into 3 tables in a Db2 database
- Execute SQL queries to answer assignment questions

Understand the datasets

To complete the assignment problems in this notebook you will be using three datasets that are available on the city of Chicago's Data Portal:

- Socioeconomic Indicators in Chicago
- Chicago Public Schools
- Chicago Crime Data

1. Socioeconomic Indicators in Chicago

This dataset contains a selection of six socioeconomic indicators of public health significance and a "hardship index," for each Chicago community area, for the years 2008 – 2012.

For this assignment you will use a snapshot of this dataset which can be downloaded from: <https://ibm.box.com/shared/static/05c3415cbfbfnr2fx4atenb2sd361ze.csv>

A detailed description of this dataset and the original dataset can be obtained from the Chicago Data Portal at: <https://data.cityofchicago.org/Health-Human-Services/Census-Data-Selected-socioeconomic-indicators-in-C/kn9c-c2s2>

2. Chicago Public Schools

This dataset shows all school level performance data used to create CPS School Report Cards for the 2011-2012 school year. This dataset is provided by the city of Chicago's Data Portal.

For this assignment you will use a snapshot of this dataset which can be downloaded from: <https://ibm.box.com/shared/static/f9gjvj1gjmxxzycdhplzt01qtz0s7ew7ew7f.csv>

A detailed description of this dataset and the original dataset can be obtained from the Chicago Data Portal at: <https://data.cityofchicago.org/Education/Chicago-Public-Schools-Progress-Report-Cards-2011-/9xs2-f89t>

3. Chicago Crime Data

This dataset reflects reported incidents of crime (with the exception of murders where data exists for each victim) that occurred in the City of Chicago from 2001 to present, minus the most recent seven days.

This dataset is quite large - over 1.5GB in size with over 6.5 million rows. For the purposes of this assignment we will use a much smaller sample of this dataset which can be downloaded from: <https://ibm.box.com/shared/static/svflyugsr9zbqy5bmowgsqemfpmlx7f.csv>

A detailed description of this dataset and the original dataset can be obtained from the Chicago Data Portal at: <https://data.cityofchicago.org/Public-Safety/Crimes-2001-to-present/ijzp-q8t2>

Download the datasets

In many cases the dataset to be analyzed is available as a .CSV (comma separated values) file, perhaps on the internet. Click on the links below to download and save the datasets (.CSV files):

- CENSUS_DATA: <https://ibm.box.com/shared/static/05c3415cbfbfnr2fx4atenb2sd361ze.csv>
- CHICAGO_PUBLIC_SCHOOLS <https://ibm.box.com/shared/static/f9gjvj1gjmxxzycdhplzt01qtz0s7ew7ew7f.csv>
- CHICAGO_CRIME_DATA: <https://ibm.box.com/shared/static/svflyugsr9zbqy5bmowgsqemfpmlx7f.csv>

NOTE: Ensure you have downloaded the datasets using the links above instead of directly from the Chicago Data Portal. The versions linked here are subsets of the original datasets and have some of the column names modified to be more database friendly which will make it easier to complete this assignment.

Store the datasets in database tables

To analyze the data using SQL, it first needs to be stored in the database.

While it is easier to read the dataset into a Pandas dataframe and then PERSIST it into the database as we saw in Week 3 Lab 3, it results in mapping to default datatypes which may not be optimal for SQL querying. For example a long textual field may map to a CLOB instead of a VARCHAR.

Therefore, **it is highly recommended to manually load the table using the database console LOAD tool, as indicated in Week 2 Lab 1 Part II.** The only difference with that lab is that in Step 5 of the instructions you will need to click on create "(+)" New Table" and specify the name of the table you want to create and then click "Next".

IBM Db2 on Cloud Storage: 89% Discover Support

LOAD

Support

Source
Target
Load Job
File Reader

You are loading the file **Chicago_Public_Schools_-_Progress_Report_Cards_2011-2012.csv**

Select a load target

| | | |
|--|--|--|
| Schema Find a schema <input type="text"/> QCM54853 <input checked="" type="checkbox"/> ERRORSCHEMA Sample ST_INFORMTN_SCHEMA Sample | Table <input type="button" value="New Table"/> 1 Find a table in QCM54853 <input type="text"/> DEPARTMENTS DOGS EMPLOYEES | Create a new Table SCHOOLS 2 <input style="background-color: #800000; color: white; border: 1px solid black; padding: 2px; margin-left: 10px;" type="button" value="Create"/> 3 4 <input type="button" value="Back"/> <input type="button" value="Next"/> |
|--|--|--|

Now open the Db2 console, open the LOAD tool, Select / Drag the .CSV file for the first dataset, Next create a New Table, and then follow the steps on-screen instructions to load the data. Name the new tables as follows:

1. CENSUS_DATA
2. CHICAGO_PUBLIC_SCHOOLS
3. CHICAGO_CRIME_DATA

Connect to the database

Let us first load the SQL extension and establish a connection with the database

```
[1]: %load_ext sql
```

In the next cell enter your db2 connection string. Recall you created Service Credentials for your Db2 instance in first lab in Week 3. From the `uri` field of your Db2 service credentials copy everything after `db2://` (except the double quote at the end) and paste it in the cell below after `ibm_db_sa://`

IBM Cloud
Catalog Docs Support Manage
Q Search for resource...
Rav Ah...

Manage

Service credentials

Connections

Db2-fk

Location: Dallas Org: rsahuja@ca.ibm.com Space: dev

"host": "dashdb-txn-sbox-yp-dal09-03.services.dal.bluemix.net",
"jdbcurl": "jdbc:db2://dashdb-txn-sbox-yp-dal09-03.services.dal.bluemix.net:50000/BLUDB",
"uri": "db2://fbv67412:*****@dashdb-txn-sbox-yp-dal09-03.services.dal.bluemix.net:50000/BLUDB",
"db": "BLUDB",
"dsn": "DATABASE=BLUDB;HOSTNAME=dashdb-txn-sbox-yp-dal09-03.services.dal.bluemix.net;PORT=50000;PROTOCOL=TCP"

→

```
[2]: # Remember the connection string is of the format:  

# %sql ibm_db_sa://my-username:my-password@my-hostname:my-port/my-db-name  

# Enter the connection string for your Db2 on Cloud database instance below  

%sql ibm_db_sa://gkm89241:w13fqz1cdc5Epqr@dashdb-txn-sbox-yp-lon02-01.services.eu-gb.bluemix.net:50000/BLUDB
```

```
[2]: 'Connected: gkm89241@BLUDB'
```

Problems

Now write and execute SQL queries to solve assignment problems

Problem 1

Find the total number of crimes recorded in the CRIME table

```
[3]: # Rows in Crime table  

%sql SELECT count(id) FROM CHICAGO_CRIME_DATA
```

* ibm_db_sa://gkm89241:***@dashdb-txn-sbox-yp-lon02-01.services.eu-gb.bluemix.net:50000/BLUDB

Done.

```
[3]: 1
```

```
533
```

Problem 2

Retrieve first 10 rows from the CRIME table

```
[4]: %sql SELECT * FROM CHICAGO_CRIME_DATA limit(10)
```

* ibm_db_sa://gkm89241:***@dashdb-txn-sbox-yp-lon02-01.services.eu-gb.bluemix.net:50000/BLUDB

Done.

| ID | CASE_NUMBER | DATE | BLOCK | IUCR | PRIMARY_TYPE | DESCRIPTION | LOCATION_DESCRIPTION | ARREST | DOMESTIC | BEAT | DISTRICT | WARD | COMMUNITY_AREA_NUMBER | FBI_CODE |
|----------|-------------|---------------------------|--------------------------|------|--------------|--------------------------------|--------------------------------|--------|----------|------|----------|------|-----------------------|----------|
| 3512276 | HK587712 | 08/28/2004 05:50:56 PM | 047XX S KEDZIE AVE | 890 | THEFT | FROM BUILDING | SMALL RETAIL STORE | FALSE | FALSE | 911 | 9 | 14 | | 58 |
| 3406613 | HK456306 | 06/26/2004 12:40:00 PM | 009XX N CENTRAL PARK AVE | 820 | THEFT | \$500 AND UNDER | OTHER | FALSE | FALSE | 1112 | 11 | 27 | | 23 |
| 8002131 | HT233595 | 04/04/2011 05:45:00 AM | 043XX S WABASH AVE | 820 | THEFT | \$500 AND UNDER | NURSING HOME/RETIREMENT HOME | FALSE | FALSE | 221 | 2 | 3 | | 38 |
| 7903289 | HT133522 | 12/30/2010 04:30:00 PM | 083XX S KINGSTON AVE | 840 | THEFT | FINANCIAL ID THEFT: OVER \$300 | RESIDENCE | FALSE | FALSE | 423 | 4 | 7 | | 46 |
| 10402076 | HZ138551 | 02/02/2016 07:30:00 PM | 033XX W 66TH ST | 820 | THEFT | \$500 AND UNDER | ALLEY | FALSE | FALSE | 831 | 8 | 15 | | 66 |
| 7732712 | HS540106 | 09/29/2010 07:59:00 AM | 006XX W CHICAGO AVE | 810 | THEFT | OVER \$500 | PARKING LOT/GARAGE(NON.RESID.) | FALSE | FALSE | 1323 | 12 | 27 | | 24 |
| 10769475 | HZ534771 | 11/30/2016 01:15:00 AM | 050XX N KEDZIE AVE | 810 | THEFT | OVER \$500 | STREET | FALSE | FALSE | 1713 | 17 | 33 | | 14 |

Support

| | | | | | | | | | | | | | | |
|---------|----------|------------------------------|--------------------------|-----|-------|--------------------|--------------------|-------|-------|------|----|----|----|---|
| 4494340 | HL793243 | 1/28/2005 04:45:00 PM | USXX T PERSHING RD | 860 | THEFT | RETAIL THEFT | GROCERY FOOD STORE | TRUE | FALSE | 213 | 2 | 3 | 38 | 6 |
| 3778925 | HL149610 | 01/28/2005 05:00:00 PM | 100XX S WASHTENAW AVE | 810 | THEFT | OVER \$500 | STREET | FALSE | FALSE | 2211 | 22 | 19 | 72 | |
| 3324217 | HK361551 | 05/13/2004 02:15:00 PM | 033XX W BELMONT AVE | 820 | THEFT | \$500 AND UNDER | SMALL RETAIL STORE | FALSE | FALSE | 1733 | 17 | 35 | 21 | 6 |

Problem 3

How many crimes involve an arrest?

```
[5]: %sql SELECT count(*) FROM CHICAGO_CRIME_DATA WHERE arrest = 'TRUE'
* ibm_db_sa://gkm89241:***@dashdb-txn-sbox-yp-lon02-01.services.eu-gb.bluemix.net:50000/BLUDB
Done.
[5]: 1
[5]: 163
```

Problem 4

Which unique types of crimes have been recorded at GAS STATION locations?

Did you know? IBM Watson Studio lets you build and deploy an AI solution, using the best of open source and IBM software and giving your team a single environment to work in. [Learn more here.](#)

```
[6]: %sql SELECT primary_type,description, location_description FROM CHICAGO_CRIME_DATA WHERE location_description = 'GAS STATION'
* ibm_db_sa://gkm89241:***@dashdb-txn-sbox-yp-lon02-01.services.eu-gb.bluemix.net:50000/BLUDB
Done.
[6]:   primary_type          description  location_description
      THEFT                FROM BUILDING    GAS STATION
      THEFT                $500 AND UNDER  GAS STATION
      NARCOTICS  POSS: CANNABIS 30GMS OR LESS  GAS STATION
      ROBBERY              ARMED: HANDGUN  GAS STATION
      ROBBERY              AGGRAVATED    GAS STATION
      CRIMINAL TRESPASS    TO LAND       GAS STATION
```

Hint: Which column lists types of crimes e.g. THEFT?

Problem 5

In the CENSUS_DATA table list all Community Areas whose names start with the letter 'B'.

```
[7]: %sql SELECT community_area_name FROM CENSUS_DATA WHERE community_area_name like 'B%'
* ibm_db_sa://gkm89241:***@dashdb-txn-sbox-yp-lon02-01.services.eu-gb.bluemix.net:50000/BLUDB
Done.
[7]:   community_area_name
      Belmont Cragin
      Burnside
      Brighton Park
      Bridgeport
      Beverly
```

Problem 6

Which schools in Community Areas 10 to 15 are healthy school certified?

```
[8]: %sql SELECT community_area_number, name_of_school, healthy_school_certified FROM CHICAGO_PUBLIC_SCHOOLS \
WHERE community_area_number between 10 and 15 AND healthy_school_certified = 'Yes'
* ibm_db_sa://gkm89241:***@dashdb-txn-sbox-yp-lon02-01.services.eu-gb.bluemix.net:50000/BLUDB
Done.
[8]:   community_area_number          name_of_school  healthy_school_certified
      10 Rufus M Hitch Elementary School        Yes
```

Problem 7

What is the average school Safety Score?

```
[9]: %sql SELECT avg(safety_score) FROM CHICAGO_PUBLIC_SCHOOLS
* ibm_db_sa://gkm89241:***@dashdb-txn-sbox-yp-lon02-01.services.eu-gb.bluemix.net:50000/BLUDB
Done.
[9]: 1
[9]: 49.504873
```

Problem 8

List the top 5 Community Areas by average College Enrollment [number of students]

```
[10]: %sql SELECT community_area_name, college_enrollment FROM CHICAGO_PUBLIC_SCHOOLS \
order by college_enrollment limit (5)
* ibm_db_sa://gkm89241:***@dashdb-txn-sbox-yp-lon02-01.services.eu-gb.bluemix.net:50000/BLUDB
Done.
[10]:   community_area_name  college_enrollment
      NEAR WEST SIDE        21
      CALUMET HEIGHTS        26
      ENGLEWOOD               44
      NORTH LAWNDALE           48
      NORTH LAWNDALE           83
```

Problem 9

Use a sub-query to determine which Community Area has the least value for school Safety Score?

```
[11]: %sql SELECT community_area_name FROM CHICAGO_PUBLIC_SCHOOLS \
      WHERE safety_score = (SELECT MIN(safety_score) FROM CHICAGO_PUBLIC_SCHOOLS)
      * ibm_db_sa://gkm89241:***@dashdb-txn-sbox-yp-lon02-01.services.eu-gb.bluemix.net:50000/BLUDB
      Done.
[11]: community_area_name
      WASHINGTON PARK
```

Problem 10

[Without using an explicit JOIN operator] Find the Per Capita Income of the Community Area which has a school Safety Score of 1.

```
[12]: %sql SELECT per_capita_income, community_area_name FROM CENSUS_DATA \
      WHERE lower(community_area_name) IN (SELECT lower(community_area_name) FROM CHICAGO_PUBLIC_SCHOOLS WHERE safety_score = '1')
      * ibm_db_sa://gkm89241:***@dashdb-txn-sbox-yp-lon02-01.services.eu-gb.bluemix.net:50000/BLUDB
      Done.
[12]: per_capita_income  community_area_name
      13785    Washington Park
```

Copyright © 2018 cognitiveclass.ai. This notebook and its source code are released under the terms of the MIT License.