

Program 5: Build an Artificial Neural Network by implementing the Back propagation algorithm and test the same using appropriate data sets.

```
from math import exp
from random import seed
from random import random
```

```
# Initialize a network
```

```
def initialize_network(n_inputs, n_hidden, n_outputs):
    network = list()
    hidden_layer = [{ 'weights':[random() for i in range(n_inputs + 1)] } for i in
range(n_hidden)]
    network.append(hidden_layer)
    output_layer = [{ 'weights':[random() for i in range(n_hidden + 1)] } for i in
range(n_outputs)]
    network.append(output_layer)
    return network
```

```
# Calculate neuron activation for an input
```

```
def activate(weights, inputs):
    activation = weights[-1]
    for i in range(len(weights)-1):
        activation += weights[i] * inputs[i]
    return activation
```

```
# Transfer neuron activation
```

```
def transfer(activation):
    return 1.0 / (1.0 + exp(-activation))
```

```
# Forward propagate input to a network output
```

```

def forward_propagate(network, row):
    inputs = row
    for layer in network:
        new_inputs = []
        for neuron in layer:
            activation = activate(neuron['weights'], inputs)
            neuron['output'] = transfer(activation)
            new_inputs.append(neuron['output'])
        inputs = new_inputs
    return inputs

# Calculate the derivative of an neuron output
def transfer_derivative(output):
    return output * (1.0 - output)

# Backpropagate error and store in neurons
def backward_propagate_error(network, expected):
    for i in reversed(range(len(network))):
        layer = network[i]
        errors = list()
        if i != len(network)-1:
            for j in range(len(layer)):
                error = 0.0
                for neuron in network[i + 1]:
                    error += (neuron['weights'][j] * neuron['delta'])
                errors.append(error)
        else:
            for j in range(len(layer)):
                neuron = layer[j]

```

```

        errors.append(expected[j] - neuron['output'])
    for j in range(len(layer)):
        neuron = layer[j]
        neuron['delta'] = errors[j] * transfer_derivative(neuron['output'])

# Update network weights with error
def update_weights(network, row, l_rate):
    for i in range(len(network)):
        inputs = row[:-1]
        if i != 0:
            inputs = [neuron['output'] for neuron in network[i - 1]]
        for neuron in network[i]:
            for j in range(len(inputs)):
                neuron['weights'][j] += l_rate * neuron['delta'] * inputs[j]
            neuron['weights'][-1] += l_rate * neuron['delta']

# Train a network for a fixed number of epochs
def train_network(network, train, l_rate, n_epoch, n_outputs):
    for epoch in range(n_epoch):
        sum_error = 0
        for row in train:
            outputs = forward_propagate(network, row)
            expected = [0 for i in range(n_outputs)]
            expected[row[-1]] = 1
            # print(expected)
            sum_error += sum([(expected[i]-outputs[i])**2 for i in range(len(expected))])
            backward_propagate_error(network, expected)
            update_weights(network, row, l_rate)
    print('>epoch=%d, lrate=%.3f, error=%.3f' % (epoch, l_rate, sum_error))

```

```
# Test training backprop algorithm
seed(1)
dataset = [[2.7810836,2.550537003,0],
            [1.465489372,2.362125076,0],
            [3.396561688,4.400293529,0],
            [1.38807019,1.850220317,0],
            [3.06407232,3.005305973,0],
            [7.627531214,2.759262235,1],
            [5.332441248,2.088626775,1],
            [6.922596716,1.77106367,1],
            [8.675418651,-0.242068655,1],
            [7.673756466,3.508563011,1]]
n_inputs = len(dataset[0]) - 1
n_outputs = len(set([row[-1] for row in dataset]))
network = initialize_network(n_inputs, 2, n_outputs)
train_network(network, dataset, 0.5, 20, n_outputs)
for layer in network:
    print(layer)
```