


Test Report

Model	ZGDL-167/4.8×16-0.24	Vector Group	Ii6	Serial NO	25KY06161	Voltage Ratio Error (%)	Tap Position	H1A-H1B/x1x3	H1A-H1B/x1-x2	H1A-H1B/x3-x2	Vector Group	Qualified			
Rated Capacity	167kVA	No. of Phase	Single Phase	Standard	CSA C227.3/C802.1										
Conditions of use	Ourdoor Type	Frecuency	60Hz	Cooling Mode	ONAN										
Rated voltage & Rated Current	Tap Position	HV Windings		LV Windings											
		Voltage (V)	Current (A)	Voltage (V)	Current (A)										
	1	5040													
	2	4920													
	3	4800					34.79	240	695.8						
	4	4680													
	5	4560													
DC Resistance of High Voltage Windings		H1A-H1B (Ω)			Qualified	HV-LV、Earthing		/	/	x1x3	0.881	8.7			
26℃						LV - HV、Earthing		10	3.1	Frequency	200	Hz			
Tap Position	1	0.4578				60s' Test Time Qualified			Conclusion	Qualified					
	2	0.4454				No-load Current and No Load Loss Test			Short-circuit Impedance and Load Loss Test						
	3	0.4339				Test Voltage(V)	No-load Current(A)	No-load Current(%)	Test Loss (W)	No-load Loss (W)	Test Volatge (V)	Test Current (A)	Test Loss (W)	85℃Load Loss(W)	85℃Short Circuit Impedance (%)
	4	0.4226				242.9	695.8	0.75	282.8	280	4800	34.82	1159.9	1371	2.52
	5	0.4103													
DC Resistance of Low Voltage Winding		x1-x3 (Ω)	x1-x2 (Ω)	x3-x2 (Ω)		Qualified	Insulating Oil Testing			Seal test	Applied Pressure (kPa)	Duration (H)	Residual pressure (kPa)	No leakage and damage	
26℃		0.000979	0.000542	0.000564			Oil Model		Mineral Oil						
							Dielectric loss factor (90℃)		0.082						
Insulation Resistance Temperature		HV-LV、Earthing	LV - HV、Earthing	LV、HV—Earthing		Oil breakdown voltage (KV)		55.8							
26℃						Oil Test	Qualified								
26℃		5000	5000	5000		Conclusion	The test results meet the requirements of CSA C227.3/C802.1-23 standard and manufacture's technical specification								
(MΩ)						To Examine:	Qiu jianwei		Check:	Ren linhao		Print:	Yang xinglong		
						Testers:	He qiuyuan		Date of Manufacture:						



Sam Wu



Test Report

Model	ZGDL-167/4.8×16-0.24	Vector Group	Ii6	Serial NO	25KY06161	Voltage Ratio Error (%)	Tap Position	H1A-H1B/x1x3		H1A-H1B/x1-x2		H1A-H1B/x3-x2	Vector Group	Qualified	
Rated Capacity	167kVA	No. of Phase	Single Phase	Standard	CSA C227.3/C802.1		1	-0.26		-0.26		-0.26			
Conditions of use	Ourdoor Type	Frecuency	60Hz	Cooling Mode	ONAN		2	-0.24		-0.24		-0.25			
Rated voltage & Rated Current	Tap Position	HV Windings		LV Windings			3	0.00		0.00		0.00			
		Voltage (V)	Current (A)	Voltage (V)	Current (A)		4	0.26		0.25		0.25			
	1	16800					5	0.29		0.29		0.29			
	2	16400													
	3	16000	10.44	240	695.8		Power-Frequency Withstand Voltage Test			Induced over voltage withstand test					
	4	15600						Voltage(kV)	Current(A)		Voltage(kV)	Current(A)			
	5	15200													
DC Resistance of High Voltage Windings		H1A-H1B (Ω)			Qualified	HV-LV、Earthing		/	/	x1x3	0.6	9.9			
26℃						LV - HV、Earthing		10	3.1	Frequency	200	Hz			
Tap Position	1	4.3160				60s' Test Time Qualified		Conclusion	Qualified						
	2	4.2040				No-load Current and No Load Loss Test		Short-circuit Impedance and Load Loss Test							
	3	4.1000				Test Voltage(V)	No-load Current(A)	No-load Current(%)	Test Loss (W)	No-load Loss (W)	Test Volatge (V)	Test Current (A)	Test Loss (W)	85℃Load Loss(W)	85℃Short Circuit Impedance (%)
	4	3.9990				242.9	695.8	0.66	285.2	282	16000	10.43	992.9	1205	2.61
	5	3.8870				Insulating Oil Testing		Seal test	Applied Pressure (kPa)	Duration (H)	Residual pressure (kPa)	No leakage and damage			
DC Resistance of Low Voltage Winding		x1-x3 (Ω)	x1-x2 (Ω)	x3-x2 (Ω)		Oil Model	Mineral Oil								
26℃		0.000979	0.000542	0.000564		Dielectric loss factor (90℃)							0.082		
Insulation Resistance Temperature	HV-LV、Earthing	LV - HV、Earthing	LV、HV—Earthing			Oil breakdown voltage (KV)							55.8		
					Oil Test	Qualified									
26℃		5000	5000	5000		Conclusion	The test results meet the requirements of CSA C227.3/C802.1-23 standard and manufacture's technical specification								
(MΩ)	To Examine:					Qiu jianwei		Check:	Ren linhao		Print:	Yang xinglong			
	Testers:					He qiuyuan		Date of Manufacture:							

