






APPROUVÉ

Approved under integration
of comments.

ITEM	WEIGHT
TANK & ACCESSORIES	1930kg
TOTAL OIL WEIGHT	1930L
TOTAL WEIGHT	6370kg

L.V. TERMINAL

GROUND PAD
STAINLESS STEEL

TECHNICAL DATA

RATING	2500kVA
PRIMARY VOLTAGE(V)	13800-6900DELTA
SECONDARY VOLTAGE(V)	2400WYE/1386
FREQUENCY	60Hz
VECTOR GROUP	Dyn1
CONDUCTOR	COPPER
INSULATING OIL	FR3
TEMPERATURE RISE	65°C
EFFICIENCY	99.48%
LOAD LOSS AT RATED VOLTAGE	20000W
NO LOAD LOSSES	2000W
IMPEDANCE	5.75%
ALTITUDE	≤1000m
No. OF TAP POSITION	5
COLOR	ANSI 61 GRAY
CORE FORM	Three-phase Three-column

PARTS LIST

ITEM	DESCRIPTION	QTY
1	HV BUSHING (28kV,600A)	3
2	PARKING STAND BRACKET	3
3	DOUBLE VOLTAGE SWITCH	1
4	TWO POSITION LOADBREAKER SWITCH	1
5	TAP CHANGER 3PH (WSLII3125/15-2-6×5)	1
6	DRIP TRAY	1
7	BAYONET FUSE	3
8	NAMEPLATE	1
9	1" UPPER FILL VALVE	1
10	PRESSURE RELIEF VALVE	1
11	VACUUM PRESSURE GAUGE	1
12	OIL LEVEL GAUGE	1
13	OIL TEMPERATURE GAUGE WITH CONTACTS	1
14	DOOR HANDLE	1
15	LV BUSHING(3KV 12 HOLE,4000A)	4
16	750-4000 PADMOUNT LV PLATE, 304L S.S. 3/16in	1
17	GROUND BUS	1
18	GROUND BUS	1
19	JACK	4
20	GROUND STEEL PADS	2
21	1"DRAIN VALVE WITH 3/8" SAMPLER	1
22	FIXED PROJECTING CUP	3
23	RADIATOR PJ-1400-15/520	3
24	ELSP FUSE	3
25	FLIP TOP COVER	1
26	LIFTING LUG	4
27	HINGED DOOR	2

DWG. NAME
ZGS-Z-2500/13.8-6.9/2.4

General Assembly Drawing

DRAWN	CHECKED	CHECKED	APPROVED
Mike W	Ella W	Iris J	Sam S

FIRST ANGLE
PROJECTION

SCALE

1

REV.
NO.JZP
SINCE 1989 FROM USA

ZGS-3000-231102-02



APPROUVÉ



3 PHASE DISTRIBUTION

PAD MOUNTED TRANSFORMER

PRODUCT NO. :

TYPE ZGS-2500/13. 8x6. 9/2. 4

CONDUCTOR MATERIAL: COPPER

PHASE 3

FREQUENCY 60Hz

TEMPERATURE RISE 65° C/ 65° C

SERIAL NO. :

DATE OF MFG. :

H. V. Um/BIL/AC 15/95/34 kV

L. V. Um/BIL/AC 2. 4/30/10 kV

STANDARDS CSA C227. 4, CSA C802. 1
2500kVA HV 13800x6900V DELTA
LV 2400/1386V WYE

TYPE OF COILING KNAN

PERCENT IMPEDANCE: 5. 75 %


TYPE OF OIL FR3 NO PCB

CORE & COLL (UNTAKING): LBS

TANK & FITTINGS: LBS


LIQUID: GALS LBS

TOTAL: LBS



VECTOR GRAPH (Dyn1)

Tapping Range	H. V			L. V	
	Voltage (V)	Current (A)		Voltage (V)	Current (A)
1 2-3	14490	7245	99. 61	199. 22	
2 3-4	14145	7072	102. 04	204. 08	
3 4-5	13800	6900	104. 59	209. 18	2400
4 5-6	13455	6727	107. 27	214. 55	601. 41
5 6-7	13110	6554	110. 1	220. 19	



ITEM:

MANUFACTURER:

PART NUMBER:

WWW.JIEZOUPOER.COM

