




TECHNICAL DATA

RATING	3000kVA
PRIMARY VOLTAGE(V)	13800-6900DELTA
SECONDARY VOLTAGE(V)	600WYE/347
FREQUENCY	60Hz
VECTOR GROUP	Dyn1
CONDUCTOR	COPPER
INSULATING OIL	FR3
TEMPERATURE RISE	65°C
EFFICIENCY	99.48%
LOAD LOSS AT RATED VOLTAGE	22000W
NO LOAD LOSSES	2600W
IMPEDANCE	5.75%
ALTITUDE	≤1000m
No. OF TAP POSITION	5
COLOR	ANSI 61 GRAY
CORE FORM	Three-phase Three-column

PARTS LIST

ITEM	DESCRIPTION	QTY
1	HV BUSHING (28kV,600A)	3
2	PARKING STAND BRACKET	3
3	DOUBLE VOLTAGE SWITCH	1
4	TWO POSITION LOADBREAKER SWITCH	1
5	TAP CHANGER 3PH (WSLII 125/15-2-6×5)	1
6	DRIP TRAY	2
7	BAYONET FUSE (SID-PRNT4-15/180*2)	6
8	NAMEPLATE	1
9	1" UPPER FILL VALVE	1
10	PRESSURE RELIEF VALVE	1
11	VACUUM PRESSURE GAUGE	1
12	OIL LEVEL GAUGE	1
13	OIL TEMPERATURE GAUGE WITH CONTACTS	1
14	DOOR HANDLE	1
15	LV BUSHING(1.2KV 12 HOLE,4000A)	4
16	750-4000 PADMOUNT LV PLATE, 304L S.S. 3/16in	1
17	COPPER GROUND BUS	1
18	COPPER GROUND BUS	1
20	GROUND STEEL PADS	2
21	1"DRAIN VALVE WITH 3/8" SAMPLER	1
22	FIXED PROJECTING CUP	3
23	RADIATOR PJ-1400-15/520	3
24	ELSP FUSE (SID-XRNT4-15/250*2)	6
25	FLIP TOP COVER	1
26	LIFTING LUG	4
27	HINGED DOOR	2

ZGS-Z-3000/13.8-6.9/0.6

DWG. NAME

General Assembly Drawing

DRWN	CHECKED	CHECKED	APPROVED
Mike W	Ella W	Iris J	Sam S

FIRST ANGLE
PROJECTION

SCALE

1

REV.
NO.

ZGS3000-231102-02

JZP
SINCE 1989 FROM USA

150

14.0

4- ϕ 5



3 PHASE DISTRIBUTION PAD MOUNTED TRANSFORMER

PRODUCT NO. :

TYPE ZGS-3000/13.8x6.9/0.6

CONDUCTOR MATERIAL: COPPER

PHASE 3

FREQUENCY 60Hz

TEMPERATURE RISE 65° C/ 65° C

SERIAL NO. :

DATE OF MFG. :

H. V. Um/BIL/AC 15/95/34 kV

L. V. Um/BIL/AC 0.6/30/10 kV

STANDARDS CSA C227.4

3000kVA HV 13800x6900V DELTA

LV 600/347V WYE

TYPE OF COLLING KANAN

PERCENT IMPEDANCE: 5.75 %


TYPE OF OIL FR3 NO PCB

CORE & COIL (UNTAKING): LBS

TANK & FITTINGS: LBS

LIQUID: GALSS LBS

TOTAL: LBS



VECTOR GRAPH (Dym1)

Tapping Range	H.V		L.V	
	Voltage (V) A-C	Current (A) A-D/B-C	Voltage (V)	Current (A)
1 2-3	14490	7245	119.53	239.07
2 3-4	14145	7072	122.45	244.9
3 4-5	13800	6900	125.51	251.02
4 5-6	13455	6727	128.73	257.46
5 6-7	13110	6554	132.12	264.23

H1 H2 H3

ELSP FUSE SID-XRNT4-15/250*2 6


SWT

BAYONET FUSE SID-PRNT4-15/180*2 6

ITEM:

MANUFACTURER:

PART NUMBER:



WWW.JIEZOUPOWER.COM



165

175