



JIEZOU POWER

SHENYANG JIEZOU POWER TECHNOLOGY CO.,LTD

ADD:3316 Yanlord Land Plaza , Qingnian Avenue, Shenhe District, Shenyang City,Liaoning Province CHINA

E-mail:meghan@jiezougroup.com Tel: +86-18804036118

Web:www.jiezoupower.com

1000KVA 25/0.6KV 三相美式箱变加标, 见如下参数

750 KVA 24940 GRD Y/14400 - 480Y/277, 三相美式箱变加标, 见如下参数

Product brand:	JIEZOU
Product type:	Radial Feed Pad mounted transformer
Standard:	CSAC227.4 , CSA C802.1
Rated capacity:	1000 kva
Primary voltage and insulation level:	25 kv
Tapping range	±2x2.5%
Secondary voltage(load)and insulation level:	600V
Impedance:	按标准
Impedance tolerance	± 7.5%
Vector group:	按标准
Frequency:	60hz
Nos. Of phase:	Three
Cooling method:	ONAN
winding Material	Aluminum

Technical data

Type of installation:	outdoor
Altitude above sea level	≤1000m
Ambient temperature	20℃
Material core: :	Silicon steel
Oil top temperature rise:	65℃
Winding temperature rise:	65℃
Hot Spot:	80℃
No-load losses:	As per efficiency Standard and drawing design
Load-losses:	As per efficiency Standard and production drawing design
Loss tolerance:	按标准
Ambient temperature for operation:	-45℃ to 50℃
Noise level:	<55
Tank Colour :	Munsell Green
Oil type:	Mineral Oil-No PCB(45#)

Weight information:

Oil Weight:	按标准
Machine weight:	按标准
Total weight:	按标准

Dimension information:

Length:	按标准
Width:	按标准
Height:	按标准

Accessories

PRV,oil level indicator, oil temperature indicator, pressure vacuum gauge,三表一阀
BAY O NET fuse CLF FUSE protection, 熔丝保护
one load break switch
one tap changer

Test

Routine Test/Type test	YES
------------------------	-----



SHENYANG JIEZOU POWER TECHNOLOGY CO.,LTD

ADD:3316 Yanlord Land Plaza , Qingnian Avenue, Shenhe District, Shenyang City,Liaoning Province CHINA

E-mail:meghan@jiezougroup.com Tel: +86-18804036118

Web:www.jiezoupower.com

Product brand:	JIEZOU
Product type:	Radial Feed Pad mounted transformer
Standard:	CSAC227.4 , CSA C802.1
Rated capacity:	750 kva
Primary voltage and insulation level:	24940 GRD Y/14400
Tapping range	±2x2.5%
Secondary voltage(load)and insulation level:	480Y/277
Impedance:	按标准
Impedance tolerance	± 7.5%
Vector group:	按标准
Frequency:	60hz
Nos. Of phase:	Three
Cooling method:	ONAN
winding Material	Aluminum

Technical data

Type of installation:	outdoor
Altitude above sea level	≤1000m
Ambient temperature	20℃
Material core: :	Silicon steel
Oil top temperature rise:	65℃
Winding temperature rise:	65℃
Hot Spot:	80℃
No-load losses:	As per efficiency Standard and drawing design
Load-losses:	As per efficiency Standard and production drawing design
Loss tolerance:	按标准
Ambient temperature for operation:	-45℃ to 50℃
Noise level:	<55
Tank Colour :	Munsell Green
Oil type:	Mineral Oil-No PCB(45#)

Weight information:

Oil Weight:	按标准
Machine weight:	按标准
Total weight:	按标准

Dimension information:

Length:	按标准
Width:	按标准
Height:	按标准

Accessories

PRV,oil level indicator, oil temperature indicator, pressure vacuum gauge,三表一阀

BAY O NET fuse CLF FUSE protection, 熔丝保护

one load break switch

one tap changer

Test

Routine Test/Type test	YES
------------------------	-----