









L. V. TERMINAL



GROUND PAD
STAINLESS STEEL



ALL DIMENSION DEVIATIONS: $\pm 10\%$

ITEM	WEIGHT (LBS)
CORE WEIGHT	895 LBS
TOTAL OIL WEIGHT	830 LBS
TOTAL WEIGHT	3185 LBS

TECHNICAL DATA	
RATING	150kVA
PRIMARY VOLTAGE (V)	12000DELTA
SECONDARY VOLTAGE (V)	480GrdY/277
FREQUENCY	60Hz
VECTOR GROUP	Dyn1
CONDUCTOR	ALUMINUM
PRIMARY BIL VOLTAGE	95kV
SECONDARY BIL VOLTAGE	30kV
INSULATING OIL	FR3 OIL
TEMPERATURE RISE	65°C
LOAD LOSS AT RATED VOLTAGE	2310 W
NO LOAD LOSSES	200 W
IMPEDANCE	2~4.5%
ALTITUDE	$\leq 1000m$
COLOR	MUNSELL NO. 7.0 GY 3.2/1.5
CORE FORM	THREE-PHASE THREE-COLUMN

17	CONNECTED STEEL-PLATE	4
16	BUSHING SPADE SUPPORT	4
15	NAMEPLATE	2
14	DRAIN VALVE LOCKABLE BOX	1
13	DOOR HANDLE	1
12	LV BUSHING	4
11	BACK UP FUSE	3
10	LIFTING LUG	4
9	GROUND STEEL PADS	3
8	OIL TEMPERATURE GAUGE	1
7	OIL LEVEL GAUGE	1
6	VACCUM PRESSURE GAUGE	1
5	PRESSURE RELIEF VALVE	1
4	FILL PLUG	1
3	BAYONET FUSE	3
2	PARKING STAND BRACKET	5
1	HV BUSHING WITH 200AMP BUSHING WELL INSERTS	6
ITEM	DESCRIPTION	QTY

ZGSL-H-150/12-0.48
PAD MOUNTED TRANSFORMER

OUTLINE DRAWING

JZP[®]
ELECTRIC