

SDC™ Composite Bushing - 12kV

By Electro Composites
Catalog # 075-012-T-219-00

SDC™ 12kV-1200 A Transformer Condenser Bushing, Solid-Dielectric-Capacitor Type, Rated per IEC 60137, Bottom Connected for Air-to-Oil Applications, 1" Min. Oil Immersion Level/Ground Shield Length, 28.4" Min. Creepage Length

Features

- SDC™ - Solid Dielectric Capacitance Graded Composite Construction
- EC-APG-02 Cycloaliphatic Epoxy Compound for Optimal Performance
- No oil, paper or porcelain
- Can be mounted vertically or horizontally
- Meets IEC 60137 Electrical and Mechanical Requirements

Application

Transformer

General

Bottom Terminal Type	1X BLADE WITH 4X 0.56 DIA HOLES
Catalog Number	075-012-T-219-00
Color	Gray
Immersion Type - Above Flange	Air
Immersion Type - Below Flange	Oil
Material - Flange	Aluminum
Material - Insulation	APG-02 - Cycloaliphatic Epoxy
Mounting Position	Vertical to Horizontal
Number of Bolt Holes - Bottom Terminal	4
Number of Bolt Holes - Top Terminal	4
Number of Flange Mounting Holes	6
Plating - Bottom Terminal	None
Test Tap	No
Top Terminal Plating	None
Top Terminal Type	1X BLADE WITH 4X 0.56 DIA HOLES
Type	SDC - Solid Dielectric Capacitor

Dimensions

Above Flange Length	34.3 in
Below Flange Length	13.5 in
Diameter - Above Flange Maximum	4.15 in



*Representative Image

Diameter - Below Flange Maximum D <gt/> 1"	5.63 in
Diameter - Below Flange Maximum P	5.63 in
Diameter - Conductor Outside Under Insulation	1.5 in
Diameter - Live Part Bottom	4.00 in
Diameter - Live Part Top	4.00 in
Diameter - Rod / Tube	1.5 in
Dimensions	47.80 in x 9.50 in x 9.50 in
Effective Length - Bottom Terminal	4.00 in
Effective Length - Top Terminal	4.25 in
Flange Mounting Hole Bolt Circle	7.25 in
Flange Mounting Hole Diameter	0.56 in
Flange Outside Diameter	9.5 in
Height	9.5 in
Length	47.8 in
Length - Ground Shield	1.00 in
Length - Insulated Section	33.4 in
Length - Insulation Above Flange	23.30 in
Length - Insulation Below Flange	6.00 in
Length - Live Part Bottom	6.50 in
Length - Live Part Top	7.90 in
Length - Minimum Oil Immersion Level	LOWER END TO BE FULLY IMMERSED
Sealing Surface Inside Diameter	6 in
Sealing Surface Outside Diameter	8.25 in
Thickness	2.065 in
Weight	75 lb
Width	9.5 in

Electrical Ratings

BIL	75 kV
Current Rating	1200 A
Minimum Creepage	28.4 in
Minimum Creepage - Inside	9.10 in
Minimum Strike	24.3 in
Withstand Voltage - 60 Hz Dry kV Class	28 kV
	12 kV

Certifications And Compliance

Industry Standard(s) IEC 60137

Product Assets

- Catalogs - Electro Composites SDC™ composite bushings
- Installation Manuals - SDC™ Bushing General Handling and Maintenance Guide - Electro Composites
- Literature - SDC™ HV Generator Bushings - Electro Composites
- Literature - How an SDC Bushing Test Tap is Constructed

- Literature - TRAVERSÉE SDC™ ÉLECTRO COMPOSITES DE TYPE GSU
- Literature - SDC™ GSU Bushings - Electro Composites
- Literature - TRAVERSÉE SDC™ ÉLECTRO COMPOSITES POUR GÉNÉRATEUR
- Literature - Apparatus Bushings Selection Guide
- Literature - ÉLECTRO COMPOSITES TRAVERSÉE HAUTE TENSION SDC™
- Literature - SDC™ HV Bushings - Electro Composites
- Sales Drawings - 219-00_4365-3447
- Specifications - 075-012-T-219-00
- Video - ElectroComposites Factory Tour: St. Jerome



A Hubbell brand