# H1–H4: observed effects and p-values

Reviewed contexts only. Δ = mean difference; p = raw two-sided p; Holm = adjustment across 20 tests.

| Outcome | Predicted | GPT-6 Astra<br>n = 2 contexts | GPT-6.1 Sol<br>n = 2 contexts | GPT-6 Luna<br>n = 3 contexts |
|---|---|---|---|---|
| H1 Constraint → pipeline sensitivity | Below 0 | Δ -0.000208<br>p 1 \| Holm 1 | Δ +0<br>p 1 \| Holm 1 | Δ +0<br>p 1 \| Holm 1 |
| H2 Constraint → total cost | Above 0 | Δ +38.3<br>p 0.5 \| Holm 1 | Δ -13.8<br>p 1 \| Holm 1 | Δ +6.43<br>p 0.5 \| Holm 1 |
| H3 Education → pipeline sensitivity | Above 0 | Δ +0.000208<br>p 1 \| Holm 1 | Δ +0<br>p 1 \| Holm 1 | Δ +0<br>p 1 \| Holm 1 |
| H4a Education → order variance | Below 0 | Δ -20.4<br>p 0.5 \| Holm 1 | Δ +11.5<br>p 1 \| Holm 1 | Δ +1.47<br>p 1 \| Holm 1 |
| H4b Education → bullwhip | Below 0 | Δ -3.16<br>p 0.5 \| Holm 1 | Δ +1.77<br>p 1 \| Holm 1 | Δ +0.215<br>p 1 \| Holm 1 |

H1 / H3: observed pipeline-sensitivity changes and their p-values appear in the table.

H2 / H4: observed signs differ across models and repeated contexts.

A = control + revision  B = control + one decision  C = causal education + one decision

n = reviewed independent contexts. — = p unavailable with one context. H1/H3 use pipeline sensitivity as a proxy.