H1–H4 conclusions: no statistically established effects

Reviewed contexts only. Each entry is the mean condition difference; n counts independent contexts.

Outcome	Predicted	GPT-6 Astra	GPT-6.1 Sol	GPT-6 Luna	Conclusion
H1 Constraint → pipeline sensitivity	Below 0	+0 (n=1)	+0 (n=2)	+0 (n=3)	**Not established**
H2 Constraint → total cost	Above 0	+61.9 (n=1)	-13.8 (n=2)	+6.43 (n=3)	**Not established**
H3 Education → pipeline sensitivity	Above 0	+0 (n=1)	+0 (n=2)	+0 (n=3)	**Not established**
H4a Education → order variance	Below 0	-29.1 (n=1)	+11.5 (n=2)	+1.47 (n=3)	**Not established**
H4b Education → bullwhip	Below 0	-4.48 (n=1)	+1.77 (n=2)	+0.215 (n=3)	**Not established**

H1 / H3: no observed treatment differences in the reviewed pipeline-sensitivity measurements.

H2 / H4: signs vary across models and repeats; predicted directions alone do not establish support.

A = control + revision B = control + one decision C = causal education + one decision

Three-context pilot. Minimum two-sided exact p at n = 3 is 0.25. Revision opportunities are not a measured clock deadline.