

Australian GET_ENTITY V2 — Method Chaining





ENDMETHOD.

Australian zif_gw_methods~get_entity

```
METHOD zif gw methods-get entity.
TRY.
    CASE in tech request context->get source entity type name().
      WHEN 'SalesOrder'.
        DATA(source keys) = in Lech request context.->get source keys( ).
        zcl demo salesorder->get using so id(
          CONV #( source keys[ name = 'SO ID' ]-value )
          )->get customer( )->zif gw methods-map to entity(
            EXPORTING
              entity - REF #( er entity )
              entity name = io tech request context->get entity type name()
                        io model ).
              mode1
      WHEN OTHERS.
        DATA(keys) = io tech request context->get keys().
        zcl demo customer->get using bp id(
          CONV #( keys[ name = 'BP ID' ]-value )
          )->zif qw methods~map to entity(
            EXPORTING
              entity - REF # ( er entity )
              entity name = io tech request context->get entity type name()
                        io model ).
              mode1
    ENDCASE.
  CATCH zcx demo bo cx sy itab line not found INTO DATA(exception).
    RAISE EXCEPTION TYPE /iwbep/cx mgw busi exception
      KX PORT INC.

  - /iwbep/cx mgw busi exception->business error

        previous = exception
        message - |{ exception->get text( ) }|.
ENDTRY.
```

