GET_ENTITY V2 – METHOD CHAINING

```
lt_key_tab = io_tech_request_context->get_keys().

zcl_demo_customer=>get_using_bp_id(
    CONV #( lt_key_tab[ name = 'BP_ID' ]-value )
    )->zif_gw_methods~map_to_entity( REF #( er_entity ) ).
```



ZIF_GW_METHODS~GET_ENTITY

```
METHOD zif gw methods~get entity.
  TRY.
      CASE io tech request context->get source entity type name().
        WHEN 'SalesOrder'.
          DATA(source keys) = io tech request context->get source keys().
          zcl demo salesorder->get using so id(
            CONV # ( source keys[ name = 'SO ID' ]-value )
            )->qet customer( )->zif qw methods~map to entity( REF f( er entity ) ).
        WHEN OTHERS.
          DATA(keys) = io tech request context->get_keys().
          zcl demo customer->get using bp id(
            CONV # ( keys[ name = 'BP ID' ]-value )
           )->zif gw methods~map to entity( REF #( er entity ) ).
      ENDCASE.
    CATCH zcx demo bo cx sy itab line not found INTO DATA(exception).
      RAISE EXCEPTION TYPE /iwbep/cx mgw busi exception
        EXPORTING
          textid = /iwbep/cx mgw busi exception=>business error
          previous - exception
          message = |{ exception->get text( ) }|.
  ENDTRY.
ENDMETHOD.
```

