

Comment	Description	Designator	Footprint	LibRef	Quantity
	CL21 Series 0805				
CL21A106KOQNNNE	10uF 16V±10% Tolerance X5R Multilayer Ceramic	C1	FP-CL21-IPC_B	CMP-2000-06102-2	1
	Chip Capacitor				
	Cap Ceramic 100nF				
CL05B104KA5NNNC	25VX7R±10%SMD	C2	FP-CL830-IPC_C	CMP-13271-001643-1	1
	0402 +125°C Paper				
	T/R		FP-		
CL10B105KO8NNNC	CAPCER1UF16VX7R 0603	C3, C4, C5, C6, C7, C9	CL10B105KO8NNNC- MFG	CMP-2000-06093-2	6
	Chip Multilayer				
GRM31CR60J107MEA	Ceramic Capacitors	C0	FP-GRM31C-0_3-	CN 4D 0000E 0040E0 4	_
8K	for General Purpose, 1206, 100uF, X5R,	C8	e0_3_0_8-MFG	CMP-06035-034850-1	1
	15%, 20%, 6.3V				
150060BS55040	Single Color LED	D1	WL-SMCD_0603	CMP-007-00036-1	1
USBLC6-2SC6	No Description Available	D2	SOT23-6L_STM	CMP-011-000000-3	1
ESD321DYAR	USB 2.0 TVS diode, 0.9 pF, 30kVair/contact	D3, D4	SOT5x3_DYA_TEX	CMP-006-000000-6	2
ESD9B5.0ST5G	Trans Voltage			CMP-004-00031-3	
	Suppressor Diode, 5V	D5	ONSC-SOD-923-2- 514AB-01_V		1
	V(RWM), Bidirectional,				'
	1 Bement, Slicon				
0ZCG0300FF2B	PTC Fuse 6V3Ahold 5Atrip	F1	OZCG_BEL	CMP-005-00013-3	1
	USB Connector, 16				
217179-0001	Contact(s), Female,	'n	FP-2171790001-MFG	CMP-002-00072-3	
	Right Angle, Surface				1
	Mount Terminal, Locking, Receptacle				
Header 3 pin	3x1 pins	J2	Header 3 pin-Footprint	CMP-002-00071-4	1
rieader 3 piri		<u> </u>	1	CIVIF-002-0007 1-4	'
ESP32-C3-MINI-1-N4	Multiprotocol Modules SMD module, ESP32-		FP-ESP32-C3-MINI-1-		
	C3FN4, PCB antenna, -	MD1	N4-MFG	CMP-020-00023-3	1
	40 C +85 C				
ERJ-2RWF1002X	Fixed Resistor, Metal	R1, R2, R10	RESC1005X40X25LL05 T05	CMP-009-00177-1, CMP-009-00177-2	
	Glaze/thick Film, 0.1W, 10000ohm, 50V,				
	1%+/-Tol,				3
	100ppm/Cel, Surface				
	Mount, 0402 Fixed Resistor, Metal				
ERJ-2RVF1000X	Glaze/thick Film,	R3	RESC1005X40X25LL05 T05	CMP-009-00179-1	
	0.1W, 100ohm, 50V,				1
	1%+/-Tol,				'
	100ppm/Cel, Surface Mount, 0402				
ERJ-3EKF5101V	RESSMD 5.1KOHM	R4, R5, R8, R9	FP-ERJBEK-MFG	CMP-2000-00540-8	4
2302401014	1%1/10W0603	, 10, 10, 10			-
ERJ2GE0R00X	Fixed Resistor, Metal Glaze/thick Film,		RESC1005X40X25LL05 T05		
	0.1W, 0ohm, Surface	R6, R7	T05	CMP-009-00178-1	2
	Mount, 0402				
	Tactile Pushbutton Switch with Grounding				
KMR211GLFS	Pad, 0.05A @32V,	SW1, SW2	KMR2xxG_CNK	CMP-011-00013-2	2
	SPST-NO, Off-Mom				
TLV1117LV33DCYR	Single Output LDO, 1				
	A, Fixed 3.3 V Output, 2 to 5.5 V Input, 4-pin	U1	DCY0004A_N	CMP-0395-00503-2	
	SOT-223 (DCY), -40 to				1
	125 degC, Green				
	(RoHS& no Sb/Br)				
SN74LVC1T45DBVR	IC TRNSLTR BIDIRECTIONAL	U2	FP-DBV0006A-IPC B	CMP-0859-00206-4	1
C./ TEVO! HODDVIX	SOT23-6		DDV0000AII O_B	5 0000-00200-4	'
LTR-329ALS-01	SENSOR OPT AMBIENT	U3	FP-LTR-329ALS-01-	CMP-22027-000001-1	1
	4DFN		MFG		