SoM

Note:
Leave annotation
as P1, P2, P3, P4

MIPI

CSI_P1_D3_P
CSI_P1_D3_N
CSI_P1_D1_P
CSI_P1_D1_N
CSI_P1_D2_P
CSI_P1_D2_N
CSI_P1_D0_P
CSI_P1_D0_N
CSI_P1_CK_P
CSI_P1_CK_N
CLK01
CSI_RST
CSI_PWDN

Note: Some I2C devices require SDA/SCL to be high before powering them

3V3_OUT is sourced from PMIC's 3A NVCC_3P3/BUCK6 and is supplying the SoC's H7 ball "NVCC_I2C"

3V3_OUT
R101 2.2k
R102 2.2k
GPIO3_IO19
IMU_INT

Sensors

IMU_INT
I2C1_SCL
I2C1_SDA
PROX_INT
sensors.sch

PROX_INT
GPIO1_IO12

I2C1_SCL
I2C1_SDA

RTC

I2C1_SCL
I2C1_SDA
IRQ
rtc.sch

LCD_LEDK
LCD_RESET
DSI_D2_P
DSI_D2_N
DSI_D0_P
DSI_D0_N
DSI_CK_P
DSI_CK_N
DSI_D1_P
DSI_D1_N
DSI_D3_P
DSI_D3_N
CAPTOUCH_INT
CAPTOUCH_RST
GPIO1_IO05
mipi.sch

Buttons & LED

SW_VOLUP
SW_VOLDN
ONOFF
SYS_RST
GP_LED1
buttons_led.sch

MNT101 Mount_Hole
FID102 Fiducial
FID103 Fiducial
MNT104 Mount_Hole
MOD101 EmC_SoM Daughterboard plugged into main PCB
P1 P3 P2 P4
MNT102 Mount_Hole
FID101 Fiducial
MNT103 Mount_Hole
GND

P1 IMX8M-SOM1

TCPC_INT
SD2_RST
uSD_CD_B
WWAN_DISABLE
USB1_SS_SEL
LCD_RESET

Ethernet

ENET_TXC
ENET_TD0
ENET_TD1
ENET_TD2
ENET_TD3
ENET_TX_CTL
ENET_RD3
ENET_RD2
ENET_RD1
ENET_RD0
ENET_RX_CTL
ENET_RXC
ENET_MDIO
ENET_MDC
CLKO2
ENET_RST
ENET_WoL
ENET_INT
ENET_2V5
ethernet.sch

WLAN+BT M.2

WIFI_RST
WIFI_DATA3
WIFI_DATA2
WIFI_DATA1
WIFI_DATA0
WIFI_WAKE
WIFI_CMD
WIFI_CLK
BT_HOST_WAKE
BT_PCM_SYNC
BT_PCM_CLK
BT_PCM_IN
BT_PCM_OUT
WLAN_D_P
WLAN_D_N
BT_UART_TXD
BT_UART_RXD
BT_UART_RTS
BT_UART_CTS
WIFI_DISABLE
BT_DISABLE
I2C2_SDA
I2C2_SCL
SAI5_TX_BCLK
SAI5_TX_SYNC
SAI5_RXD
SAI5_TXD
UART4_TXD
UART4_RXD
UART4_RTS
UART4_CTS
wifi_bt_m2.sch

3V3_OUT
R103 10k
R104 10k
I2C2_SDA
I2C2_SCL

5V_SOM
C101 22uF
C102 22uF
C103 100nF
C104 100nF
C105 22uF
C106 22uF
C107 100nF
C108 100nF
3V3_OUT
3V3_SNVS
GND

P2.55 P2.56 P2.57 P2.58 P2.59 P2.60 P2.61 P2.62 P2.63 P2.64 P2.65 P2.66 P2.67 P2.68 P2.69 P2.70 P2.71 P2.72 P2.73 P2.74 P2.75 P2.76 P2.77 P2.78 P2.79 P2.80
+5V Input
P2.14
P2.16
P2.18 +3.3V Output
P2.24 +3.3V Output
P2.22 +2.5V Input

JTAG

POR_B
JTAG_TDI
JTAG_TMS
JTAG_TRST
JTAG_TDO
JTAG_TCK
jtag.sch

TP101
TEST_1P

DSI_BL_PWM
WDG
HDMI_DDC_SCL
HDMI_DDC_SDA
CSI_PWDN
CAPTOUCH_RST
IMU_INT
CSI_RST
PWR_EN
SAI5_RXD
ENET_RST
R107 10k
HP_DET
PROX_INT
SAI1_RXD0(GPIO4_IO02)
SAI5_TXD
LED
SAI1_RXD4(GPIO4_IO06)
SAI1_RXD3(GPIO4_IO05)
BTN1
SAI1_RXD2(GPIO4_IO04)
SAI2_TXFS
SAI2_RXD
SAI1_RXD6(GPIO4_IO08)

P3 IMX8M-SOM3

P3.01 P3.03 P3.05 P3.07 P3.09 P3.11 P3.13 P3.15 P3.02 P3.06 P3.08 P3.12 P3.14 P3.18 P3.20 P3.24 P3.26 P3.30 P3.32 P3.21 P3.23 P3.25 P3.27 P3.29 P3.33 P3.35 P3.37 P3.41 P3.43 P3.45 P3.53 P3.57 P3.59 P3.61 P3.63 P3.65 P3.67 P3.69 P3.73 P3.75 P3.77 P3.79 P3.36 P3.42 P3.44 P3.46 P3.48 P3.58 P3.62 P3.66 P3.70 P3.74 P3.78

HDMI

HDMI_CEC
HDMI_HPD
HDMI_AUX_N
HDMI_AUX_P
HDMI_TX1_P
HDMI_TX1_N
HDMI_TX0_P
HDMI_TX0_N
HDMI_TX2_P
HDMI_TX2_N
HDMI_CLK_P
HDMI_CLK_N
HDMI_DDC_SCL
HDMI_DDC_SDA
hdmi.sch

SAI5_TX_BCLK
ENET_WoL
SAI1_RXD1(GPIO4_IO03)
SAI5_TX_SYNC
ENET_INT
CHRG_INT
CLKO2

Audio

SAI2_TXC
SAI2_MCLK
MIC_SEL
HP_DET
SAI2_TXFS
SAI2_RXD
SAI2_TXD
I2C1_SDA
I2C1_SCL
audio.sch

CLK01
BTN2
GPIO5_IO05

SPI Flash

MISO
MOSI
SCLK
CS
flash.sch

ECSPI1_MISO
ECSPI1_MOSI

USB Hub + SDIO Bridge

WWAN_D_P
WWAN_D_N
WLAN_D_P
WLAN_D_N
SMARTCARD_D_P
SMARTCARD_D_N
USB2_ID
SRST
SDCD
uSD_CLK
uSD_CMD
uSD_DATA0
uSD_DATA1
USB2_D_N
USB2_D_P
uSD_DATA2
uSD_DATA3
usb_hub_sdio.sch

SAI1_RXD7(GPIO4_IO09)
I2C2_SCL
IRQ
UART4_TXD
ECSPI1_SCLK
ECSPI1_SS0
UART4_RXD

Boot Config

BOOT_MODE1
BOOT_MODE0
BOOT_CFG00
BOOT_CFG01
BOOT_CFG02
BOOT_CFG03
BOOT_CFG04
BOOT_CFG05
BOOT_CFG06
BOOT_CFG07
BOOT_CFG08
BOOT_CFG09
BOOT_CFG10
BOOT_CFG11
BOOT_CFG12
BOOT_CFG13
BOOT_CFG14
BOOT_CFG15
boot.sch

SAI1_RXD0(GPIO4_IO02)
SAI1_RXD1(GPIO4_IO03)
SAI1_RXD2(GPIO4_IO04)
SAI1_RXD3(GPIO4_IO05)
SAI1_RXD4(GPIO4_IO06)
SAI1_RXD5(GPIO4_IO07)
SAI1_RXD6(GPIO4_IO08)
SAI1_RXD7(GPIO4_IO09)
SAI1_TXD0(GPIO4_IO12)
SAI1_TXD1(GPIO4_IO13)
SAI1_TXD2(GPIO4_IO14)
SAI1_TXD3(GPIO4_IO15)
SAI1_TXD4(GPIO4_IO16)
SAI1_TXD5(GPIO4_IO17)
SAI1_TXD6(GPIO4_IO18)
SAI1_TXD7(GPIO4_IO19)

Alternate Functions:
SAI6_TXD0
SAI6_TXFS/RXFS
SAI6_TXC/RXC
SAI6_RXD0

WWAN mPCIe

WoWWAN
W_DISABLE1
RESET
PCM_CLK/I2S_SCK
PCM_SYNC/I2S_FSC
PCM_IN/I2S_IN
PCM_OUT/I2S_OUT
wwan_mpcie.sch

WoWWAN
GPIO3_IO08
WWAN_DISABLE
GPIO3_IO04
WWAN_RESET
GPIO3_IO09
SAI1_TXD4(GPIO4_IO16)
SAI6_TXC/RXC
SAI1_RXD6(GPIO4_IO08)
SAI6_TXFS/RXFS
SAI1_RXD5(GPIO4_IO07)
SAI6_TXD0
SAI1_TXD5(GPIO4_IO17)
SAI6_RXD0

Smart Card

SMARTCARD_D_P
SMARTCARD_D_N
smartcard.sch

uSD Card

CONN_SD2_CD_B
CONN_SD2_CLK
CONN_SD2_CMD
CONN_SD2_DATA0
CONN_SD2_DATA1
CONN_SD2_DATA2
CONN_SD2_DATA3
sd.sch

USB-C

USB1_SS_SEL
USB1_RX_N
USB1_RX_P
USB1_TX_N
USB1_TX_P
USB1_D_N
USB1_D_P
TCPC_INT
USB1_ID
USB1_VBUS
I2C1_SCL
I2C1_SDA
VBUS
EN_SRC
EN_SNK
usb-c.sch

Battery

VBUS
EN_SRC
EN_SNK
I2C1_SCL
I2C1_SDA
ONOFF
battery.sch

Power

VBAT_REG
LCD_LEDK
DSI_BL_PWM
PWR_EN
CHRG_INT
GPIO3_IO25
ONOFF
5V_SOM
5V_P
3V3
3V3_P
1V8_P
22V4_P
2V8_P
power.sch

P2 IMX8M-SOM2

WIFI_DISABLE
WWAN_RESET
WoWWAN
CAPTOUCH_INT

P4 IMX8M-SOM4

SAI2_TXD
HAPTIC_GPIO5_IO04
SAI1_RXD5(GPIO4_IO07)
SAI1_TXD0(GPIO4_IO12)
ONOFF
I2C2_SDA
SAI1_TXD1(GPIO4_IO13)
SYS_RST
I2C1_SCL
I2C1_SDA
SAI1_TXD3(GPIO4_IO15)
SAI1_TXD4(GPIO4_IO16)
SAI1_TXD7(GPIO4_IO19)
UART3_TXD
BT_DISABLE
SAI1_TXD5(GPIO4_IO17)
POR_B
UART1_RXD
SAI1_TXD2(GPIO4_IO14)
SAI1_TXD6(GPIO4_IO18)
ECSPI1_MOSI
UART4_CTS
UART3_RXD
ECSPI1_MISO
UART4_RTS
UART1_TXD
USB2_VBUS
USB2_ID
PWM3
PWM4

Spare GPIO:
GPIO5_IO03 (was PWM3)
GPIO5_IO18 (PWM4/CLKO2/I2C3_SCL)

GPIO that can be swapped around:
GPIO1_IO05 (was CSI_P2_PWDN)
GPIO1_IO12 (was IR_CAP)
GPIO3_IO19 (was LED1)
GPIO3_IO20
GPIO3_IO25
GPIO5_IO03 (was PWM3)
GPIO5_IO04 (was PWM2)
GPIO5_IO05 (was PWM1)
GPIO5_IO18 (PWM4/CLKO2/I2C3_SCL)

UART Debug

UART1_RXD
UART1_TXD
uart.sch

GNSS

UART3_RXD
UART3_TXD
gnss.sch

Haptic Motor

HAPTIC
GPIO5_IO04
haptic.sch

5V_P
R105 10k
R106 19.6k
GND

EmCraft System on Module

NXP i.MX 8M Quad Applications Processor with DDR4 LPRAM and eMMC
Connectors: 4x dual row 80 pin 0.4mm pitch headers (P1..P4)

Librem 5 Dev Kit
Purism
Copyright 2018 GNU GPLv3

eric.kuzmenko@puri.sm
angus.ainslie@puri.sm
nicole.faerber@puri.sm
christian.schilmoeller@puri.sm

Sheet: /
File: dvk-mx8m-bsb.sch

Size: A3	Date: 2018-06-18	Rev: v0.1.0
KiCad E.D.A. kicad 4.0.7		Id: 1/24

USB-C TCPC – Config Channel (CC) and PD Role Controller



"Under dead battery operation, PTN5110 applies voltage clamps to both CC pins so that the system may receive power as a Sink. To support platforms with buck-boost configuration, PTN5110 asserts EN_SNK1 pin based on validity of VBUS voltage (facilitates 5 V VBUS sinking)."

USB-C





USB Type C

Purism

eric.kuzmenko@puri.sm
angus.ainslie@puri.sm
nicole.faerber@puri.sm
christian.schilmoeller@puri.sm

Sheet: /USB-C/
File: usb-c.sch

Size: A4	Date: 2018-06-18	Rev: v0.1.0
KiCad E.D.A. kicad 4.0.7		Id: 2/24

Battery Charge Controller



(interpret RSOC% based on this plot)

Drawing ~320mA,
or consuming ≤1.152W,
should give close to
10 hours going from
100% to 0% charge

use AUTO_DPDM_EN
to auto-detect IINLIM

1.658≤ILIM≤2.063
ILIM(nom)≅1.859A
3.9≤VIN≤14

7-bit Slave Address: 0x6B
(1101 011x)

U301 BQ25896

I(Lsat)=7A

Default LOW:
adapter source

sink current ~5mA

Read: 0xD7
Write: 0xD6

Ihold=3.5A
Itrip=6.3A
Ttrip(max)=5s@8A

Vrwm(max)=5.0V
Vbr(min)=6.2V
Pd=150mW

Vf(max)=1.1V

VBAT(DPL)=2.15~2.5V

0.4mA~2.4mA

NCR18650B meets requirements

VBAT(ovp_default)=REG06[7:2]=4.208V (reduce to 4.192V [010110])
Worst Case:
VBAT(default_max_ovp)=(REG06[7:2]×1.005)×1.04=4.3982016V
BQ29705 provides 4.425V as OVP!

ICHG(default)=REG[6:0]=2048mA (reduce to ~1.6A [0011001])

reference design: http://www.ti.com/lit/ug/sluuba2b/sluuba2b.pdf

may want to include BQ29705 protection as in:
http://www.ti.com/lit/ug/tiducl1/tiducl1.pdf
schematic: http://www.ti.com/lit/df/tidrp70/tidrp70.pdf
(PTC may be good enough)

This disables charging
but maybe not VBUS->VOUT
if PTN5110HQ's FAULT_STATUS[6]==1
(Force Off VBUS bit) then set EN_HiZ=1
EN_HiZ may be auto-set when in hiccup

Reading PTN5110HQ's CC_STATUS and POWER_STATUS
registers will tell TCPM (i.MX8M) when to set EN_HiZ

Also, reading PTN5110HQ's CC_STATUS and POWER_STATUS
registers will tell TCPM (i.MX8M) when to set OTG_CONFIG=1
(this will also happen when PTN5110HQ sets EN_SRC HIGH)

BC1.2 is not mandated by PD spec
ICO used to determine max current
Also negotiated from CC pins (I2C)

Battery holder gives ~1mm clearance underneath the battery
Thermistor is 1.1±0.15mm thick, should fit fine with stack-up

Battery holder seems to fit up to ~68.88mm long batteries
need to test 18650 protected cells which are ~69.35mm long

Purism

eric.kuzmenko@puri.sm
angus.ainslie@puri.sm
nicole.faerber@puri.sm
christian.schilmoeller@puri.sm

Sheet: /Battery/
File: battery.sch

Size: A4 | Date: 2018-06-18 | Rev: v0.1.0
KiCad E.D.A. kicad 4.0.7 | Id: 3/24


3.3V/3A
When VBAT_REG can fall below 3.3V use TPS63020 instead
Power TCPC chip first
AP22814: Ilimit=3.45A
AP22804: Ilimit=3.00A (drop-in)
1.8V/600mA
SW4A of PF4210 is 1.8V but SoM doesn't bring it out
Buck instead of TLV70218 LDO saving up to ~100mW loss
LM3670MF-1.8 is much more expensive
ST1S12G18R is a drop-in
Worst-case current draw:
Camera =140mA
USB Switch=113mA
Audio Codec=12mA
Level Shifters=1.5mA
Display=7mA
Remaining≥333.5mA
5.0V/3.8A
If using fixed MIC2876-5.0 then short FB-VOUT resistor open FB-GND resistor
~30ms until EN is HIGH
Cheaper, more efficient, smaller, and simpler than RT6150A
Explicitly mentions USB/smartphone application
AP22814: Ilimit=3.45A
AP22804: Ilimit=3.00A (drop-in)
22.4V/40mA
Optional: if PWR_EN == LOW set PWM = LOW (0% duty)
Reference: https://www.diodes.com/assets/Evaluation-Boards/PAM2841-User-Guide.pdf
(brochure lists backlight as an application)
Spread all the decoupling/stitching capacitors all over the power plane
2.8V/150mA
0.5V drop
Power
Purism
Copyright 2018 GNU GPLv3
eric.kuzmenko@puri.sm
angus.ainslie@puri.sm
nicole.faerber@puri.sm
christian.schilmoeller@puri.sm
Sheet: /Power/
File: power.sch
Size: A4
Date: 2018-06-18
Rev: v0.1.0
KiCad E.D.A. kicad 4.0.7
Id: 4/24

Boot Config

Only eMMC

BOOT_CFG[14:12]	Boot device
001	SD/eSD
010	MMC/eMMC
011	NAND

Fuse	Config	Definition	GPIO[1]	Shipped value	Settings
BOOT_CFG[11:10]	OEM	USDHC port selection	Yes	00	00 - USDHC-1
					01 - USDHC-2
					10 - USDHC-3
					else - reserved





2–>1: eMMC
2–>3: USB (Serial Downloader)

BOOT_MODE[1:0]	Boot Type
00	Boot From Fuses
01	Serial Downloader
10	Internal Boot
11	Reserved









Boot Configuration

Purism

eric.kuzmenko@puri.sm
angus.ainslie@puri.sm
nicole.faerber@puri.sm
christian.schilmoeller@puri.sm

Sheet: /Boot Config/
File: boot.sch

Size: A4 | Date: 2018–06–18 | **Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7 | Id: 5/24

Real-Time Clock



Note:
Datasheet says slave address is 0xD0
with a R/W bit appended, since 0xD must
be 4-bits wide the actual 7-bit address is
0x68 (110 1000), and becomes 0xD0 during a
write operation (1101 0000)

Reference:
https://github.com/HIO-Project/linux-imx6-nano-imx_3.10.17_1.0.1_ga/
blob/8848e94b2f889fe44f6736e2d4c98851a2282275/arch/arm/boot/dts/
imx6qdl-mtp.dtsi#L351

RTC

Purism

eric.kuzmenko@puri.sm
angus.ainslie@puri.sm
nicole.faerber@puri.sm
christian.schilmoeller@puri.sm

Sheet: /RTC/
File: rtc.sch

Size: A4	Date: 2018-06-18	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 6/24

UART Debug



UART Debug

Purism

eric.kuzmenko@puri.sm
angus.ainslie@puri.sm
nicole.faerber@puri.sm
christian.schilmoeller@puri.sm

Sheet: /UART Debug/
File: uart.sch

Size: A4	Date: 2018-06-18	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 7/24

JTAG



JTAG

Purism

eric.kuzmenko@puri.sm
angus.ainslie@puri.sm
nicole.faerber@puri.sm
christian.schilmoeller@puri.sm

Sheet: /JTAG/
File: jtag.sch

Size: A4	Date: 2018-06-18	Rev: v0.1.0
KiCad E.D.A. kicad 4.0.7		Id: 8/24

USB Hub + SDIO Bridge



USB Hub + SDIO Bridge		eric.kuzmenko@puri.sm angus.ainslie@puri.sm nicole.faerber@puri.sm christian.schilmoeller@puri.sm
Purism		
Sheet: /USB Hub + SDIO Bridge/ File: usb_hub_sdio.sch		
Size: A4	Date: 2018-06-18	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 9/24

µSD



Normally Open?

uSD Card	eric.kuzmenko@puri.sm angus.ainslie@puri.sm nicole.faerber@puri.sm christian.schilmoeller@puri.sm
Purism	
Sheet: /uSD Card/ File: sd.sch	
Size: A4 | Date: 2018-06-18	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7	Id: 10/24

MIPI



MIPI

Purism

eric.kuzmenko@puri.sm
angus.ainslie@puri.sm
nicole.faerber@puri.sm
christian.schilmoeller@puri.sm

Sheet: /MIPI/
File: mipi.sch

Size: A4	Date: 2018-06-18	Rev: v0.1.0
KiCad E.D.A. kicad 4.0.7		Id: 11/24

Display & Touch Controller

LCD PN:
Shenzhen Jinghong Electronics Co., Ltd.
JH057N00900

Note:
No power-up sequence is given in the spec sheet

7-bit Slave Address: 0x5D
(1011 101x)

Read: 0xBB
Write: 0xBA

Cap-Touch Controller IC PN:
Goodix GT5688



The upper 7 bits are the address,
and bit 0 is used to select read or write.
GT5688 has two slave device addresses to choose from:

INT	7-Bit Address	8-Bit Write Address	8-Bit Read Address
LOW	0x5D	0xBA	0xBB
HIGH	0x14	0x28	0x29

Every time you power on or reset, you need to use the INT pin to set the I2C address:

eric.kuzmenko@puri.sm
angus.ainslie@puri.sm
nicole.faerber@puri.sm
christian.schilmoeller@puri.sm

Sheet: /MIPI/DSI/
File: dsi.sch

Size: A4 | Date: 2018-06-18 | **Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7 | Id: 12/24

Camera

Using Internal DVDD 1.5V Regulator:



2.7 POWER UP SEQUENCE

Based on the system power configuration (1.8V or 2.8V for I/O power, using external DVDD or internal DVDD, requiring access to the I2C during power up period or not), the power up sequence will differ. If 1.8V is used for I/O power, using the internal DVDD is preferred. If 2.8V is used for I/O power, due to a high voltage drop at the internal DVDD regulator, there is a potential heat issue. Hence, for a 2.8V power system, OmniVision recommends using an external DVDD source. Due to the higher power down current when using an external DVDD source, OmniVision strongly recommends cutting off all powers, including the external DVDD, when the sensor is not in use in the case of 2.8V I/O and external DVDD.

2.7.1 POWER UP WITH INTERNAL DVDD

For powering up with the internal DVDD and I2C access during the power ON period, the following conditions must occur:

1. when DOVDD and AVDD are turned ON, make sure DOVDD becomes stable before AVDD becomes stable
2. PWDN is active high with an asynchronized design (does not need clock)
3. PWDN pin tied to digital ground if it is not controlled.
4. if PWDN pin is controlled as below, for PWDN to go low, power must first become stable (AVDD to PWDN ≥ 5 ms)
5. RESETB is active low with an asynchronized design
6. master clock XVCLK should provide at least 1 ms before host accesses the sensor's registers
7. host can access I2C bus (if shared) during entire period. 20ms after RESETB goes high, host can access the sensor's registers to initialize sensor

figure 2-3 power up timing with internal DVDD



note
- t_0 ≥ 0ms, delay from DOVDD stable to AVDD stable, it is recommended to power up AVDD shortly after DOVDD has been powered up
- t_1 ≥ 0ms, delay from XVCLK off to AVDD off
- t_2 ≥ 5ms, delay from AVDD stable to sensor power up stable, PWDN can be pulled low after this point, XVCLK can be turned on after power on
- t_3 ≥ 1ms, delay from sensor power up stable to RESETB pull up
- t_4 ≥ 20ms, delay from RESETB pull high to SCCB initialization
- t_5 ≥ 0ms, delay from AVDD off to DOVDD off
- t_6 ≥ 0ms, delay from RESETB pull low to AVDD off

S640_DS_2_2

Note:
All switches' pins can be swapped
e.g. 2<->3
or 1<->3
(+mic)



Camera PN:
Truly C08725-B5SA-E

7-bit Slave Address: 0x78
(1111 000x)

Read: 0xF1
Write 0xF0



OV5640 CMOS Image Sensor Datasheet:
https://cdn.sparkfun.com/datasheets/Sensors/LightImaging/OV5640_datasheet.pdf



MIPI CSI

Purism

eric.kuzmenko@puri.sm
angus.ainslie@puri.sm
nicole.faerber@puri.sm
christian.schilmoeller@puri.sm

Sheet: /MIPI/CSI/
File: csi.sch

Size: A4	Date: 2018-06-18	Rev: v0.1.0
KiCad E.D.A. kicad 4.0.7		Id: 13/24

Buttons & LED



Use PWM2_PWMSAR to set the compare value (duty cycle)
Use PWM2_PWMCR[15:4] to set the PRESCALER (frequency)
Use PWM2_PWMPR to set the top of the counter (frequency)



Buttons & LED

Purism

eric.kuzmenko@puri.sm
angus.ainslie@puri.sm
nicole.faerber@puri.sm
christian.schilmoeller@puri.sm

Sheet: /Buttons & LED/
File: buttons_led.sch

Size: A4	Date: 2018-06-18	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 14/24

WWAN mPCIe



WWAN mPCIe
Purism
eric.kuzmenko@puri.sm
angus.ainslie@puri.sm
nicole.faerber@puri.sm
christian.schilmoeller@puri.sm

Sheet: /WWAN mPCIe/		
File: wwan_mpcie.sch		
Size: A4	Date: 2018-06-18	Rev: v0.1.0
KiCad E.D.A. kicad 4.0.7		Id: 15/24

Audio

Reference:
http://www.52rd.com/S_txt/2011_3/TXT26685.htm
http://www.sengpielaudio.com/calculator-transferfactor.htm
https://electronics.stackexchange.com/questions/31442/how-can-i-switch-this-audio-jack-using-its-own-mechanical-switches-without-cre
(Nit6 does the same)
+Zener diode to protect against ranges outside of -0.9V to 3.3V

dB specs in datasheet is a unit of power gain (not dBu or VU)
with respect to the DAC's unattenuated output

"HP Output - 62.5mW max, 1.02kHz sine into 16Ω load at 3.3 V"
⇒ $(1V)^2/(16Ω)=62.5mW$
∴ Vrms=1V ⇒ Vp(amplitude)=1.414V
∴ Irms(max)=62.5mA

If HP_DET is HIGH for >100ms then HPs are present

S/E button on earbud headsets
shorts the mic for key function

Could use FSA8008 to detect mic









-37dB=14.1254mV/Pa
∴ mic produces 14.1254mVrms when exposed to a 1kHz tone of 94dB-SPL at the capsule (or 19.98mV amplitude)

⇒ 40dB gain would produce ~2V amplitude (4Vpp, clipping)
30dB gain would produce ~0.632V amplitude (1.264Vpp)
38.33dB gain would yield 3.3Vpp

LCR Measurements:

Earbud Microphone: @1kHz	Headset Speaker: @1kHz	Earbud Speaker: @1kHz
Ls = 3.844mH	Ls = 244.4uH	Ls = 25.2uH
Lp = 15.757H	Lp = 141.99mH	Lp = 311.0mH
Cs = 6.583uF	Cs = 103.6uF	Cs = 1.0mF
Cp = 1612.8pF	Cp = 178.77nF	Cp = 81.95nF
Rs = 1.5465kOhms	Rs = 36.860hms	Rs = 17.0300hms
Rp = 1.5478kOhms	Rp = 36.860hms	Rp = 17.0340hms
θ = -0.8deg	θ = -2.3deg	θ = 0.5deg

Audio

Purism

eric.kuzmenko@puri.sm
angus.ainslie@puri.sm
nicole.faerber@puri.sm
christian.schilmoeller@puri.sm

Sheet: /Audio/
File: audio.sch

Size: A4	Date: 2018-06-18	Rev: v0.1.0
KiCad E.D.A. kicad 4.0.7		Id: 16/24

RGMII 10/100/1000 Ethernet



Ethernet

Purism

eric.kuzmenko@puri.sm
angus.ainslie@puri.sm
nicole.faerber@puri.sm
christian.schilmoeller@puri.sm

Sheet: /Ethernet/
File: ethernet.sch

Size: A4	Date: 2018-06-18	Rev: v0.1.0
KiCad E.D.A. kicad 4.0.7		Id: 17/24

WLAN+BT M.2

Socket: Table 46
Module: Table 23

M.2 Key E

RS9116 NC:
RTS, CTS, BT_HOST_WAKE

RS9116 datasheet says
no WIFI_WAKE
but the schematic has it

RedPine RS9116 MB0
Requires 5V on
Pin 54 if USB used

3V3_P
R1802 NC
JP1801
C1809 6.8pF, C1810 8.2pF, C1811 18pF, C1812 33pF, C1813 39pF, C1814 100nF, C1816 1uF, C1817 220uF, C1818 220uF
GND

J1803 Key_E

WLAN_D_P
WLAN_D_N
WIFI_CLK
WIFI_CMD
WIFI_DATA0
WIFI_DATA1
WIFI_DATA2
WIFI_DATA3
WIFI_WAKE
M2_PCM_CLK
M2_PCM_SYNC
M2_PCM_IN
M2_PCM_OUT
SoC's IN/OUT
BT_HOST_WAKE
BT_UART_RXD
SoC's RX
Module's TX
SoC's TX
Module's RX
BT_UART_TXD
BT_UART_RTS
BT_UART_CTS
i.MX8M in DCE mode (POR state)
has CTS output, RTS input

1V8_P
R1801 100k
D1801 DB2J209
WIFI_RST
VIH=2.31V
W_DISABLE1
D1802 DB2J209

RedPine RS9116
has 100k pull-up to
3.3V making SDIO_RST
~2.55V when HIGH

6.2 M.2 Signal Directions
UARTn_UFCR[DCEDTE]=0 on POR



TX output
RX input
CTS output
RTS input

⇒TX→RX
RX←TX
CTS→CTS
RTS←RTS

AE1801 FR05-S1-NO-1-004
CBL1801 Coax_cable_ufl_ufl
u.FL
J1801
GND

TODO:
Assign antennae
footprints

AE1802 FR05-S1-NO-1-004
CBL1802 Coax_cable_ufl_ufl
J1802

MOD1801
WifiBTCard
WiFi + Bluetooth
M.2 Form Factor
Key ID "E"
width: 22 mm
length: 30 mm

3V3_P
C1815 100nF
GND

Pin 54 on RS9116 is
USB_VBUS Sink

RS9116 SUSCLK
is a GPIO (unused)
SUSCLK
R1803 10k

U1803A 74LVC2G08
U1803B 74LVC2G08
VCC

Leave BT_DISABLE
LOW for RS9116
BT_DISABLE
WIFI_DISABLE

Input pins are
interchangeable

D1803 DB2J209
R1805 100k
R1807 100k
C1819 100nF

SW1801A WLAN_HKS
SW1801B WLAN_HKS
Open = ON
Closed = OFF

Note:
All switches' pins
can be swapped
e.g. 2<->3
or 1<->3

W_DISABLE2
W_DISABLE1
M2_I2C_SDA
M2_I2C_SCL

R1804 10k
R1806 10k
Q1801 FDV301N
Q1802 FDV301N
I2C2_SDA
I2C2_SCL

RS9116 is an I2C master
⇒its SCL is an output
(ok bc only device on I2C2)

C1801 1uF, C1802 10nF
C1803 10nF, C1804 1uF
U1801 NTB0104GU12
OE VCCA VCCB GND

BT_UART_RXD
BT_UART_TXD
BT_UART_RTS
BT_UART_CTS

RS9116 does not
use RTX & CTS

internal 10k pull-up

RX, TX, RTS, CTS
of the SoC

C1805 1uF, C1806 10nF
C1807 10nF, C1808 1uF
U1802 NTB0104GU12

BCLK
M2_PCM_CLK
M2_PCM_SYNC
M2_PCM_IN
M2_PCM_OUT

BT_PCM_CLK
BT_PCM_SYNC
BT_PCM_IN
BT_PCM_OUT

configure as slave

IN, OUT
of the SoC

WLAN+BT M.2
Purism

eric.kuzmenko@puri.sm
angus.ainslie@puri.sm
nicole.faerber@puri.sm
christian.schilmoeller@puri.sm

Sheet: /WLAN+BT M.2/
File: wifi_bt_m2.sch

Size: A4 | Date: 2018-06-18 | Rev: v0.1.0
KiCad E.D.A. kicad 4.0.7 | Id: 18/24

TUSB1046 can be used for DP over USB-C

HDMI



HDMI

Purism

eric.kuzmenko@puri.sm
angus.ainslie@puri.sm
nicole.faerber@puri.sm
christian.schilmoeller@puri.sm

Sheet: /HDMI/
File: hdmi.sch

Size: A4 | Date: 2018-06-18 | **Rev: v0.1.0**

KiCad E.D.A. kicad 4.0.7 | Id: 19/24

Sensors

Proximity & Ambient Light



Note:
I2C 2.2kΩ pull-up suggested
check input capacitance & rise time

7-bit Slave Address: 0x60
(1100 000x)

Read: 0xC1
Write: 0xC0

Reference:
https://www.vishay.com/docs/84307/designingvcnl4040.pdf
http://www.vishay.com/docs/84931/vcnl4040sensorboardfiles.pdf

9-Axis IMU



Accel/Gyro:
7-bit Slave Address: 0x6A
(1101 010x)

Read: 0xD5
Write: 0xD4

must guarantee 1nF value
under 11V bias condition

Mag:
7-bit Slave Address: 0x1E
(0011 110x)

Read: 0x3D
Write: 0x3C

Reference:
http://www.st.com/en/evaluation-tools/steval-mki159v1.html



Table 19. Accelerometer and gyroscope SAD+Read/Write patterns

Command	SAD[6:1]	SAD[0] = SA0	R/W	SAD+R/W
Read	110101	0	1	11010101 (D5h)
Write	110101	0	0	11010100 (D4h)
Read	110101	1	1	11010111 (D7h)
Write	110101	1	0	11010110 (D6h)

Table 20. Magnetic sensor SAD+Read/Write patterns

Command	SAD[6:2]	SAD[1] = SDO/SA1	SAD[0]	R/W	SAD+R/W
Read	00111	0	0	1	00111001 (39h)
Write	00111	0	0	0	00111000 (38h)
Read	00111	1	0	1	00111101 (3Dh)
Write	00111	1	0	0	00111100 (3Ch)

Sensors

Purism

eric.kuzmenko@puri.sm
angus.ainslie@puri.sm
nicole.faerber@puri.sm
christian.schilmoeller@puri.sm

Sheet: /Sensors/
File: sensors.sch

Size: A4 | Date: 2018-06-18 | Rev: v0.1.0
KiCad E.D.A. kicad 4.0.7 | Id: 20/24

SPI NOR Flash



SPI NOR Flash		eric.kuzmenko@puri.sm angus.ainslie@puri.sm nicole.faerber@puri.sm christian.schilmoeller@puri.sm
Purism		
Sheet: /SPI Flash/ File: flash.sch		
Size: A4	Date: 2018-06-18	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 21/24

Smart Card



Reference:
http://www.microchip.com/DevelopmentTools/ProductDetails.aspx?PartNO=EVB-SEC1110

Smart Card

Purism

eric.kuzmenko@puri.sm
angus.ainslie@puri.sm
nicole.faerber@puri.sm
christian.schilmoeller@puri.sm

Sheet: /Smart Card/
File: smartcard.sch

Size: A4 | Date: 2018-06-18 | **Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7 | Id: 22/24

GNSS



References:
https://www.u-blox.com/sites/default/files/MAX-M8_HardwareIntegrationManual_%28UBX-13004876%29.pdf
https://www.u-blox.com/sites/default/files/MAX-8-M8-FW3_HardwareIntegrationManual_%28UBX-15030059%29.pdf

GNSS

Purism

eric.kuzmenko@puri.sm
angus.ainslie@puri.sm
nicole.faerber@puri.sm
christian.schilmoeller@puri.sm

Sheet: /GNSS/
File: gnss.sch

Size: A4 | Date: 2018-06-18 | **Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7 | Id: 23/24

Haptic Motor

PWM pins occupied:
GPIO1_IO01 – LCD Backlight
GPIO1_IO13 – LED
GPIO1_IO14 – Ethernet (CLKO_25MHz)
GPIO1_IO15 – CSI (CLKO2)

PWM needed?
Only needs to be toggled
ON 1 sec, OFF 1 sec (0.5Hz)

Can MUX as either
GPIO or PWM2
swapping with LED



Cap will reduce dV/dt
effectively less EMI

When the motor is off
both terminals are at GND

Motor will have wire leads
with a 2-pin Molex or Boom Precision
connector installed (by request)

Metal housing is floating
thick adhesive layer underneath
(not connected to either pin)

Haptic/Vibration Motor

Purism

eric.kuzmenko@puri.sm
angus.ainslie@puri.sm
nicole.faerber@puri.sm
christian.schilmoeller@puri.sm

Sheet: /Haptic Motor/
File: haptic.sch

Size: A4	Date: 2018-06-18	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 24/24