


USB-C TCPC - Config Channel (CC) and PD Role Controller




"Under dead battery operation, PTN5110 applies voltage clamps to both CC pins so that the system may receive power as a Sink. To support platforms with buck-boost configuration, PTN5110 asserts EN_SNK1 pin based on validity of VBUS voltage (facilitates 5 V VBUS sinking)."

fast role swap is optional
PTN5110 8.1.4 leaves it floating (good)!




Unused
Open-drain output
tied with CHRG_INT
3V3_OUT
Read: 0xA5
Write: 0xA4
7-Bit Slave Address: 0x52
(1010 010x)

Initialize as the UFP (device)
read CC_STATUS to determine role
use Host Negotiation Protocol (HNP)
to become an DFP (host)
∴ USB ID is effectively unused
⇒ Legacy devices would "wait" for this
⇒ If CC initializes as UFP then no HNP needed

USB1_VBUS=5V when VBUS>4.31V



USB-C



USB Type C

Purism

Copyright 2018 GNU GPLv3

Sheet: /USB-C/
File: usb-c.sch

Size: A4
KiCad E.D.A. kicad 4.0.7

Date: 2018-06-18

Rev: v0.1.0
Id: 2/24

eric.kuzmenko@puri.sm
angus.ainstlie@puri.sm
nicole.farber@puri.sm
christian.schilmoeller@puri.sm




Drawing ~333.33mA,
or consuming <1.2W,
should give close to
10 hours going from
100% to 0% charge

$$1.658 \leq ILIM \leq 2.063$$

$$ILIM(nom) \cong 1.859A$$

$$3.9 < V_{IN} \leq 14$$
$$I(\text{sat}) = 7\text{A}$$

L301



Also, reading PTN5110HQ's CC_STATUS and POWER_STATUS registers will tell TCPM (i.MX8M) when to set OTG_CONFIG=1 (this will also happen when PTN5110HQ sets EN_SRC HIGH)

Battery holder gives ~1mm clearance underneath the battery
Thermistor is 1.1 ± 0.15 mm thick, should fit fine with stack-up
Battery holder seems to fit up to ~68.88mm long batteries
need to test 18650 protected cells which are ~69.35mm long

Purism

eric.kuzmenko@puri.sm
angus.ainslie@puri.sm
nicole.ferber@puri.sm
christian.schilmoeller@puri.sm

Id: 3/24


3.3V/3A



1.8V/600mA



5.0V/3.8A



22.4V/40mA



2.8V/150mA



Power

Power

Purism

Copyright 2018 GNU GPLv3

Sheet: /Power/
File: power.sch

Size: A4
KiCad E.D.A. kicad 4.0.7

Date: 2018-06-18

Rev: v0.1.0

Id: 4/24


eric.kuzmenko@puri.sm

angus.ainslie@puri.sm


nicole.farber@puri.sm

christian.schilmoeller@puri.sm

Boot Config







BOOT_CFG04: 0 - 1-bit SD bus
1 - 4-bit SD bus (pull-up DATA1-3?)
BOOT_CFG05: 1 - 8-bit eMMC bus
0 - 1-bit eMMC bus



Note:
All switches' pins
can be swapped
e.g. 2<->3
or 1<->3
(+BOOT_MODE2)

2->1: eMMC 2->3: USB (Serial Downloader)	
BOOT_MODE[1:0]	Boot Type
00	Boot From Fuses
01	Serial Downloader
10	Internal Boot
11	Reserved

Only eMMC					
BOOT_CFG[14:12]			Boot device		
001			SD/eSD		
010			MMC/eMMC		
011			NAND		
Fuse	Config	Definition	GPIO ¹	Shipped value	Settings
BOOT_CFG[11:10]	OEM	USDHC port selection	Yes	00	00 - USDHC-1
					01 - USDHC-2
					10 - USDHC-3
					else - reserved



Boot Configuration



Copyright 2018 GNU GPLv3

Sheet: /Boot Config/
File: boot.sch

Size: A4
KiCad E.D.A. kicad 4.0.7

Date: 2018-06-18

Rev: v0.1.0
Id: 5/24

eric.kuzmenko@puri.sm

angus.ainstlie@puri.sm

nicole.farber@puri.sm

christian.schilmoeller@puri.sm

Real-Time Clock



Note:

Datasheet says slave address is 0xD0
with a R/W bit appended, since 0xD must
be 4-bits wide the actual 7-bit address is
0x68 (110 1000), and becomes 0xD0 during a
write operation (1101 0000)

Reference:

https://github.com/HIO-Project/linux-imx6-nano-imx_3.10.17_1.0.1_ga/blob/8848e94b2f889fe44f6736e2d4c98851a2282275/arch/arm/boot/dts/imx6qdl-mtp.dtsi#L351

RTC



Copyright 2018 GNU GPLv3

Sheet: /RTC/

File: rtc.sch

Size: A4

Date: 2018-06-18

KiCad E.D.A. kicad 4.0.7

Rev: v0.1.0

Id: 6/24


eric.kuzmenko@puri.sm

angus.ainslie@puri.sm

nicole.farber@puri.sm

christian.schilmoeller@puri.sm

UART Debug



UART Debug



Copyright 2018 GNU GPLv3

Sheet: /UART Debug/
File: uart.sch

Size: A4 Date: 2018-06-18
KiCad E.D.A. kicad 4.0.7

eric.kuzmenko@puri.sm
angus.ainstlie@puri.sm
nicole.farber@puri.sm
christian.schilmoeller@puri.sm

Rev: v0.1.0
Id: 7/24

JTAG



JTAG



Copyright 2018 GNU GPLv3

Sheet: /JTAG/

File: jtag.sch

Size: A4

Date: 2018-06-18

KiCad E.D.A. kicad 4.0.7

Rev: v0.1.0

Id: 8/24


eric.kuzmenko@puri.sm

angus.ainstlie@puri.sm

nicole.farber@puri.sm

christian.schilmoeller@puri.sm

USB Hub + SDIO Bridge



USB Hub + SDIO Bridge



Copyright 2018 GNU GPLv3

Sheet: /USB Hub + SDIO Bridge/

File: usb_hub_sdio.sch

Size: A4	Date: 2018-06-18
----------	------------------

KiCad E.D.A.	kiCad 4.0.7
--------------	-------------

eric.kuzmenko@puri.sm

angus.ainslie@puri.sm


nicole.faerber@puri.sm

christian.schilmoeller@puri.sm

Rev: v0.1.0

Id: 9/24

μ SD



uSD Card



Purism

Copyright 2018 GNU GPLv3

Sheet: /uSD Card/

File: sd.sch

eric.kuzmenko@puri.sm

angus.ainslie@puri.sm

nicole.faerber@puri.sm

christian.schilmoeller@puri.sm

Size: A4


Date: 2018-06-18

Rev: v0.1.0

Size: A4	Date: 11/01/2025
KiCad E.D.A.	kicad 4.0.7

Id: 10/24

MIPI



MIPI



Copyright 2018 GNU GPLv3

Sheet: /MIPI/

File: mipi.sch

Size: A4 Date: 2018-06-18

KiCad E.D.A. kicad 4.0.7

eric.kuzmenko@puri.sm

angus.ainstlie@puri.sm

nicole.ferber@puri.sm

christian.schilmoeller@puri.sm


Rev: v0.1.0

Id: 11/24

Display & Touch Controller

LCD PN:
Shenzhen Jinghong Electronics Co., Ltd.
JH057N00900


Note:
No power-up sequence is
given in the spec sheet



The upper 7 bits are the address,
and bit 0 is used to select read or write.
GT5688 has two slave device addresses to choose from:

	7-Bit Address	8-Bit Write Address	8-Bit Read Address
INT LOW	0x5D	0xBA	0xBB
INT HIGH	0x14	0x28	0x29


Every time you power on or reset, you need
to use the INT pin to set the I2C address:





Cap-Touch FPC:

Pin#	Definition
1	SCL
2	SDA
3	INT
4	RESET
5	VDD2_R5
6	GND

Front: Back:



100Ω Differential Impedance



MIPI DSI



Copyright 2018 GNU GPLv3

Sheet: /MIPI/DSI/
File: dsi.sch


Size: A4 Date: 2018-06-18
KiCad E.D.A. kicad 4.0.7

eric.kuzmenko@puri.sm
angus.ainslie@puri.sm
nicole.farber@puri.sm
christian.schilmoeller@puri.sm

Rev: v0.1.0
Id: 12/24

Camera

Using Internal DVDD 1.5V Regulator:



2.7 POWER UP SEQUENCE


Based on the system power configuration (1.8V or 2.8V for I/O power, using external DVDD or internal DVDD, requiring access to the I2C during power up period or not), the power up sequence will differ. If 1.8V is used for I/O power, using the internal DVDD is preferred. If 2.8V is used for I/O power, due to a high voltage drop at the internal DVDD regulator, there is a potential heat issue. Hence, for a 2.8V power system, OmniVision recommends using an external DVDD source. Due to the higher power down current when using an external DVDD source, OmniVision strongly recommends cutting off all powers, including the external DVDD, when the sensor is not in use in the case of 2.8V I/O and external DVDD.

2.7.1 POWER UP WITH INTERNAL DVDD

For powering up with the internal DVDD and I2C access during the power ON period, the following conditions must occur:

1. when DOVDD and AVDD are turned ON, make sure DOVDD becomes stable before AVDD becomes stable
2. PWDN is active high with an asynchronous design (does not need clock)
3. PWDN pin tied to digital ground if it is not controlled.
4. if PWDN pin is controlled as below, for PWDN to go low, power must first become stable (AVDD to PWDN ≥ 5 ms)
5. RESETB is active low with an asynchronous design
6. master clock XVCLK should provide at least 1 ms before host accesses the sensor's registers
7. host can access I2C bus (if shared) during entire period. 20ms after RESETB goes high, host can access the sensor's registers to initialize sensor


figure 2-3 power up timing with internal DVDD



- note $t_0 \geq 0$ ms, delay from DOVDD stable to AVDD stable, it is recommended to power up AVDD shortly after DOVDD has been powered up
- $t_1 \geq 0$ ms, delay from XVCLK off to AVDD off
- $t_2 \geq 5$ ms, delay from AVDD stable to sensor power up stable, PWDN can be pulled low after this point. XVCLK can be turned on after power on
- $t_3 \geq 1$ ms, delay from sensor power up stable to RESETB pull up
- $t_4 \geq 20$ ms, delay from RESETB pull high to SCCB initialization
- $t_5 \geq 0$ ms, delay from AVDD off to DOVDD off
- $t_6 \geq 0$ ms, delay from RESETB pull low to AVDD off

5640_05_2.2

Note:
All switches' pins
can be swapped
e.g. 2<->3
or 1<->3
(+mic)



Camera PN:
Truly C08725-B5SA-E
7-bit Slave Address: 0x78
(1111 000x)
Read: 0xF1
Write 0xF0

OV5640 CMOS Image Sensor Datasheet:
https://cdn.sparkfun.com/datasheets/Sensors/LightImaging/OV5640_datasheet.pdf

MIPI CSI



Copyright 2018 GNU GPLv3

Sheet: /MIPI/CSI/

File: csi.sch

Size: A4

Date: 2018-06-18

KiCad E.D.A. kicad 4.0.7

Rev: v0.1.0

Id: 13/24

eric.kuzmenko@puri.sm

angus.ainslie@puri.sm

nicole.farber@puri.sm

christian.schilmoeller@puri.sm

A	
B	
C	
D	





C




1

WWAN M.2



Standards:
3GPP TS 51.010-1
ISO/IEC 7816





DET is normally closed!
<10cm away from module!
UIM-CLK up to 5MHz

SIM_DETECT:

Sierra, Huawei, and Telit are Active High
SimCom and Gemalto needs to be inverted!
"When SIM is present, SIM_DET is high"
SIM_DET needs to open when card inserted!

"It is recommended to place the UIM_RST trace
between UIM_DATA and UIM_CLK to provide isolation"
"It is recommended to surround the UIM_DATA with ground."



Some modems are NC
for the USB3.0 interface
Some modules do
GNSS over USB
Some modems require
the USB3.0 interface
Typically host support
for USB3.0 is optional
USB3.0 unused with
Gemalto, SimCom, Fibocom

Even pins 40-48 are unused

	Pin	Port Config_0 ¹	Port Config_1 ²	Port Config_2 ³	Port Config_3 ⁴
GPIO_0	40	GNSS_SCL	GNSS_SCL	SIM_DET2	HSIC_Data
GPIO_1	42	GNSS_SDA	GNSS_SDA	UIM_DTA2	HSIC_Strobe
GPIO_2	44	GNSS_IRQ	GNSS_IRQ	UIM_CLK2	IPC_0
GPIO_3	46	SYSClk	GNSS_0	UIM_RST2	IPC_1
GPIO_4	48	TX_BLANKING	GNSS_1	UIM_PWR2	IPC_2
GPIO_5	20	AUDIO_0	AUDIO_0	RFU	Audio_0
GPIO_6	22	AUDIO_1	AUDIO_1	RFU	Audio_1
GPIO_7	24	AUDIO_2	AUDIO_2	RFU	IPC_3/Audio_2
GPIO_8	28	AUDIO_3	AUDIO_3	RFU	IPC_4/Audio_3
GPIO_9	10	LED#1	LED#1	LED#1	IPC_5
GPIO_10	26	W_Disable2#	W_Disable2#	W_Disable2#	IPC_6
GPIO_11	23	Wake_On_WWAN	Wake_On_WWAN	Wake_On_WWAN	IPC_7
GPIO_12	25	DPR	DPR	DPR	IPC_8

Module Configuration Decodes				Module Type and Main Host Interface ¹	Port Configuration ²	State
CONFIG_0 (Pin 21)	CONFIG_1 (Pin 69)	CONFIG_2 (Pin 75)	CONFIG_3 (Pin 1)			
GND	GND	GND	GND	SSD - SATA	N/A	
GND	NC	GND	GND	SSD - PCIe	N/A	0
GND	GND	NC	GND	WWAN - PCIe	0	1
GND	NC	NC	GND	WWAN - PCIe	1	2
GND	GND	GND	NC	WWAN - USB 3.0	0	3
GND	NC	GND	NC	WWAN - USB 3.0	1	4
GND	GND	NC	NC	WWAN - USB 3.0	2	5
GND	NC	NC	NC	WWAN - USB 3.0	3	6
NC	GND	GND	GND	WWAN - SSIC	0	7
NC	NC	GND	GND	WWAN - SSIC	1	8
NC	GND	NC	GND	WWAN - SSIC	2	9
NC	NC	NC	GND	WWAN - SSIC	3	10
NC	GND	NC	NC	WWAN - PCIe	2	11
NC	NC	GND	NC	WWAN - PCIe	3	12
NC	GND	NC	NC	RFU	N/A	13
NC	NC	NC	NC	No Module Present	N/A	14
NC	NC	NC	NC	No Module Present	N/A	15

WWAN M.2

Purism

Copyright 2018 GNU GPLv3

Sheet: /WWAN M.2/
File: wwan_m2.sch

Size: A4 Date: 2018-06-18
KiCad E.D.A. kicad 4.0.7

eric.kuzmenko@puri.sm

angus.ainslie@puri.sm

nicole.farber@puri.sm

christian.schilmoeller@puri.sm

Rev: v0.1.0

Id: 15/24

Audio

Reference:
http://www.52rd.com/S_txt/2011_3/TXT26685.htm
<http://www.sengpielaudio.com/calculator-transferfactor.htm>
<https://electronics.stackexchange.com/questions/31442/how-can-i-switch-this-audio-jack-using-its-own-mechanical-switches-without-cre>
 (Nit6 does the same)
 +Zener diode to protect against ranges outside of -0.9V to 3.3V

dB specs in datasheet is a unit of power gain (not dBu or VU) with respect to the DAC's unattenuated output

"HP Output - 62.5mW max, 1.02kHz sine into 16Ω load at 3.3 V"
 $\Rightarrow (1V)^2 / (16\Omega) = 62.5mW$
 $\therefore V_{rms} = 1V \Rightarrow V_p(\text{amplitude}) = 1.414V$
 $\therefore I_{rms}(\text{max}) = 62.5mA$

If HP_DET is HIGH for >100ms then HPs are present

S/E button on earbud headsets shorts the mic for key function

Could use FSA8008 to detect mic



$Z(\text{hp}) \geq 16\Omega$

Pin 5 (tip switch) is NC, open when inserted
 If just headphones then HP_DET=HIGH, R(mic)=0

may add ~220uF cap parallel to Zener

Ext-Mic enabled MIC_SEL=LOW

Int-Mic enabled MIC_SEL=LOW
 Add TVS next to int-mic? (OpenMoko does this)

-37dB=14.1254mV/Pa
 \therefore mic produces 14.1254mVrms when exposed to a 1kHz tone of 94dB-SPL at the capsule (or 19.98mV amplitude)
 \Rightarrow 40dB gain would produce -2V amplitude (4Vpp, clipping)
 30dB gain would produce -0.632V amplitude (1.264Vpp)
 38.33dB gain would yield 3.3Vpp

SW Mute Mic: MUTE_ADC=1

Note:
 All switches' pins can be swapped
 e.g. 5<->4 or 5<->6 (+camera)

LCR Measurements:

Earbud Microphone: @1kHz
 $L_s = 3.844mH$
 $L_p = 15.757H$
 $C_s = 6.583uF$
 $C_p = 1612.8pF$
 $R_s = 1.5465k\Omega$
 $R_p = 1.5478k\Omega$
 $\theta = -0.8deg$

Headset Speaker: @1kHz
 $L_s = 244.4uH$
 $L_p = 141.99mH$
 $C_s = 103.6uF$
 $C_p = 178.77nF$
 $R_s = 36.860\Omega$
 $R_p = 36.860\Omega$
 $\theta = -2.3deg$

Earbud Speaker: @1kHz
 $L_s = 25.2uH$
 $L_p = 311.0mH$
 $C_s = 1.0mF$
 $C_p = 81.95nF$
 $R_s = 17.0300\Omega$
 $R_p = 17.0340\Omega$
 $\theta = 0.5deg$

Audio

Purism

Copyright 2018 GNU GPLv3

Sheet: /Audio/
 File: audio.sch

Size: A4 Date: 2018-06-18

KiCad E.D.A. kicad 4.0.7

eric.kuzmenko@puri.sm


angus.ainslie@puri.sm

nicole.farber@puri.sm


christian.schilmoeller@puri.sm

Rev: v0.1.0


Id: 16/24




Built-In Speaker's Frequency Response:



Built-In Mic's Frequency Response:



Simulation of HP_DET @ 1kHz output without HP jack inserted:



RGMII 10/100/1000 Ethernet

Eric Kuzmenko
Angus Ainslie
Nicole Faerber
Christian Schilmoeller

Copyright 2018 GNU GPLv3

Sheet: /Ethernet/
File: ethernet.sch


Size: A4 Date: 2018-06-18 Rev: v0.1.0
KiCad E.D.A. kicad 4.0.7 Id: 17/24

 **Purism**

eric.kuzmenko@puri.sm
angus.ainslie@puri.sm
nicole.farber@puri.sm
christian.schilmoeller@puri.sm


Rev: v0.1.0
Id: 17/24

WLAN+BT M.2




RS9116 NC:
RTS, CTS, BT_HOST_WAKE

RS9116 datasheet says
no WIFI_WAKE
but the schematic has it





6.2 M.2 Signal Directions



TX output
RX input
CTS output
RTS input
⇒ TX→RX
RX→TX
CTS→CTS
RTS→RTS

Note:
All switches' pins
can be swapped
e.g. 2<->3
or 1<->3



WLAN+BT M.2



Copyright 2018 GNU GPLv3

Sheet: /WLAN+BT M.2/
File: wifi_bt_m2.sch

Size: A4 Date: 2018-06-18
KiCad E.D.A. kicad 4.0.7



eric.kuzmenko@puri.sm
angus.ainslie@puri.sm
nicole.faerber@puri.sm
christian.schilmoeller@puri.sm

Rev: v0.1.0
Id: 18/24

TUSB1046 can be used for DP over USB-C

HDMI

Layout Note:
May need swap some signals
due to micro-HDMI pinout diff
depending on pin location/routing



HDMI



Copyright 2018 GNU GPLv3

Sheet: /HDMI/
File: hdmi.sch

Size: A4
KiCad E.D.A. kicad 4.0.7

Date: 2018-06-18

eric.kuzmenko@puri.sm

angus.ainstie@puri.sm

nicole.farber@puri.sm

christian.schilmoeller@puri.sm

Rev: v0.1.0

Id: 19/24

1

B



C

D

1




1



Id: 20/24

SPI NOR Flash



SPI NOR Flash



Copyright 2018 GNU GPLv3

Sheet: /SPI Flash/
File: flash.sch

Size: A4 Date: 2018-06-18

KiCad E.D.A. kicad 4.0.7

eric.kuzmenko@puri.sm

angus.ainstlie@puri.sm


nicole.farber@puri.sm

christian.schilmoeller@puri.sm

Rev: v0.1.0

Id: 21/24

Smart Card



Reference:
<http://www.microchip.com/DevelopmentTools/ProductDetails.aspx?PartNO=EVB-SEC1110>

Smart Card



Copyright 2018 GNU GPLv3

Sheet: /Smart Card/

File: smartcard.sch

Size: A4 Date: 2018-06-18

KiCad E.D.A. kicad 4.0.7

eric.kuzmenko@puri.sm

angus.ainstlie@puri.sm

nicole.farber@puri.sm

christian.schilmoeller@puri.sm

Rev: v0.1.0

Id: 22/24

GNSS



References:

https://www.u-blox.com/sites/default/files/MAX-M8_HardwareIntegrationManual_L%28UBX-13004876%29.pdf
https://www.u-blox.com/sites/default/files/MAX-8-M8-FW3_HardwareIntegrationManual_L%28UBX-15030059%29.pdf

GNSS



Copyright 2018 GNU GPLv3

Sheet: /GNSS/

File: gnss.sch

Size: A4

Date: 2018-06-18

KiCad E.D.A. kicad 4.0.7

Rev: v0.1.0

Id: 23/24

eric.kuzmenko@puri.sm

angus.ainstlie@puri.sm


nicole.farber@puri.sm

christian.schilmoeller@puri.sm

Haptic Motor

PWM pins occupied:
 GPIO1_I001 - LCD Backlight
 GPIO1_I013 - LED
 GPIO1_I014 - Ethernet (CLK0_25MHz)
 GPIO1_I015 - CSI (CLK02)

PWM needed?
 Only needs to be toggled
 ON 1 sec, OFF 1 sec (0.5Hz)
 Can MUX as either
 GPIO or PWM2
 swapping with LED



When the motor is off
 both terminals are at GND

Motor will have wire leads
 with a 2-pin Molex or Boom Precision
 connector installed (by request)!
 Metal housing is floating
 (not connected to either pin)
 => could connect housing to GND

Cheaper Motor Connector:
https://lcsc.com/product-detail/1-25T-Connectors_1-25T-1-2AW_C10832.html

Motor Source:
https://www.alibaba.com/product-detail/Coin-motor-vibration-dc-motor-cellphone_1994583657.html?spm=a2700.8443308.0.0.5aa13e5f1wxHgs

Motor Datasheet:
<https://cloud.puri.sm/s/z8JR6DJ4KrJYzoW>

Motor PN:
 BY0820Z021L20

Haptic/Vibration Motor



Copyright 2018 GNU GPLv3

Sheet: /Haptic Motor/
 File: haptic.sch

Size: A4 Date: 2018-06-18

KiCad E.D.A. kicad 4.0.7

eric.kuzmenko@puri.sm

angus.ainstlie@puri.sm

nicole.farber@puri.sm

christian.schilmoeller@puri.sm

Rev: v0.1.0

Id: 24/24