USB-C
VBUS
USB1_VBUS
USB1_ID
USB1_SS_SEL
USB1_DP
USB1_DN
USB1_TXP
USB1_TXN
USB1_RXP
USB1_RXN
TCPC_INT
I2C1_SDA
I2C1_SCL
EN_SNK
EN_SRC
usb-c.sch

Battery
VBUS
battery.sch

VBAT_REG
I2C1_SDA
I2C1_SCL
CHRG_INT
EN_SRC
EN_SNK
ONOFF

Power
VBAT_REG
5V_SOM
5V_P
3V3
3V3_P
1V8_P
PWR_EN
power.sch

Spare GPIO:
GPIO5_IO03 (was PWM3)
GPIO3_IO25

GPIO that can be swapped around:
GPIO1_IO12 (was IR_CAP)
GPIO3_IO20
GPIO3_IO25
GPIO3_IO19 (was LED1)
GPIO5_IO05 (was PWM1)
GPIO5_IO03 (was PWM3)

Boot Config
BOOT_CFG00 SAI1_RXD0(GPIO4_IO02)
BOOT_CFG01 SAI1_RXD1(GPIO4_IO03)
BOOT_CFG02 SAI1_RXD2(GPIO4_IO04)
BOOT_CFG03 SAI1_RXD3(GPIO4_IO05)
BOOT_CFG04 SAI1_RXD4(GPIO4_IO06)
BOOT_CFG05 SAI1_RXD5(GPIO4_IO07)
BOOT_CFG06 SAI1_RXD6(GPIO4_IO08)
BOOT_CFG07 SAI1_RXD7(GPIO4_IO09)
BOOT_CFG08 SAI1_TXD0(GPIO4_IO12)
BOOT_CFG09 SAI1_TXD1(GPIO4_IO13)
BOOT_CFG10 SAI1_TXD2(GPIO4_IO14)
BOOT_CFG11 SAI1_TXD3(GPIO4_IO15)
BOOT_CFG12 SAI1_TXD4(GPIO4_IO16)
BOOT_CFG13 SAI1_TXD5(GPIO4_IO17)
BOOT_CFG14 SAI1_TXD6(GPIO4_IO18)
BOOT_CFG15 SAI1_TXD7(GPIO4_IO19)
BOOT_MODE0
BOOT_MODE1
boot.sch

Alternate Functions:
CAPTOUCH_RST
SW_BACK
SAI6_TXD0
SAI6_TXFS/RXFS
SW_HOME
SAI6_TXC/RXC
SAI6_RXD0

RTC
I2C1_SDA
I2C1_SCL
rtc.sch

UART Debug
UART1_TXD
UART1_RXD
uart.sch

JTAG
JTAG_TMS
JTAG_TCK
JTAG_TDO
JTAG_TDI
POR_B
JTAG_TRST
jtag.sch

uSD Card
CONN_SD2_DATA1 uSD_DATA1
CONN_SD2_DATA0 uSD_DATA0
CONN_SD2_CMD uSD_CMD
CONN_SD2_DATA3 uSD_DATA3
CONN_SD2_DATA2 uSD_DATA2
CONN_SD2_CLK uSD_CLK
CONN_SD2_CD_B uSD_CD
sd.sch

MIPI
DSI_DP0
DSI_DN0
DSI_DP1
DSI_DN1
DSI_DP2
DSI_DN2
DSI_DP3
DSI_DN3
DSI_CKP
DSI_CKN
DSI_BL_PWM
CAPTOUCH_INT
CAPTOUCH_RST SAI1_RXD3(GPIO4_IO05)
CSI_P1_DP0
CSI_P1_DN0
CSI_P1_DP1
CSI_P1_DN1
CSI_P1_DP2
CSI_P1_DN2
CSI_P1_DP3
CSI_P1_DN3
CSI_P1_CKP
CSI_P1_CKN
I2C1_SDA
I2C1_SCL
mipi.sch

Buttons & LED
SW_BACK SAI1_RXD4(GPIO4_IO06)
SW_VOLDN BTN1
SW_VOLUP BTN2
SW_HOME SAI1_TXD1(GPIO4_IO13)
ONOFF
SYS_RST
GP_LED1 GPIO1_IO13
buttons_led.sch

WWAN M.2
WoWWAN GPIO3_IO08
W_DISABLE1 WWAN_DISABLE GPIO3_IO04
RESET GPIO3_IO09
UART_TX/LED UART3_RXD
UART_RX/DPR UART3_TXD
USB_D+ USB_WWAN_DP
USB_D- USB_WWAN_DM
PCM_CLK/I2S_SCK SAI1_TXD4(GPIO4_IO16) SAI6_TXC/RXC
PCM_SYNC/I2S_FSC SAI1_RXD6(GPIO4_IO08) SAI6_TXFS/RXFS
PCM_IN/I2S_IN SAI1_RXD5(GPIO4_IO07) SAI6_TXD0
PCM_OUT/I2S_OUT SAI1_TXD5(GPIO4_IO17) SAI6_RXD0
wwan_m2.sch

Audio
HP_DET GPIO3_IO20
MIC_SEL GPIO5_IO05 (was PWM1)
SAI2_RXD
SAI2_TXD
SAI2_TXFS
SAI2_TXC
SAI2_MCLK
I2C1_SDA
I2C1_SCL
audio.sch

WLAN+BT M.2
USB_WLAN_DP
USB_WLAN_DM
UART4_TXD
UART4_RXD
UART4_RTS
UART4_CTS
BT_HOST_WAKE
WIFI_DISABLE
BT_DISABLE
WIFI_CLK
WIFI_CMD
WIFI_DATA0
WIFI_DATA1
WIFI_DATA2
WIFI_DATA3
SD2_RST
WIFI_WAKE
I2C2_SDA
I2C2_SCL
SAI5_TX_BCLK
SAI5_TX_SYNC
SAI5_RXD
SAI5_TXD
wifi_bt_m2.sch

USB Hub + SDIO Bridge
USB2_DP
USB2_DN
USB2_ID
USB_WWAN_DP
USB_WWAN_DM
USB_WLAN_DP
USB_WLAN_DM
SMARTCARD_DP
SMARTCARD_DM
SDCD
uSD_CLK
uSD_CMD
uSD_DATA0
uSD_DATA1
uSD_DATA2
uSD_DATA3
SD2_RST
SRST
usb_hub_sdio.sch

Ethernet
ENET_2V5
CLKO_25MHz
ENET_TXC
ENET_TD0
ENET_TD1
ENET_TD2
ENET_TD3
ENET_TX_CTL
ENET_RXC
ENET_RD0
ENET_RD1
ENET_RD2
ENET_RD3
ENET_RX_CTL
ENET_MDC
ENET_MDIO
ENET_RST
ENET_WoL
ENET_INT
ethernet.sch

HDMI
HDMI_AUXP
HDMI_AUXN
HDMI_CLKP
HDMI_CLKN
HDMI_TXP0
HDMI_TXN0
HDMI_TXP1
HDMI_TXN1
HDMI_TXP2
HDMI_TXN2
HDMI_DDC_SDA
HDMI_DDC_SCL
HDMI_CEC
HDMI_HPD
hdmi.sch

Sensors
I2C1_SDA
I2C1_SCL
PROX_INT GPIO1_IO12 (was IR_CAP)
IMU_INT GPIO3_IO19 (was LED1)
sensors.sch

SPI Flash
SCLK ECSPI1_SCLK
MOSI ECSPI1_MOSI
MISO ECSPI1_MISO
CS ECSPI1_SS0
flash.sch

Haptic Motor
HAPTIC GPIO5_IO04 (was PWM2)
haptic.sch

TODO:
GNSS
MIPI CSI/DSI
Smartcard

J101A
ENET_TXC
ENET_TD0
ENET_TD1
ENET_TD2
ENET_TD3
ENET_TX_CTL
ENET_RD0
ENET_RD1
ENET_RD2
ENET_RD3
CSI_P1_DP3
CSI_P1_DN3
ENET_RX_CTL
ENET_RXC
CSI_P1_DP1
CSI_P1_DN1
ENET_MDIO
ENET_MDC
DSI_P1_DP2
CSI_P1_DN2
SD2_RST
WIFI_DATA3
WIFI_DATA2
WIFI_DATA1
CSI_P1_DP0
CSI_P1_DN0
WIFI_DATA0
WIFI_WAKE
CSI_P1_CKP
CSI_P1_CKN
WIFI_CMD
uSD_CD_B
WIFI_CLK
TCPC_INT
WWAN_DISABLE
USB1_SS_SEL
BT_HOST_WAKE
CAPTOUCH_INT
IMX8M-SOM
GND GND

J101B
WIFI_DISABLE
GPIO3_IO09
GPIO3_IO08
PWR_FLAG 3V3_OUT
ENET_2V5
PWR_FLAG NVCC_SD2
DSI_DP2
DSI_DN2
DSI_DP0
DSI_DN0
DSI_CKN
DSI_CKP
DSI_DP1
DSI_DN1
DSI_DP3
DSI_DN3
5V_SOM
C101 22uF
C102 22uF
C103 100nF
C104 100nF
C105 22uF
C106 22uF
IMX8M-SOM
GND GND

J101C
HDMI_CEC
BOOT_MODE0
BOOT_MODE1
JTAG_TDI
JTAG_TMS
JTAG_TRST
JTAG_TDO
JTAG_TCK
HDMI_HPD
HDMI_AUXN
HDMI_AUXP
HDMI_TXP1
HDMI_TXN1
HDMI_TXP0
HDMI_TXN0
J102 TEST_1P
DSI_BL_PWM
WDG
HDMI_DDC_SCL
HDMI_DDC_SDA
HDMI_CLKP
HDMI_CLKN
HDMI_TXP2
HDMI_TXN2
IMU_INT
SAI5_TX_BCLK
PWR_EN
SAI5_RXD
ENET_RST
ENET_WoL
SAI1_RXD1(GPIO4_IO03)
SAI5_TX_SYNC
ENET_INT
HP_DET
PROX_INT
SAI1_RXD0(GPIO4_IO02)
SAI5_TXD
CLKO_25MHz
GPIO1_IO13
SAI1_RXD4(GPIO4_IO06)
SAI2_TXC
SAI1_RXD3(GPIO4_IO05)
BTN1
BTN2
SAI1_RXD2(GPIO4_IO04)
SAI2_TXFS
SAI2_RXD
SAI2_MCLK
IMX8M-SOM
GND GND

J101D
3V3_OUT
R106 10k
SAI2_TXD
SAI1_RXD7(GPIO4_IO09)
I2C2_SCL
HAPTIC
SAI1_RXD5(GPIO4_IO07)
R101 10k
R102 10k
R105 10k
SAI1_TXD0(GPIO4_IO12)
ONOFF
I2C2_SDA
MIC_SEL
SAI1_TXD1(GPIO4_IO13)
SYS_RST
UART4_TXD
I2C1_SCL
I2C1_SDA
ECSPI1_SCLK
SAI1_TXD3(GPIO4_IO15)
SAI1_TXD4(GPIO4_IO16)
ECSPI1_SS0
SAI1_TXD7(GPIO4_IO19)
UART3_TXD
BT_DISABLE
SAI1_TXD5(GPIO4_IO17)
POR_B
UART4_RXD
UART1_RXD
SAI1_TXD2(GPIO4_IO14)
SAI1_TXD6(GPIO4_IO18)
ECSPI1_MISO
UART4_CTS
UART3_RXD
USB2_DN
USB2_DP
5V_P
R103 10k
R104 19.6k
ECSPI1_MOSI
UART4_RTS
UART1_TXD
USB2_VBUS
USB2_ID
USB1_VBUS
USB1_ID
USB1_RXN
USB1_RXP
USB1_TXN
USB1_TXP
USB1_DN
USB1_DP
IMX8M-SOM
GND GND

Purism SPC

Sheet: /	
File: dvk-mx8m-bsb.sch	
Title: DVK-MX8M-BSB	
Size: A2	Date: 2018-05-18
KiCad E.D.A. kicad 4.0.7	Rev: v0.1.0 Id: 1/22

USB-C Config Channel (CC) and PD Role Controller



Sheet: /USB-C/		
File: usb-c.sch		
Title: USB Type C		
Size: A4	Date: 2018-05-18	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 2/22

Battery Charge Controller



(interpret RSOC% based on this plot)

use AUTO_DPDM_EN
to auto-detect IINLIM

1.658≤ILIM≤2.063
ILIM(nom)≅1.859
3.9≤VIN≤14

U301 BQ25896

I(Lsat)=7A

Ihold=3.5A
Itrip=6.3A
Ttrip(max)=5s@8A

NCR18650B is recommended

VBAT(nom)=REG06[7:2]
VBAT(default_max_ovp)=(REG06[7:2]×1.005)×1.04=4.3982016V
REG06[7:2]=010111⇒VBAT(max_ovp)=4.3814784
BQ29705 provides 4.425V as OVP!!!

reference design: http://www.ti.com/lit/ug/sluuba2b/sluuba2b.pdf

may want to include BQ29705 protection as in:
http://www.ti.com/lit/ug/tiducl1/tiducl1.pdf
schematic: http://www.ti.com/lit/df/tidrp70/tidrp70.pdf
(PTC may be good enough)

TODO:
Keystone 1042 footprint???

Default LOW:
adapter source

Open-drain output
tied with TCPC_INT

If enough I/O is available then
separate CHRG_INT & TCPC_INT

This disables charging
but maybe not VBUS->VOUT
if PTN5110HQ's FAULT_STATUS[6]==1
(Force Off VBUS bit) then set EN_HiZ=1
EN_HiZ may be auto-set when in hiccup

Reading PTN5110HQ's CC_STATUS and POWER_STATUS
registers will tell TCPM (i.MX8M) when to set EN_HiZ

Also, reading PTN5110HQ's CC_STATUS and POWER_STATUS
registers will tell TCPM (i.MX8M) when to set OTG_CONFIG=1
(this will also happen when PTN5110HQ sets EN_SRC HIGH)

BC1.2 is not mandated by PD spec
ICO used to determine max current
Also negotiated from CC pins (I2C)

VBAT(DPL)=2.15~2.5V

Battery holder gives ~1mm clearance underneath the battery
Thermistor is 1.1±0.15mm thick, should fit fine with stack-up

Battery holder seems to fit up to ~68.88mm long batteries
need to test 18650 protected cells which are ~69.35mm long

Sheet: /Battery/		
File: battery.sch		
Title: Battery		
Size: A4	Date: 2018-05-18	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 3/22







TODO:
add parallel 100nF bulk caps!
& spread all over the power plane

Sheet: /Power/
File: power.sch

Title: Power

Size: A4	Date: 2018-05-18	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 4/22

BOOT_CFG[14:12]	Boot device
001	SD/eSD
010	MMC/eMMC
011	NAND

Fuse	Config	Definition	GPIO[1]	Shipped value	Settings
BOOT_CFG[11:10]	OEM	USDHC port selection	Yes	00	00 - USDHC-1 01 - USDHC-2 10 - USDHC-3 else - reserved



BOOT_MODE[1:0]	Boot Type
00	Boot From Fuses
01	Serial Downloader
10	Internal Boot
11	Reserved

Sheet: /Boot Config/
File: boot.sch

Title: Boot Configuration

Size: A4	Date: 2018–05–18	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 5/22



Sheet: /RTC/
File: rtc.sch

Title: RTC

Size: A4	Date: 2018-05-18	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 6/22



Sheet: /UART Debug/
File: uart.sch

Title: UART Debug

Size: A4	Date: 2018-05-18	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 7/22



Sheet: /JTAG/
File: jtag.sch

Title: JTAG

Size: A4	Date: 2018-05-18	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 8/22



GNU GPLv3
Copyright 2018
Purism SPC

Sheet: /USB Hub + SDIO Bridge/
File: usb_hub_sdio.sch

Title:

Size: A4	Date: 2018-05-18	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 9/22



Sheet: /uSD Card/
File: sd.sch

Title: uSD Card

Size: A4	Date: 2018-05-18	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 10/22





Sheet: /MIPI/ File: mipi.sch		
Title:		
Size: A4	Date:	**Rev:**
KiCad E.D.A. kicad 4.0.7		Id: 11/22

TODO:
ensure power sequence is satisfied
based on the display used



called "C_1V8_S1" in the
"plink20170817" schematic

Reset input timing

RESX Puise	Action
Shorter than 5µs	Invalid Reset
Longer than 10µs	Valid Reset
Between 5µs and 10µs	Reset Initialization Precedure

TODO: low power state signal??

Sheet: /MIPI/DSI/
File: dsi.sch

Title: MIPI DSI

Size: A4	Date: 2018-05-18	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 12/22

C0_P
C0_N
C1_P
C1_N
C2_P
C2_N
C3_P
C3_N
CLK_P
CLK_N

I2C1_SDA_1V8
I2C1_SCL_1V8

Sheet: /MIPI/CSI/
File: csi.sch

Title:

Size: A4	Date:	**Rev:**
KiCad E.D.A. kicad 4.0.7		Id: 13/22



Use PWM2_PWMSAR to set the compare value (duty cycle)
Use PWM2_PWMCR[15:4] to set the PRESCALER (frequency)
Use PWM2_PWMPR to set the top of the counter (frequency)



Sheet: /Buttons & LED/
File: buttons_led.sch

Title: Buttons & LED

Size: A4	Date: 2018-05-18	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 14/22



	Pin	Port Config_0[1]	Port Config_1[2]	Port Config_2[3]	Port Config_3[4]
GPIO_0	40	GNSS_SCL	GNSS_SCL	SIM_DET2	HSIC_Data
GPIO_1	42	GNSS_SDA	GNSS_SDA	UIM_DTA2	HSIC_Strobe
GPIO_2	44	GNSS_IRQ	GNSS_IRQ	UIM_CLK2	IPC_0
GPIO_3	46	SYSCLK	GNSS_0	UIM_RST2	IPC_1
GPIO_4	48	TX_BLANKING	GNSS_1	UIM_PWR2	IPC_2
GPIO_5	20	AUDIO_0	AUDIO_0	RFU	Audio_0
GPIO_6	22	AUDIO_1	AUDIO_1	RFU	Audio_1
GPIO_7	24	AUDIO_2	AUDIO_2	RFU	IPC_3/Audio_2
GPIO_8	28	AUDIO_3	AUDIO_3	RFU	IPC_4/Audio_3
GPIO_9	10	LED#1	LED#1	LED#1	IPC_5
GPIO_10	26	W_Disable2#	W_Disable2#	W_Disable2#	IPC_6
GPIO_11	23	Wake_On_WWAN	Wake_On_WWAN	Wake_On_WWAN	IPC_7
GPIO_12	25	DPR	DPR	DPR	IPC_8

Module Configuration Decodes						State
CONFIG_0 (Pin 21)	CONFIG_1 (Pin 69)	CONFIG_2 (Pin 75	CONFIG_3 (Pin 1)	Module Type and Main Host Interface[1]	Port Configuration[2]	
GND	GND	GND	GND	SSD – SATA	N/A	
GND	NC	GND	GND	SSD – PCIe	N/A	
GND	GND	NC	GND	WWAN – PCIe	0	0
GND	NC	NC	GND	WWAN – PCIe	1	1
GND	GND	GND	NC	WWAN – USB 3.0	0	2
GND	NC	GND	NC	WWAN – USB 3.0	1	3
GND	GND	NC	NC	WWAN – USB 3.0	2	4
GND	NC	NC	NC	WWAN – USB 3.0	3	5
NC	GND	GND	GND	WWAN – SSIC	0	6
NC	NC	GND	GND	WWAN – SSIC	1	7
NC	GND	NC	GND	WWAN – SSIC	2	8
NC	NC	NC	GND	WWAN – SSIC	3	9
NC	GND	GND	NC	WWAN – PCIe	2	10
NC	NC	GND	NC	WWAN – PCIe	3	11
NC	GND	NC	NC	RFU	N/A	12
NC	NC	NC	NC	No Module Present	N/A	13
						14
						15

Sheet: /WWAN M.2/
File: wwan_m2.sch

Title: WWAN M.2

Size: A4	Date: 2018-05-18	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 15/22

Reference:
http://www.52rd.com/S_txt/2011_3/TXT26685.htm
http://www.sengpielaudio.com/calculator-transferfactor.htm
https://electronics.stackexchange.com/questions/31442/how-can-i-switch-this-audio-jack-using-its-own-mechanical-switches-without-cre
(Nit6 does the same)
+Zener diode to protect against ranges outside of −0.9V to 3.3V

dB specs in datasheet is a unit of power gain (not dBu or VU)
with respect to the DAC's unattenuated output

"HP Output – 62.5mW max, 1.02kHz sine into 16Ω load at 3.3 V"
⇒ $(1V)^2/(16Ω)=62.5mW$
∴ Vrms=1V ⇒ Vp(amplitude)=1.414V
∴ Irms(max)=62.5mA

If HP_DET is HIGH for >100ms then HPs are present

S/E button on earbud headsets
shorts the mic for key function

Could use FSA8008 to detect mic

U1501 SGTL5000

Mute via MUTE_LO=1

may use lineout left channel for pseudo-earpiece speaker

U1502 PAM8301

DLW21SN900SQ2L

LS1501 AS01608MS-SP9

fc=106Hz

FL1501

FL1502

Z(hp)≥16Ω

<3.3µA

CTIA/AHJ

Microphone
Ground
Audio (Right)
Audio (Left)

J1501

SMD Equivalent: SJ-43515RS-SMT-TR

SJ-43515TS

Pin 5 (tip switch) is NC, open when inserted

If just headphones then HP_DET=HIGH, R(mic)=0

D1501 ESD5B5.0S

D1502 ESD5B5.0S

D1503 SZMM5Z3V3T1G

Vz=3.3V
Vf=0.9V

may add ~220uF cap parallel to Zener

U1503 FSA6157L6X

Ext-Mic enabled
MIC_SEL=LOW

Int-Mic enabled
MIC_SEL=LOW

SW Mute Mic:
MUTE_ADC=1

SW1501A SW_DPST_x2

TODO:
DPST with camera!

MK1501 CMC-6022

Add TVS next to int-mic?
(OpenMoko does this)

−37dB=14.1254mV/Pa
∴ mic produces 14.1254mVrms when exposed to a 1kHz tone of 94dB-SPL at the capsule (or 19.98mV amplitude)

⇒ 40dB gain would produce ~2V amplitude (4Vpp, clipping)
30dB gain would produce ~0.632V amplitude (1.264Vpp)
38.33dB gain would yield 3.3Vpp

Built-In Speaker's Frequency Response:



Built-In Mic's Frequency Response:



Simulation of HP_DET @ 1kHz output without HP jack inserted:



LCR Measurements:

Earbud Microphone: @1kHz	Headset Speaker: @1kHz	Earbud Speaker: @1kHz
Ls = 3.844mH	Ls = 244.4uH	Ls = 25.2uH
Lp = 15.757H	Lp = 141.99mH	Lp = 311.0mH
Cs = 6.583uF	Cs = 103.6uF	Cs = 1.0mF
Cp = 1612.8pF	Cp = 178.77nF	Cp = 81.95nF
Rs = 1.5465kOhms	Rs = 36.860hms	Rs = 17.0300hms
Rp = 1.5478kOhms	Rp = 36.860hms	Rp = 17.0340hms
θ = −0.8deg	θ = −2.3deg	θ = 0.5deg

Purism SPC

Sheet: /Audio/
File: audio.sch

Title: Audio

Size: A4	Date: 2018-05-18	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 16/22

RGMII 10/100/1000 Ethernet



Sheet: /Ethernet/		
File: ethernet.sch		
Title: Ethernet		
Size: A4	Date: 2018-05-18	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 17/22

Module: Table 23
Socket: Table 46

RS9116 NC:
RTS, CTS, BT_HOST_WAKE

RS9116 datasheet says
no WIFI_WAKE
but the schematic has it

RedPine RS9116 MB0
Requires 5V on
Pin 54 for USB!

3V3_P
R1702 NC
JP1701
NC

J1701 M.2_Key_E

USB_WLAN_DP
USB_WLAN_DN
WIFI_CLK
WIFI_CMD
WIFI_DATA0
WIFI_DATA1
WIFI_DATA2
WIFI_DATA3
WIFI_WAKE

M2_PCM_CLK
M2_PCM_SYNC
M2_PCM_IN
M2_PCM_OUT
SoC's IN/OUT

BT_HOST_WAKE
BT_UART_RXD
SoC's RX
Module's TX
SoC's TX
Module's RX
BT_UART_TXD
BT_UART_RTS
BT_UART_CTS

i.MX8M in DCE mode (POR state)
has CTS output, RTS input

1V8_P
R1701 100k
D1701 DB2J209
WIFI_RST
VIH=2.31V
W_DISABLE1
D1702 DB2J209

RedPine RS9116
has 100k pull-up to
3.3V making SDIO_RST
~2.55V when HIGH

RS9116 SUSCLK
is a GPIO (unused)
SUSCLK
W_DISABLE2
W_DISABLE1
M2_I2C_SDA
M2_I2C_SCL

6.2 M.2 Signal Directions

UARTn_UFCR[DCEDTE]=0 on POR



TX output
RX input
CTS output
RTS input

⇒TX→RX
RX←TX
CTS→CTS
RTS←RTS

Note:
Dual 2-input AND much more
available and cheaper than NOR

TODO:
Pin 54 on RS9116 is USB_VBUS Sink!!!

U1703A 74AUP2G08
U1703B 74AUP2G08
R1703 10k
BT_DISABLE
WIFI_DISABLE
D1703 DB2J209
R1705 100k
R1707 100k
C1709 10nF
SW1701 WWAN_HKS
Open = ON
Closed = OFF

RS9116 is an I2C master
⇒its SCL is an output
(ok bc only device on I2C2)

R1704 10k
M2_I2C_SDA
I2C2_SDA
Q1701 FDV301N

R1706 10k
M2_I2C_SCL
I2C2_SCL
Q1702 FDV301N

U1701 NTB0104GU12
C1701 C1702 1uF 10nF
C1703 C1704 10nF 1uF

BT_UART_RXD
BT_UART_TXD
BT_UART_RTS
BT_UART_CTS

RX, TX, RTS, CTS
of the SoC

internal 10k pull-up

U1702 NTB0104GU12
C1705 C1706 1uF 10nF
C1707 C1708 10nF 1uF

BCLK
M2_PCM_CLK
M2_PCM_SYNC
M2_PCM_IN
M2_PCM_OUT

BT_PCM_CLK
BT_PCM_SYNC
BT_PCM_IN
BT_PCM_OUT

configure as slave

IN, OUT
of the SoC

Sheet: /WLAN+BT M.2/
File: wifi_bt_m2.sch

Title: WLAN+BT M.2

Size: A4	Date: 2018-05-18	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 18/22

HD3SS460 can be used for DP over USB-C

Layout Note:
May need swap some signals
due to micro-HDMI pinout diff
depending on pin location/routing

100Ω diff pairs





Sheet: /HDMI/
File: hdmi.sch

Title: HDMI

Size: A4	Date: 2018-05-18	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 19/22

Proximity & Ambient Light



Reference:
http://www.rohm.com/web/global/sensor-shield-support/ps-als-sensor

9-Axis IMU



Reference:
https://store.invensense.com/datasheets/invensense/AN-IVS-0001EVB-00%20v1%202.pdf

AD0 sets the slave address's LSB (110100X)

INT1_ACTL sets if IMU_INT
is active-high or active-low

"FSYNC - Connect to GND if unused"

I2C's VIH=1.8V







Figure 12. Orientation of Axes of Sensitivity and Polarity of Rotation



Figure 13. Orientation of Axes of Sensitivity for Magnetometer

Sheet: /Sensors/
File: sensors.sch

Title: Sensors

Size: A4	Date: 2018-05-18	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 20/22



Sheet: /SPI Flash/
File: flash.sch

Title: SPI NOR Flash

Size: A4	Date: 2018-05-18	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 21/22

PWM pins occupied:
GPIO1_IO01 – DSI (DSI_BL_PWM??)
GPIO1_IO13 – LED
GPIO1_IO14 – Ethernet (CLKO_25MHz)
GPIO1_IO15 – CSI (CLKO2)

PWM needed?
Only needs to be toggled
ON 1 sec, OFF 1 sec (0.5Hz)

Can MUX as either
GPIO or PWM2
swapping with LED



When the motor is off
both terminals are at GND

Motor will have wire leads
with a 2-pin Molex or JST
connector installed (by request)!

Cap will reduce dV/dt
effectively less EMI

Motor Connector:
https://lcsc.com/product-detail/1-25T-Connectors_1-25T-1-2AW_C10832.html

Alibaba Alternative Motor:
https://www.alibaba.com/product-detail/Coin-motor-vibration-dc-motor
cellphone_1994583657.html?spm=a2700.8443308.0.0.5aa13e5f1wxHgs

Sheet: /Haptic Motor/
File: haptic.sch

Title: Haptic/Vibration Motor

Size: A4	Date: 2018-05-18	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 22/22