

GNU GPLv3
Copyright 2018
Purism SPC

Sheet: /
File: dvk-mx8m-bsb.sch

Title: DVK-MX8M-BSB

Size: A2	Date: 2018-05-02	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 1/17

"Under dead battery operation, PTN5110 applies voltage clamps to both CC pins so that the system may receive power as a Sink. To support platforms with buck-boost configuration, PTN5110 asserts EN_SNK1 pin based on validity of VBUS voltage (facilitates 5 V VBUS sinking)."

USB-C Config Channel (CC) and PD Role Controller







Sheet: /USB-C/		
File: usb-c.sch		
Title: USB Type C		
Size: A3	Date: 2018-05-02	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 2/17

Battery Charge Controller



(interpret RSOC% based on this plot)

use AUTO_DPDM_EN
to auto-detect IINLIM

1.658≤ILIM≤2.063
ILIM(nom)≅1.859
3.9≤VIN≤14

U301 BQ25896

I(Lsat)=7A

3.5~4.25V

Default LOW:
adapter source

Open-drain output
tied with TCPC_INT

If enough I/O is available then
separate CHRG_INT & TCPC_INT

This disables charging
but maybe not VBUS->VOUT
if PTN5110HQ's FAULT_STATUS[6]==1
(Force Off VBUS bit) then set EN_HiZ=1
EN_HiZ may be auto-set when in hiccup

Reading PTN5110HQ's CC_STATUS and POWER_STATUS
registers will tell TCPM (i.MX8M) when to set EN_HiZ

Also, reading PTN5110HQ's CC_STATUS and POWER_STATUS
registers will tell TCPM (i.MX8M) when to set OTG_CONFIG=1
(this will also happen when PTN5110HQ sets EN_SRC HIGH)

BC1.2 is not mandated by PD spec
ICO used to determine max current
Also negotiated from CC pins (I2C)

Ihold=3.5A
Itrip=6.3A
Ttrip(max)=5s@8A

VBAT(DPL)=2.15~2.5V

NCR18650BD is recommended

VBAT(nom)=REG06[7:2]
VBAT(default_max_ovp)=(REG06[7:2]×1.005)×1.04=4.3982016V
REG06[7:2]=010111⇒VBAT(max_ovp)=4.3814784
BQ29705 provides 4.425V as OVP!!!

reference design: http://www.ti.com/lit/ug/sluuba2b/sluuba2b.pdf

may want to include BQ29705 protection as in:
http://www.ti.com/lit/ug/tiducl1/tiducl1.pdf
schematic: http://www.ti.com/lit/df/tidrp70/tidrp70.pdf
(PTC may be good enough)

Sheet: /Battery/		
File: battery.sch		
Title: Battery		
Size: A4	Date: 2018-05-02	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 3/17

5.0V/3.8A



Cheaper, more efficient, smaller, and simpler than RT6150A
Explicitly mentions USB/smartphone application

3.3V/3A

When VBAT can fall below
3.3V use TPS63020 instead!



AMOLED POWER



1.8V/600mA



SW4A of PF4210 is 1.8V
but SoM doesn't bring it out

V_IH(typ)=1.0V≅30.3%×3.3V
t(0-30.3%)≈0.361RC
⇒0.361RC≈10ms
∴ R=10k
C=2.77uF≅3.3uF

Buck instead of TLV70218 LDO
saving up to ~100mW loss
LM3670MF-1.8 is much more expensive
ST1S12G18R is a drop-in

SD POWER



Sheet: /Power/		
File: power.sch		
Title: Power		
Size: A4	Date: 2018-05-02	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 4/17

BOOT_CFG[14:12]	Boot device
001	SD/eSD
010	MMC/eMMC
011	NAND

Fuse	Config	Definition	GPIO[1]	Shipped value	Settings
BOOT_CFG[11:10]	OEM	USDHC port selection	Yes	00	00 - USDHC-1 01 - USDHC-2 10 - USDHC-3 else - reserved



BOOT_MODE[1:0]	Boot Type
00	Boot From Fuses
01	Serial Downloader
10	Internal Boot
11	Reserved

Sheet: /Boot Config/
File: boot.sch

Title: Boot Configuration

Size: A4	Date: 2018–05–02	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 5/17



Sheet: /RTC/
File: rtc.sch

Title: RTC

Size: A4	Date: 2018-05-02	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 6/17



GNU GPLv3
Copyright 2018
Purism SPC

Sheet: /UART Debug/
File: uart.sch

Title: UART Debug

Size: A4	Date: 2018-05-02	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 7/17



Sheet: /JTAG/
File: jtag.sch

Title: JTAG

Size: A4	Date: 2018-05-02	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 8/17





Sheet: /uSD Card/
File: sd.sch

Title: uSD Card

Size: A4	Date: 2018-05-02	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 9/17



Sheet: /USB Hub/		
File: usb_hub.sch		
Title:		
Size: A4	Date: 2018-05-02	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 10/17

Using H546DLB01.1 pin assignment may need
to be changed depending on display used



called "C_1V8_S1" in the
"plink20170817" schematic

Reset input timing

RESX Puise	Action
Shorter than 5µs	Invalid Reset
Longer than 10µs	Valid Reset
Between 5µs and 10µs	Reset Initialization Precedure

TODO: low power state signal??

Sheet: /MIPI DSI/
File: mipi_dsi.sch

Title: MIPI DSI

Size: A4	Date: 2018-05-02	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 11/17



Sheet: /Buttons & LED/
File: buttons_led.sch

Title: Buttons & LED

Size: A4	Date: 2018-05-02	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 12/17



	Pin	Port Config_0[1]	Port Config_1[2]	Port Config_2[3]	Port Config_3[4]
GPIO_0	40	GNSS_SCL	GNSS_SCL	SIM_DET2	HSIC_Data
GPIO_1	42	GNSS_SDA	GNSS_SDA	UIM_DTA2	HSIC_Strobe
GPIO_2	44	GNSS_IRQ	GNSS_IRQ	UIM_CLK2	IPC_0
GPIO_3	46	SYSCLK	GNSS_0	UIM_RST2	IPC_1
GPIO_4	48	TX_BLANKING	GNSS_1	UIM_PWR2	IPC_2
GPIO_5	20	AUDIO_0	AUDIO_0	RFU	Audio_0
GPIO_6	22	AUDIO_1	AUDIO_1	RFU	Audio_1
GPIO_7	24	AUDIO_2	AUDIO_2	RFU	IPC_3/Audio_2
GPIO_8	28	AUDIO_3	AUDIO_3	RFU	IPC_4/Audio_3
GPIO_9	10	LED#1	LED#1	LED#1	IPC_5
GPIO_10	26	W_Disable2#	W_Disable2#	W_Disable2#	IPC_6
GPIO_11	23	Wake_On_WWAN	Wake_On_WWAN	Wake_On_WWAN	IPC_7
GPIO_12	25	DPR	DPR	DPR	IPC_8

CONFIG_0 (Pin 21)	CONFIG_1 (Pin 69)	CONFIG_2 (Pin 75)	CONFIG_3 (Pin 1)	Module Type and Main Host Interface[1]	Port Configuration[2]	State
GND	GND	GND	GND	SSD – SATA	N/A	
GND	NC	GND	GND	SSD – PCIe	N/A	
GND	GND	NC	GND	WWAN – PCIe	0	0
GND	NC	NC	GND	WWAN – PCIe	1	1
GND	GND	GND	NC	WWAN – USB 3.0	0	2
GND	NC	GND	NC	WWAN – USB 3.0	1	3
GND	GND	NC	NC	WWAN – USB 3.0	2	4
GND	NC	NC	NC	WWAN – USB 3.0	3	5
NC	GND	GND	GND	WWAN – SSIC	0	6
NC	NC	GND	GND	WWAN – SSIC	1	7
NC	GND	NC	GND	WWAN – SSIC	2	8
NC	NC	NC	GND	WWAN – SSIC	3	9
NC	GND	GND	NC	WWAN – PCIe	2	10
NC	NC	GND	NC	WWAN – PCIe	3	11
NC	GND	NC	NC	RFU	N/A	12
NC	NC	NC	NC	No Module Present	N/A	13
						14
						15

Sheet: /WWAN M.2/
File: wwan_m2.sch

Title: WWAN M.2

Size: A4	Date: 2018-05-02	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 13/17


Reference:
https://electronics.stackexchange.com/questions/31442/how-can-i-switch-this-audio-jack-using-its-own-mechanical-switches-without-cre
(Nit6 does the same)
+Zener diode to protect against ranges outside of −0.9V to 3.3V
min headphone speaker impedance = 16Ω
dB specs in datasheet is a unit of power gain (not dBu or VU)
with respect to the DAC's unattenuated output
"HP Output − 62.5mW max, 1.02kHz sine into 16Ω load at 3.3 V"
⇒ (1V)²/(16Ω)=62.5mW
∴ Vrms=1V ⇒ Vp(amplitude)=1.414V
∴ Irms(max)=62.5mA
If HP_DET is HIGH for >100ms then HPs are present
U1501
SGTL5000
may only use one channel to GND
(not differential outputs)
DLW21SN900SQ2L
FL1501
CTIA/AHJ
Microphone
Ground
Audio (Right)
Audio (Left)
J1404
SJ-43515TS
Pin 5 (tip switch) is NC,
open when inserted
If just headphones then
HP_DET=HIGH, R(mic)=0
D1402
SZMM5Z3V3T1G
Vz=3.3V
Vf=0.9V
TODO:
DPST with camera!
U1405
SN74LVC1G66
U1406
74AHC1G14
schmitt-triggered
VIL≅0.9V
Mic only enabled
if nothing in jack
MK1401
Microphone
LCR Measurements:
headset microphone:
@1kHz
Ls = 3.844mH
Lp = 15.757H
Cs = 6.583uF
Cp = 1612.8pF
Rs = 1.5465kOhms
Rp = 1.5478kOhms
θ = −0.8deg
headset speaker:
@1kHz
Ls = 244.4uH
Lp = 141.99mH
Cs = 103.6uF
Cp = 178.77nF
Rs = 36.860hms
Rp = 36.860hms
θ = −2.3deg
headphone speaker:
@1kHz
Ls = 25.2uH
Lp = 311.0mH
Cs = 1.0mF
Cp = 81.95nF
Rs = 17.0300hms
Rp = 17.0340hms
θ = 0.5deg
Simulation of 1kHz output
without HP jack inserted:
transient
simulation
GNU GPLv3
Copyright 2018
Purism SPC
Sheet: /Audio/
File: audio.sch
Title: Audio
Size: A4
Date: 2018-05-02
Rev: v0.1.0
KiCad E.D.A. kicad 4.0.7
Id: 14/17

Can swap around signals in the layout:

EN	IN1	IN2	NC1/2/3 TO COM1/2/3, COM1/2/3 TO NC1/2/3	NC4/5/6 TO COM4/5/6, COM4/5/6 TO NC4/5/6	NO1/2/3 TO COM1/2/3, COM1/2/3 TO NO1/2/3	NO4/5/6 TO COM4/5/6, COM4/5/6 TO NO4/5/6
H	X	X	OFF	OFF	OFF	OFF
L	L	L	ON	ON	OFF	OFF
L	H	L	OFF	OFF	ON	OFF
L	L	H	ON	OFF	OFF	ON
L	H	H	OFF	OFF	ON	ON



Sheet: /SDIO DEMUX/
File: sdio_demux.sch

Title: SDIO Demultiplexer

Size: A4	Date: 2018-05-02	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 15/17

RGMII 10/100/1000 Ethernet



Sheet: /Ethernet/		
File: ethernet.sch		
Title:		
Size: A4	Date:	**Rev:**
KiCad E.D.A. kicad 4.0.7		Id: 16/17

6.2 M.2 Signal Directions

RS9116 NC:
RTS, CTS, BT_HOST_WAKE, WIFI_WAKE

Module: Table 23
Socket: Table 46

UARTn_UFCR[DCEDTE]=0 on POR



TX output
RX input
CTS output
RTS input

⇒TX→RX
RX←TX
CTS→CTS
RTS←RTS

RedPine RS9116 MB0
Requires +5V for USB!

J1502

3V3_P

USB_WLAN_DP
USB_WLAN_DN

M2_PCM_CLK
M2_PCM_SYNC
M2_PCM_IN
M2_PCM_OUT

WIFI_CLK
WIFI_CMD
WIFI_DATA0
WIFI_DATA1
WIFI_DATA2
WIFI_DATA3
WIFI_WAKE

1V8_P

R1506
10k

BT_HOST_WAKE
BT_UART_RXD

SoC's RX
Module's TX

SoC's TX
Module's RX

BT_UART_TXD
BT_UART_RTS
BT_UART_CTS

WIFI_RST
D1503
ZLLS400

W_DISABLE1
D1504
ZLLS400

RS9116 SUSCLK
is a GPIO (unused)
SUSCLK

W_DISABLE2
W_DISABLE1
M2_I2C_SDA
M2_I2C_SCL

M.2_Key_E

GND

i.MX8M in DCE mode has
CTS output, RTS input

U1502A
74AUP2G00

U1502B
74AUP2G00

BT_DISABLE
WIFI_DISABLE

D1505
CFSH05-20L

Closed = ON (*_DISABLE HIGH)
Open = OFF

SW1501
WWAN_HKS

R1508
10k

C1515
100nF

R1510
10k

TODO:
M.2 spec defines
UART&PCM 1.8V!
but RS9116 is 3.3V!!

U1702
NTB0104GU12

C1722 C1723
1uF 10nF

C1724 C1725
10nF 1uF

OE VCCA VCCB GND
A1 A2 A3 A4
B1 B2 B3 B4

BT_UART_RXD
BT_UART_TXD
BT_UART_RTS
BT_UART_CTS

RX, TX, RTS, CTS
of the SoC

internal 10k pull-up

U1504
NTB0104GU12

C1520 C1521
1uF 10nF

C1522 C1523
10nF 1uF

BCLK
M2_PCM_CLK
M2_PCM_SYNC
M2_PCM_IN
M2_PCM_OUT

BT_PCM_CLK
BT_PCM_SYNC
BT_PCM_IN
BT_PCM_OUT

configure as slave

R1507
10k

M2_I2C_SDA

I2C2_SDA

Q1501
FDV301N

TODO!!!
verify if translators
with PWR_EN is needed!

RS9116's I2C is part of its
IO_VDD_1 domain
which is 3.0-3.6V!
TODO!!!

R1509
10k

M2_I2C_SCL

I2C2_SCL

Q1502
FDV301N

RS9116 has SCL as output
⇒master?
(only device on I2C2 bus)

Purism SPC

Sheet: /WLAN+BT M.2/
File: wifi_bt_m2.sch

Title: WLAN+BT M.2

Size: A4	Date: 2018-05-02	**Rev: v0.1.0**
KiCad E.D.A. kicad 4.0.7		Id: 17/17