


USB-C TCPC - Config Channel (CC) and PD Role Controller

USB-C



USB Type C

Purism

Copyright 2018 GNU GPLv3


Sheet: /USB-C/
File: usb-c.sch

Size: A4 Date: 2018-08-14
KiCad E.D.A. kicad 5.0.0


eric.kuzmenko@puri.sm
angus.ainstie@puri.sm
nicole.faeber@puri.sm
christian.schilmoeller@puri.sm

Rev: v0.1.0
Id: 2/24

Battery Charge Controller



Drawing ~320mA, or consuming $\leq 1.152W$, should give close to 10 hours going from 100% to 0% charge



Reading PTN5110HQ's CC_STATUS and POWER_STATUS registers will tell TCPM (i.MX8M) when to set EN_HiZ

Also, reading PTN5110HQ's CC_STATUS and POWER_STATUS registers will tell TCPM (i.MX8M) when to set OTG_CONFIG=1 (this will also happen when PTN5110HQ sets EN_SRC HIGH)

Battery

Purism

Copyright 2018 GNU GPLv3

Sheet: /Battery/
 File: battery.sch

Size: A4 Date: 2018-08-14
 KiCad E.D.A. kicad 5.0.0

eric.kuzmenko@puri.sm

angus.ainslie@puri.sm


nicole.ferber@puri.sm

christian.schilmoeller@puri.sm


Rev: v0.1.0

Id: 3/24


3.3V/3A




1.8V/600mA




5.0V/3.8A



22.4V/40mA



2.8V/150mA



Boot Config



2->1: eMMC 2->3: USB (Serial Downloader)	
BOOT_MODE[1:0]	Boot Type
00	Boot From Fuses
01	Serial Downloader
10	Internal Boot
11	Reserved

Only eMMC	
BOOT_CFG[14:12]	Boot device
001	SD/eSD
010	MMC/eMMC
011	NAND

Fuse	Config	Definition	GPIO ¹	Shipped value	Settings
BOOT_CFG[11:10]	OEM	USDHC port selection	Yes	00	00 - USDHC-1 01 - USDHC-2 10 - USDHC-3 else - reserved



Boot Configuration



Copyright 2018 GNU GPLv3

Sheet: /Boot Config/
File: boot.sch

Size: A4
KiCad E.D.A. kicad 5.0.0

Date: 2018-08-14

Rev: v0.1.0

Id: 5/24


eric.kuzmenko@puri.sm

angus.ainstlie@puri.sm

nicole.ferber@puri.sm

christian.schilmoeller@puri.sm

Real-Time Clock



Note:
Datasheet says slave address is 0xD0
with a R/W bit appended, since 0xD must
be 4-bits wide the actual 7-bit address is
0x68 (110 1000), and becomes 0xD0 during a
write operation (1101 0000)

Reference:
https://github.com/HIO-Project/linux-imx6-nano-imx_3.10.17_1.0.1_ga/blob/8848e94b2f889fe44f6736e2d4c98851a2282275/arch/arm/boot/dts/imx6qdl-mtp.dtsi#L351

RTC



Copyright 2018 GNU GPLv3

Sheet: /RTC/

File: rtc.sch

Size: A4 Date: 2018-08-14

KiCad E.D.A. kicad 5.0.0

Rev: v0.1.0

Id: 6/24


eric.kuzmenko@puri.sm

angus.ainstlie@puri.sm

nicole.farber@puri.sm

christian.schilmoeller@puri.sm

UART Debug



UART Debug



Copyright 2018 GNU GPLv3

Sheet: /UART Debug/

File: uart.sch

Size: A4

Date: 2018-08-14

KiCad E.D.A. kicad 5.0.0

Rev: v0.1.0

Id: 7/24


eric.kuzmenko@puri.sm

angus.ainstlie@puri.sm

nicole.farber@puri.sm

christian.schilmoeller@puri.sm

JTAG



JTAG



Copyright 2018 GNU GPLv3

Sheet: /JTAG/

File: jtag.sch

Size: A4	Date: 2018-08-14
----------	------------------

Size: A4	Date: 2
KiCad E.D.A.	kicad 5.0.0

eric.kuzmenko@puri.sm

angus.ainslie@puri.sm


nicole.faerber@puri.sm

christian.schilmoeller@puri.sm

Rev: v0.1.0

Id: 8/24

USB Hub + SDIO Bridge



Can be swapped around depending on layout

USB Hub + SDIO Bridge



Copyright 2018 GNU GPLv3

Sheet: /USB Hub + SDIO Bridge/

Size: A4

Date: 2018-08-14

KiCad E.D.A.	kicad 5.0.0
--------------	-------------

eric.kuzmenko@puri.sm

angus.ainslie@puri.sm


nicole.faeber@puri.sm

christian.schilmoeller@puri.sm

Rev: v0.1.0

Id: 9/24

μSD



uSD Card



Purism

Copyright 2018 GNU GPLv3

Sheet: /uSD Card/

File: sd.sch

eric.kuzmenko@puri.sm

angus.ainslie@puri.sm

nicole.faerber@puri.sm

christian.schilmoeller@puri.sm

Size: A4	Date: 2018-08-14
----------	------------------

Size: A4	Date: 11/01/2025
KiCad E.D.A.	kicad 5.0.0

Rev: v0.1.0

Id: 10/24

MIPI



MIPI



Copyright 2018 GNU GPLv3

Sheet: /MIPI/
File: mipi.sch

Size: A4
KiCad E.D.A. kicad 5.0.0

Date: 2018-08-14

Rev: v0.1.0
Id: 11/24

eric.kuzmenko@puri.sm
angus.ainstlie@puri.sm
nicole.ferber@puri.sm
christian.schilmoeller@puri.sm

Id: 13/24

Buttons & LED



Use PWM2_PWMSAR to set the compare value (duty cycle)
Use PWM2_PWMCR[15:4] to set the PRESCALER (frequency)
Use PWM2_PWMPR to set the top of the counter (frequency)



Buttons & LED



Copyright 2018 GNU GPLv3


Sheet: /Buttons & LED/
File: buttons_led.sch

Size: A4 Date: 2018-08-14
KiCad E.D.A. kicad 5.0.0


eric.kuzmenko@puri.sm
angus.ainstie@puri.sm
nicole.farber@puri.sm
christian.schilmoeller@puri.sm

Rev: v0.1.0
Id: 14/24

WWAN mPCIe



Audio



Reference:
http://www.52rd.com/S_txt/2011_3/TXT26685.htm
<http://www.sengpielaudio.com/calculator-transferfactor.htm>
<https://electronics.stackexchange.com/questions/31442/how-can-i-switch-this-audio-jack-using-its-own-mechanical-switches-without-crc>
 -switch-this-audio-jack-using-its-own-mechanical-switches-without-crc (Nit6 does the same)
 +Zener diode to protect against ranges outside of -0.9V to 3.3V


dB specs in datasheet is a unit of power gain (not dBu or VU) with respect to the DAC's unattenuated output

"HP Output - 62.5mW max, 1.02kHz sine into 16Ω load at 3.3 V"
 $\Rightarrow (1V)^2 / (16\Omega) = 62.5mW$
 $\therefore V_{rms} = 1V \Rightarrow V_p(\text{amplitude}) = 1.414V$
 $\therefore I_{rms}(\text{max}) = 62.5mA$

If HP_DET is HIGH for >100ms then HPs are present

S/E button on earbud headsets shorts the mic for key function

Could use FSA8008 to detect mic





CTIA/AHJ
 Microphone Ground
 Audio (Right)
 Audio (Left)

<3.3μA
 R1608 1M

SJ-43515TS
 SMD Equivalent: SJ-43515RS-SMT-TR

Pin 5 (tip switch) is NC, open when inserted
 If just headphones then HP_DET=HIGH, R(mic)=0

may add ~220uF cap parallel to Zener



LCR Measurements:

Earbud Microphone: @1kHz Ls = 3.844mH Lp = 15.757H Cs = 6.583uF Cp = 1612.8pF Rs = 1.5465kOhms Rp = 1.5478kOhms θ = -0.8deg	Headset Speaker: @1kHz Ls = 244.4uH Lp = 141.99mH Cs = 103.6uF Cp = 178.77nF Rs = 36.86Ohms Rp = 36.86Ohms θ = -2.3deg	Earbud Speaker: @1kHz Ls = 25.2uH Lp = 311.0mH Cs = 1.0mF Cp = 81.95nF Rs = 17.030Ohms Rp = 17.034Ohms θ = 0.5deg
---	--	---

Audio

Purism

Copyright 2018 GNU GPLv3

Sheet: /Audio/
 File: audio.sch

Size: A4
 KiCad E.D.A. kicad 5.0.0

eric.kuzmenko@puri.sm
 angus.ainstie@puri.sm
 nicole.farber@puri.sm
 christian.schilmoeller@puri.sm

Rev: v0.1.0
 Id: 16/24

[illegible]

Purism

eric.kuzmenko@puri.sm
angus.ainslie@puri.sm
nicole.faeber@puri.sm
christian.schilmoeller@puri.sm

WLAN+BT M.2

RS9116 NC:
RTS, CTS, BT_HOST_WAKE

RS9116 datasheet says
no WIFI_WAKE
but the schematic has it

RedPine RS9116 MB0
Requires 5V on
Pin 54 if USB used

WLAN_D_P
WLAN_D_N
WIFI_CLK
WIFI_CMD
WIFI_DATA0
WIFI_DATA1
WIFI_DATA2
WIFI_DATA3
WIFI_WAKE

VIH=2.31V

WIFI_RST

W_DISABLE1

RedPine RS9116
has 100k pull-up to
3.3V making SDIO_RST
~2.55V when HIGH

MOD1801
WifiBTCard

WiFi + Bluetooth

M.2 Form Factor

Key ID "E"

width: 22 mm

length: 30 mm

W_DISABLE2

W_DISABLE1

M2_I2C_SDA

M2_I2C_SCL

W_DISABLE2

W_DISABLE1

M2_I2C_SDA

M2_I2C_SCL

W_DISABLE2

W_DISABLE1

M2_I2C_SDA

M2_I2C_SCL

W_DISABLE2

W_DISABLE1

M2_I2C_SDA

M2_I2C_SCL

W_DISABLE2

W_DISABLE1

M2_I2C_SDA

M2_I2C_SCL

W_DISABLE2

W_DISABLE1

M2_I2C_SDA

M2_I2C_SCL

W_DISABLE2

W_DISABLE1

M2_I2C_SDA

M2_I2C_SCL

W_DISABLE2

W_DISABLE1

M2_I2C_SDA

M2_I2C_SCL

W_DISABLE2

W_DISABLE1

M2_I2C_SDA

M2_I2C_SCL

W_DISABLE2

W_DISABLE1

Socket: Table 46
Module: Table 23

3V3_P

M.2 Key E

R1802

J1803

NC

Key E

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

47

48

49

50

51

52

53

54

55

56

57

58

59

60

61

62

63

64

65

66

67

68

69

70

71

72

73

74

75

76

77

78

79

80

81

82

83

84

85

86

87

88

89

90

91

92

93

94

95

96

97

98

99

100

101

102

103

104

105

106

107

108

109

110

111

112

113

114

115

116

117

118

119

120

121

122

123

124

125

126

127

128

129

130

131

132

133

134

135

136

137

138

139

140

141

142

143

144

145

146

147

148

149

150

151

152

153

154

155

156

157

158

159

160

161

162

163

164

165

166

167

168

169

170

171

172

173

174

175

176

177

178

179

180

181

182

183

184

185

186

187

188

189

190

191

192

193

194

195

196

197

198

199

200

201

202

203

204

205

206

207

208

209

210

211

212

213

214

215

216

217

218

219

220

221

222

223

224

225

226

227

228

229

230

231

232

233

234



235

236

237

TUSB1046 can be used for DP over USB-C

HDMI



HDMI



Copyright 2018 GNU GPLv3

Sheet: /HDMI/
File: hdmi.sch


Size: A4 Date: 2018-08-14
KiCad E.D.A. kicad 5.0.0

eric.kuzmenko@puri.sm
angus.ainstie@puri.sm
nicole.farber@puri.sm
christian.schilmoeller@puri.sm

Rev: v0.1.0
Id: 19/24


Sensors

Proximity & Ambient Light




Reference:
<https://www.vishay.com/docs/84307/designingvcnl4040.pdf>
<http://www.vishay.com/docs/84931/vcni4040sensorboardfiles.pdf>

9-Axis IMU



Reference:
<http://www.st.com/en/evaluation-tools/steval-mki159v1.html>



Sensors



Purism

Copyright 2018 GNU GPLv3

Sheet: /Sensors/
File: sensors.sch

eric.kuzmenko@puri.sm

angus.ainslie@puri.sm

nicole.farber@puri.sm


christian.schilmoeller@puri.sm

Size: A4	Date: 2018-08-14
----------	------------------

Size: 771	Date:
KiCad E.D.A.	kicad 5.0.0

Rev: v0.1.0

Id: 20/24

SPI NOR Flash  Purism		eric.kuzmenko@puri.sm angus.ainslie@puri.sm nicole.faeber@puri.sm christian.schilmoeller@puri.sm
Copyright 2018 GNU GPLv3		
Sheet: /SPI Flash/ File: flash.sch		
Size: A4	Date: 2018-08-14	Rev: v0.1.0
KiCad E.D.A. kicad 5.0.0		Id: 21/24

[illegible]

Smart Card



christian.schilmoeller@puri.sm

Id: 22/24

GNSS



References:
https://www.u-blox.com/sites/default/files/MAX-M8_HardwareIntegrationManual_L%28UBX-13004876%29.pdf
https://www.u-blox.com/sites/default/files/MAX-8-M8-FW3_HardwareIntegrationManual_L%28UBX-15030059%29.pdf

GNSS



Copyright 2018 GNU GPLv3

Sheet: /GNSS/
 File: gnss.sch

Size: A4
 KiCad E.D.A. kicad 5.0.0

Date: 2018-08-14

Rev: v0.1.0


Id: 23/24

eric.kuzmenko@puri.sm
 angus.ainstlie@puri.sm
 nicole.ferber@puri.sm
 christian.schilmoeller@puri.sm

Haptic Motor

PWM pins occupied:
 GPIO1_I001 - LCD Backlight
 GPIO1_I013 - LED
 GPIO1_I014 - Ethernet (CLKO_25MHz)
 GPIO1_I015 - CSI (CLKO2)

PWM needed?
 Only needs to be toggled
 ON 1 sec, OFF 1 sec (0.5Hz)
 Can MUX as either
 GPIO or PWM2
 swapping with LED



When the motor is off
 both terminals are at GND
 Motor will have wire leads
 with a 2-pin Molex or Boom Precision
 connector installed (by request)
 Metal housing is floating
 thick adhesive layer underneath
 (not connected to either pin)

Haptic/Vibration Motor



Copyright 2018 GNU GPLv3

Sheet: /Haptic Motor/
 File: haptic.sch

eric.kuzmenko@puri.sm

angus.ainstlie@puri.sm

nicole.farber@puri.sm

christian.schilmoeller@puri.sm

Size: A4 Date: 2018-08-14

KiCad E.D.A. kicad 5.0.0

Rev: v0.1.0

Id: 24/24