

```
1: // $Id: thingstack.cpp,v 1.19 2013-01-23 19:35:49-08 - - $
2:
3: #include <iostream>
4: #include <list>
5:
6: using namespace std;
7:
8: #include "iterstack.h"
9:
10: int serial = 0;
11:
12: #define PRINT(FUNC) print(FUNC, __LINE__)
13:
14: struct thing {
15:     int ser;
16:     int val;
17:     explicit thing(int v = int());
18:     thing (const thing &that);
19:     thing &operator= (const thing &that);
20:     ~thing();
21:     void print (const char *name, int line);
22: };
23:
24: thing::thing(int v): ser(++serial), val(v) {
25:     PRINT("thing(int)");
26: }
27:
28: thing::thing (const thing &that): ser(++serial), val(that.val) {
29:     PRINT("thing(const thing &)");
30: }
31:
32: thing &thing::operator= (const thing &that) {
33:     if (this != &that) {
34:         val = that.val;
35:     }
36:     PRINT("operator=(const thing &)");
37:     return *this;
38: }
39:
40: thing::~~thing() {
41:     PRINT("~thing()");
42: }
43:
44: void thing::print (const char *name, int line) {
45:     cout << name << "[" << line << "]: " << this << "-> ser="
46:         << ser << ", val=" << val << endl;
47: }
48:
```

```
49:
50: #define SCOPE(X) cout << endl << X << " scope " << __LINE__ << endl
51:
52: int main() {
53:     iterstack<thing> stk;
54:     for (int i = 0; i < 3; ++i) {
55:         SCOPE("enter");
56:         thing t(i);
57:         cout << endl << "stk.push (t);" << endl;
58:         stk.push (t);
59:         SCOPE("leave");
60:     }
61:     while (! stk.empty()) {
62:         SCOPE("enter");
63:         thing t = stk.top();
64:         t.PRINT("stk.top()");
65:         cout << endl << "stk.pop();" << endl;
66:         stk.pop();
67:         SCOPE("leave");
68:     }
69:     return 0;
70: }
71:
72: /*
73: //TEST// valgrind --leak-check=full --show-reachable=yes \
74: //TEST//      --log-file=thingstack.out.grind \
75: //TEST//      thingstack >thingstack.out 2>&1
76: //TEST// mkpspdf thingstack.ps thingstack.cpp* iterstack.h \
77: //TEST//      thingstack.out*
78: */
79:
```

[illegible]

```
1: // $Id: iterstack.h,v 1.5 2014-05-30 13:47:32-07 - - $
2:
3: //
4: // The class std::stack does not provide an iterator, which is
5: // needed for this class. So, like std::stack, class iterstack
6: // is implemented on top of a container.
7: //
8: // We use private inheritance because we want to restrict
9: // operations only to those few that are approved. All functions
10: // are merely inherited from the container, with only ones needed
11: // being exported as public.
12: //
13: // No implementation file is needed because all functions are
14: // inherited, and the convenience functions that are added are
15: // trivial, and so can be inline.
16: //
17: // Any underlying container which supports the necessary operations
18: // could be used, such as vector, list, or deque.
19: //
20:
21: #ifndef __ITERSTACK_H__
22: #define __ITERSTACK_H__
23:
24: #include <vector>
25: using namespace std;
26:
27: template <typename value_type>
28: class iterstack: private vector<value_type> {
29:     private:
30:         using vector<value_type>::crbegin;
31:         using vector<value_type>::crend;
32:         using vector<value_type>::push_back;
33:         using vector<value_type>::pop_back;
34:         using vector<value_type>::back;
35:         using const_iterator = typename
36:             vector<value_type>::const_reverse_iterator;
37:     public:
38:         using vector<value_type>::clear;
39:         using vector<value_type>::empty;
40:         using vector<value_type>::size;
41:         const_iterator begin() { return crbegin(); }
42:         const_iterator end() { return crend(); }
43:         void push (const value_type& value) { push_back (value); }
44:         void pop() { pop_back(); }
45:         const value_type& top() const { return back(); }
46: };
47:
48: #endif
49:
```

```
1:
2: enter scope 55
3: thing(int)[25]: 0x7feffffb60-> ser=1, val=0
4:
5: stk.push (t);
6: thing(const thing &)[29]: 0x4e79090-> ser=2, val=0
7:
8: leave scope 59
9: ~thing()[41]: 0x7feffffb60-> ser=1, val=0
10:
11: enter scope 55
12: thing(int)[25]: 0x7feffffb60-> ser=3, val=1
13:
14: stk.push (t);
15: thing(const thing &)[29]: 0x4e790e8-> ser=4, val=1
16: thing(const thing &)[29]: 0x4e790e0-> ser=5, val=0
17: ~thing()[41]: 0x4e79090-> ser=2, val=0
18:
19: leave scope 59
20: ~thing()[41]: 0x7feffffb60-> ser=3, val=1
21:
22: enter scope 55
23: thing(int)[25]: 0x7feffffb60-> ser=6, val=2
24:
25: stk.push (t);
26: thing(const thing &)[29]: 0x4e79140-> ser=7, val=2
27: thing(const thing &)[29]: 0x4e79130-> ser=8, val=0
28: thing(const thing &)[29]: 0x4e79138-> ser=9, val=1
29: ~thing()[41]: 0x4e790e0-> ser=5, val=0
30: ~thing()[41]: 0x4e790e8-> ser=4, val=1
31:
32: leave scope 59
33: ~thing()[41]: 0x7feffffb60-> ser=6, val=2
34:
35: enter scope 62
36: thing(const thing &)[29]: 0x7feffffb50-> ser=10, val=2
37: stk.top()[64]: 0x7feffffb50-> ser=10, val=2
38:
39: stk.pop();
40: ~thing()[41]: 0x4e79140-> ser=7, val=2
41:
42: leave scope 67
43: ~thing()[41]: 0x7feffffb50-> ser=10, val=2
44:
45: enter scope 62
46: thing(const thing &)[29]: 0x7feffffb50-> ser=11, val=1
47: stk.top()[64]: 0x7feffffb50-> ser=11, val=1
48:
49: stk.pop();
50: ~thing()[41]: 0x4e79138-> ser=9, val=1
51:
52: leave scope 67
53: ~thing()[41]: 0x7feffffb50-> ser=11, val=1
54:
55: enter scope 62
56: thing(const thing &)[29]: 0x7feffffb50-> ser=12, val=0
57: stk.top()[64]: 0x7feffffb50-> ser=12, val=0
58:
```

06/26/14  
17:25:16

\$cmpps109-wm/2014-spring-Assignments/asg2-dc-bigint/misc/  
thingstack.out

2/2

```
59: stk.pop();  
60: ~thing()[41]: 0x4e79130-> ser=8, val=0  
61:  
62: leave scope 67  
63: ~thing()[41]: 0x7feffffb50-> ser=12, val=0
```

```
1: ==27253== Memcheck, a memory error detector
2: ==27253== Copyright (C) 2002-2012, and GNU GPL'd, by Julian Seward et al
.
3: ==27253== Using Valgrind-3.8.1 and LibVEX; rerun with -h for copyright i
nfo
4: ==27253== Command: thingstack
5: ==27253== Parent PID: 27252
6: ==27253==
7: ==27253==
8: ==27253== HEAP SUMMARY:
9: ==27253==      in use at exit: 0 bytes in 0 blocks
10: ==27253==    total heap usage: 4 allocs, 4 frees, 65 bytes allocated
11: ==27253==
12: ==27253== All heap blocks were freed -- no leaks are possible
13: ==27253==
14: ==27253== For counts of detected and suppressed errors, rerun with: -v
15: ==27253== ERROR SUMMARY: 0 errors from 0 contexts (suppressed: 6 from 6)
```