

CSci487 Penetration Testing Project: AILEE

Grant Haataja
UND Computer Science
Grand Forks, USA
grant.haataja@und.edu

David Wilson
UND Computer Science
Grand Forks, USA
david.andrew.wilson@und.edu

Michael Turnbull
UND Computer Science
Grand Forks, USA
michael.turnbull@und.edu

Abstract—This document details the planning, development, and workings of the penetration testing game AILEE, created as a final project for CSCI 487 Penetration Testing class at the University of North Dakota.

I. INTRODUCTION

For this project on penetration testing topics, a hacking simulation game was created. The premise of the game is as follows: the user plays the role of a penetration-testing AI software named AILEE, which stands for Artificial Intelligence Linux Exploit Environment. The game takes place exclusively in a Linux-style terminal environment, with a limited arsenal of commands for the player to use. As the player progresses through the game and “learns” as an AI, the commands available for use increase. Throughout the game, the player is given typed instructions and information from the AI’s administrator to assist in learning.

There are two targets to hack in this demo, although there is much potential for expansion. The game uses simulated port scanning, vulnerability scanning, exploitation, and other penetration testing tools to mimic real-life penetration testing methods. Additionally, the game features a storyline with three possible endings, depending on player actions. Special care was taken to handle proper sequence of events.

II. INVESTIGATION

A. Planning the Project

Before beginning the development of the game, a suitable platform to run the environment needed to be found. The website Repl.it was decided upon, due to their extensive language support and the ability for multiple people to work simultaneously and have all changes automatically saved to the cloud. [1] The “Multiplayer” mode, as this feature was called, still had a lot of bugs, so forking the project and saving work manually was still necessary, but overall it made the development of AILEE much smoother.

Python3 was selected as the programming language of choice, due to its ease of scripting and strong object-oriented nature. The various classes corresponding to different aspects of the game and environment would be programmed separately, as well as Python scripts for each command available to the player, and every storyline event that could be run. The original plan was for there to be three different targets for the player to hack, but due to time limitations the scope was decreased to two targets.

To enable smooth graphics for the intro screen and the game’s ending events, the Python Curses library was referenced and used extensively. [2] This provided the ability to control keyboard input while text displayed on the screen or the ending event graphics played, to increase the smoothness of gameplay.

III. PROJECT DESCRIPTION

A. Intro Screen

For the graphics of the intro screen for the game, ASCII art was used to spell the word AILEE, along with a selection for New Game or Exit. The user can move between the selection using the up or down arrow keys and choose by pressing the enter key. Selecting Exit will cause the terminal session within Repl.it to exit and the game will have to be run again, selecting New Game creates a new session and runs the game.

In addition to these, pressing the up arrow six times in a row will show a hidden third selection, Skip Dialog. This will run the game without displaying any of the instructions and information from the administrator to AILEE, and was very useful for testing the game during development. This mode is not explained or mentioned in the game, as it is not recommended to play without reading the dialogue.

The intro screen makes use of the Python curses library to allow smooth use of the arrow keys keyboard input and prevent buggy graphics.

B. Starting the Game

Upon choosing New Game, the user watches as the administrator logs into their account and launches AILEE.exe to start a new shell. After the shell loads, the first event triggers and text displays on the screen to inform the user what is going on. The administrator gives a brief explanation, and then the user is free to experiment with the Linux-style terminal environment. The terminal runs in the Shell class, (in tandem with the Game and DoStory classes), which supports multiple terminals on various computers. The code for the Shell class is as follows:

```
1 from termcolor import colored
2 import replit
3
4 import time
5 import traceback, sys, random
6
7 import executables
8 import events
9 from MainMenuException import MainMenuException
```

```

10 DEFAULT_PROMPT = colored("AILEE@{COMP}: {CWD}$ ", '
11 green')
12
13 CMD_NOT_FOUND_STRS = [
14     "command not found"
15 ]
16
17 class Shell(object):
18     """
19     Like a seashell.
20     """
21
22     def __init__(self, computer, user, agent=None, cwd
23     =None, game=None):
24         """
25         Create a shell.
26         """
27
28         self.computer = computer
29         self.user = user
30         self.agent = agent
31         self.cwd = cwd or computer.fs
32         self.prompt = DEFAULT_PROMPT
33         self.running = False
34         self._command_dictionary = {}
35         self.variables = {}
36         self.game = game
37         self.history = []
38
39         self._setup()
40
41     def _setup(self):
42         replit.clear()
43         s = "Loading new shell"
44
45         print(s, end='\r')
46         i = 0
47
48         # load command dictionary
49         for module in executables.__all__:
50             self._command_dictionary.update({module:
51             getattr(executables, module).run})
52             print(s + '.'*i, end='\r')
53             i += 1
54             time.sleep(0.1)
55             time.sleep(0.3)
56             replit.clear()
57             #print(constants.title)
58
59     def _get_command_from_str(self, command_str):
60         """
61         Takes a command name, returns the executable
62         object.
63         """
64
65         if command_str == '':
66             return False
67         if command_str not in self.game.allowed_commands:
68             return None
69         cmd = self._command_dictionary[command_str]
70         return cmd
71
72     def run_command(self, command, args):
73         """
74         Runs a command.
75
76         Input must be a runnable command that accepts **
77         kwargs.
78         """
79
80         command(
81             *args,
82             computer=self.computer,
83             cwd=self.cwd,
84             user=self.user,
85             agent=self.agent,
86             shell=self,
87             game=self.game,
88         )
89
90     def take_input(self):
91         user_input = input(self.prompt.format(
92             COMP=str(self.computer.name),
93             CWD=str(self.cwd),
94             USER=self.user),
95         )
96
97         parts = [p.strip() for p in user_input.split(' '
98         )]
99         command = parts[0]
100         args = parts[1:]
101
102         return command, args
103
104     def one_command(self):
105         command, args = self.take_input()
106         cmd = self._get_command_from_str(command)
107         if cmd is None:
108             self.cmd_not_found()
109             return
110         elif cmd is False:
111             return # nothing on empty commands
112         cname = cmd.__module__.split('.')[1]
113         if not cname == 'doStory':
114             self.game.history.append([cname, args])
115             self.history.append([cname, args])
116
117         if not (command or args):
118             return # skip empty input
119         self.run_command(cmd, args)
120
121     def halt(self):
122         self.running = False
123
124     def cmd_not_found(self):
125         self.history.append([None, []])
126         self.game.history.append([None, []])
127         print("Command not found")
128         #print(random.choice(CMD_NOT_FOUND_STRS))
129
130     def start_shell_loop(self):
131         self.running = True
132         while self.running:
133
134             # This is the line of code that integrates the
135             story VVV
136
137             try:
138                 self.run_command(events.doStory.run, [])
139                 self.one_command()
140             except KeyboardInterrupt:
141                 print()
142                 #print("\nYou can't leave! ", end='')
143             except KeyError as e:
144                 self.cmd_not_found()
145             except AssertionError as e:
146                 print(str(e))
147             except MainMenuException:
148                 raise MainMenuException
149             except Exception as e:
150                 print(colored("Something went wrong. I'm
151                 not quite sure what. Maybe try again?", 'red'))
152                 # Uncomment VV for full tracebacks
153                 #einfo = sys.exc_info()
154                 #traceback.print_exception(*einfo)

```

The user is encouraged to try out the various possible commands, which can be displayed using the *help* command. The story continues after the user has ran ten commands, (they can be the same or different commands, it doesn't matter).

C. Gameplay and Commands

As the game progresses, the user will utilize the available penetration testing tools to gain access to the target computers. There are tools for finding IP addresses, port scanning, vulnerability scanning, exploitation, password cracking, and connecting through the ftp file sharing network. Generally, some of the commands require the results from running other commands in order to be run successfully.

In particular, the *exploit* command is extremely useful for gaining access to other computers. This command is similar to the Metasploit framework which is commonly used in real-life penetration testing. In the game, it only has two possible exploits to choose from, and if ran against a vulnerable IP address with the proper port selection, will successfully open a new shell on the target computer.

```
'''
Start the exploitation station.
'''
Description: exploit is a software used for gaining
unauthorized access to remote\computers. There
are different exploits within the framework for
the user to choose\from. Upon running the
exploit software, user will need to choose the
exploit to\ntry, enter the target IP address,
enter the port to connect to, and then type\n
run" to attempt the exploit.

Usage: exploit
'''
#Would like 2 different exploit options to start
with
#one for 'windoors' systems and one for 'lionux'
systems

from funfunctions import dots

def run(*args, **kwargs):
    emptyList = True
    for arg in args:
        if arg:
            emptyList = False
    assert len(args) == 0 or emptyList, "Invalid use
of exploit.\n\nUsage: exploit"

    print('***Welcome to the exploitation station***')
    print('Available exploits:')

    exploits = {
        1: 'WD45_702 reverse tcp shell',
        2: 'LI38_612 meta ssh security flaw',
    }

    for i, exploit in exploits.items():
        print("{:2d}. {}".format(i, exploit))

    sel = 0
    while not sel in exploits.keys():
        try:
            sel = int(input("Exploit selection > "))
        except ValueError:
            print("Enter a number")
```

```
addr = input("Enter target IP address > ")
port = -1
while port < 0:
    try:
        port = int(input("Select port to use > "))
    except ValueError:
        print("Enter a number")
run = input("Type 'run' to begin exploitation > ")

if run != 'run':
    return

dots("Running exploit", 9, 0.333)

if sel == 1:
    if (addr == '120.45.30.6') and (port == 1100)
    and (run == 'run') and kwargs['game'].network['
120.45.30.6']:
        print("Exploit success.")
        kwargs['game'].network['120.45.30.6'].
exploited = True
        kwargs['shell'].run_command(
            kwargs['shell']._get_command_from_str('shell
'),
            ['new', '120.45.30.6']
        )
    else:
        # the failure mode
        print("Exploit failed.")

elif sel == 2:
    # run exploit 2
    if (addr == '120.33.7.242') and (port == 22) and
    (run == 'run'):
        print("Exploit success.")
        kwargs['game'].network['120.33.7.242'].
exploited = True
        kwargs['shell'].run_command(
            kwargs['shell']._get_command_from_str('shell
'),
            ['new', '120.33.7.242']
        )
    else:
        # the failure mode
        print("Exploit failed.")
```

Above is the code for the *exploit* command in the game. In terms of options, it does not compare to the Metasploit framework, but the goal was to create it to feel similarly in the terminal environment.

```
AILEE@localhost: /$ exploit
***Welcome to the exploitation station***
Available exploits:
1. WD45_702 reverse tcp shell
2. LI38_612 meta ssh security flaw
Exploit selection > 1
Enter target IP address > 120.45.30.6
Select port to use > 1100
Type 'run' to begin exploitation > run
Running exploit....
```

Fig. 1. Running the *exploit* executable

First, the user enters the number corresponding to the exploit they wish to run. Then, the target IP address is entered, followed by the specific port, and finally the command 'run'

must be entered and the exploitation software will attempt to gain access to the target (Fig. 1).



Fig. 2. Gaining a shell on target machine

If the exploit is successful, the screen will clear and the words "Loading new shell...." will appear on the screen with increasing dots as the shell loads (Fig. 2).



Fig. 3. A new shell on an exploited target

Once the shell loads, the name of the computer exploited will be shown before the /\$ symbol where commands are typed (Fig. 3).

Most of the other commands play an important role in the game, with a few exceptions that were included for comedic value.

D. Events and Storyline

The story development of the game is controlled by event scripts that are triggered at specific times. Running the events in the proper order is critical for the game to play as planned. The first event is run immediately after the game loads its first shell on the localhost computer. Each event after that has a condition that must be met to trigger it. The second event runs after ten commands have been run, the third event runs after the *pscan* command runs, and so on. Each event runs instructions for the user that should allow them to trigger the next event and progress in the game.

```
1 #Third dialogue of the game
2 #triggers after port scanning has been done
3 import time
4 from funfunctions import typewriter
5 from termcolor import colored
6
```

```
7 def check_run(*args, **kwargs):
8     # check for 'pscan' in history, most recently run,
9     # and exactly once
10    if len(kwargs['game'].history) == 0:
11        return False
12    if not 'event2' in kwargs['game'].events_run:
13        return False
14
15    command = ['pscan', ['120.45.30.6']]
16
17    a = kwargs['game'].history[-1] == command
18    return a
19
20 def run(*args, **kwargs):
21     # using kwargs we can get access to the shell, and
22     # from within the event
23     # have the user run commands
24
25     color = 'cyan'
26     game = kwargs['game']
27
28     text = [
29         '\nGood job, Ailee. I see you have successfully
30         found which open ports are running\nnon our
31         target.\n\n',
32         'Our next step is to run our vulnerability
33         scanning software against the target\nto see if
34         we can use any exploits against them.\n\n'
35     ]
36
37     filename = 'message03.txt'
38     if filename not in game.eventLogDir:
39         game.eventLogDir.addFile(filename, colored('',
40             join(text), color))
41
42     if not game.skip_dialog:
43         typewriter(colored(text[0], color))
44         typewriter(colored(text[1], color))
45     else:
46         print(colored('Event3 text skipped', 'red'))
47
48     # Create chat log in AILEE's directory
```

This is how the scripts for the events are written, implementing a custom-built "typewriter" function created to display text to the screen word by word as if it were typed, and using a blue color to differentiate it from the rest of the game text.




Fig. 4. The dialogue for event 3

This is the text for the third event (Fig. 4), which triggers after the user runs the command *pscan* against the first target IP address.

There are three special events that do not trigger in a normal play-through of the game. These events will only trigger if the player thinks for themselves and uses information

found in the game creatively and without instruction from the administrator. Interestingly, if the user follows the instructions without diverging on their own, they will lose the game during the final hack. The only way to win is by finding what the information leads to and changing the fate of the game before attempting to exploit the final target.

E. Computers and Filesystems

AILEE uses a filesystem structure that feels like a Linux terminal. There are a total of four computers in the game, localhost (AILEE's home computer), the two targets, and one other computer. Each computer has a unique filesystem, with directories and files. As time was limited, the *bin* and *log* directories were left empty on all computers, but the *home* directories all have files in them that either pertain to the gameplay or exist for comedic value or storyline development.

To navigate the filesystems, the traditional Linux commands *ls* and *cd* are used, as well as the commands *read* and *run*, which display file text and run executable files, respectively.

```
1 import termcolor
2
3 class Directory:
4     '''
5     Tree structure of directories and files
6     '''
7     def __init__(self, name=None, parent=None,
8                 children=None):
9         self.name = name or ''
10        self.parent = parent or self # So root node
11        # points to itself as parent
12        self.children = {
13            '.': self,
14            '..': self.parent
15        }
16        if type(children) is dict:
17            self.children.update(children)
18
19        def mkdir(self, name):
20            assert (name not in self.children), 'Directory
21            already exists'
22            newDir = Directory(name, self)
23            self.children.update({name: newDir})
24            return newDir
25
26        def addFile(self, fileName, fileContents):
27            assert (fileName not in self.children), 'File
28            already exists'
29            assert ('.' in fileName), 'File has no type'
30            newFile = File(fileName, fileContents)
31            self.children.update({fileName: newFile})
32            return newFile
33
34        def rmFile(self, fileName):
35            assert (fileName in self.children), "File does
36            not exist"
37            assert ('.' in fileName), "File has no type"
38            del self.children[fileName]
39
40        def __iter__(self):
41            return (fName for fName in self.children)
```

```
42 def __getitem__(self, item):
43     assert (item in self.children), "File or
44     Directory not found"
45     return self.children[item]
46
47 def __len__(self):
48     return len(self.children)
49
50 class File:
51     '''
52     Stores things. Like data, machine code, and
53     blackmail
54     '''
55     def __init__(self, name, data='', permissions='rw-
56     rw-', owner=None):
57         self.name = name
58         self.data = data
59         self.permissions = permissions
60         self.owner = owner
61
62     def append(self, data):
63         self.data += data
64
65     def __repr__(self):
66         return self.name
67     __str__ = __repr__ # set __str__ as the same
68     method as __repr__
69
70     def __len__(self):
71         return len(self.data)
```

This is the code for the structure and mechanics of the computer filesystems.

```
AILEE@localhost: /$ ls
chat_log      go_here_first  folder1
AILEE@localhost: /$ cd go_here_first
AILEE@localhost: go_here_first/$ ls
readme.txt    executable.exe
AILEE@localhost: go_here_first/$ read readme.txt
The "run" command runs .exe files.

You can use the command "cd .." to move up a directory
AILEE@localhost: go_here_first/$ run executable.exe
I am an executable file! You just ran me.
AILEE@localhost: go_here_first/$
```

Fig. 5. Filesystem navigation

The directories are colored light blue, executable files are colored light green and all have a .exe extension, and regular files are colored white and must have a .something extension (Fig. 5). One difference between AILEE and a real-life Linux terminal is that the *ls* command cannot be given an argument in the game, and thus can only be used in the current directory.

IV. CONCLUSION

In summary, this project dives into many core concepts and facets of penetration testing, and simulates them to feel like the real-world counterparts. Many of the commands that simulate complicated software are coded creatively to look realistic even though they only work in the specific instances inside the game. AILEE is a demo, and there is much opportunity to expand the game into something far more complex and realistic if enough time and energy was dedicated to doing so.

REFERENCES

- [1] Repl.it, “The world’s leading online coding platform,” repl.it. [Online]. Available: <https://repl.it/site/features>. [Accessed: 02-May-2019].
- [2] A. M. Kuchling and E. S. Raymond, “Curses Programming with Python[.],” Curses Programming with Python - Python 3.7.3 documentation. [Online]. Available: <https://docs.python.org/3/howto/curses.html>. [Accessed: 02-May-2019].