

CSci487 Penetration Testing Project: AILEE

Grant Haataja
UND Computer Science
Grand Forks, ND, USA
grant.haataja@und.edu

David Wilson
UND Computer Science
Grand Forks, ND, USA
david.andrew.wilson@und.edu

Michael Turnbull
UND Computer Science
Monroe, NH, USA
michael.turnbull@und.edu

Abstract—This document details the planning, development, and workings of the penetration testing game AILEE, created as a final project for CSCI 487 Penetration Testing class at the University of North Dakota.

I. INTRODUCTION

For this project on penetration testing topics, a hacking simulation game was created. The premise of the game is as follows: the user plays the role of a penetration-testing AI software named AILEE, which stands for Artificial Intelligence Linux Exploit Environment. The game takes place exclusively in a Linux-style terminal environment, with a limited arsenal of commands for the player to use. As the player progresses through the game and learns as an AI, the commands available for use increase. Throughout the game, the player is given typed instructions and information from the AIs administrator to assist in learning.

There are two targets to hack in this demo, although there is much potential for expansion. The game uses simulated port scanning, vulnerability scanning, exploitation, and other penetration testing tools to mimic real-life penetration testing methods. Additionally, the game features a storyline with three possible endings, depending on player actions. Special care was taken to handle proper sequence of events.

II. INVESTIGATION

A. Planning the Project

Before beginning the development of the game, a suitable platform to run the environment needed to be found. The website Repl.it was decided upon, due to their extensive language support and the ability for multiple people to work simultaneously and have all changes automatically saved to the cloud. [1] The Multiplayer mode, as this feature was called, still had a lot of bugs, so forking the project and saving work manually was still necessary, but overall it made the development of AILEE much smoother.

Python3 was selected as the programming language of choice, due to its ease of scripting and strong object-oriented nature. The various classes corresponding to different aspects of the game and environment would be programmed separately, as well as Python scripts for each command available to the player, and every storyline event that could be run. The original plan was for there to be three different targets for the player to hack, but due to time limitations the scope was decreased to two targets.

To enable smooth graphics for the intro screen and the games ending events, the Python Curses library was referenced and used extensively. [2] This provided the ability to control keyboard input while text displayed on the screen or the ending event graphics played, to increase the smoothness of gameplay.

III. PROJECT DESCRIPTION

A. Intro Screen

For the graphics of the intro screen for the game, ASCII art was used to spell the word AILEE, along with a selection for New Game or Exit. The user can move between the selection using the up or down arrow keys and choose by pressing the enter key. Selecting Exit will cause the terminal session within Repl.it to exit and the game will have to be run again, selecting New Game creates a new session and runs the game.

In addition to these, pressing the up arrow six times in a row will show a hidden third selection, Skip Dialog. This will run the game without displaying any of the instructions and information from the administrator to AILEE, and was very useful for testing the game during development. This mode is not explained or mentioned in the game, as it is not recommended to play without reading the dialogue.

The intro screen makes use of the Python curses library to allow smooth use of the arrow keys keyboard input and prevent buggy graphics.

B. Starting the Game

Upon choosing New Game, the user watches as the administrator logs into their account and launches AILEE.exe to start a new shell. After the shell loads, the first event triggers and text displays on the screen to inform the user what is going on. The administrator gives a brief explanation, and then the user is free to experiment with the Linux-style terminal environment. The terminal runs in the Shell class, (in tandem with the Game and DoStory classes), which supports multiple terminals on various computers. The code for the Shell class is as follows:

```
1 # -*- coding: utf-8 -*-
2
3 from termcolor import colored
4 import funfunctions
5
6 import time
7 import traceback
8 import sys
9 import random
10
```

```

11 import executables
12 import events
13 from MainMenuException import MainMenuException
14
15 DEFAULT_PROMPT = colored("AILEE@{COMP}: {CWD}$ ", '
green')
16
17 CMD_NOT_FOUND_STRS = [
18     "command not found",
19     "Nope, don't know that one",
20     "This isn't Google",
21     "NOOB!",
22     "Segmentation fault (core dumped)",
23 ]
24
25
26
27 class Shell(object):
28     """
29     Like a seashell.
30     """
31
32     def __init__(self, computer, user, agent=None,
33                  cwd=None, game=None):
34         """
35         Create a shell.
36         """
37
38         self.computer = computer
39         self.user = user
40         self.agent = agent
41         self.cwd = cwd or computer.fs
42         self.prompt = DEFAULT_PROMPT
43         self.running = False
44         self._command_dictionary = {}
45         self.variables = {}
46         self.game = game
47         self.history = []
48
49         self._setup()
50
51     def _setup(self):
52         funfunctions.clear()
53         s = "Loading new shell"
54
55         print(s, end='\r')
56         i = 0
57
58         # load command dictionary
59         for module in executables._all_:
60             self._command_dictionary.update({module:
61             getattr(executables, module).run})
62             print(s + '.' * i, end='\r')
63             i += 1
64             time.sleep(0.1)
65         time.sleep(0.3)
66         funfunctions.clear()
67         # print(constants.title)
68
69     def _get_command_from_str(self, command_str):
70         """
71         Takes a command name, returns the executable
72         object.
73         """
74
75         if command_str == '':
76             return False
77         if command_str not in self.game.
78         allowed_commands:
79             return None
80         cmd = self._command_dictionary[command_str]
81         return cmd
82
83     def run_command(self, command, args, **kwargs):

```

```

80
81     """
82     Runs a command.
83
84     Input must be a runnable command that
85     accepts **kwargs.
86     """
87
88     command(
89         *args,
90         computer=self.computer,
91         cwd=self.cwd,
92         user=self.user,
93         agent=self.agent,
94         shell=self,
95         game=self.game,
96         **kwargs
97     )
98
99     def take_input(self):
100         user_input = input(self.prompt.format(
101             COMP=str(self.computer.name),
102             CWD=str(self.cwd),
103             USER=self.user),
104         )
105
106         parts = [p.strip() for p in user_input.split(
107             ' ')]
108         command = parts[0]
109         args = parts[1:]
110
111         return command, args
112
113     def one_command(self):
114         command, args = self.take_input()
115         cmd = self._get_command_from_str(command)
116         if cmd is None:
117             self.cmd_not_found()
118             return
119         elif cmd is False:
120             return # nothing on empty commands
121         cname = cmd.__module__.split('.')[1]
122         if not cname == 'doStory':
123             self.game.history.append([cname, args])
124             self.history.append([cname, args])
125
126         if not (command or args):
127             return # skip empty input
128         self.run_command(cmd, args)
129
130     def halt(self):
131         self.running = False
132
133     def cmd_not_found(self):
134         self.history.append([None, []])
135         self.game.history.append([None, []])
136         print("Command not found")
137         # print(random.choice(CMD_NOT_FOUND_STRS))
138
139     def start_shell_loop(self):
140         self.running = True
141         while self.running:
142             try:
143                 self.run_command(events.doStory.run,
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999

```

```

151         #print(colored(
152             # "Something went wrong. I'm not
quite sure what. "
153             # "Maybe try again?", 'red'))
154         # Uncomment VV for full tracebacks
155         einfo = sys.exc_info()
156         traceback.print_exception(*einfo)

```

The user is encouraged to try out the various possible commands, which can be displayed using the *help* command. The story continues after the user has ran ten commands, (they can be the same or different commands, it doesn't matter).




Fig. 1. Shell flow diagram

C. Gameplay and Commands

As the game progresses, the user will utilize the available penetration testing tools to gain access to the target computers. There are tools for finding IP addresses, port scanning, vulnerability scanning, exploitation, password cracking, and connecting through the ftp file sharing network. Generally, some of the commands require the results from running other commands in order to be run successfully.

In particular, the *exploit* command is extremely useful for gaining access to other computers. This command is similar to the Metasploit framework, commonly used in real-life penetration testing. In the game, as the player uncovers exploits in different computers with the *vscan* command, those exploits are added to a global database of exploits which the user can then pick from in the *exploit* command. Exploits are specific to a port on a computer, and if correctly used, will successfully open a new shell on the target computer.

```

1  """
2  "Start the exploitation station."
3
4  Description: exploit is a software used for gaining
unauthorized access to remote
5  computers. There are different exploits within the
framework for the user to choose
6  from. Upon running the exploit software, user will
need to choose the exploit to
7  try, enter the target IP address, enter the port to
connect to, and then type
8  "run" to attempt the exploit.
9
10 Usage: exploit
11 """
12 # Would like 2 different exploit options to start
with
13 # one for 'windoors' systems and one for 'lionux'
systems
14
15 from funfunctions import dots
16
17 def run(*args, **kwargs):
18     emptyList = True
19     for arg in args:
20         if arg:
21             emptyList = False
22     assert len(args) == 0 or emptyList, "Invalid use
of exploit.\n\nUsage: exploit"
23
24     print('***Welcome to the exploitation station***')
25     print('Available exploits:')
26
27     vdb = kwargs['game'].vuln_database
28     visible_exploits = [name for name in vdb if not
name.startswith('_')]
29     exploits = {i+1: vdb[i] for i in range(len(
visible_exploits))}
30
31     for i, exploit in exploits.items():
32         print("{:2d}. {}".format(i, exploit))
33
34     sel = 0
35     while sel not in exploits.keys():
36         try:
37             sel = int(input("Exploit selection > "))
38         except ValueError:
39             print("Enter a number")
40
41

```

```

42 addr = input("Enter target IP address > ")
43 port = -1
44 while port < 0:
45     try:
46         port = int(input("Select port to use > "))
47     except ValueError:
48         print("Enter a number")
49 chkrun = input("Type 'run' to begin exploitation > ")
50
51 if chkrun != 'run':
52     return
53
54 dots("Running exploit", 9, 0.333)
55
56 try:
57     box = kwargs['game'].network[addr]
58     vuln = exploits[sel]
59 except KeyError:
60     print("Invalid options specified.")
61     return
62
63 if (vuln in box.vulns) and \
64     (port == box.vulns[vuln][1]):
65     box.vulns[vuln][0] = True
66     print("Exploit success!")
67     kwargs['shell'].run_command(
68         kwargs['shell'].get_command_from_str('
69         shell'),
70         ['new', addr]
71     )
72 else:
73     print("Exploit failed")

```

Above is the code for the *exploit* command in the game. In terms of options, it does not compare to the Metasploit framework, but the goal was to create it to feel similarly in the terminal environment.

```

AILEE@localhost: /$ exploit
***Welcome to the exploitation station***
Available exploits:
1. WP45_702 reverse tcp shell
2. LI38_612 meta ssh security flaw
Exploit selection > 1
Enter target IP address > 120.45.30.6
Select port to use > 1100
Type 'run' to begin exploitation > run
Running exploit....

```

Fig. 2. Running the *exploit* executable

First, the user enters the number corresponding to the exploit they wish to run. Then, the target IP address is entered, followed by the specific port, and finally the command 'run' must be entered and the exploitation software will attempt to gain access to the target (Fig. 2)

If the exploit is successful, the screen will clear and the words "Loading new shell...." will appear on the screen with increasing dots as the shell loads (Fig. 3)

Once the shell loads, the name of the computer exploited will be shown before the `/ $` symbol where commands are typed (Fig. 4).

```

Loading new shell.....

```

Fig. 3. Gaining a shell on target machine

```

AILEE@safeandsecurebanking: /$

```

Fig. 4. A new shell on an exploited target

Most of the other commands play an important role in the game, with a few exceptions that were included for comedic value.

D. Events and Storyline

The story development of the game is controlled by event scripts that are triggered at specific times. Running the events in the proper order is critical for the game to play as planned. The first event is run immediately after the game loads its first shell on the localhost computer. Each event after that has a condition that must be met to trigger it. The second event runs after ten commands have been run, the third event runs after the *pscan* command runs, and so on. Each event runs instructions for the user that should allow them to trigger the next event and progress in the game.

```

1 #Third dialogue of the game
2 #triggers after port scanning has been done
3 import time
4 from funfunctions import typewriter
5 from termcolor import colored
6
7 def check_run(*args, **kwargs):
8     # check for 'pscan' in history, most recently run,
9     # and exactly once
10    if len(kwargs['game'].history) == 0:
11        return False
12    if not 'event2' in kwargs['game'].events_run:
13        return False
14
15    command = ['pscan', ['120.45.30.6']]
16
17    a = kwargs['game'].history[-1] == command
18    return a

```

```

18
19 def run(*args, **kwargs):
20     # using kwargs we can get access to the shell, and
21     # from within the event
22     # have the user run commands
23
24     color = 'cyan'
25     game = kwargs['game']
26
27     text = [
28         '\nGood job, Ailee. I see you have successfully
29         found which open ports are running\non our
30         target.\n\n',
31         'Our next step is to run our vulnerability
32         scanning software against the target\nto see if
33         we can use any exploits against them.\n\n'
34     ]
35     filename = 'message03.txt'
36     if filename not in game.eventLogDir:
37         game.eventLogDir.addFile(filename, colored('',
38             join(text), color))
39
40     if not game.skip_dialog:
41         typewriter(colored(text[0], color))
42         typewriter(colored(text[1], color))
43     else:
44         print(colored('Event3 text skipped', 'red'))
45
46     # Create chat log in AILEE's directory

```

This is how the scripts for the events are written, implementing a custom-built "typewriter" function created to display text to the screen word by word as if it were typed, and using a blue color to differentiate it from the rest of the game text.

```

AILEE@localhost: /$ iplist -a safeandsecurebanking@ssb.com
127.0.0.1      localhost
120.45.30.6    safeandsecurebanking
AILEE@localhost: /$ pscan 120.45.30.6
Scanning 120.45.30.6...
Searching for open ports...
Results:
Port  Status  Service
-----
22    Open    ssh
80    Open    http
1100  Open    unknown

Good job, Ailee. I see you have successfully found which open ports are running
on our target.

Our next step is to run our vulnerability scanning software against the target
to see if we can use any exploits against them.
AILEE@localhost: /$

```

Fig. 5. The dialogue for event 3

This is the text for the third event (Fig. 5), which triggers after the user runs the command *pscan* against the first target IP address.

There are three special events that do not trigger in a normal play-through of the game. These events will only trigger if the player thinks for themselves and uses information found in the game creatively and without instruction from the administrator. Interestingly, if the user follows the instructions without diverging on their own, they will lose the game during the final hack. The only way to win is by finding what the information leads to and changing the fate of the game before attempting to exploit the final target.

E. Computers and Filesystems

AILEE uses a filesystem structure that feels like a Linux terminal. There are a total of four computers in the game,




Fig. 6. The sequence of events in play order

localhost (AILEE's home computer), the two targets, and one other computer. Each computer has a unique filesystem, with directories and files. As time was limited, the *bin* and *log* directories were left empty on all computers, but the *home* directories all have files in them that either pertain to the gameplay or exist for comedic value or storyline development.

To navigate the filesystems, the traditional Linux commands *ls* and *cd* are used, as well as the commands *read* and *run*, which display file text and run executable files, respectively.

```

1 import hashlib
2
3
4 class Permissions(object):
5     """
6     rwxrwx
7     ||||\ Owner exec
8     ||||\ Owner write
9     |||\ Owner read
10    ||\ General user exec
11    |\ General user write
12    \ General user read
13    """
14

```

```

15 def __init__(self, perms):
16     self._bits = perms
17     assert len(self._bits) == 6
18
19 def _set_bit(self, n, newval):
20     bits = list(self._bits)
21     bits[n] = newval
22     self._bits = ''.join(bits)
23
24 def __str__(self):
25     return self._bits
26
27 def __eq__(self, other):
28     if isinstance(other, Permissions):
29         return self._bits == other._bits
30     elif isinstance(other, str):
31         return self._bits == other
32     else:
33         return False
34
35 def __hash__(self):
36     return hash(self._bits)
37
38 def __getitem__(self, bit):
39     return self._bits[bit]
40
41 def __setitem__(self, bit, newval):
42     self._set_bit(bit, newval)
43
44 @property
45 def read_users(self):
46     return self._bits[0] == 'r'
47
48 @read_users.setter
49 def read_users(self, allowed):
50     self._set_bit(0, 'r' if allowed else '-')
51
52 @property
53 def write_users(self):
54     return self._bits[1] == 'w'
55
56 @write_users.setter
57 def write_users(self, allowed):
58     self._set_bit(1, 'w' if allowed else '-')
59
60 @property
61 def exec_users(self):
62     return self._bits[2] == 'x'
63
64 @exec_users.setter
65 def exec_users(self, allowed):
66     self._set_bit(2, 'x' if allowed else '-')
67
68 @property
69 def read_owner(self):
70     return self._bits[3] == 'r'
71
72 @read_owner.setter
73 def read_owner(self, allowed):
74     self._set_bit(3, 'r' if allowed else '-')
75
76 @property
77 def write_owner(self):
78     return self._bits[4] == 'w'
79
80 @write_owner.setter
81 def write_owner(self, allowed):
82     self._set_bit(4, 'w' if allowed else '-')
83
84 @property
85 def exec_owner(self):
86     return self._bits[5] == 'x'
87
88 @exec_owner.setter

```

```

89 def exec_owner(self, allowed):
90     self._set_bit(5, 'x' if allowed else '-')
91
92
93 class Directory(object):
94     """
95     Tree structure of directories and files
96     """
97
98     def __init__(self, name=None, parent=None,
99                 children=None, permissions='r-xr-x',
100                 owner=None):
101         self.name = name or ''
102         if parent is None:
103             self.parent = self
104         else:
105             self.parent = parent
106         self.permissions = Permissions(permissions)
107         self.owner = owner or 'n/a'
108         self.children = {
109             '.': self,
110             '..': self.parent
111         }
112         if type(children) is dict:
113             self.children.update(children)
114
115     def mkdir(self, name, **kwargs):
116         assert (name not in self.children), '
117             Directory already exists'
118         newDir = Directory(name=name, parent=self,
119                             **kwargs)
120         self.children.update({name: newDir})
121         return newDir
122
123     def addFile(self, fileName, fileContents, **
124                 kwargs):
125         assert (fileName not in self.children), '
126             File already exists'
127         assert ('.' in fileName), 'File has no type'
128         newFile = File(fileName, fileContents, **
129                             kwargs)
130         self.children.update({fileName: newFile})
131         return newFile
132
133     def addPrebuiltFile(self, file, **kwargs):
134         assert (file.name not in self.children), "
135             File already exists"
136         self.children.update({file.name: file})
137         return file
138
139     def rmFile(self, fileName):
140         assert (fileName in self.children), "File
141             does not exist"
142         assert ('.' in fileName), "File has no type"
143         del self.children[fileName]
144
145     def __iter__(self):
146         return (fName for fName in self.children)
147
148     def __repr__(self, base=True):
149         output = ""
150         if self.parent is not self:
151             up1 = self.parent
152             while isinstance(up1, Directory):
153                 output = up1.name + "/" + output
154                 if up1 is up1.parent:
155                     break
156             else:
157                 up1 = up1.parent
158         output += self.name
159         if base:
160             output += '/'
161         return output
162
163     __str__ = __repr__ # set __str__ as the same

```



```

155     method as __repr__
156
157     def __getitem__(self, item):
158         assert (item in self.children), "File or
159         Directory not found"
160         return self.children[item]
161
162     def __len__(self):
163         # Remove the "." and ".." folders from the
164         size
165         # They're not really there
166         return len(self.children) - 2
167
168 class File(object):
169     """
170     Stores things. Like data, machine code, and
171     blackmail
172     """
173     def __init__(self, name, data='', permissions='r
174     —r—', owner=None, **kwargs):
175         self.name = name
176         self._data = data
177         self.permissions = Permissions(permissions)
178         self.owner = owner or 'n/a'
179         self._original_hash = hashlib.md5(data.
180         encode('utf-8')).hexdigest()
181         self._current_hash = hashlib.md5(data.encode
182         ('utf-8')).hexdigest()
183         self._kwargs = kwargs
184
185     def append(self, data):
186         self._data += data
187         self._current_hash = hashlib.md5(self._data.
188         encode('utf-8')).hexdigest()
189
190     @property
191     def original_hash(self):
192         return self._original_hash
193
194     @property
195     def current_hash(self):
196         return self._current_hash
197
198     @property
199     def data(self):
200         return self._data
201
202     @data.setter
203     def data(self, newdata):
204         self._data = newdata
205         self._current_hash = hashlib.md5(self._data.
206         encode('utf-8')).hexdigest()
207
208     def __repr__(self):
209         return self.name
210     __str__ = __repr__ # set __str__ as the same
211     method as __repr__
212
213     def __len__(self):
214         return len(self._data)

```

This is the code for the structure and mechanics of the computer filesystems. Similar to Linux, both files and folders have and use discrete permissions, marking certain files as readable, writable, and executable. While there are not yet any provisions for editing/creating files in-game¹, the permissions architecture is in place for adding future file-editing utilities.

¹The `gcc` command creates a file `a.out`, which promptly throws a segmentation fault.

Executable files are created from a separate filesystem constructor. Each executable file simply is a `File` object with the executable bit set in its permissions object, and the file contents are pure Python code that executes when the file is run via the `run` command. To verify that arbitrary code is not run (which would break the game), executable files compare hashes from creation to runtime to and will not run if the contents have been altered.

```

AILEE@localhost: /$ ls
chat_log      go_here_first  folder1
AILEE@localhost: /$ cd go_here_first
AILEE@localhost: go_here_first/$ ls
readme.txt    executable.exe
AILEE@localhost: go_here_first/$ read readme.txt
The "run" command runs .exe files.

You can use the command "cd .." to move up a directory
AILEE@localhost: go_here_first/$ run executable.exe
I am an executable file! You just ran me.
AILEE@localhost: go_here_first/$

```

Fig. 7. Filesystem navigation

Directories are colored light blue, executables are light green, and regular files are white. Because of the permissions associated with each file and directory, and the fact that `File` and `Directory` objects are implemented as separate classes, there are no special requirements to file/folder names or attributes. However, due to the difficult implementation of a directory tree, the `ls` command cannot be given a path argument as in real life, and thus can only be used in the current directory.

IV. CONCLUSION

In summary, this project dives into many core concepts and facets of penetration testing, and simulates them to feel like the real-world counterparts. Many of the commands that simulate complicated software are coded creatively to look realistic even though they only work in the specific instances inside the game. AILEE is a demo, and there is much opportunity to expand the game into something far more complex and realistic if enough time and energy was dedicated to doing so.

REFERENCES

- [1] Repl.it, "The world's leading online coding platform," repl.it. [Online]. Available: <https://repl.it/site/features>. [Accessed: 02-May-2019].
- [2] A. M. Kuchling and E. S. Raymond, "Curses Programming with Python," Curses Programming with Python - Python 3.7.3 documentation. [Online]. Available: <https://docs.python.org/3/howto/curses.html>. [Accessed: 02-May-2019].