

The Crystal Series is our most versatile MicroLED video wall — delivering stunning BlackFire contrast at an accessible price point. Available in 0.9mm and 1.2mm pixel pitch, Crystal fits everything from intimate home theaters to expansive commercial installations.

P0.9

0.9375mm pixel pitch
640 × 360 per cabinet
ULTRA-FINE DETAIL

P1.2

1.25mm pixel pitch
480 × 270 per cabinet
VERSATILE PERFORMANCE

BLACKFIRE ANTI-GLARE**600**

NITS BRIGHTNESS

Extended
GRAYSCALE**3,840Hz**

REFRESH RATE

10K:1

CONTRAST RATIO

4kg

PER PANEL

TECHNICAL SPECIFICATIONS

PARAMETER	P0.9 (0.9375MM)	P1.2 (1.25MM)
CABINET SIZE	600 × 337.5 × 39.75mm	
CABINET RESOLUTION	640 × 360 dots	480 × 270 dots
MODULE SIZE	150 × 168.75mm (8 modules/cabinet)	
BRIGHTNESS	600 nits	
MAX POWER CONSUMPTION	75W / cabinet	70W / cabinet
ESTIMATED TYPICAL THERMAL LOAD*	102–128 BTU/h / cabinet 47–59 BTU/h/ft ²	96–119 BTU/h / cabinet 44–55 BTU/h/ft ²
MAXIMUM THERMAL LOAD†	256 BTU/h / cabinet 117 BTU/h/ft ²	239 BTU/h / cabinet 110 BTU/h/ft ²
PANEL REFRESH RATE	3,840Hz	
VIDEO REFRESH RATE	60Hz	
CONTRAST RATIO	100,000:1	
GRAYSCALE	Extended	
LED TECHNOLOGY	BlackFire	
POWER SUPPLY	3.8V / 30A	
MAINTENANCE	100% Front Access — Magnetic Modules	
SURFACE PROTECTION	Dustproof, moisture-proof, 4H hardness, scrubbable	

*Planning estimate at 40–50% of rated maximum; actual load varies with brightness and content. †Display cabinets only. Use maximum for HVAC sizing unless project-specific measured data is approved. External processing and rack equipment are excluded.

KEY FEATURES

- BlackFire low-glare surface for deep blacks and strong ambient-light contrast
- Golden 16:9 ratio — seamlessly build 2K, 4K, or 8K configurations
- Ultra-lightweight 4kg panels for flexible installation
- Multi-level calibration ensures pixel-perfect color uniformity
- Front-serviceable magnetic modules for tool-free maintenance
- Custom sizing from ~110" to 270"+ diagonal

APPLICATIONS

HOME THEATERS

MEDIA ROOMS

CONFERENCE ROOMS

LOBBIES

SHOWROOMS

CORPORATE