

The Doublet Series delivers reliable MicroLED performance for large-format commercial installations where viewing distances are greater and value matters. At 1.5mm pixel pitch, Doublet is built for corporate lobbies, retail displays, houses of worship, and any space where impact and reliability come first.

P1.5

1.56mm pixel pitch
384 × 216 per cabinet
VALUE AT SCALE

DIRECT-VIEW MICROLED

FRONT ACCESS

600

NITS BRIGHTNESS

Extended

GRAYSCALE

3,840Hz

REFRESH RATE

10K:1

CONTRAST RATIO

4kg

PER PANEL

TECHNICAL SPECIFICATIONS

PARAMETER	P1.5 (1.56MM)
CABINET SIZE	600 × 337.5 × 39.75mm
CABINET RESOLUTION	384 × 216 dots
MODULE SIZE	150 × 168.75mm (8 modules/cabinet)
BRIGHTNESS	600 nits
MAX POWER CONSUMPTION	70W / cabinet
ESTIMATED TYPICAL THERMAL LOAD*	96–119 BTU/h / cabinet · 44–55 BTU/h/ft ²
MAXIMUM THERMAL LOAD†	239 BTU/h / cabinet · 110 BTU/h/ft ²
PANEL REFRESH RATE	3,840Hz
VIDEO REFRESH RATE	60Hz
CONTRAST RATIO	100,000:1
GRAYSCALE	Extended
LED TECHNOLOGY	Direct-view MicroLED
POWER SUPPLY	3.8V / 30A
MAINTENANCE	100% Front Access — Magnetic Modules
SURFACE PROTECTION	Dustproof, moisture-proof, 4H hardness, scrubbable

*Planning estimate at 40–50% of rated maximum; actual load varies with brightness and content. †Display cabinets only. Use maximum for HVAC sizing unless project-specific measured data is approved. External processing and rack equipment are excluded.

KEY FEATURES

- Direct-view MicroLED architecture for deep blacks and excellent contrast
- Golden 16:9 ratio — seamlessly build 2K or 4K configurations
- Ultra-lightweight 4kg panels for flexible installation
- Multi-level calibration ensures pixel-perfect color uniformity
- Front-serviceable magnetic modules for tool-free maintenance
- Value-optimized for large format commercial installations

APPLICATIONS

CORPORATE LOBBIES

RETAIL

HOUSES OF WORSHIP

HOSPITALITY

EDUCATION

DIGITAL SIGNAGE