OPAL SCREENS

BOULDER SERIES

MICROLED VIDEO WALL SYSTEM — 240HZ

The Boulder Series pairs BlackFire contrast with SilkStream — our proprietary 240Hz refresh rate technology. With a 15,360Hz panel refresh rate (4× industry standard), Boulder delivers the smoothest, sharpest motion in fast-moving content of any video wall on the market. Built for sports, cinema, and live action.

SILKSTREAM

240Hz video refresh with **15,360Hz panel refresh rate** — 4× industry standard.
Eliminates flicker, banding, and motion blur for true 240fps content playback.

P0.9
0.9375mm pixel pitch
640 × 360 per cabinet

SILKSTREAM 240HZ

BLACKFIRE ANTI-GLARE

240Hz	15,360Hz	1,000	Extended	10K:1	4kg
VIDEO REFRESH	PANEL REFRESH	NITS BRIGHTNESS	GRAYSCALE	CONTRAST RATIO	PER PANEL

TECHNICAL SPECIFICATIONS

PARAMETER	BOULDER P0.9
PIXEL PITCH	0.9375mm
CABINET SIZE	600 × 337.5 × 39.75mm
CABINET RESOLUTION	640 × 360 dots
MODULE SIZE	150 × 168.75mm (8 modules/cabinet)
BRIGHTNESS	1,000 nits
MAX POWER CONSUMPTION	75W / panel
PANEL REFRESH RATE	15,360Hz (SilkStream — 4× standard)
VIDEO REFRESH RATE	240Hz (SilkStream)
CONTRAST RATIO	10,000:1
GRAYSCALE	Extended
LED TECHNOLOGY	Flip-chip COB (BlackFire + SilkStream)
POWER SUPPLY	3.8V / 30A
MAINTENANCE	100% Front Access — Magnetic Modules
SURFACE PROTECTION	Dustproof, moisture-proof, 4H hardness, scrubbable

KEY FEATURES

- SilkStream 240Hz — true 240fps playback for sports and fast action
- 1,000 nits brightness for vibrant, high-impact visuals
- Multi-level calibration for pixel-perfect uniformity
- 15,360Hz panel refresh eliminates flicker, banding, and motion blur
- BlackFire anti-glare COB for deep blacks and zero reflections
- Front-serviceable magnetic modules for tool-free maintenance

APPLICATIONS

SPORTS VIEWING | HOME CINEMA | LIVE EVENTS | BROADCAST | PREMIUM RESIDENTIAL

CE CB FCC ETL ROHS

info@opalscreens.com | opalscreens.com

© 2026 Opal Screens. All rights reserved. Specifications subject to change without notice.