OPAL SCREENS

DOUBLET SERIES

MICROLED VIDEO WALL SYSTEM

The Doublet Series delivers reliable MicroLED performance for large-format commercial installations where viewing distances are greater and value matters. At 1.5mm pixel pitch, Doublet is built for corporate lobbies, retail displays, houses of worship, and any space where impact and reliability come first.

P1.5

1.56mm pixel pitch
384 × 216 per cabinet
VALUE AT SCALE

FLIP-CHIP COB | FRONT ACCESS

600	Extended	3,840Hz	10K:1	4kg
NITS BRIGHTNESS	GRAYSCALE	REFRESH RATE	CONTRAST RATIO	PER PANEL

TECHNICAL SPECIFICATIONS

PARAMETER	P1.5 (1.56MM)
CABINET SIZE	600 × 337.5 × 39.75mm
CABINET RESOLUTION	384 × 216 dots
MODULE SIZE	150 × 168.75mm (8 modules/cabinet)
BRIGHTNESS	600 nits
MAX POWER CONSUMPTION	70W / panel
PANEL REFRESH RATE	3,840Hz
VIDEO REFRESH RATE	60Hz
CONTRAST RATIO	10,000:1
GRAYSCALE	Extended
LED TECHNOLOGY	Flip-chip COB
POWER SUPPLY	3.8V / 30A
MAINTENANCE	100% Front Access — Magnetic Modules
SURFACE PROTECTION	Dustproof, moisture-proof, 4H hardness, scrubbable

KEY FEATURES

- Flip-chip COB technology for deep blacks and excellent contrast
- Golden 16:9 ratio — seamlessly build 2K or 4K configurations
- Ultra-lightweight 4kg panels for flexible installation
- Multi-level calibration ensures pixel-perfect color uniformity
- Front-serviceable magnetic modules for tool-free maintenance
- Value-optimized for large format commercial installations

APPLICATIONS

CORPORATE LOBBIES | RETAIL | HOUSES OF WORSHIP | HOSPITALITY | EDUCATION | DIGITAL SIGNAGE

CE | CB | FCC | ETL | ROHS

info@opalscreens.com | opalscreens.com

© 2026 Opal Screens. All rights reserved. Specifications subject to change without notice.