

The Crystal Series combines BlackFire contrast with SilkStream 384Hz full-panel refresh and 1,000-nit brightness. It supports 4K60 or 1080p120 video input for private cinemas and residential media rooms.

P0.9

0.9375mm pixel pitch
640 × 360 per cabinet
ULTRA-FINE DETAIL

P1.2

1.25mm pixel pitch
480 × 270 per cabinet
VERSATILE PERFORMANCE

BLACKFIRE SILKSTREAM

1,000

NITS BRIGHTNESS

Extended
GRAYSCALE**384Hz**

FULL-PANEL REFRESH

100K:1

CONTRAST RATIO

4kg

PER PANEL

TECHNICAL SPECIFICATIONS

PARAMETER	P0.9 (0.9375MM)	P1.2 (1.25MM)
CABINET SIZE	600 × 337.5 × 39.75mm	
CABINET RESOLUTION	640 × 360 dots	480 × 270 dots
MODULE SIZE	150 × 168.75mm (8 modules/cabinet)	
BRIGHTNESS	1,000 nits	
MAX POWER CONSUMPTION	Confirmation pending for current configuration	
TYPICAL THERMAL LOAD	Not yet specified for current configuration	
MAXIMUM THERMAL LOAD	Confirmation pending for current configuration	
FULL-PANEL REFRESH	384Hz (SilkStream)	
VIDEO INPUT	4K60 / 1080p120 via HDMI 2.0	
CONTRAST RATIO	100,000:1	
GRAYSCALE	Extended	
DISPLAY TECHNOLOGY	BlackFire + SilkStream	
POWER SUPPLY	Confirm for selected configuration	
MAINTENANCE	100% Front Access — Magnetic Modules	
SURFACE PROTECTION	Dustproof, moisture-proof, 4H hardness, scrubbable	

Electrical and cooling loads for the 1,000-nit SilkStream configuration must be confirmed with your authorized dealer before design. Do not use earlier Crystal power figures for this configuration. External processing and rack equipment require separate allowances.

KEY FEATURES

- BlackFire low-glare surface for deep blacks and strong ambient-light contrast
- Golden 16:9 ratio — seamlessly build 2K, 4K, or 8K configurations
- Ultra-lightweight 4kg panels for flexible installation
- SilkStream 384Hz panel refresh with video input up to 120Hz
- Front-serviceable magnetic modules for tool-free maintenance
- Custom sizing from ~110" to 270"+ diagonal

APPLICATIONS

HOME THEATERS

MEDIA ROOMS

CONFERENCE ROOMS

LOBBIES

SHOWROOMS

CORPORATE