

Doublet combines BlackFire technology with 0.9mm, 1.2mm and 1.5mm nominal pixel-pitch options. Select the pitch to suit the display dimensions and viewing distance. Video input supports up to 60Hz.

P0.9

0.9mm nominal pixel pitch

P1.2

1.2mm nominal pixel pitch

P1.5

1.5mm nominal pixel pitch

BLACKFIRE**3**

PITCH OPTIONS

60Hz

MAXIMUM VIDEO INPUT

BlackFire

DISPLAY TECHNOLOGY

TECHNICAL SPECIFICATIONS

PARAMETER	DOUBLET SERIES
NOMINAL PIXEL PITCH	0.9mm / 1.2mm / 1.5mm
DISPLAY TECHNOLOGY	BlackFire MicroLED
MAXIMUM VIDEO INPUT	60Hz
VIDEO INPUT CONFIGURATION	4K60 via HDMI 2.0
CABINET DIMENSIONS & RESOLUTION	Confirm for selected pitch and configuration
MODULE SIZE & CABINET WEIGHT	Confirm for selected pitch and configuration
MAX POWER & POWER SUPPLY	Confirmation pending for current configuration
TYPICAL & MAXIMUM THERMAL LOAD	Confirmation pending for current configuration

Pitch values are nominal product classes. Request the exact pitch, cabinet layout, photometric specifications and electrical schedule for the selected BlackFire configuration before design. Earlier P1.5 cabinet and thermal data must not be assumed to apply across the updated range.

KEY FEATURES

- BlackFire technology across the Doublet range
- Video input up to 60Hz
- 0.9mm, 1.2mm and 1.5mm nominal pitch options
- Dealer-led display sizing and system specification

APPLICATIONS

CORPORATE LOBBIES

RETAIL

HOUSES OF WORSHIP

HOSPITALITY

EDUCATION

DIGITAL SIGNAGE