

Onyx offers 0.7mm and 0.6mm pixel-pitch options for close-viewing rooms. BlackFire contrast and NanoPix color precision support detailed images in dedicated theaters, media rooms and art displays. Video input supports up to 60Hz.

P0.7

0.7mm nominal pixel pitch
Cabinet layout: confirm per project
ULTRA-FINE PRECISION

P0.6

0.6mm nominal pixel pitch
Cabinet layout: confirm per project
ULTRA-FINE PRECISION

BLACKFIRE NANOPIX**600**

NITS BRIGHTNESS

Extended

GRayscale

3,840Hz

REFRESH RATE

100K:1

CONTRAST RATIO

60Hz

VIDEO INPUT

TECHNICAL SPECIFICATIONS

PARAMETER	P0.7 / P0.6
NOMINAL PIXEL PITCH	0.7mm or 0.6mm
CABINET SIZE / RESOLUTION	Confirmation pending per pitch
MODULE SIZE / WEIGHT	Confirmation pending per pitch
BRIGHTNESS	600 nits
MAX POWER CONSUMPTION	Confirmation pending per pitch
TYPICAL / MAXIMUM THERMAL LOAD	Confirmation pending per pitch
PANEL REFRESH RATE	3,840Hz
VIDEO REFRESH RATE	60Hz
CONTRAST RATIO	100,000:1
GRayscale	Extended
LED TECHNOLOGY	BlackFire + NanoPix
POWER SUPPLY	Confirmation pending per pitch
MAINTENANCE	100% Front Access — Magnetic Modules
SURFACE PROTECTION	Dustproof, moisture-proof, 4H hardness, scrubbable

0.7mm and 0.6mm are the nominal pitch designations. Confirm exact pixel spacing, cabinet geometry and electrical/thermal loads for the selected configuration before design. Earlier single-configuration values must not be applied to both options. External processing and rack equipment require separate allowances.

KEY FEATURES

- BlackFire low-glare surface for deep blacks and strong ambient-light contrast
- 0.7mm and 0.6mm nominal pixel-pitch options for close viewing
- Front-serviceable magnetic modules for tool-free maintenance
- NanoPix multi-level calibration for pixel-perfect color uniformity
- Cabinet layout specified around image size and native resolution
- Golden 16:9 ratio for seamless 4K and 8K configurations

APPLICATIONS

DEDICATED HOME THEATERS

EXECUTIVE BOARDROOMS

PRIVATE CINEMAS

LUXURY RESIDENTIAL

MUSEUMS & GALLERIES

CONTROL ROOMS