OPAL SCREENS

ONYX SERIES

MICROLED VIDEO WALL SYSTEM

The Onyx Series is the pinnacle of close-viewing clarity — delivering the finest pixel pitch in the Opal Screens lineup at just 0.625mm. Powered by both BlackFire anti-glare technology and NanoPix precision calibration, Onyx produces flawless images even at arm's length. Built for dedicated home theaters, executive boardrooms, and any environment where picture quality is everything.

P0.7
0.625mm pixel pitch
960 × 540 per cabinet
ULTRA-FINE PRECISION

BLACKFIRE ANTI-GLARE

nanoPix PRECISION CAL

600	Extended	3,840Hz	10K:1	4kg
NITS BRIGHTNESS	GRAYSCALE	REFRESH RATE	CONTRAST RATIO	PER PANEL

TECHNICAL SPECIFICATIONS

PARAMETER	P0.7 (0.625MM)
CABINET SIZE	600 × 337.5 × 39.75mm
CABINET RESOLUTION	960 × 540 dots
MODULE SIZE	150 × 168.75mm (8 modules/cabinet)
WEIGHT	4kg / panel
BRIGHTNESS	600 nits
MAX POWER CONSUMPTION	92W / panel
PANEL REFRESH RATE	3,840Hz
VIDEO REFRESH RATE	60Hz
CONTRAST RATIO	10,000:1
GRAYSCALE	Extended
LED TECHNOLOGY	Flip-chip COB (BlackFire + NanoPix)
POWER SUPPLY	3.8V / 30A
MAINTENANCE	100% Front Access — Magnetic Modules
SURFACE PROTECTION	Dustproof, moisture-proof, 4H hardness, scrubbable

KEY FEATURES

- BlackFire anti-glare COB technology for deep blacks and zero glare
- Ultra-fine 0.625mm pixel pitch — flawless at any viewing distance
- Front-serviceable magnetic modules for tool-free maintenance
- NanoPix multi-level calibration for pixel-perfect color uniformity
- 960×540 dots per cabinet — highest density in the lineup
- Golden 16:9 ratio for seamless 4K and 8K configurations

APPLICATIONS

DEDICATED HOME THEATERS | EXECUTIVE BOARDROOMS | PRIVATE CINEMAS | LUXURY RESIDENTIAL | MUSEUMS & GALLERIES | CONTROL ROOMS

Opal Screens — Premium MicroLED Video Walls

CE CB FCC ETL ROHS

info@opalscreens.com | opalscreens.com

© 2026 Opal Screens. All rights reserved. Specifications subject to change without notice.