OPAL SCREENS

WATER SERIES

OUTDOOR MICROLED VIDEO WALL SYSTEM

The Water Series is built to thrive outdoors. With IP65-rated panels, 4,000+ nit brightness, and an operating range from -20°C to 50°C, Water delivers vivid, high-contrast images in direct sunlight, rain, and extreme temperatures. Available in three pixel pitches for installations from poolside displays to large-format outdoor signage.

P1.2
1.25mm pixel pitch
384 × 432 per panel
FINE OUTDOOR

P1.5
1.5mm pixel pitch
320 × 360 per panel
VERSATILE OUTDOOR

P1.875
1.875mm pixel pitch
256 × 288 per panel
LARGE FORMAT

IP65 OUTDOOR | FRONT & REAR ACCESS

4,000+	IP65	3,840Hz	4K:1	100Khrs
NITS BRIGHTNESS	WEATHER RATED	REFRESH RATE	CONTRAST RATIO	LED LIFETIME

TECHNICAL SPECIFICATIONS

PARAMETER	P1.2 (1.25MM)	P1.5 (1.5MM)	P1.875 (1.875MM)
PANEL SIZE	480 × 540mm (full) / 480 × 270mm (half)		
PANEL RESOLUTION	384 × 432 / 384 × 216	320 × 360 / 320 × 180	256 × 288 / 256 × 144
MODULE SIZE	192 × 216mm / 192 × 108mm		
MODULES PER PANEL	2 × 2 (4 modules)		
WEIGHT	9kg (full) / 5kg (half)		
BRIGHTNESS	>3,500 nits	>4,000 nits	>4,000 nits
PANEL REFRESH RATE	1,920 – 3,840Hz		
VIDEO REFRESH RATE	60Hz		
CONTRAST RATIO	4,000:1		
PROCESSING DEPTH	14-bit		
VIEWING ANGLE	160° H / 160° V		
IP RATING	IP65 (front)		
CABINET MATERIAL	Aluminum		
SERVICING	Front and Rear		
OPERATING TEMP	-20°C to 50°C		
AVG POWER	216 W/m²		
MAX POWER	720 W/m²		
LED LIFETIME	100,000 hours		
COLORS	281 trillion		

KEY FEATURES

- IP65-rated front panels for rain, dust, and weather protection
- Aluminum cabinet construction — durable and lightweight
- Operating temperature range -20°C to 50°C
- 4,000+ nit brightness for direct sunlight visibility
- Front and rear serviceable for flexible installation
- 100,000-hour LED lifetime for years of outdoor use

APPLICATIONS

POOLSIDE & OUTDOOR ENTERTAINMENT | OUTDOOR SIGNAGE | STADIUMS & ARENAS | RESTAURANTS & BARS | HOSPITALITY | RETAIL STOREFRONTS

Opal Screens — Premium MicroLED Video Walls

CE | CB | FCC | ETL | ROHS | IP65

info@opalscreens.com | opalscreens.com

© 2026 Opal Screens. All rights reserved. Specifications subject to change without notice.