

(310) 965-0909 E mail: autotownmayor@sbcglobal.net

## Order Us to Pay Less!

[F National and and Subset Nation See Section 6.00 And Add See See Section 6.00 And Add See See See See See See See See See S	The Section of the Se	Redline Detection Smoke Pro Total Tech Diagnostic Leak Detector Kit part#: RDL-95-0003B  • New sensitive flow meter to locate the toughest to find leaks • Find leaks fast, drastically reducing diagnostic time • No need to use inert gas • OEM Approved smoke producing oil • The OEM Approved Smoke Pro® Total-Tech® is the world's best-
		selling diagnostic leak detector, and guaranteed to be the most profitable tool you will ever own  • Smoke Pro® gives technicians full-featured diagnostic capabilities to detect, locate, and repair leaks in sealed systems  • This compact, yet powerful machine not only finds more repair jobs, it helps you sell those repairs to your customers  • Kit includes: Smoke Pro® Total-Tech®, OEM approved smoke agent. halogen inspection light, EVAP service port tool, EVAP Schrader valve removal tool, cap plug kit, exhaust cone adapter, and plastic accessory case
		Weight: 13.0000 lbs. Case quantity:
		Case quantity.
		Sale Price: <b>\$999.99</b> .
	(E) The first rap part's black 16 to the bad root code; code; and she first part in contributions or contributions.	Jump-N-Carry Jump-N-Carry® 1700 Peak Amp 12 Volt Jump Starter part#: KKC-660
The Name and Address Name Name and Address Add		The JNC660 delivers 1700 Peak Amps and 425 Cranking Amps of starting power and weighs just 18 lbs. Perfect for a variety of professional starting environments, including automotive service, fleet service, auto dealerships, auto auctions, marinas, implement dealerships and more Give it a try and you'll see why it's the choice of Pros the world around 1700 Peak Amps Clore PROFORMER battery technology 46" #2 AWG welding cable leads Industrial-grade clamps Built-in charger Automatic charging Voltmeter provides charge status of onboard battery 12VDC outlet to power accessories 1 year limited warranty
		Weight: 21.6000 lbs.
		Case quantity: 1
		Sale Price: <b>\$159.00</b>

## **Auto Town Mayor**

(310) 965-0909 E mail: autotownmayor@sbcglobal.net

## Order Us to Pay Less!

The American control deposits in the law was an extent of south and the deposits in the control deposits of the control deposits in the control deposi	Makita 14 in. Portable Cut-Off Saw part#: MKT-2414NB	
	D-shape handle for easy gripping Cuts 4-1/2 in. round stock at 45 and 90 degrees Lock-off button to prevent accidental starting Spark diversion guard for operators safety Guide plate adjusts 45 degrees right and left - 3 locations for various sizes of materials Quick release vise for secure stock retention and fast repeated cut-offs Socket wrench stores on base for convenience Adjustable depth stop for precise, repeatable cutting depth Shaft lock for easy wheel changes 14 in. Portable Cut-Off Saw - 2414NB Abrasive Wheel - 724603-3 Socket Wrench - 782210-8 (2) Switch Buttons - 411478-6 Operating Manual  Weight: 41.8000 lbs. Case quantity: 1  Sale Price: \$295.00	
Dent Fix Equipment		
(C) to be interlugation and depart to the total total and a state of total to the state of total and a state of to	Maxi Multiple Pull Dent Station part#: DTF-DF-505  The Maxi Multiple Pull Dent Station is a 220V single phase dent pulling station that provides the technician with the power they need to shrink, pull rocker panels, hail damage, creases, dents in hard to access areas and all types of metal damage.  Weld pins  Weld a slide hammer directly to the panel  Weld a light pulling rod  Weld wiggle wire for even crease pulling  Weld a rod for leverage pulling  Shrink metal  Maxi Multiple Pull Dent Station - DF-505  (2) Light Pulling Rod  (2) Slide Hammer Rod with Strike Weight  Stud Pin Electrode  Shrinking Electrode  Wiggle Wire Weld Tip  9-Finger Bear Claw  4-Finger Bear Claw  (50) Stud Weld Pin  1 lb. Wiggle Wire  21 ft. Power Cable  9 ft. Welding Cable	
	Weight: 62.0000 lbs. Case quantity:	
	Sale Price: <b>\$1250.00</b>	

**Expiration Date: 4/30/2016**