

Up Bank → YNAB Sync

Setup checklist & worksheet

Print this out and tick off each step as you go. Space is included below for the keys and IDs you'll collect along the way, so you don't have to keep them all in your head. Full instructions for every step are in the project's README — this sheet is just a companion to it.

This sheet will hold real API keys and secrets once filled in. Treat it like a password: don't photograph it, leave it out, or leave it lying around once you're finished. Shred it (or securely dispose of it) once your setup is working and you no longer need to refer back to it.

Step 1 Install the tools you need

- ☐ Homebrew installed (Mac only)
- ☐ Node.js installed
- ☐ Yarn installed
- ☐ Checked `node --version` and `yarn --version` both work
- ☐ A text editor installed (e.g. VS Code)

Step 2 Download the code

- ☐ Repo downloaded (git clone or ZIP) and unzipped
- ☐ Folder moved to its long-term home (not Downloads) and opened in text editor

Step 3 Get your Up Bank API key

- ☐ Personal Access Token generated at api.up.com.au/getting_started

Up API key (starts with `up:yeah:`)

Step 4 Get your YNAB API key

- ☐ New Token created at app.ynab.com/settings/developer

YNAB API key

Step 5 Set up AWS

- ☐ AWS account created
- ☐ IAM user created with AdministratorAccess
- ☐ Access key created for that IAM user
- ☐ AWS CLI installed
- ☐ Ran `aws configure` with the access key, secret key, and region

AWS Access Key ID

AWS Secret Access Key

AWS region used (e.g. ap-southeast-2)

Step 6 Map Up accounts to YNAB accounts

- ☐ `accountMapping.json` created from the `.example` file
- ☐ Up account IDs looked up via the API (matched by `displayName`)
- ☐ YNAB account IDs copied from account URLs
- ☐ Every account (incl. catchall, if used) added to `accountMapping.json`

Account name	Up account ID	YNAB account ID

Step 7 Add your secret keys

- ☐ `.env` created from `.env.example`
- ☐ `UP_API_KEY`, `YNAB_API_KEY` and `YNAB_BUDGET_ID` filled in
- ☐ `UP_WEBHOOK_SECRET` left blank for now

YNAB Budget ID (from the budget URL)

Step 8 Install dependencies and deploy

- ☐ Ran `yarn` to install dependencies
- ☐ Ran `yarn sls deploy` (upWebhookHandler shows a few hundred kB)
- ☐ Copied the endpoint URL — just the part from `https://` onwards
- ☐ Registered the webhook with Up via `curl` (once only)
- ☐ Copied the `secretKey` from the response into `UP_WEBHOOK_SECRET`
- ☐ Ran `yarn sls deploy` again

Webhook endpoint URL

Webhook ID (the id straight after `"type":"webhooks"`)

Webhook secret (`UP_WEBHOOK_SECRET`)

Check it's working

- ☐ Listed webhooks: exactly one, and its url matches the endpoint URL above
- ☐ Sent a test ping (with `-d ""`)
- ☐ Newest entry in the delivery log shows `"statusCode":200`
- ☐ Real test: moved \$1 (a transfer, not a card purchase) and it appeared in YNAB

Full step-by-step instructions, troubleshooting, and explanations for everything above are in the project's [README.md](#).