

Edge Addition Planarity Suite and Generalized Graph Library

John M. Boyer¹ and Wanda B. K. Boyer¹

¹ Independent Researcher, Canada Corresponding author

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#)
- [Repository](#)
- [Archive](#)

Editor: [Open Journals](#)

Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#))

Summary

A *graph* is a mathematical structure comprising a set V of vertices and a set E of edges, with each edge e corresponding to a pair of vertices called the *endpoints* of e . A graph is *planar* if its vertices can be placed in distinct locations on a plane surface and its edges can be drawn on the plane without the edges intersecting, except at their common vertex endpoints. For a planar graph, a planarity algorithm typically outputs a combinatorial data structure that validation code can use to certify the planarity of the input graph. A planar graph drawing is typically produced by a separate algorithm. On the other hand, if an input graph is not planar, then a planarity algorithm typically outputs a minimal subgraph of the input graph that obstructs planarity. Validation code can use a minimal planarity-obstructing subgraph to certify the non-planarity of an input graph. Moreover, a minimal subgraph obstructing planarity can be used to help decide how to amend an input graph to *planarize* it.

Graphs are used to model a very wide array of real-world problems in which there are objects and relationships between the objects. In artificial intelligence, graphs are used to help with reasoning tasks, such as about the relationship pathways between persons of interest in law enforcement or between genes, tissues, diseases, and medications in bioinformatics research. In Physics, graphs and planarity are used to help compute material phase transitions, particle interactions, and electromagnetic duality. Similarly, in chemistry, graphs may be used to represent atoms and their valence bonds in molecules. Planarity testing can help determine feasible molecular arrangements because the molecular graphs for many compounds of interest must be planar. In electronics, a graph may be used to represent the electrical components and wiring in a circuit, such as transistors and etchings on a silicon wafer. The graph of a circuit must be planar or planarized to eliminate short circuits.

The open source software described in this paper provides a highly performant generalized graph library that also implements state-of-the-art algorithms for planarity-related problems. The generalized graph library and planarity-related algorithms are available to C/C++ and Python graph application developers.

Statement of need

The Edge Addition Planarity Suite is an open source software package that was originally developed to implement a new planarity algorithm in (Boyer & Myrvold, 2004). The Edge Addition Planarity Algorithm is currently regarded as one of two state-of-the-art planarity algorithms due to its conceptual simplicity as well as its speed of execution (Contributors to Wikipedia, 2026). The software package is available from the [edge-addition-planarity-suite GitHub repository](#) under a 3-clause BSD license.

To enable development of the Edge Addition Planarity Algorithm, as well as the other planarity-related algorithms in (Boyer, 2006) and (Boyer, 2012), it was necessary to develop an extensible,

41 generalized graph library. This generalized graph library provides a high-performance solution
42 for the graph algorithm representation and processing needs of a very wide array of graph
43 applications.

44 In addition to enabling graph application development in C/C++, the popularity of Python as
45 a scientific application development language has prompted the need for making this
46 graph library and the algorithms it implements available to Python developers. The source code
47 may be accessed by the [planarity Github repository](#), and the [planarity Python package](#) may
48 be installed via the Python Package Index (PyPI) by simply running `pip install planarity`.

49 State of the field

50 Several large scientific software packages offer a graph planarity algorithm, which is a complex
51 graph algorithm suitable for benchmarking graph libraries. Mathematica and Wolfram Alpha
52 include planarity algorithms, but these packages are not meant for high performance graph
53 algorithms, so the Library for Efficient Data Types and Algorithms ([LEDA](#)) is significantly
54 faster than they are because it is an industrial library designed for computational efficiency.
55 Yet, in ([Boyer et al., 2004](#)), all planarity algorithms implemented in LEDA were shown to
56 be several times slower than the Edge Addition Planarity Algorithm implementation. LEDA
57 also has the disadvantage of being C++ only and has a proprietary license. The only graph
58 library shown (in ([Boyer et al., 2004](#))) to have similar performance to the Edge Addition
59 Planarity Suite is the Public Implementation of a Graph Algorithm Library and Editor ([PIGALE](#)).
60 However, PIGALE is also C++ only, has a GPLv2 license, and lacks advanced algorithms
61 for homeomorphic subgraph search. For example, torus embedding algorithms and torus
62 obstruction isolation algorithms are able to operate differently based on whether a search for a
63 subgraph homeomorphic to $K_{3,3}$ finds a result ([Myrvold & Kocay, 2011](#); [Myrvold & Woodcock, 2018](#)).
64 Similarly, several graph theoretic results are applicable to graphs that are known to be
65 $K_{3,3}$ -free, including results related to graph isomorphism, reachability, and finding matching
66 cuts ([Datta et al., 2009](#); [Feghali et al., 2025](#); [Thierauf & Wagner, 2014](#)).

67 Software design

68 The generalized graph library in the Edge Addition Planarity Suite has a carefully curated API
69 and an object-oriented architecture. The base **Graph** class structure includes

- 70 ■ base graph, vertex, and edge structure definitions and getter/setter methods;
- 71 ■ graph, vertex and edge allocation, deallocation, and reset methods;
- 72 ■ methods for iterating through all vertices, edges, and edge adjacency lists;
- 73 ■ graph readers and writers for several formats; and
- 74 ■ a dynamic subclassing/extension mechanisms and virtual function table.

75 The base Graph is extendable with utility methods for exploring a graph, labelling vertices and
76 edges according to a depth-first search (DFS), and for managing connectivity and biconnectivity
77 information. The vertex and edge structures are extended to enable storage of the information
78 generated by the utility methods.

79 A Graph structure extended with the DFS-related utilities is further extendable to a **Planarity**
80 **Graph**, which also further extends the vertex and edge structures. The main additional method
81 provided by a Planarity Graph is `gp_Embed()`, which takes a Planarity Graph as input and
82 outputs either a combinatorial planar embedding or a minimal planarity-obstructing subgraph.

83 Given a Planarity Graph, a number of subclass extensions are available for planarity-related
84 problems. One extension solves outerplanarity. Another implements the planar graph drawing
85 algorithm in ([Boyer, 2006](#)). Three other extensions provide Graph subclasses that solve the
86 homeomorphic subgraph search algorithms appearing in ([Boyer, 2012](#)). All of these extensions
87 further extend the vertex and edge structures and overload the `gp_Embed()` function.

In addition to being available to C and C++ developers, the APIs of the Edge Addition Planarity Suite and Generalized Graph Library are also made available via the planarity Python package with the source code made available in the [planarity Github repository](#). Cython is used to preserve high performance while also broadening availability to the Python developer community.

A final aspect of this open source software project is our emphasis on software reliability. We perform validation code on `gp_Embed()` and its five overloads on billions of randomly generated graphs up to 10 million vertices and 30 million edges. The GitHub actions that run on every pull request include sanitizer tests on all graphs on 8 vertices. Finally, the [edge-addition-planarity-suite-testing Github repository](#) provides our multithreaded Python code for validating `gp_Embed()` and its five overloads on the more than one billion graphs having 11 or fewer vertices, as generated by the geng tool in Nauty and Traces (McKay & Piperno, 2025).

Research impact statement

The journal publication of the Edge Addition Planarity Algorithm, (Boyer & Myrvold, 2004), currently has over 360 scholarly citations according to [Google Scholar](#). The algorithm has been implemented in several large open source projects, including Boost, Magma, nauty and Traces (McKay & Piperno, 2025), and the Open Graph Drawing Framework ([web archive](#)). An executable program built from the source code was used to build a knot theory software package (Jablan & Sazdanović, 2007, pp. 7, 38). The source code from the Edge Addition Planarity Suite repository has been directly included in several large open source projects, including SageMath, Digraphs, and over 80 Linux platforms releases including for Debian, Devuan, Kali, openSUSE, Raspbian, Ubuntu, Alpine, ALT, Fedora, FreeBSD, Gentoo, Manjaro, MSYS2, and Parabola, according to [repology/edge-addition-planarity-suite \(web archive\)](#) and [repology/planarity \(web archive\)](#).

The Python package named planarity was originally developed in 2013 by Aric Hagberg as a way to get the planarity testing and drawing algorithms from (Boyer & Myrvold, 2004) and (Boyer, 2006) to work with graphs from NetworkX (Hagberg et al., 2008). Recently, Hagberg transferred the [planarity Github repository](#) to the [Github Graph Algorithms Organization](#) and the [planarity Python package](#) to the [PyPI Graph Algorithms Organization](#), which are both maintained by the authors. On August 1, 2026, the [Top PyPI Packages](#) website indicated that the planarity Python package had over 700,000 downloads for the preceding month and was ranked in the top 1% of PyPI package downloads (ranked 5262 out of [864,036 projects](#)). According to [pepy.tech \(web archive\)](#) the planarity Python package has been downloaded over 2 million times in total. The planarity Python package has now been included as a standard Python package in several versions of Linux including Debian, Devuan, Kali, Raspbian, and Ubuntu, according to [repology/python:planarity \(web archive\)](#).

AI usage disclosure

No generative AI tools were used in the development of this software, the writing of this manuscript, nor the preparation of supporting materials.

References

- Boyer, J. M. (2006). A new method for efficiently generating planar graph visibility representations. In P. Eades & P. Healy (Eds.), *Proceedings of the 13th international symposium on graph drawing 2005* (Vol. 3843, pp. 508–511). Springer-Verlag. https://doi.org/10.1007/11618058_47

- 132 Boyer, J. M. (2012). Subgraph homeomorphism via the edge addition planarity algorithm.
 133 *Journal of Graph Algorithms and Applications*, 16(2), 381–410. [https://doi.org/10.7155/](https://doi.org/10.7155/jgaa.00268)
 134 [jgaa.00268](https://doi.org/10.7155/jgaa.00268)
- 135 Boyer, J. M., Cortese, P. F., Patrignani, M., & Di Battista, G. (2004). Stop minding your
 136 P's and Q's: Implementing a fast and simple DFS-based planarity testing and embedding
 137 algorithm. In G. Liotta (Ed.), *Proceedings of the 11th international symposium on graph*
 138 *drawing 2003* (Vol. 2912, pp. 25–36). Springer-Verlag. [https://doi.org/10.1007/978-3-](https://doi.org/10.1007/978-3-540-24595-7_3)
 139 [540-24595-7_3](https://doi.org/10.1007/978-3-540-24595-7_3)
- 140 Boyer, J. M., & Myrvold, W. J. (2004). On the cutting edge: Simplified $O(n)$ planarity
 141 by edge addition. *Journal of Graph Algorithms and Applications*, 8(3), 241–273. <https://doi.org/10.7155/jgaa.00091>
- 142 Contributors to Wikipedia. (2026). Planarity testing. In *Wikipedia, the free encyclopedia*.
 143 Wikipedia. [https://en.wikipedia.org/w/index.php?title=Planarity_testing&oldid=](https://en.wikipedia.org/w/index.php?title=Planarity_testing&oldid=1336627782)
 144 [1336627782](https://en.wikipedia.org/w/index.php?title=Planarity_testing&oldid=1336627782)
- 145 Datta, S., Nimbhorkar, P., Thierauf, T., & Wagner, F. (2009). Graph isomorphism for
 146 $K_{3,3}$ -free and K_5 -free graphs is in log-space. *Proceedings of the 29th Annual Conference*
 147 *on Foundation of Software Technology and Theoretical Computer Science (FSTTCS)*,
 148 145–156. <https://doi.org/10.4230/LIPIcs.FSTTCS.2009.2314>
- 149 Feghali, C., Lucke, F., Paulusma, D., & Ries, B. (2025). Matching cuts in graphs of high girth
 150 and H -free graphs. *Algorithmica*, 87, 1199–1221. [https://doi.org/10.1007/s00453-025-](https://doi.org/10.1007/s00453-025-01318-8)
 151 [01318-8](https://doi.org/10.1007/s00453-025-01318-8)
- 152 Hagberg, A. A., Schult, D. A., & Swart, P. J. (2008). Exploring network structure, dynamics,
 153 and function using NetworkX. *Python in Science Conference*. [https://doi.org/10.25080/](https://doi.org/10.25080/TCWV9851)
 154 [TCWV9851](https://doi.org/10.25080/TCWV9851)
- 155 Jablan, S., & Sazdanović, R. (2007). *LinKnot: Knot theory by computer* (Vol. 21). World
 156 Scientific. <https://doi.org/10.1142/6623>
- 157 McKay, B. D., & Piperno, A. (2025). *Nauty and traces user's guide (version 2.9.0)*. <https://pallini.di.uniroma1.it/nug29.pdf>
- 158 Myrvold, W., & Kocay, W. (2011). Errors in graph embedding algorithms. *Journal of Computer*
 159 *and System Sciences*, 77(2), 430–438. <https://doi.org/10.1016/j.jcss.2010.06.002>
- 160 Myrvold, W., & Woodcock, J. (2018). A large set of torus obstructions and how they were
 161 discovered. *The Electronic Journal of Combinatorics*, 25(1), 1–17. [https://doi.org/10.](https://doi.org/10.37236/3797)
 162 [37236/3797](https://doi.org/10.37236/3797)
- 163 Thierauf, T., & Wagner, F. (2014). Reachability in $K_{3,3}$ -free and K_5 -free graphs is in
 164 unambiguous logspace. *Chicago Journal of Theoretical Computer Science*, 2014, 1–29.
 165 <https://doi.org/10.4086/cjtc.2014.002>
- 166
- 167